

**Professional
cleaning
detergents**
Selection Guide

www.electroluxprofessional.com

Electrolux Professional Genuine Chemicals

With Electrolux Professional chemicals we take care of the Environment, People and your Equipment:

Our products ensure best performance and highly effective cleaning solutions with perfect balance between equipment and chemicals.

We guarantee appliances' longevity by means of intensive and accurate laboratory testing, always ensuring perfect cleaning results as well as the highest performance of the equipment and its components.

We have developed Ecofriendly chemicals with high quality raw material and low environmental impact, which are able for example to avoid glass wear and extend textile life.

All Electrolux Professional Chemicals are over 95% biodegradable fulfilling the strictest regulations on the global market and complying with REACH regulation; moreover, our internal Restricted Material List is even more severe to provide you the safest solution.

Furthermore, discover our brand-new ECOLABEL and NORDIC SWAN products developed to be effective and safe for the environment.






Index

Coronaviruses: scientific evidence on inactivation	page 4	Descaling chemicals	
Chemicals for food segment		C30 Multipurpose descaler	page 24
Ovens Liquid Chemicals	page 8	C25 Rinse & Descale Tab	page 25
Ovens Solid Chemicals	page 9	Water Treatment	
Dishwashing Chemicals	page 10	Automatic water softeners	page 28
The right solution	page 12	Manual water softeners	page 31
Speedelight chemical	page 14	Water softeners consumables	page 32
Degreaser	page 15	Water treatment	page 33
Chemicals for Laundry segment		Water treatment with reverse osmosis system	page 38
lagoon® Advanced Care	page 18	Pumps for detergents	
Pre-spotting agents	page 19	Pumps for food segment	page 42
Washers & Dryers	page 20	Pumps for laundry segment	page 44
		Safety at a glance	page 46

Coronaviruses: Scientific studies on inactivation^{(1),(2)}

Infectivity of Coronavirus is sensitive^{(1), (2)} to:

- ▶ **Chemicals with extreme pH values** (highly acid or highly alkaline)
- ▶ **High temperature exposure** for a certain period of time



Combining our appliances to our selected chemicals can provide a valid and effective solution to provide you, your customers and your staff with the confidence that their well-being is safeguarded at all times.

* Logarithmic scale of coronavirus concentration after chemical substance and temperature exposure. Please note that safety is below the concentration line of log₁₀(1) which corresponds to zero units.

- (1) M. E. R. Darnell et al., Inactivation of the coronavirus that induces severe acute respiratory syndrome, SARS-CoV, Journal of Virological Methods 121 (2004) 85-91
- (2) Bio Basic Europe, Bibliographic verification aimed to assess the virucidal efficacy of processes and products used during washing and rinsing cycles with Electrolux Professional dishwasher, 17th July 2020



Accessories for protection and prevention



OS2644

Face mask with filter FFP2
 Foldable single-use with EN149 valve. Adjustable aluminum nose piece.
 PPE class III,
 EN 149:2001 + A1:2009
 Single pack



OS2646

Face mask with filter FFP2
 Foldable single-use without valve; nose part with flexible insert
 EN 149:2001 + A1:2009
 Pack of 10 pieces



OS2659

Protective visor
 Face shield with 90° opening protective visor
 • visor in PET, thickness 0.8mm
 • dimensions: 250mm x 310mm
 • front strip with polyethylene pad
 • polyester rear elastic
 • in accordance with standard EN 166
 • Category II PPE



Thick blue nitrile glove

- Ambidextrous and reusable
- Excellent mechanical and chemical resistance to detergents, abrasive cleaning agents, oils and greases
- Excellent tactile sensitivity, dexterity and elasticity
- Thickness 0.23mm
- Category III
 EN388:E362016
 EN ISO 374-1:2016
 EN ISO 374-5:2016
- Pack of 2 pieces



OS2653

Clear goggles OX3000
 Wrap-around, can be worn over prescription eyewear
 Anti-fogging coating
 UV protection cert EN170
 EN166 Certification
 Class II PPE

OS2674 size S

OS2675 size M

OS2676 size L

OS2677 size XL





Chemicals for food segment

Index

Ovens

Liquid Chemicals

page 8

Solid Chemicals

page 9

Dishwashing

Wash, rinse & descale

page 10

The right solution

page 12

Speedelight

page 14

Degreaser

page 15

Ovens Liquid Chemicals

Code 0S2282

C20 Extra Strong Detergent for Ovens

- ▶ High degreasing power for ovens with integrated washing cycle
- ▶ **Environmental friendly chemical with revised formula without EDTA**
- ▶ Reliability commitment with no risk of premature parts break due to chemical usage
- ▶ Intensively field tested by Experts and Customers
- ▶ Ergonomic packaging with n.2 x 5 liter jugs for easy handling and stocking
- ▶ Safety commitment with QR code for immediate Safety Data Sheet download



Code 0S2283

C21 Extra Strong Rinse Aid for Ovens

- ▶ Quick drying and perfect shining cavity for ovens with integrated washing cycle
- ▶ Eco friendly chemical with low environmental impact by use of vegetable origin surfactants
- ▶ Reliability commitment with no risk of premature parts break due to chemical usage
- ▶ Intensively field tested by Experts and Customers
- ▶ Ergonomic packaging with n.2 x 5 liter jugs for easy handling and stocking
- ▶ Safety commitment with QR code for immediate Safety Data Sheet download



Accessories for liquid chemicals



Code 0S2347

Wall mounted holder for detergent tank

- ▶ Ideal to keep detergents away from the floor



Code 0S2559

Open base hanging holder

- ▶ Ideal to keep detergents away from the floor



Ovens Solid Chemicals

Innovative range of solid chemicals to ensure the best cleaning performance for the entire lifecycle of your professional oven.



Code 0S2395

C22 Cleaning tab

- ▶ Effective cleaning tab for ovens with integrated washing cycles.
- ▶ Concentrated formula effective with low dosage.
- ▶ No risk of premature breakage.
- ▶ Intensively tested in Electrolux Professional laboratories
- ▶ 100 tabs bucket; 65 gr. each



Code 0S2392

C23 Cleaning powder

- ▶ Effective cleaning powder for ovens with integrated washing cycles.
- ▶ Concentrated formula effective with low dosage.
- ▶ No risk of premature breakage.
- ▶ Intensively tested in Electrolux Professional laboratories
- ▶ 100 bags bucket; 65 gr. each



Code 0S2393

C24 Enzymatic powder

- ▶ Sustainable cleaning powder in single use bags for SkyLine ovens.
- ▶ Professional detergent for new generation ovens with automatic washing system.
- ▶ Suitable for all types of water
- ▶ 100 bags bucket; 65 gr. each



Code 0S2394

C25 Rinse & Descale Tab

- ▶ Effective rinse&descale tab for ovens with integrated washing cycles.
- ▶ For a fast drying with perfectly shining cavity and a descaled boiler.
- ▶ Concentrated formula effective with low dosage.
- ▶ No risk of premature breakage.
- ▶ Intensively tested in Electrolux Professional laboratories
- ▶ 50 tabs buckets; 30 gr. each



20% less chemical consumption compared to main players on the market

- ▶ reduced environmental impact
- ▶ money saving

Dishwashing Chemicals

To get the **best washing results**, you need to choose not only the **right machine** and matching the proper **water treatment system**, but also select the **specific detergent and rinse aid**. To provide our customers the most **specific solution** for every need, we have developed two couples of chemicals and a selection guide that can be found on the next pages.

All our dishwashing chemicals have controlled foaming properties and have demonstrated excellent results when compared to currently distributed commercial brands.

Furthermore, by using genuine Electrolux Professional chemicals, the life of the glasses is extended since they are not worn by the chemical aggression of a standard detergent and rinse aid (see testing results on pag.9).



Code 0S2092

C11 Detergent for Dishwashers

- ▶ Concentrated formula for reduced consumption
- ▶ Ideal for all types of crockery: ceramic, porcelain, glass, crystal and metal
- ▶ Its delicate aroma helps minimize the unpleasant odor which can sometimes be found in dishwashers
- ▶ Highly recommended for restaurants preparing fish and sea food
- ▶ Particularly suitable for hard and medium hard water
- ▶ Intensively field tested by Experts and Customers
- ▶ Low environmental impact with reduced carbon footprint
- ▶ Reliability commitment with no risk of premature parts break due to chemical usage
- ▶ Ergonomic packaging with n.2 x 5 liters jugs for easy handling and stocking



Code 0S2094

C12 Rinse Aid for Dishwashers

- ▶ Concentrated formula for reduced consumption
- ▶ Ideal for all types of crockery: ceramic, porcelain, glass, crystal and metal
- ▶ Removes lime scale from dishes, leaving a perfect bright surface
- ▶ Reduced appliance lime scale deposit
- ▶ Guarantees sparkling clean and dry crockery
- ▶ Perfect drying results guaranteed, without manual actions
- ▶ Particularly suitable for hard and medium hard water
- ▶ Intensively field tested by Experts and Customers
- ▶ Eco friendly chemical with low environmental impact by use of vegetable origin surfactants
- ▶ Ergonomic packaging with n.2 x 5 liters jugs for easy handling and stocking



ECO
friendly

Code 0S2093

C13 Eco Detergent for Dishwashers

- ▶ Highly concentrated and Ecofriendly formula without EDTA, NTA and polyphosphates
- ▶ Ideal for all type of crockery: ceramic, porcelain, glass, crystal and metals
- ▶ Particularly suitable for soft water
- ▶ Ideal for all type of crockery: ceramic, porcelain, glass, crystal and metals
- ▶ Very efficient in case of dried food residues on all kind of dishes
- ▶ Intensively field tested by Experts and Customers
- ▶ Reliability commitment with no risk of premature parts break due to chemical usage
- ▶ Eco friendly chemical with low environmental impact and reduced carbon footprint
- ▶ Ergonomic packaging with n.2 x 5 liters jugs for easy handling and stocking



ECO
friendly


Code 0S2095

C14 Rinse Aid Plus for Dishwashers


- ▶ Highly concentrated formula for reduced consumption with surfactants of vegetable origin
- ▶ Perfect drying results guaranteed without stains or any water trace, with no need of manual actions
- ▶ Reduced appliance lime scale deposit
- ▶ Removes lime scale from dishes, leaving a perfect bright surface
- ▶ Particularly suitable for soft water
- ▶ Ideal for all type of crockery: ceramic, porcelain, glass, crystal and metals
- ▶ Intensively field tested by Experts and Customers
- ▶ Eco friendly chemical with low environmental impact by use of vegetable origin surfactants
- ▶ Ergonomic packaging with n.2 x 5 liters jugs for easy handling and stocking

Did you know that your glasses loose “weight” each cycle and become more and more fragile?


Soda-lime (the most common glass)



Crystal (crystal glass)



Lead crystal (best quality glass)



◆ Glass weight loss using Electrolux Professional recommended solutions
 ◆ Glass weight loss using standard chemicals





















Code 0S2362


C30 Multipurpose descaler



- ▶ Effectively eliminates encrustations and scale from washing appliances and boilers of any professional equipment
- ▶ The regular use of C30 Multipurpose descaler keeps the equipment always efficient, while slowing down the natural wear and tear
- ▶ Thanks to its low foaming power, C30 Multipurpose descaler is recommended for cleaning boilers and equipment with an automatic descaling device
- ▶ The neutral fragrance makes its use more pleasant

The right solution

1	2	3	4	5
What are you going to wash?	Water hardness (°F) *	Recommended water treatment	Water hardness after treatment (°F) *	Detergent to be used
 Glasses and crystals	Soft 0 ÷ 7	None	Soft 0 ÷ 7	 
	Medium Soft 7 ÷ 15	For crystals use total or partial demineralization (refer to the chart on the right for the proper solution for your machine)		C13 Eco Detergent for Dishwashers C14 Rinse Aid Plus for Dishwashers
	Medium Hard 15 ÷ 25	For crystals use total or partial demineralization while for standard glasses use water softener (refer to the chart on the right for the proper solution for your machine)		 
	Hard / Very Hard 25 ÷ 45	For standard glasses use water softener while for crystals use water softener plus reverse osmosis (refer to the chart on the right for the proper solution for your machine)		C11 Detergent for Dishwashers C12 Rinse Aid for Dishwashers
 Cups and mugs	Soft 0 ÷ 7	None	Soft 0 ÷ 7	 
	Medium Soft 7 ÷ 15			C13 Eco Detergent for Dishwashers C14 Rinse Aid Plus for Dishwashers
	Medium Hard 15 ÷ 25	Total or partial demineralization (refer to the chart on the right for the proper solution for your machine)		 
	Hard / Very Hard 25 ÷ 45	Water softener (refer to the chart on the right for the proper solution for your machine)		C11 Detergent for Dishwashers C12 Rinse Aid for Dishwashers
 Plates and cutlery	Soft 0 ÷ 7	None	Soft 0 ÷ 7	 
	Medium Soft 7 ÷ 15			C13 Eco Detergent for Dishwashers C14 Rinse Aid Plus for Dishwashers
	Medium Hard 15 ÷ 25	Water softener (refer to the chart on the right for the proper solution for your machine)		 
	Hard / Very Hard 25 ÷ 45			C11 Detergent for Dishwashers C12 Rinse Aid for Dishwashers
 Stainless Steel Pots	Soft 0 ÷ 7	None	Soft 0 ÷ 7	 
	Medium Soft 7 ÷ 15			C13 Eco Detergent for Dishwashers C14 Rinse Aid Plus for Dishwashers
	Medium Hard 15 ÷ 25			 
	Hard / Very Hard 25 ÷ 45	Water softener (refer to the chart on the right for the proper solution for your machine)		C11 Detergent for Dishwashers C12 Rinse Aid for Dishwashers



		Undercounter/ Glasswasher	Hood Type Dishwasher	Pot&Pan Washer	Single&Compact Rack Type with ESD	Single&Compact Rack Type	Multi Rinse Rack Type
Manual Water Softener	OS1074 (cold) 8 lt with bypass	•	•	•			
	OC1903 (cold) 8 lt without bypass	•	•	•			
	OS1076 (cold) 12 lt with bypass	•	•	•			
	860412 (cold) 12 lt without bypass	•	•	•			
	860430 (cold) 20 lt	•	•	•			
	860413 (cold) 8 lt	•	•	•			
	OS1946 (cold) 8 lt	•	•	•			
	OS1079 (cold) 8 lt	•	•	•			
	002454 (cold) 8 lt	•	•	•			
Automatic Water Softener	OS1083 (cold) 12 lt	•	•	•			
	865495 (hot) 12 lt			•			
	OS1089 (cold) 24 l	•	•	•			
	PNC 865284 2x13 lt (cold) + 12 lt (hot&cold)				•		•
	865284 (hot&cold) 12 lt				•	•	•
Partial Demineralization	864017 (hot or cold)	•	•				
Total Demineralization	864367 (hot or cold)	•	•				
	864388	•	•				
Osmosis	865494 (hot&cold - WS or cold RO)						•

SpeeDelight chemical



Code 0S2292

C41 Rapid Grease for SpeeDelight

- ▶ Specifically developed formula for use with SpeeDelight
- ▶ Best cleaning performance at high temperature, protecting glass, silicon and stainless steel
- ▶ Food safe chemical
- ▶ Makes daily cleaning easier and faster, removing all type of carbonized residuals
- ▶ Intensively field tested by Experts and Customers
- ▶ Reliability commitment with no risk of premature parts break due to chemical usage
- ▶ N. 6 x 1 liter bottles with practical nozzle, including an extra spraying unit
- ▶ Safety commitment with QR code for immediate Safety Data Sheet download



Tutorial video



Follow the cleaning path
with Electrolux Professional

Watch the video tutorial
SpeeDelight cleaning

Degreaser



Code 0S1841

C40 Degreaser for Hot Surfaces

- ▶ Recommended for fry tops and braising pans with mild steel or chromed surfaces
- ▶ Best cleaning performance at high temperature (165°C - 175°C), without damaging cooking surfaces
- ▶ Food safe chemical
- ▶ Makes daily cleaning easier and faster, removing all type of carbonized residuals
- ▶ Eliminates the risk of food cross-contamination
- ▶ Intensively field tested by Experts and Customers
- ▶ Reliability commitment with no risk of premature parts break due to chemical usage
- ▶ Packaging consisting of n.6 x 1 liter bottles with practical nozzle, including an extra spraying unit
- ▶ Safety commitment with QR code for immediate Safety Data Sheet download

Tutorial video



Follow the cleaning path with Electrolux Professional







Chemicals for laundry segment

Index

lagoon® Advanced Care
Washers & Dryers

page 18
page 20

lagoon®

Advanced Care

Electrolux Professional launches lagoon® Advanced Care system: delicate on fabrics, gentle on the environment, and a game changer for the business.

lagoon® Advanced Care system makes it possible to operate wet-cleaning with less process time, higher productivity and seamless handling of dry cleaning.

Imagine... to be able to offer excellent cleaning results in a truly sustainable way.



Code 0W7095 - PNC 432731085 (20 lt tank) / Code 0W7096 - PNC 432731086 (10 lt tank)

W01 - lagoon® Sensitive Detergent

Detergent for use in professional wet cleaning, with the appropriate Electrolux Professional lagoon® wet cleaning programs and together with W03 - lagoon® Sensitive Conditioner.



Code 0W7099 - PNC 432731089 (20 lt tank) / Code 0W709A - PNC 432731090 (10 lt tank)

W02 - lagoon® Delicate Detergent

Detergent for use in professional wet cleaning. With the appropriate Electrolux Professional lagoon® wet cleaning programs for mixed fibers and together with W03 - lagoon® Sensitive Conditioner. Suitable for washing colored textiles at 40 °C.



Code 0W7097 - PNC 432731087 (20 lt tank) / Code 0W7098 - PNC 432731088 (10 lt tank)

W03 - lagoon® Sensitive Conditioner

Conditioner for use in professional wet cleaning. With the appropriate Electrolux Professional lagoon® wet cleaning programs and together with W01 - lagoon® Sensitive Detergent for delicate fibers. Suitable for robust fabrics together with W02 - lagoon® Delicate Detergent.

Complete
range of smart
detergents for
unprecedented
cleaning results.



Pre-spotting agents



Code 0W709B - PNC 432731091
(1 pack of two 5 lt tanks)

A01 - lagoon® Pre-treatment

Universal mild prebrushing agent for use in professional wet cleaning. Can be applied as pre-treatment on any type of fibers.



Code 0W709K - PNC 432731099
(1 pack of two 5 lt tanks)

A02 - lagoon® Colour Transfer Reducer

Colour fixing and levelling agent for direct dyes on textiles. Helps to reduce risk of colour transfer in Electrolux Professional lagoon® wet cleaning programs.



Code 0W7Q1A - PNC 432731148
(1 pack of one 10 lt tank)

A03 - lagoon® Leather Care

Conditioner oil to restore natural leather appearance with nurturing and softening effect while balancing the color.



Code 0W709E - PNC 432731094
(1 pack of six 0.5 lt bottles)
Code 0W709J - PNC 432731098
(1 pack of two 5 lt tanks)

P01 - lagoon® Protein Stain Remover

Pre-spotting agent for use in professional wet cleaning. To be applied as pre-treatment on stains caused by blood, egg, milk, vomit and urine.



Code 0W709C - PNC 432731092
(1 pack of six 0.5 lt bottles)
Code 0W709G - 432731096
(1 pack of two 5 lt tanks)

P02 - lagoon® Tannin Stain Remover

Pre-spotting agent for use in professional wet cleaning. To be applied as pre-treatment on stains caused by fruits, coffee, tea, red wine and grass.



Code 0W709D - PNC 432731093
(1 pack of six 0.5 lt bottles)
Code 0W709H - PNC 432731097
(1 pack of two 5 lt tanks)

P03 - lagoon® Grease Remover

Pre-spotting agent for use in professional wet cleaning. To be applied as pre-treatment on stains caused by waxes, polishes, oils, greases and make-up.



Code 0W709F - PNC 432731095
(1 pack of six 0.5 lt bottles)

P04 - lagoon® Ink Remover

Pre-spotting agent for use in professional wet cleaning. To be applied as pre-treatment on synthetic stains, stains caused by inks, adhesives, lacquers, synthetic paints and tar.

Code 0W7LLV - PNC 432731110

Starter kit

contains 4x0.5L of P01, P02, P03, P04
The perfect solution to have the chance to test our spotting agents



Code 0W7RW6 - PNC 432731156

lagoon® Leather Care Starter - Kit

The kit consist of all tools that ensure basic and advanced treatment of leather textiles in the lagoon® Advanced Care - cleaning process

Washers & Dryers

The new range of Laundry detergents has been developed to offer high quality, safety and effectiveness ensuring a low environmental impact thanks to reduced water pollution, waste production and energy consumption compared to standard product on the market. Electrolux Professional commitment is guaranteed by **ECOLABEL** and **NORDIC SWAN** certification and approval.



Code 0W7RBB - PNC 432131139 (15 kg bag)

L01 - Laundry Eco Powder

High-performance powder detergent allowing a perfect cleaning with a minimum dose. Removes grease and stains protecting fabrics and colors. Lightly scented.



Code 0W7RBC - PNC 432731140 (20 l tank)

L02 - Laundry Eco Wash

Liquid detergent for all linen, with strong efficacy even at 30°C and low doses. Respects textile fibers and colors by giving them back the original luster.



Code 0W7RBF - PNC 432731143 (20 l tank)

L03 - Laundry Eco Booster

In case of difficult soil and in presence of hard/very hard water, L03 Laundry Eco Booster ensures high standard performances. Use in combination with L01 or L02 detergents.



Code 0W7RBD - PNC 432731141 (20 l tank)

L04 - Laundry Eco Bleach

New generation of bleaching agent, effective even at 30°C while preserving textiles quality and colors.



Code 0W7RBE - PNC 432731142 (20 l tank)

L05 - Laundry Eco Softener

Slightly scented softener for pleasant textiles, easy ironing and with no residuals of static electricity.

PENDING



Satisfying the requirements of the **EUROPEAN ECOLABEL** means respecting very strict specifications on raw materials, high performance criteria and rigorous environmental-friendly approach.

The EU Ecolabel helps you identify products and services that have a **reduced environmental impact throughout their life cycle**, from the extraction of raw material through to production, use and disposal. Recognised throughout Europe, EU Ecolabel is a voluntary label promoting environmental excellence which can be trusted. Providing you a complete range of products including detergent, booster, softener and bleach reflects a strong commitment on the entire process.



Using our **NORDIC SWAN** products range means providing effective cleaning with the guarantee of a green process from raw material choices to performance tests, verified by an external auditing procedure.

The **Nordic Swan Ecolabel** is the official Ecolabel of the Nordic countries, a voluntary and positive practical tool for consumers to help them actively choose environmentally sound products. The Nordic Swan Ecolabel is an ISO 14024 type 1 Ecolabelling system and is a third-party control organ. Products carrying the Nordic Swan Ecolabel meet extremely high environmental and often climate requirements.

The life-cycle perspective of the product is analysed, i.e., **the product's impact on the environment from raw material/source to waste**. Criteria is also set with regard to quality, health aspects and performance/ functionality. Each product group has overriding general criteria requirements as well as product-specific requirements.



Code 0W7RBG - PNC 432731144 (20 lt tank)

L06 - Laundry Swan Wash

Strong detergent for the most stubborn stain. Phosphate and silicate free alkaline detergent for excellent stain removal. Effective even on garment and work wear.



Code 0W7RBH - PNC 432731145 (20 lt tank)

L07 - Laundry Swan gentle Wash

Detergent for the most stubborn stain. Liquid detergent for all types of tissues even colored. Excellent soil and stain removal properties. Prevents "greying" of tissues.



Code 0W7RBI - PNC 432731146 (20 lt tank)

L08 - Laundry Swan Bleach

Peracetic base bleach. Provides outstanding bleaching performances. Acts also as an alkalinity neutralizer to bring your tissues back to a neutral pH.



Code 0W7RBJ - PNC 432731147 (20 lt tank)

L09 - Laundry Swan Softener

Softener for all textiles. Optimal softening effect, also at short cycle times; diminishes static electricity. Ensures fast drying and easy to be ironed textiles.

Maintain a high standard drying experience with a periodic cleaning of your tumble dryers thanks to a fast and easy descaling process allowing the automatic residual moisture control to act efficiently and also ensuring to remove any eventual soap/softener that could remain.



Code 0S2394

C25 Rinse & Descale Tab

The perfect combination of citric acid (*Acidum citricum*) together with our dedicated formula ensure a perfect removal of any limestone and/or soap and softener residuals. Dissolve 1 tab in 1 liter of water and rinse the tumble dryer. If necessary you can use the **scouring pad** (0W7PM8)





Descaling chemicals

Index

C30 Multipurpose descaler
C25 Rinse & Descale Tab

page 24
page 25

Descaling chemicals




Code 0S2362 (1 pack of two 5 lt tanks)

C30 Multipurpose descaler

- ▶ Effectively eliminates encrustations and scale from washing appliances and boilers of any professional equipment
- ▶ The regular use of C30 Multipurpose descaler keeps the equipment always efficient, while slowing down the natural wear and tear
- ▶ Thanks to its low foaming power, C30 Multipurpose descaler is recommended for cleaning boilers and equipment with an automatic descaling device
- ▶ The neutral fragrance makes its use more pleasant

**Take care of
your appliances
ensuring better
performances
and longevity
with dedicated
chemicals**





Code 0S2394

C25 Rinse & Descale Tab



- ▶ Effective rinse&descale tab for ovens with integrated washing cycles.
- ▶ Dissolve 1 tab in 1 liter of water to descale the tumble dryer's drum
- ▶ For a fast drying with perfectly shining cavity and a descaled boiler.
- ▶ Concentrated formula effective with low dosage.
- ▶ No risk of premature breakage.
- ▶ Intensively tested in Electrolux Professional laboratories
- ▶ 50 tabs buckets; 30 gr. each

The new solid oven descaler can be used even for a professional descaling of tumble dryers' drum







Water treatment

Index

Automatic water softeners	page 28
Manual water softeners	page 31
Water softeners consumables	page 32
Water treatment	page 33
Water treatment with reverse osmosis system	page 38

Providing the proper water treatment will:

- ▶ avoid the risk of altering the taste and appearance of your foods
- ▶ reduce scale build-up therefore de-liming is less frequent, thus resulting in additional savings in operating costs
- ▶ extend the life of your appliance
- ▶ guarantee lower maintenance costs

Electrolux Professional suggest you to check your water quality in order to choose the right water treatment solution:

- ▶ water softener for high concentration of calcium
- ▶ water nanofilter or reverse osmosis filter for high concentration of calcium and chloride

Automatic water softeners

Automatic softeners with ALIA valve



Product code	AISI 304 cylinder	Cationic resins for cylinder	Max flow rate	Brine	Salt for regener. cycle	Supply power	Water conn.	Min/max pressure	Temp. water supply	LxDxH
OS1945	5 lt	3,5 lt	1500 lt/h	10 kg	0,6 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-30°C	230x360x515 mm
OS1946	8 lt	5,6 lt	1500 lt/h	20 kg	1,0 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-30°C	250x460x540 mm
OS1947	12 lt	8,5 lt	1500 lt/h	25 kg	1,5 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-30°C	285x405x595 mm

Automatic softeners GIX

TIMED with Autotrol valve 255
Logix 740



Product code	AISI 304 cylinder	Cationic resins for cylinder	Max flow rate	Brine	Salt for regener. cycle	Supply power	Water conn.	Min/max pressure	Temp. water supply	LxDxH
OS2457	5 lt	3,5 lt	1500 lt/h	10 kg	0,6 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	230x385x515 mm
OS1079	8 lt	5,6 lt	1500 lt/h	20 kg	1,0 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	245x450x540 mm
002454* pnc 921305	8 lt	5,6 lt	1500 lt/h	20 kg	1,0 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	245x450x540 mm
OS2458	12 lt	8,5 lt	1500 lt/h	25 kg	1,4 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	285x425x650 mm

*Water softener coated with stainless steel panels

Amount of softened water based on hardness

°f	20	30	40	50	60
°d	11	16	22	28	33
ppm CaCO ₃	200	300	400	500	600
OS1945 / OS2457	1050	700	525	420	350
OS1946 / OS1079 / 002454	1680	1120	840	672	560
OS1947 / OS2458	2520	1680	1260	1008	840

Automatic water softeners

Automatic softeners
TIMED cabinet
with Autotrol valve 255
Logix 740



Product code	Fibreglass cylinder	Cationic resins for cylinder	Max flow rate	Brine	Salt for regener. cycle	Supply power	Water conn.	Min/max pressure	Temp. water supply	LxDxH
OS1083	12 lt	8,5 lt	1500 lt/h	25 kg	1,4 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	320x500x660 mm
OS1089	24 lt	17 lt	1500 lt/h	50 kg	2,7 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	320x500x1120 mm

Amount of softened water based on hardness

°f	20	30	40	50	60
°d	11	16	22	28	33
ppm CaCO ₃	200	300	400	500	600
OS1083	2520	1680	1260	1008	840
OS1089	5040	3360	2520	2016	1680

Automatic softeners
LARGE SERIES VOLUMETRIC
with valve Autotrol 255 Logix 760



Product code	Fibreglass cylinder	Cationic resins for cylinder	Max flow rate	Brine	Salt for regener. cycle	Supply power	Water conn.	Min/max pressure	Temp. water supply	LxDxH
OS2459	50 lt 10"x44"	35 lt	1500 lt/h	120 kg	7,2 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	Cylinder: Ø271x1300mm Brine: Ø541x810mm
OS2460	84 lt 13"x44"	59 lt	1500 lt/h	120 kg	12,2 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	Cylinder: Ø360x1300mm Brine: Ø541x810mm

Amount of softened water based on hardness

°f	20	30	40	50	60
°d	11	16	22	28	33
ppm CaCO ₃	200	300	400	500	600
OS2459	10500	7000	5250	4200	3500
OS2460	17640	11760	8820	7056	5880

Automatic water softeners

Automatic softeners
LARGE SERIES PERFORMA VOLUMETRIC
with valve Autotrol 268 Logix 760



Cylinder Brine

Product code	Fibreglass cylinder	Cationic resins for cylinder	Max flow rate	Brine	Salt for regener. cycle	Supply power	Water conn.	Min/max pressure	Temp. water supply	LxDxH
OS2461	24 lt 8"x35"	17 lt	4000 lt/h	80 kg	2,7 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	Cylinder: Ø219x1060mm Brine: Ø480x660mm
OS2462	50 lt 10"x44"	35 lt	4000 lt/h	120 kg	7,2 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	Cylinder: Ø271x1300mm Brine: Ø541x810mm
OS2463	84 lt 13"x44"	59 lt	4000 lt/h	120 kg	12,2 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	Cylinder: Ø360x1300mm Brine: Ø541x810mm

Automatic softeners
LARGE SERIES PERFORMA TIMED
with valve Autotrol 268 Logix 740



Cylinder Brine

Product code	Fibreglass cylinder	Cationic resins for cylinder	Max flow rate	Brine	Salt for regener. cycle	Supply power	Water conn.	Min/max pressure	Temp. water supply	LxDxH
OS2464	24 lt 8"x35"	17 lt	4000 lt/h	80 kg	2,7 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	Cylinder: Ø219x1060mm Brine: Ø480x660mm
OS2325	50 lt 10"x44"	35 lt	4000 lt/h	120 kg	7,2 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	Cylinder: Ø271x1300mm Brine: Ø541x810mm
OS2326	84 lt 13"x44"	59 lt	4000 lt/h	120 kg	12,2 kg	230V 50/60 Hz	Ø 3/4" G	2-8 bar	4-25°C	Cylinder: Ø360x1300mm Brine: Ø541x810mm

Amount of softened water
based on hardness

°f	20	30	40	50	60
°d	11	16	22	28	33
ppm CaCO ₃	200	300	400	500	600
OS2461 / OS2464	5040	3360	2520	2016	1680
OS2462 / OS2325	10500	7000	5250	4200	3500
OS2463 / OS2326	17640	11760	8820	7056	5880

Manual water softeners

Manual water softeners



Product code	AISI 304 cylinder	Cationic resins for cylinder	Max flow rate	Salt for regeneration cycle	Water conn.	Min/max pressure	Temp. water supply	LxDxH
OC1903	8 lt	5,6 lt	1000 lt/h	1,0 kg	Ø 3/4" G	1-8 bar	8-25°C	Ø190x400 mm
OS0330	12 lt	8,4 lt	1000 lt/h	1,5 kg	Ø 3/4" G	1-8 bar	8-25°C	Ø190x515 mm
OS0329	20 lt	14 lt	1000 lt/h	2,5 kg	Ø 3/4" G	1-8 bar	8-25°C	Ø190x900 mm

Manual water softeners "by pass"



Product code	AISI 304 cylinder	Cationic resins for cylinder	Max flow rate	Salt for regeneration cycle	Water conn.	Min/max pressure	Temp. water supply	LxDxH
OS1074	8 lt	5,6 lt	1000 lt/h	1,0 kg	Ø 3/4" G	1-8 bar	8-25°C	Ø190x400 mm
OS1076	12 lt	8,4 lt	1000 lt/h	1,5 kg	Ø 3/4" G	1-8 bar	8-25°C	Ø190x500 mm

Amount of softened water based on hardness

°f	20	30	40	50	60
°d	11	16	22	28	33
ppm CaCO ₃	200	300	400	500	600
OC1903 / OS1074	1680	1120	840	672	560
OS0330 / OS1076	2520	1680	1260	1008	840
OS0329	4200	2800	2100	1680	1400

Water softeners consumables



OL1140
Water filter NK111
 with wound cartridge 50µm.
 Recommended for manual water softeners.
 Ø 5", Coupling 3/8" G



OS1423
Complete filter NK223C
 with carbon block cartridge 5µm.
 Recommended for manual water softeners.
 Ø 9, Coupling 1/2" G m/f

OS1027



OL1141
Water filter NK112
 with wound cartridge 50µm.
 Recommended for manual water softeners.
 Ø 5", Coupling 3/4" G

005480



OS1029
Wound cartridge 9" 50µm
 Ø 61 H 247 mm
 for OS1423

005480
Carbon block cartridge 5µm
 for OS1423

OS1027
Wound cartridge 5" 50µm
 Ø 61 H 127 mm
 for OL1140 and OL1141

OS2250
Carbon block cartridge 5µm
 for OL1140 and OL1141



OS2165
Salt for water softener
 25 kg package



Cationic Resin
 suitable for all softeners with use of resin, of any capacity

OS2191
 5 kg package (lt 6,14)

OS2192
 10 kg package (lt 12,28)

OS0333
 25 kg package (lt 30,71)



OS1090
Resin sanitiser for automatic water softeners
 ▶ resin disinfection device for Autotrol 255 Logix valve with salt alarm
 ▶ water softeners codes OS1079-OS1083-OS1089



OS2245
Watertight pH/EC/TDS/ Temperature meter – scale EC/TDS low

Pocket watertight instrument for :
 - pH/EC/TDS/ (3999 µS/cm, 2000 ppm)
 - temperature 0: 60°C
 - scale EC/TDS low



OS1701
Total carbonate hardness kit

Floating watertight body
 Replaceable pH electrode with renewable fibre junction with a large display with two levels of reading and auto shutoff in case of inactivity.
 The instrument comes complete with protective hood, electrode replacement key, batteries and instructions.

Dim.mm 163 x 40 x 26 mm
 Weight: 100 g



002453
Resin sanitizer for water softener



Water treatment

Purity C Quell ST



OS1628

Purity C 150 Quell ST System

- Capacity 2408 l at 10° dH with bypass 40% (coffee machines)
- Capacity 1656 l at 10° dH with bypass 10% (ovens)
- working temp. 4°C-30°C
- min/max pressure 2-8.6 bar
- Head connections 3/8"
- dim. Ø117x417h, complete with digital flow meter (OS2555), water hardness test (OS1701) and Head with bypass (OS1638)



OS1629

Purity C 300 Quell ST System

- Capacity 4000 l at 10° dH with bypass 40% (coffee machines)
- Capacity 2750 l at 10° dH with bypass 10% (ovens)
- working temp. 4°C-30°C
- min/max pressure 2-8.6 bar
- Head connections 3/8"
- dim. Ø125x464h, complete with digital flow meter (OS2555), water hardness test (OS1701) and Head with bypass (OS1638)



OS1630

Purity C 500 Quell ST system

- Capacity 6800 l at 10° dH with bypass 40% (breakfasts)
- Capacity 4675 l at 10° dH with bypass 10% (ovens)
- working temp. 4°C-30°C
- min/max pressure 2-8.6 bar
- Head connections 3/8"
- dim. Ø149x553h, complete with digital flow meter (OS2555), water hardness test (OS1701) and Head with bypass (OS1638)



OS1631

Purity C 1100 Quell ST System

- Capacity 11,500 l at 10° dH with bypass 40% (breakfasts)
- Capacity 7906 l at 10° dH with bypass 10% (ovens)
- working temp. 4°C-30°C
- min/max pressure 2-8.6 bar
- Head connections 3/8"
- dim. Ø184x553h, complete with digital flow meter (OS2555), water hardness test (OS1701) and Head with bypass (OS1638)

Water treatment

Purity C Quell ST System accessories and replacement cartridges



OS1054
Cartridge
Purity C 150 Quell ST

OS1055
Cartridge
Purity C 300 Quell ST



OS1056
Cartridge
Purity C 500 Quell ST

OS1708
Cartridge
Purity C 1100 Quell ST



OS1892
Service cartridge Purity C
for cleaning, disinfection
and descaling of
equipment directly
connected.
Ø 125 mm - H 233 mm
maximum cartridge capacity 0.5 l
operating pressure 0.5-8.6 bar
temp. water inlet 4-30 ° C
The cartridge does not include the
head OS1638



OS2555
Digital volumetric litre counter
Flow meter 10-100A
flow rate 10-100 l/h
temp. 4°C-30°C
max 8 bar
indicates the remaining litres the
filtration
system can treat
Battery powered



OS1638
Head with bypass
variable 0%-70%
and rinsing valves
male connections 3/8"

OS2123
Brita PURITY C reduction kit
3/4"-3/8"
Set of 2 pieces



OS2132
Cartridge
Filter Purity C 1000 AC
Ideal for vending machines for
cold and hot drinks

OS2226
Set of 20 cartridges
Purity C 1000 AC

Water treatment

Purity STEAM for OVENS



OS1632
Purity STEAM 450 filter
with MDU -litre counter system
included
Capacity 3,680 l at 10° dH with
bypass at pos.1
working temp. 4°C-30°C
max press. 6.9 bar
Inlet/outlet head connections
G1" - G3/4"
dim. Ø249x408h



OS1633
Purity STEAM 600 filter
with MDU -litre counter system
included
Capacity 5,771 l at 10° dH with
bypass at pos.1
working temp. 4°C-30°C
max press. 6.9 bar
Inlet/outlet head connections
G1" - G3/4"
dim. Ø249x520h



OS1634
Purity STEAM 1200 filter
with MDU- litre counter system
included
Capacity 10,800 l at 10° dH with
bypass at pos.1
working temp. 4°C-30°C
max press. 6.9 bar
Inlet/outlet head connections
G1" - G3/4"
dim. Ø249x550h

Purity STEAM System accessories and replacement cartridges

OS1635



OS1635
Purity STEAM 450 cartridge

OS1636
Purity STEAM 600 cartridge

OS1637
Purity STEAM 1200 cartridge

Water treatment

Purity C STEAM for ovens



OS2491
PURITY C 500 STEAM kit
complete with cartridge (OS2490)
and head (OS2489)



OS2492
PURITY C 1100 STEAM kit
complete with cartridge (OS2488)
and head (OS2489)

Accessories Purity C STEAM for ovens and replacement cartridges



OS2490
Cartridge PURITY C 500 STEAM



OS2489
Head PURITY C STEAM
3/8" M

OS2488
Cartridge PURITY C 1100 STEAM



OS1701
Total carbonate hardness kit

Water treatment

Purity Clean and Clean Extra



OS0801
PURITY 1200 CLEAN filter system
 with PARTIAL demineralisation
 including filter cartridge.
 Connections: inlet G1"- outlet
 G3/4"
 Min./max inlet pressure: 2-6 bar
 Working temperature 4°-60°C
 Capacity: 13.000 l at 10° KH



OS0803
PURITY 1200 EXTRA filter system
 with TOTAL demineralisation
 including filter cartridge.
 Connections: inlet G1"- outlet
 G3/4"
 Min./max inlet pressure: 2-6 bar
 Working temperature 4°-60°C
 Capacity: 5.000 l at 10° KH

Purity CLEAN and CLEAN EXTRA System accessories and replacement cartridges



OS0802
PURITY 1200 CLEAN cartridge



OS0804
PURITY 1200 CLEAN EXTRA
 cartridge



OS2555
Digital volumetric litre counter
 Flow meter 100-100A
 flow rate 10-100 l/h
 temp. 4°C - 30°C max 8 bar
 Indicates the remaining litres the
 filtration system can treat
 Battery powered



OS1223
**Head for Purity CLEAN and
 CLEAN EXTRA**
 with bypass

OS2556
Digital volumetric litre counter
 Flow meter 100-700A
 flow rate 100-700 l/h

Purity AquaQuell System accessories and replacement cartridges

OS0797



OS0797
Purity AquaQuell 450 cartridge

OS0798
Purity AquaQuell 600 cartridge

OS0683
Purity AquaQuell 1200 cartridge

Water treatment with reverse osmosis system

Reverse osmosis filtration system with atmospheric boiler



OS1822
Reverse osmosis filter
supply voltage:
220 ... 240 V / 1N ph / 50/60 Hz
power consumption 0.18kw
feed water pressure: 1 - 4 bar
water temperature of
power supply: 5-35 ° C
water inlet pipe dimensions: 3/4 "



OL1140
Water filter NK111
with wound cartridge 50µm.
Recommended for manual water
softeners. Ø5" , Coupling 3/8" G

OS2250
Carbon block cartridge 5µm
for OL1140 and OL1141

OPRAH2
Wheels for reverse osmosis filter
Kit of 4 pcs



OS1821
Replacement filter cartridge
for osmosis



OS1826
Head with wall bracket



OPY39
Container
for filter membrane 3012
connection 1/4 "- 3/8"
(membrane not included)



OS1848
Filter membrane 3012
300 GPD

Water treatment with reverse osmosis system

Spare parts for reverse osmosis filter RO600C



OS0730
Descaler kit for osmosis membrane cleaning
Complete with 2 carbon filters and 1 descaling agent 200gr

OS0728
Carbon filter for RO600C



OS0735
Pump filter with membranes for RO400/600"

OS0738



OS0738
Pump kit RO600

OS0736
Protective bushing

OS0737
Motor RO600 23V



ml.

1200

1150


1100

1050

1000

950

900



Pumps for detergents

Index

Pumps for food segment	page 42
Pumps for laundry segment	page 44

Pumps for food segment



Peristaltic pump for detergent

model PR4 with analogic dosing regulation squeeze tubes made in santoprene used as accessory for the dishwashers without built-in dosing systems

- ▶ easy regulation
- ▶ supplied with fixing bracket, injection connection, suction tube, outlet tube and filter

Code	Compatible with
OS0669	glasswasher, undercounter, front loading, hood type, rack type without built-in dosing system

- ▶ power consumption: 3,5w
- ▶ power supply: 230V, 50Hz
- ▶ pressure: 0,1 bar
- ▶ flow: 0,6 - 4l/h



Fixed speed peristaltic pump for detergent

model PR6 with analogic dosing regulation by conductivity probe, squeeze tubes made in santoprene

- ▶ used as accessory for the dishwashers without built-in dosing systems
- ▶ easy regulation
- ▶ supplied with fixing bracket, injection connection, suction tube, outlet tube filter and conductivity probe

Code	Compatible with
OS0670	glasswasher, undercounter, front loading, hood type, rack type without built-in dosing system

- ▶ power consumption: 3,5w
- ▶ power supply: 230V, 50Hz
- ▶ pressure: 0,1 bar
- ▶ flow: 6l/h



Peristaltic pump for rinse aid

model PR1 with analogic dosing regulation tubes made in sekobil

- ▶ used as accessory for the dishwashers without built-in dosing systems
- ▶ easy regulation
- ▶ supplied with fixing bracket, injection connection with non-return valve, suction tube, outlet tube, filter, pipe connection of "f" 6-8 mm, for single tank machines

Code	Compatible with
OS0671	glasswasher, undercounter, front loading, hood type, rack type without built-in dosing system

- ▶ power consumption: 3,5w
- ▶ power supply: 230V, 50Hz
- ▶ pressure: 3 bar
- ▶ flow: 0,2 - 1l/h



OU1032

Dosing pump G200

230V 50Hz;
detergent flow rate 0.777g/sec,
max flow rate 2 l/h



OS0672

Dosing system TWINDOSE 40

- ▶ microprocessor control with
- ▶ LCD display
- ▶ Detergent dosing - conductivity or timed
- ▶ Rinse aid dosing - speed or timed
- ▶ Detergent pump: santoprene tube flow rate 12.5 l/h
- ▶ Rinse aid pump: SekoBril tube
- ▶ flow rate 2.5 l/h 3 bar
- ▶ Max absorb. 20 W
- ▶ Switching power supply from 80 to 265 Vac 50Hz for tunnel machines

Pumps for food segment



OL3182
Rinse aid dispenser
 flow adjustment screw
 from 0 to 4 cm³/cycle complete
 with hose connectors
 bottom filter with bushing
 in steel and tube



OL3200
Rinse aid dispenser
 flow adjustment screw
 from 0 to 4 cm³/cycle



OHA055
Rinse aid dispenser
 type 1000



OHA056
Rinse aid dispenser
 type 3000 with filter



OS2285
Rinse aid peristaltic pump
 model PG 0.4
 flow rate: 0.4 l/h
 pressure: 3 bar
 Power supply:
 230 V - 50/60 Hz
 complete with: 4 m PE tube
 4x6, filter and bottom weight, rinse
 aid
 injection valve
 ROHS certification



OS1986
Detergent peristaltic pump
 model PG 3
 flow rate: 3 l/h
 pressure: 0.1 bar
 Power supply:
 230V - 50/60 Hz
 complete with: 4 m PE tube 4x6,
 filter and bottom weight, passwall
 ROHS certification




OS0706
Rinse aid peristaltic pump
 model NBR 0.4
 flow rate reg. t/p: 0.4 l/h
 pressure: 3bar
 Power supply: 230V- 50Hz
 complete with:
 ▶ 2 m suction pipe
 ▶ 2 m delivery pipe, s/steel
 bottom weight and filter,
 injection connection with non-
 return valve for rinse aid
 ▶ ROHS certification



OS1987
Detergent peristaltic pump
 model NBR 3
 flow rate reg. t/p : 3 l/h
 pressure: 0.1 bar
 Power supply: 230V - 50 Hz
 complete with pipes and
 connections
 ROHS certification

Pumps for laundry segment



Dosave

Peristaltic pumps, with external easy connection box from washer extractors, designed for easy installation, easy programming, easy savings:

- ▶ **ClarusVibe:** Electrolux Professional washer extractors with ClarusVibe control.
- ▶ **Save on chemicals:** never overuse chemicals again.
- ▶ **Easy installation:** plug&play connection from washers. No need to open the washer panels for wiring.
- ▶ **Easy programming:** all is managed by ClarusVibe from washers in ml/kg. No need extra PC with dedicated software installed.
- ▶ **Flexible pumps extension:** available for 2,3,4,5 products, while if more needed, easily fit up to 15 pumps via modular extension.
- ▶ **Low level alarm:** always a step ahead when the chemical is running low. A warning message appears on the washers' ClarusVibe screen.
- ▶ **Statistics management:** All dosing reports/ statistics can be download directly from washer and easily monitor the savings.

Code	PNC	Description
1LSMZT	988930011	Complete kit with 2 pumps, Silicone tubes, 350 ml/min
1LSMZU	988930012	Complete kit with 3 pumps, Silicone tubes, 350 ml/min
1LSMZV	988930013	Complete kit with 4 pumps, Silicone tubes, 350 ml/min
1LSMZW	988930014	Complete kit with 5 pumps, Silicone tubes, 350 ml/min

- ▶ Power supply from the washer extractor 220-240V 50-60Hz /3A (Max)
- ▶ Water supply (flush manifold): Min 1.8bar - Max 6bar



Jetsave

Venturi pumps, designed for easy installation, easy programming, easy savings, enhance the accuracy of chemical delivery while reducing costly system maintenance.

- ▶ **ClarusVibe:** Eletrolux Professional washer extractors with ClarusVibe control.
- ▶ **Save on chemicals:** impossible to avoid chemical savings, never overuse chemicals again.
- ▶ **Easy installation:** plug&play connection from washers. No need to open the washer's panels for wiring.
- ▶ **Easy programming:** all is managed by ClarusVibe from washers in ml/kg. No need extra PC with dedicated software installed.
- ▶ **Flexible pumps extension:** available for 2,3,4,5 products, while if more needed, easily fit up to 15 pumps via modular extension.
- ▶ **Low level alarm:** always a step ahead when the chemical is running low. A warning message appears on the washers' ClarusVibe screen.
- ▶ **Statistics management:** All dosing reports/ statistics can be download directly from washer and easily monitor the savings.
- ▶ **Less maintenance:** no moving parts or squeeze tubes to wear out
- ▶ **Consistent dosage:** No drop-off, even over a long period of time.
- ▶ **Easier & tidier installation:** built-in flush manifold.

Code	PNC	Description
1LSMZP	988930001	Complete kit with 2 pumps, 550 ml/min
1LSMZR	988930002	Complete kit with 3 pumps, 550 ml/min
1LSMZS	988930003	Complete kit with 4 pumps, 550 ml/min
1LSMZK	988930004	Complete kit with 5 pumps, 550 ml/min

- ▶ Power supply from the washer extractor 100-240V 50-60Hz /0.1A (Max)
- ▶ Water supply: Min 1.8bar - Max 6bar

Pumps for laundry segment



EDS – Efficient Dosing System

Efficient Dosing System automatically adjusts the quantity of detergent to the real load of your Electrolux Professional washer extractor.

- ▶ Compatible with Electrolux Professional Laundry washer extractors equipped with Compass Control ,
- ▶ Compass Pro or Clarus Control
- ▶ Knows the selected program directly from the washer extractors control panel
- ▶ Variable temperature and time process validation to fulfill different hygiene regulation in different countries
- ▶ Integrated USB port to collect statistics and monitor easily the savings
- ▶ PC software to prepare the formulas an upload in the controller via a USB memory for an easy installation
- ▶ 350 ml squeeze tube for a fast dosing of detergent
- ▶ Made on measure for Electrolux Professional Compass Control® , Compass Pro® and Clarus Control® all connections delivered with the apparel for an easy and quick installation
- ▶ Available in 2, 3, 4, 5 or 6 pumps version to match any kind of application

Code	PNC	Description
1L081P	988916901	Complete kit with 2 pumps: 230V 50/60Hz
1L081V	988916911	Complete kit with 2 pumps: 115V 60Hz
1L081R	988916902	Complete kit with 3 pumps: 230V 50/60Hz
1L081W	988916912	Complete kit with 3 pumps: 115V 60Hz
1L081S	988916903	Complete kit with 4 pumps: 230V 50/60Hz
1L081X	988916913	Complete kit with 4 pumps: 115V 60Hz
1L081T	988916904	Complete kit with 5 pumps: 230V 50/60Hz
1L081Y	988916914	Complete kit with 5 pumps: 115V 60Hz
1L081U	988916905	Complete kit with 6 pumps: 230V 50/60Hz
1L081Z	988916915	Complete kit with 6 pumps: 115V 60Hz



ED Venturi

Combines the best of EDS with the best of Venturi pumps to automatically adjust the quantity of detergent to the real load of your Electrolux Professional washer extractor, delivering the best wash result in a sustainable way together with a low maintenance, venturi-based, water-powered laundry unit.

- ▶ Compatible with Electrolux Professional Laundry washer extractors equipped with Compass Control® , Compass Pro® or Clarus Control®
- ▶ 3 or 5 chemical products in a single cabinet
- ▶ Chemical saving: thanks to our unique Automatic Saving and Efficient Dosing controller
- ▶ Low maintenance - No peristaltic tubes, no routine maintenance, low total installed cost, no moving parts
- ▶ Wide range of consistent output - 500ml/min or 1500ml/min
- ▶ Integrated flushing manifold for long distance delivery
- ▶ Integrated USB port to collect statistics and monitor easily the chemical savings
- ▶ PC software to prepare the formulas and upload in the controller via a USB memory for an easy installation

Code	PNC	Description
1LSNCG	988930024	ED Venturi 3 PROD LF Low Flow 500ml
1LSNCF	988930023	ED Venturi 3 PROD HF High Flow 1500ml
1LSNCE	988930022	ED Venturi 5 PROD LF Low Flow 500ml
1LSNCD	988930021	ED Venturi 5 PROD HF High Flow 1500ml

Safety at a glance

QR code

All Electrolux Professional chemicals present a label QR code for immediate safety data sheet download



Safety Data Sheet

Safety Data Sheets are compatible with all devices (i.e. smart phones, tablets, computers).

Just select your Country and the proper SDS will be immediately available for you.



A safety data sheet, or SDS, is a standardized document that contains safety and health data, chemical properties, health and environmental hazards, protective measures, as well as safety precautions for storing, handling, and transporting chemicals.



Safety data sheets have sixteen sections; here the list of the sections you may be more interested in:

- Section 1** Product identifier and Emergency telephone numbers
- Section 3** Composition
- Section 4** First aid measures
- Section 7** Handling and storage
- Section 8** PPE
- Section 9** Physical and chemical properties
- Section 14** Transport Information



Excellence is central to everything we do.
By anticipating our customers' needs, we strive for
Excellence with our people, innovations, solutions and services.
To be the OnE making our customers' work-life easier,
more profitable – and truly sustainable every day.

Follow us on



www.electroluxprofessional.com

Excellence with the environment in mind

- ▶ All our factories are ISO 14001-certified
- ▶ All our solutions are designed for low consumption of water, energy, detergents and harmful emissions
- ▶ In recent years over 70% of our product features have been updated with the environmental needs of our customers in mind
- ▶ Our technology is RoHS and REACH compliant and over 95% recyclable
- ▶ Our products are 100% quality tested by experts

