



Electrolux
PROFESSIONAL



**Genuine
Replacement
Parts,
Accessories
& Consumables
Catalogue 2026**

www.electroluxprofessional.com

INDEX

Genuine Replacement Parts, Accessories and Consumables Catalogue	1
---	----------

INDEX

Genuine Replacement Parts, Accessories and Consumables Catalogue

Genuine Replacement Parts

Cam Switches	1
Castors	5
Electric Plates	10
Energy Regulators	14
Extractor Fans, Speed Regulators and Filters	15
Feet	18
Flame Controls	20
Flexible Gas Pipes	21
Flexible-Extensible Gas Pipes	22
Gas Taps	22
Accessories for Gas Taps	25
Heating Elements	28
Oven Hinges	30
Piezo Electric Igniters and Wires	30
Pilot Burners	32
Safety Gas Valves	42
Safety Thermostats	51
Spark Plugs	56
Switches	58
Thermocouples	59
Accessories for Thermocouples	63
Thermostats	64
Water Columns	69
Water Gas Steam Valves	71
Water Taps	73
Brass Solenoid Valves	77
Contactors	79
Cords for Tray Conveyors	84
External Dosing Systems for Dishwashers	85
Accessories for External Dosing Systems	86
Inlet and Drain Water Pipes	89
Internal Dosing Systems for Dishwashers	92
Accessories for Internal Dosing Systems	93
Magnetic Coils for Solenoid Valves	94
Pressure Switches	95
Siphons - Drains - Overflows	99
Solenoid Valves	101
Taps	109
Water Columns for Counters (K-series)	111
Cables and Plugs	111
Fuses	112
Lighting	115
Quartz Heating Elements	120
Switches	120
Accessories for Cold Rooms	122
Anti-Acid Filter Driers	123
Castors	125

Cold Room Handles	125
Digital Thermoregulators	126
Accessories for Thermoregulators	129
Fan Motors and Timers	133
Hermetic Compressors	134
Accessories for Compressors	141
Hermetic Condensing Units	143
Pressure Switches	146
Tangential Fans	147
Thermostatic Valves and Orifices	148

Accessories and Consumables

Bundles	151
Router/Hub/Boards	152
Blast Chiller Probes	152
Castors	153
Detergents for Automatic Washing	153
Feet	154
Gas Conversion Kits	155
GN Grids and Trays	155
GN Inox Basins	159
GN Plastic Basins	161
Accessories for Basins	163
GN Stainless Steel Trays	164
Grease Filters	166
Grids and Trays for Bakery - Pastry	167
Grids and Trays for Convection Ovens	168
Oven Probes	169
Professional Tool Supplies	169
Smokers and Accessories	170
Sous-vide Cooking	171
Sous-vide Storage	172
Thermal Covers	180
Washing Systems	180
Water Treatment for Ovens	182
Accessories for Boiling Pans	184
Accessories for Bain-Marie	185
Accessories for Braising Pans	185
Castors	185
Accessories for Electric Modular Cookers	185
Accessories for Fry Tops	186
Accessories for Fryers	187
Accessories for Gas Modular Cookers	193
Accessories for GourmeXpress - Cleaning	196
Accessories for GourmeXpress - Cooking	197
Grids	197
Accessories for Grills	199
Accessories for Induction	199
Accessories for Modular Cooking Ovens	201
Accessories for Pasta Cookers	201

Accessories for Speedelight - Cleaning	205
Accessories for Speedelight - Cooking	206
Chemical Products	207
Detergency	212
Electrolux Professional Descaling	216
Electrolux Professional Detergents for Cooking Plates	216
Electrolux Professional Detergents for Coffee Machines	217
Electrolux Professional Detergents for Dishwashers	217
Electrolux Professional Detergents for Equipment and Surfaces	218
Electrolux Professional Detergents for Ovens, Speedelight and GourmeXpress	219
Electrolux Professional Liquid Detergents for Ovens	219
Electrolux Professional Powder Detergents for Ovens	220
Baskets for Pot Washers	220
Accessories for Baskets	221
Baskets for HeroDry	225
Electrolux Professional Detergents for Dishwashers	226
External Dosing Systems For Dishwashers	227
Accessories For External Dosing Systems	227
Foot Mixer Taps	227
Mixer Taps and Shower Groups	230
Accessories for Water Taps and Shower Groups	235
Plastic Baskets 500x250mm	236
Plastic Baskets 500x500mm	237
Plastic Baskets 600X500mm	241
Plastic Baskets for Glasswashers	242
Accessories for Plastic Baskets - Glasswashers	242
Rubber Collar for Waste Disposal	243
Shower Groups	243
Accessories for Shower Groups	245
Wall Washing Units	245
Water Treatment	247
Wire Baskets 500x500mm	248
Wire Baskets for Glasswashers	249
Accessories for Wire Baskets	251
B2000 - B3000	252
BE5	254
BE8	255
BMX60 - BMXE60 - XBE60	255
BMXE80 - XBE80	257
CT6/10 - DTA - CF4	258
Ditomix	258
Emix	259
K120/KE120 - K120S/KE120S	260
K180/KE180 - K180S/KE180S	261
K25 - K35 - K45 -K 55 -K70	262
MB40 - MBE40	263
Mini Green	265
Multigreen	266
RC14	268
Speedy Mixer	269
T10E - T15E	270

T5S - T5E/T5M - T8E/T8M	271
Ti25 - T25E	273
TR260	274
TR300	279
TrinityPro	280
TRK45 - TRK55 -TRK 70	284
TRS - TR210	286
XBM10 - XBE10	294
XBM20 - XBE20 - XBB20	295
XBM30 - XBE30 - XBB30	297
Accessories For Planetary Mixers	298
Accessories for Dynamic Preparation	299
Accessories for Cold Rooms	300
Accessories for Breeding Station	300
Anti-Vibration Plates	304
Basins	304
Castors	305
Grids	306
Modular Shelving	309
Shelf Guides	312
Wire Baskets	313
Measuring Gauges	314
Ppe	325
Tools	328
Trolleys	330
Automatic Water Softeners	331
Manual Water Softeners	335
Consumables For Manual and Automatic Water Softeners	336
Reverse Osmosis Water Treatment	338
Water Treatment	341

Cam Switches

Code	Spare Part Description	Picture
003142	Cam switch 0-1 pos 2 control positions - 2 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23mm faston connections 6.3x0.8mm	
0K8420	Cam switch 0-1 pos 2 control positions - 2 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23mm screw connections	
0A2036	Cam switch 0-1 pos 2 control positions - 2 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23mm faston connections 6.3x0.8mm rear hole for thermostat	
028390	Cam switch 0-1 0-1 pos 2 control positions - 2 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23mm screw connections	
0A2241	Cam switch 0-1 0-1 pos 4 control positions - 4 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23mm faston connections 6.3x0.8mm	
0H6682	Cam switch 0-1 0-1 pos 4 control positions - 4 poles contacts with capacity 32A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm screw connections	
032677	Cam switch 0-1 pos 2 control positions - 4 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23mm faston connections 6.3x0.8mm	
026945	Cam switch 0-1 pos 2 control positions - 4 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23mm screw connections rear hole for thermostat	
0A2134	Cam switch 0-1 auxiliary pos 2 control positions - 4 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23mm faston connections 6.3x0.8mm	



Cam Switches

Code	Spare Part Description	Picture
048271	Cam switch 0-1-2 pos 3 control positions - 3 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 26mm faston connections 6.3x0.8mm	
054375	Cam switch 0-1 auxiliary pos 2 control positions - 2 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23mm faston connections 6.3x0.8mm	
006649	Cam switch 0-1 pos 2 control positions - 4 poles contacts with capacity 32A-250V crescent pin Ø 6x4.6 mm shaft length 23mm screw connections	
0L3145	Cam switch 0-1-2 pos 3 control positions - 3 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23mm faston connections 6.3x0.8mm	
0KV045	Cam switch 0-1-2 pos 3 control positions - 8 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23mm faston connections 6.3x0.8mm	
032857	Cam switch 0-3 pos 4 control positions - 2 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 17 mm screw connections	
0K6631	Cam switch 0-3 pos 4 control positions - 3 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	
0G7663	Cam switch 0-3 pos 4 control positions - 3 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	
059544	Cam switch 0-3 pos 4 control positions - 5 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	



Cam Switches

Code	Spare Part Description	Picture
0K4921	Cam switch 0-3 pos 4 control positions - 4 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm screw connections	
0S3298	Cam switch 0-3 pos 4 control positions - 4 pole contacts with 16A-250V capacity, crescent pin Ø 6x4.6 mm, shaft length 23 mm, faston connections 6.3x0.8 mm	
0C7965	Cam switch 0-3 pos 4 control positions - 8 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 17 mm faston connections 6.3x0.8mm	
0H6683	Cam switch 0-3 pos 4 control positions - 4 poles contacts with capacity 32A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm screw connections	
0C9725	Cam switch 0-3 pos 4 control positions - 11 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	
0K1383	Cam switch 0-3 pos 4 control positions - 3 poles contacts with capacity 32A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm screw connections	
052749	Cam switch 0-4 pos 5 control positions - 3 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm screw connections	
0C9080	Cam switch 0-4 pos 5 control positions - 7 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 24 mm faston connections 6.3x0.8mm	
0C7353	Cam switch 0-4 pos 5 control positions - 11 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	



Genuine Replacement Parts

Cam Switches

Code	Spare Part Description	Picture
0K5159	Cam switch 0-5 pos 6 control positions - 6 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	
048286	Cam switch 0-5 pos 6 control positions - 1 pole contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	
0H6685	Cam switch 0-6 pos 7 control positions - 3 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	
053408	Cam switch 0-6 pos 7 control positions - 6 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	
0K4914	Cam switch 0-6 pos 7 control positions - 5 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	
0C3936	Cam switch 0-6 pos 7 control positions - 7 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm screw connections	
0A2021 710A2021	Cam switch 0-6 pos 7 control positions - 3 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm screw connections	
0A2022	Cam switch 0-6 pos 7 control positions - 3 poles contacts with capacity 32A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm screw connections	
002661	Cam switch 0-6 pos 7 control positions - 5 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	



Cam Switches

Code	Spare Part Description	Picture
004741	Cam switch 0-6 pos 7 control positions - 7 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	
0CBCZ3	Cam switch 0-6 pos 7 control positions - 6 pole contacts with 16A-250V capacity crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8 mm	

Castors

Code	Spare Part Description	Picture
0S0124	Pivoting wheel with brake with round expansion Ø 21.5 H 68 mm dim. Ø 125x30 mm	
0S0125	Pivoting wheel with brake with square expansion 20.5x20.5 H 68 mm dim. Ø 125x30 mm	
0S0126	Pivoting wheel with brake with square expansion 37.5x37.5 H 68 mm dim. Ø 125x30 mm	
0S1428	Pivoting wheel with brake dim. Ø 125x30 mm	



Genuine Replacement Parts

Castors

Code	Spare Part Description	Picture
003342	Swivel wheel with brake and pin Ø 19 mm H 45 mm dim. Ø 125x30 mm	
003656	Swivel wheel with brake with M10x1.5 screw dim. Ø 100x30 mm	
0S0127	Swivel caster without brake with round expansion Ø 21.5 H 68 mm dim. Ø 125x30 mm	
0S0128	Swivel caster without brake with square expansion 20.5x20.5 H 68 mm dim. Ø 125x30 mm	
0S0129	Pivoting wheel without brake with square expansion 37.5x37.5 H 68 mm dim. Ø 125x30 mm	
0S1427	Swivel wheel without brake dim. Ø 125x30 mm	
003341	Swivel wheel without brake with pin Ø 19 mm H 45 mm dim. Ø 125x30 mm	



Castors

Code	Spare Part Description	Picture
033657	Swivel wheel without brake dim. Ø 100x30 mm	
0S0122	Swivel plate wheel without brake fixing plate 90x70 mm wheelbase 70x50 mm dim. Ø 125x30 mm	
0S3041	Fixed plate wheel without brake fixing plate 100x85 mm hole distance 80/77 x 60 mm dim. Or 100x36 mm	
0S1434	Fixed plate wheel without brake fixing plate 105x85 mm hole distance 80/77 x 60 mm dim. Ø 125x32 mm For kit PNC 922003	
0CA963	Fixed plate wheel without brake fixing plate dim. 105x85 mm hole spacing 80/77 x 60 mm dim. Ø 125x40 mm For kit PNC 206135	
032148	Fixed plate wheel without brake fixing plate 136x105 mm wheelbase 105x80 mm dim. Ø 160x40 mm	
032146	Swivel plate wheel with brake fixing plate 136x105 mm wheelbase 105x80 mm dim. Ø 160x40 mm	



Castors

Code	Spare Part Description	Picture
087111	Swivel plate wheel without brake fixing plate dim. 105x85 mm hole spacing 80/77 x 60 mm dim. Ø 125x32 mm For kit PNC 880025	
0S3024	Swivel wheel without brake with pin M12x30 mm dim. Ø 100x30 mm	
093280	Swivel plate wheel with brake fixing plate dim. 105x85 mm hole spacing 80/77 x 60 mm dim. Ø 125x40 mm For kit PNC 206135	
0C1631	Swivel wheel with brake and pin M12x30 mm dim. Ø 100x30 mm	
0C1632	Swivel wheel without brake with pin M12x30 mm dim. Ø 125x30 mm	
0S2626	Swivel wheel with brake and pin M12x30 dim. Ø 125x30 mm	



Castors

Code	Spare Part Description	Picture
0S2627	Swivel wheel without brake with M12x30 pin dim. Ø 125x30 mm	
0S0882	Square expansion nut zinc. M10 E14 20.5x20.5mm H 68 mm for OS0125 Code Qt. Description OS2590 1 Screw, OS2591 1 Adaptor from 12.8 to 10, OS2592 1 Washer, OS2593 1 Knurled washer, OS2594 1 Square expander	
033655	Square expansion nut zinc. M10 E14 36x36mm H 42 mm for square section leg tables For kit PNC 855030	
0S1209	Round expansion Ø 21.5 H 68 mm for OS0127 Code Qt. Description OS2590 1 Screw, OS2591 1 Adaptor from 12.8 to 10, OS2592 1 Washer, OS2593 1 Knurled washer, OS2595 1 Round expander	
0PE119	Round expansion nut zinc. M10 E14 Ø 50mm H 42 mm for round section leg tables	
0S0123	Swivel plate wheel with brake fixing plate 90x70 mm wheelbase 70x50 mm dim. Ø 125x30 mm	
0S1068	Round hole bumper Ø 25 mm Code Qt. Description 032018 4 Bumper	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Genuine Replacement Parts

Castors

Code	Spare Part Description	Picture
0S1069	Kit of 4 bumpers with square hole 25x25 mm Code Qt. Description 0S0121 4 Bumper	
033717	Bumper for trolley side 90 mm	
087110	Swivel plate wheel with brake fixing plate dim. 105x85 mm hole spacing 80/77 x 60 mm dim. Ø 125x32 mm For kit PNC 922003 and 880025	

Electric Plates

Code	Spare Part Description	Picture
0S1438	Radiant resistance 1200W 230 V for glass ceramic dim. Ø 165 mm	
053406	Electric griddle 1500W 230V dim. Ø 145 mm	
0G6313	Electric griddle 1500W 230V dim. Ø 180 mm	



Electric Plates

Code	Spare Part Description	Picture
0KJ793	Electric plate 1500W 400V dim. Ø 180 mm	
0KI634	Radiant resistance 1800W 230 V for glass ceramic dim. Ø 180 mm	
003930	Electric plate 1500W 400V dim. Ø 145 mm	
0K0356	Electric griddle 2000W 400V dim. Ø 220 mm	
0H6080	Electric plate 2500W 400V dim. Ø 310 mm	
004914	Electric hotplate 2000W 230V dim. Ø 180 mm	
053407	Electric plate 2600W 230V dim. Ø 220 mm	



Electric Plates

Code	Spare Part Description	Picture
053606	Electric plate 2600W 240V dim. Ø 220 mm	
003931	Electric plate 2600W 400V dim. Ø 220 mm	
003929	Electric plate 2600W 440V dim. Ø 220 mm	
0S2625	Electric griddle 2000W 230V dim. Ø 220 mm	
006220	Electric plate 2600W 230V dim. 220x220 mm	
0C6243	Electric plate 2600W 400V dim. 220x220 mm	
0C6244	Electric plate 2600W 440V dim. 220x220 mm	
0H6079	Electric griddle 2500W 400 V folding plate dim. 300x300 mm	



Electric Plates

Code	Spare Part Description	Picture
052198	Electric plate 3000W 240V dim. 300x300 mm	
0K4756	Electric plate 3000W 400V dim. 300x300 mm	
0C4077	Radiant resistance 3400W 230 V for glass ceramic dim. Ø 320 mm	
052199	Electric plate 4000W 230V dim. 300x300 mm	
0C2524	Electric plate 4000W 440V dim. 300x300 mm	
0KD885	Radiant resistance 4000W 400 V for ceramic glass hob with pot size sensor. 300x300 mm	
0H6082	Electric griddle 4000W 400 V folding plate dim. 300x300 mm	



Electric Plates

Code	Spare Part Description	Picture
0K0589	Electric plate 4000W 400 V for ceramic glass hob without sensor pot size. 300x300 mm	
052200	Electric plate 4000W 400V dim. 300x300 mm	
0C8351	Electric plate total power 6500W at a nominal voltage of 400V 3, single element power 2160W at a voltage of 230V. Single-core silicone glass cable THT-VT or equivalent. Conductor: elementary nickel-plated copper wires L=1500mm, nominal voltage 300/500V, operating temperature 250°C, connector with Cembre fork BF-U 4/1 or equivalent.	
0C7411	Electric plate total power 8500W at a nominal voltage of 400V 3, single element power 2830W at a voltage of 230V. Single-core silicone glass cable THT-VT or equivalent. Conductor: elementary nickel-plated copper wires L=1500mm, nominal voltage 300/500V, operating temperature 250°C, connector with Cembre fork BF-U 4/1 or equivalent.	

Energy Regulators

Code	Spare Part Description	Picture
0C1605	Supply voltage 230V; Contact rating: S1-S2 0.6A 400V, P2-4 7A 400V-13A 240V +++ >3mm, P1-2 7A 400V-13A 240V class II; Working range 52-308 degrees (increasing clockwise); maximum ambient temperature 125°C; uniform power regulation 6-70%	

Extractor Fans, Speed Regulators and Filters

Code	Spare Part Description	Picture
0S0708	DDM 7/7 double inlet centrifugal electric fan with directly coupled forward blade impeller complete with inlet protection grille 184W 1400 rpm 4 poles 1 speed power supply 230V single phase 50 Hz	
0S0709	DDM 9/9 double inlet centrifugal electric fan with directly coupled forward blade impeller complete with inlet protection grille 550W 1400 rpm 4 poles 1 speed power supply 230V single phase 50 Hz	
0PE621	DDM 7/7 double inlet centrifugal electric fan with directly coupled forward blade impeller complete with inlet protection grille 300W 1400 rpm 4 poles 1 speed; 230V single-phase 50 Hz power supply	
037807	DDM 8/9 TIGHT double inlet centrifugal fan with forward-curved blades directly coupled complete with inlet protection grille 420W 1400 rpm 4 poles 1 speed; power supply 230V single phase 50 Hz Dim. (LxWxH): 318x378x334 mm	
032279	IP55 single-phase speed regulator - Power 1170 W - Max 6 AMP - dim. 135x74x73h mm	
0S0710	IP55 single-phase speed regulator - Power 1700 W - Max 8 AMP - dim. 160x80x95h mm	
0PR284	Feet for DD 7/7	
0PR285	Feet for DD 9/9	



Extractor Fans, Speed Regulators and Filters

Code	Spare Part Description	Picture
0PR286	Flange for DD 7/7	
0PR287	Flange for DD 9/9	
0PE616	DA 10/8 double inlet centrifugal electric fan with directly coupled forward blade impeller complete with inlet protection grille 550W 1400 rpm 4 poles 1 speed; 230V single-phase 50 Hz power supply	
032986	IP55 single-phase speed regulator - Power 1700 W - Max 8 AMP - dim. 170x105x82h mm	
0S1021	Filter size 350x500x22 mm	
0S0052	Filter size 400x250x22 mm	
0S0050	Filter size 400x400x22 mm	
0S0049	Filter size 400x500x22 mm	
0S2575	Filter size 500x500x22 mm	



Extractor Fans, Speed Regulators and Filters

Code	Spare Part Description	Picture
0S1814	Activated carbon in 25 kg bag, BET surface 750 m ² /g	
032267	Dedalus filter dim. 400x250x30 mm	
032268	Dedalus filter dim. 400x350x30 mm	
032269	Dedalus filter dim. 400x500x30 mm	
0S2402	"Labyrinth" filter dim. 400x250x22 mm	
0S2403	"Labyrinth" filter dim. 400x350x22 mm	
0S2404	"Labyrinth" filter dim. 400x400x22 mm	
0S2405	"Labyrinth" filter dim. 400x500x22 mm	

Genuine Replacement Parts, Accessories and Consumables Catalogue

Genuine Replacement Parts

Feet

Code	Spare Part Description	Picture
053792	Adjustable stainless steel foot connection Ø 2" H 125 mm	
059218	Adjustable foot in AISI 304 connection Ø 2" sleeve and flange H 150÷220 mm	
032550	Adjustable foot in AISI 304 connection Ø 1" black plastic threaded 40x40 mm base ESA H 115÷175 mm	
004249	Adjustable foot in AISI 304 Ø 1" ¾ round base connection Ø 50mm sleeve and flange 80x80 mm H 145÷250 mm	
0C4823	Adjustable foot in AISI 304 connection Ø2" sleeve and flange 74x74 mm H 130÷210 mm	
054418	Adjustable stainless steel foot connection Ø 1½" H 125 mm	



Feet

Code	Spare Part Description	Picture
048579	Adjustable foot in AISI 304 connection Ø 2" round base sleeve and flange 74x74 mm H 135÷235 mm	
0PE204	Adjustable foot in AISI 304 connection Ø 1" white plastic threaded 40x40 mm base ESA H 115÷175 mm	
089140	Adjustable foot in AISI 304 connection Ø 1" 3/4 round base connection Ø 60mm plasticized sleeve and flange 100x110 mm H 130÷190 mm	
0C4824	Adjustable foot in AISI 304 connection Ø 2" sleeve and flange 74x74 mm H 190÷270 mm	
0C0204	Adjustable foot in AISI 304 1" 3/4 connection round base Ø 50 mm sleeve and screw M10x1.5 H 150÷200 mm	
0C4664	Adjustable foot in AISI 304 round base Ø 2" H 135÷210 mm sleeve and flange 74x74 mm	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Genuine Replacement Parts

Feet

Code	Spare Part Description	Picture
049393	Rubber foot Ø 30 mm with M8x1 H 30 mm screw	
0C9565	Flanged foot for floor fixing SET 2PCS in AISI 304 base 80x80 mm center distance 60x60 mm threaded connection 1" 3/4 Ø 50.5 mm height 140mm - useful 100mm Compatible with 0C0204	
026806	Rubber foot Ø 17 mm with M6 screw H 37 mm	
096652	Rubber foot Ø 50 mm with screw M10x35 H 52 mm	

Flame Controls

Code	Spare Part Description	Picture
0C8189	Power supply voltage 220/240Vac 50/60Hz, absorbed power 12VA, operating temperature -20 + 60°C; Humidity 90% max at 40°C; IP40 protection rating; Electrical connections: Flame detection -> male faston 4.8x0.8; CN1 and CN4 -> Molex Male series 2599 for Molex Female series 3001/3002 or compatible	

Flexible Gas Pipes

Code	Spare Part Description	Picture
0S1026	316L stainless steel flexible gas hose with SMOOTH sheath Ø 1/2" FF swivel, L= 500 mm;	
0S1005	316L stainless steel flexible gas hose with SMOOTH sheath Ø 1/2" FF swivel, L= 1000 mm;	
0S1008	316L stainless steel flexible gas hose with SMOOTH sheath Ø 1/2" FF swivel, L= 1500 mm;	
0S1003	316L stainless steel flexible gas hose with SMOOTH sheath Ø 1/2" FF swivel, L= 2000 mm;	
0S1025	316L stainless steel flexible gas hose with SMOOTH sheath Ø 1/2" MF swivel, L= 500 mm;	
0S1006	316L stainless steel flexible gas hose with SMOOTH sheath Ø 1/2" MF swivel, L= 1000 mm;	
0S1007	316L stainless steel flexible gas hose with SMOOTH sheath Ø 1/2" MF swivel, L= 1500 mm;	
0S1015	316L stainless steel flexible gas hose with SMOOTH sheath Ø 1/2" MF swivel, L= 2000 mm;	

Flexible-Extensible Gas Pipes

Code	Spare Part Description	Picture
0S1258	316L stainless steel extensible flexible gas hose with CORRUGATED sheath Ø 3/4" FF swivel, L= 500÷1000mm;	
0S1259	316L stainless steel extensible flexible gas hose with CORRUGATED sheath Ø 3/4" FF swivel, L= 1000÷2000mm;	
0C1074	Gas pressure regulator dim. mm 75x85x71 PNC 927225 Code Qt. Description 006422 1 Pressure regulator , 0C6506 1 Reducer; 3/4"m-1/2"f	
0C6506	Gas reduction from 3/4" to 1/2"	

Gas Taps

Code	Spare Part Description	Picture
054109	PEL 20S gas tap without pilot flame fittings ØM16x1.5 mm thermocouple connection M8x1 crescent pin Ø 8x6.5 mm	
059460	PEL 21S gas tap with pilot flame fittings ØM16x1.5 mm thermocouple connection M8x1 crescent pin Ø 8x6.5 mm	
0C0205	PEL 21S gas tap with pilot flame and special bridle inlet connection Ø 9mm outlet connection ØM16x1.5 mm thermocouple connection M8x1 crescent pin Ø 8x6.5 mm	



Gas Taps

Code	Spare Part Description	Picture
0CBB0G	PEL 21S gas tap Modular 260° radius with pilot flame and special bridle inlet fitting O 9mm outlet fitting OM16x1.5 mm thermocouple connection M8x1 crescent pin O 8x6.5 mm	
052146	PEL 22 V gas tap with pilot flame and vertical flange fittings ØM20x1.5 mm thermocouple connection M9x1 crescent pin length. 26.5 mm Ø 10x8 mm	
052432	PEL 22 V gas tap with pilot flame and vertical flange fittings ØM20x1.5 mm thermocouple connection M9x1 minimum screw Ø 0.30 mm crescent pin Ø 10x8 mm Code Qt. Description 052146 1 Valved gas tap; 22s , 052433 1 Screw; 0,3mm	
004237	PEL 20S gas tap without pilot flame fittings ØM16x1.5 mm thermocouple connection M9x1 crescent pin Ø 8x6.5 mm	
004282	PEL 21S gas tap with pilot flame fittings ØM16x1.5 mm thermocouple connection M8x1 crescent pin Ø 8x6.5 mm pin length 39 mm	
052145	PEL 22 V gas tap with pilot flame and vertical flange fittings ØM20x1.5 mm crescent pin Ø 10x8 mm	
0C0489	PEL 22 V gas tap with pilot flame and vertical flange fittings ØM20x1.5 mm thermocouple connection M9x1 crescent pin Ø 10x8 mm pin length 33.5 mm	
0A2001	PEL 22 O gas tap with pilot flame and horizontal flange with flow regulator fittings ØM20x1.5 mm thermocouple connection M8x1 crescent pin Ø 10x8 mm	
0S0595	PEL 22 O gas tap with pilot flame and horizontal flange with flow regulator fittings ØM20x1.5 mm thermocouple connection M9x1 crescent pin Ø 10x8 mm	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Genuine Replacement Parts

Gas Taps

Code	Spare Part Description	Picture
0C8647	PEL 22S/V gas tap with fine adjustment with pilot flame and vertical flange fittings ØM20x1.5 mm thermocouple connection M9x1 crescent pin Ø 10x8 mm length pin 33 mm / 26 mm	
005466	PEL 23O gas tap with pilot flame and horizontal flange inlet connection ØM28x1.5 mm outlet connection ØM24x1.5 mm thermocouple connection M9x1 crescent pin Ø 10x8 mm length 25 mm pin	
058369	Thermostatic gas tap PEL 24ST fixed fittings ØM20x1.5 mm adjustment range: 120°-320°C thermocouple connection M9x1 bulb Ø 6x100 mm capillary length 1200mm crescent pin Ø 10x8 mm	
0C0060	Thermostatic gas tap PEL 25ST inlet outlet fittings ØM16x1.5 mm adjustment range: 140°-300°C thermocouple connection: M8x1 bulb Ø 6x86 mm capillary length 1000mm crescent pin Ø 8x6.5 mm	
004956	SABAF gas tap gas inlet pipe flange Ø 16mm gas outlet 1/4" Ø 8mm thermocouple connection M8x1 crescent pin Ø 8x6.5 mm complete with bracket and various screws	
0S2375	SABAF gas tap without bracket and various screws	
0C6758	PEL 22 S gas tap with pilot flame and vertical flange with flow regulator fittings ØM20x1.5 mm thermocouple connection M9x1 crescent pin Ø 10x8 mm length. 24.5 mm pin	
054811	PEL 23O gas tap with pilot flame and horizontal flange inlet connection ØM28x1.5 mm outlet connection ØM24x1.5 mm thermocouple connection M9x1 crescent pin Ø 10x8 mm length 34 mm pin	



Gas Taps

Code	Spare Part Description	Picture
006597	Thermostatic gas tap PEL 25ST inlet outlet fittings ØM16x1.5 mm adjustment range: 140°-300°C thermocouple connection: M8x1 bulb Ø 6x120 mm capillary length 1000mm crescent pin Ø 8x6.5 mm Code Qt. Description 002947 1 Minimum screw; dia.0,70 , 004257 1 Gas tap , 004260 1 Minimum screw; dia.0,55 , 004261 1 Minimum screw; dia.0,45 , 005003 1 Minimum screw; dia.1,30 , 052605 1 Minimum screw; dia.0,90 , 052607 1 Minimum screw; dia.1,40 , 056743 1 Minimum screw; dia.0,80	
0K9985	PEL 23S/V gas tap with pilot flame and vertical flange inlet connection Ø 1/2"F outlet connection Ø 1/2"M thermocouple connection M10x1 crescent pin Ø 10mm length. 25 mm pin	
0K5756	22S/O gas tap with pilot flame, horizontal flange, M20x1.5 mm fittings, complete with by-pass ø 0.35 mm, M8x1 thermocouple connection, crescent pin ø 6x4.6 mm, pin length 45/20 mm left	
003719	Approved gas valve, 220/240V supply voltage, M10X1 pilot pipe connection, with slow ignition. Fixed value=4 +-1mbar, pressure adjustment range 20-50mbar	

Accessories for Gas Taps

Code	Spare Part Description	Picture
059854	Cap with PEL 20 pin for taps cod. 054109 - 054628 054629 - 054166 A=Ø 8x6.5 B=22 mm C=21 mm	
0S1934	Cap with PEL 20 pin for tap cod. 004237 A=Ø 8x6.5 B=39.5 mm C=21 mm	



Accessories for Gas Taps

Code	Spare Part Description	Picture
002185	Cap with PEL 21 pin for tap cod. 059460 A=Ø 8x6.5 B=22 mm C=21 mm	
0S0661	Cap with PEL 21 pin for tap cod. 0C0205 A=Ø 8x6.5 B=32 mm C=21 mm	
056597	Cap with PEL 22 pin for taps 052146 - 052145 - 0S0595 - 0A2001 - 0C6758 A=Ø 10x8 B=27 mm C=25 mm	
0S2733	Cap with pin PEL 22 for taps 0C8647 A=Ø 10x8 B=33 mm C=25 mm	
059853	Cap with PEL 23 pin for taps cod. 054811 - 005466 A=Ø 10x8 B=35 mm C=30 mm	
0S0053	Horizontal flange with pressure port for PEL 22	
056594	Magnetic assembly for PEL 22 tap with large head	
056595	Magnetic assembly for PEL 20-21 tap with small head	



Accessories for Gas Taps

Code	Spare Part Description	Picture
0A2125	Pipe fitting Ø10mm for PEL 20-21	
052124	Pipe fitting Ø10mm for PEL 22	
054816	Pipe fitting Ø16mm for PEL 23	
052127	Pilot bicone for Ø4mm tube for PEL 21-22	
020992	Pilot bicone for Ø6mm tube for PEL 21-22	
0K0059	Copper gas tube for pilot ignition Ø 4 mm	
0S3256	Copper gas pipe for pilot ignition Ø 6 mm	
060325	Bicone for Ø10mm tube for PEL 20-21	
052128	Bicone for Ø10mm tube for PEL 22	



Accessories for Gas Taps

Code	Spare Part Description	Picture
052671	Bicone for Ø16mm MINISIT tube	
054815	Bicone for Ø20mm tube for PEL 23	
054817	Bicone for Ø16mm tube for PEL 23 (h 11mm)	

Heating Elements

Code	Spare Part Description	Picture
032086	Etch Foil adhesive resistance 500/595W 220/240V Complete with 150°C thermostat with automatic reset Dim. 290X175 mm	
088274	Etch Foil adhesive resistance 1000W 220V Complete with 200°C thermostat with automatic reset Dim. 400X290 mm	
032666	Etch Foil adhesive resistance 1000/1190W 220/240V Complete with cables Dim. 470X275 mm	
032094	Etch Foil adhesive resistance 1000W 230V Complete with 150°C thermostat with automatic reset Dim. 400X290 mm	



Heating Elements

Code	Spare Part Description	Picture
0RT229	Etch Foil adhesive resistance 390W 240V Complete with cables Dim. 370X95 mm	
088319	Etch Foil adhesive resistance 286W 230V Complete with cables and 150°C thermostat with automatic reset Dim. 470x290 mm	
0S2982	Ceramic resistance 250W 230V Complete with cables Dim. 245x60 mm	
058144	Ceramic resistance 400W 230V Complete with cables Dim. 245x60 mm	
0S2564	Ceramic resistance 1000W 230V Complete with cables Dim. 245x60 mm	
0S2291	Ceramic resistance 500W 230V Complete with cables Dim. 245x60 mm	
0CB382	6000W 400V heating element, with aluminised steel container, lower insulation in pyrogenic silica. Molex connector 42816-0612	
0S3144	Etch Foil Adhesive Resistance 400W 230V Complete with 150°C automatic reset thermostat Dim. 480X280 mm	
0T6667	Ceramic resistance 325W 230V Complete with cables Dim. 122x60x34 mm	

Oven Hinges

Code	Spare Part Description	Picture
059227	Oven hinge complete with roller holder base for HD900	
0A2005	Right oven door hinge with roller holder for mod. ECO 70, ECO 90	
0C0203	Oven hinge complete with roller holder base for N700 and N900	
050766	Oven hinge complete with roller holder base for R700, MD700, PR700, H900	
0S3226	Right hinge for oven door with roller holder for mod. ECO 70, ECO 90	
0S3225	Left hinge for oven door with roller holder for mod. ECO 70, ECO 90	

Piezo Electric Igniters and Wires

Code	Spare Part Description	Picture
0C9240	Piezo igniter complete with rubber cap male faston Ø 2.4 mm serves Ø 18 mm hole	
0C9409	Pasta Cooker Push button cover kit Code Qt. Description 0C9407 1 Push button cover , 0C9408 1 Washer; for piezoelectric igniter	



Piezo Electric Igniters and Wires

Code	Spare Part Description	Picture
0C8410	Piezo igniter mod.MINISIT with faston cover for ignition 6.35x0.8 mm	
0H6070	VERNITRON piezo igniter male faston Ø 2.4 mm serves Ø 22 mm hole	
0C7190	Ignition cable for Mertik valves L=1550 mm ignition faston Ø 2.4 mm spark plug faston Ø 4 mm	
005559	Ignition cable L=1000 mm ignition faston Ø 2.4 mm spark plug faston Ø 2.4 mm	
0C9198	Ignition cable L=710 mm ignition faston Ø 2.4 mm spark plug faston Ø 4 mm silicone rubber tube	
058225	Piezo igniter mod. CP/101 Junkers ignition faston 6.35x0.8 mm spark plug faston Ø 4 mm	
059578	Ignition cable L= 500 mm ignition faston Ø 2.4 mm spark plug faston Ø 4 mm	
004943	Ignition cable L= 600 mm ignition faston Ø 2.4 mm spark plug faston Ø 4 mm	
054273	Ignition cable L= 1000 mm faston 6.35x0.8 mm for ignition faston Ø 4 mm for spark plug	



Piezo Electric Igniters and Wires

Code	Spare Part Description	Picture
002544	Ignition cable L= 1000 mm ignition faston Ø 2.4 mm spark plug faston Ø 4 mm	

Pilot Burners

Code	Spare Part Description	Picture
027073	Single flame pilot burner with Ø 0.20 multigas nozzle complete with 2-position bracket	
004946	2-flame multigas pilot burner with Ø 0.20 mm nozzle complete with bracket, 3 positions	
004216	3-flame pilot burner with Ø 0.20 multigas nozzle complete with 2-position bracket	
029776	2-flame pilot burner with Ø 0.20 multigas nozzle complete with 2-position bracket	
054335	3-flame pilot burner with Ø 0.20 multigas nozzle complete with 3-position bracket	
0H6338	Pilot burner supplied with head and gasket Code Qt. Description 0CBAJ4 1 Pilot burner, 0K2497 1 Screw connection; m10x1 , 0PRS3F 1 Gasket for pilot burner	



Pilot Burners

Code	Spare Part Description	Picture
059379	TARGET pilot burner supplied without spark plug, nozzle and gasket	
0C7102	TARGET pilot burner supplied without spark plug, nozzle and gasket	
059214	Pilot burner supplied without nozzle for HD 900 cooking	
0A2472	Single flame pilot burner supplied without spark plug, nozzle and gasket	
003204	2-flame SX molded pilot burner supplied without spark plug, nozzle and gasket	
0H6336	Molded 3-flame pilot burner supplied without spark plug, nozzle and gasket	
058383	Right molded pilot burner with 2 flames supplied without spark plug, nozzle and gasket	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Genuine Replacement Parts

Pilot Burners

Code	Spare Part Description	Picture
057411	Molded 3-flame pilot burner supplied without spark plug, nozzle and gasket	
0C0744	3-flame pilot burner supplied without nozzle	
058146	Molded 3-flame pilot burner supplied without spark plug, nozzle and gasket	
0C3770	Pilot gasket (pack of 5 pcs) Code Qt. Description 0C5170 5 Gasket	
020152	3-flame pilot burner with Ø 0.20 multigas nozzle complete with 2-position bracket	
058329	3-flame pilot burner with Ø 0.35 multigas nozzle complete with 3-position bracket	
052246	2-position bracket to be ordered together	
052256	2-position bracket to be ordered together	



Pilot Burners

Code	Spare Part Description	Picture
002783	3 flame pilot burner supplied without candle, nozzle	
051624	3-flame pilot burner with Ø 0.25 multigas nozzle complete with 2-position bracket	
056751	Pilot lance burner with Ø 0.35 GN nozzle	
0C3644	Pilot burner For N700 and N900 Supplied without nozzle	
0C5534	M4x10 stainless steel screws for modular cooking fixing N900 pilots Pack of 30pcs Code Qt. Description 0C5533 30 Screw; m4x10	
0H6342	Upper pilot burner	
0G2024	Lower part pilot burner body	



Pilot Burners

Code	Spare Part Description	Picture
0H6343	Pilot burner support	
052280	Torch for pilot dim. mm 49x35h	
054032	3-flame pilot burner supplied without nozzle	
059301	Torch for pilot dim. mm 40x40h	
0A5441	Torch for pilot dim. mm 64x40h	
003328	Torch for pilot dim. mm 65x39.5h	
006128	Torch for pilot dim. mm 88x41h	



Pilot Burners

Code	Spare Part Description	Picture
054593	Pilot nozzle Ø 0.25 LPG	
053667	Pilot nozzle Ø 0.30 LPG	
053670	Pilot nozzle Ø 0.41 GN	
053668	Pilot nozzle Ø 0.51 GN	
052125	Fitting for Ø 4mm tube	
0C0121	Fixing fitting for thermocouple M10x1 Ø 6.5 mm	



Pilot Burners

Code	Spare Part Description	Picture
053665	Pilot bicone for Ø 4mm tube	
057960	Fitting for spark plug fixing	
059216	Pilot nozzle Ø 0.14 LPG	
0S2469	Pilot nozzle Ø 0.19 LPG	
059215	Pilot nozzle Ø 0.27 GN	
059161	TARGET pilot bicone Ø 4mm	
003863	TARGET pilot bicone Ø 6mm	
003859	Fitting for Ø 6mm tube Code Qt. Description 0C6289 10 Nut	



Pilot Burners

Code	Spare Part Description	Picture
052281	Pilot body with Ø 0.25 mm nozzle	
052686	Pilot body with Ø 0.35 mm nozzle	
006725	Pilot body with Ø 0.40 mm nozzle	
056799	Pilot nozzle Ø 0.20 LPG	
058330	Pilot nozzle Ø 0.25 LPG	
058525	Pilot nozzle Ø 0.30 GN	
056656	Pilot nozzle Ø 0.35 GN	



Pilot Burners

Code	Spare Part Description	Picture
056578	Pilot nozzle Ø 0.30 GN	
056750	Pilot nozzle Ø 0.20 LPG	
052833	Connection and bicone Ø 4 mm	
052834	Fitting and bicone Ø 6 mm	
0G2223	Fitting for Ø 12 mm pipe	
050682	Bicone for Ø 12 mm tube	
0C6621	Pilot nozzle Ø 0.21 LPG	



Pilot Burners

Code	Spare Part Description	Picture
054286	Pilot nozzle Ø 0.25 LPG	
054037	Pilot nozzle Ø 0.25 GN	
054038	Pilot nozzle Ø 0.45 GN	
0S2818	2-flame pilot burner with Ø 0.20 multigas nozzle complete with 3-position bracket	
0C0494	Pilot burner assembly without thermocouple and spark plug, including nut and bicone diam.4, nozzle D. 20mm, body in brass and steel (no light alloy)	
0S3304	12pcs Gas Nozzle Reamer Set for Diameters (mm): 0.5/0.6/0.7/0.8/0.9 1.0/1.1/1.2/1.4/1.6/1.8/2.0 Complete with support	

Safety Gas Valves

Code	Spare Part Description	Picture
053368	MINISIT gas valve adjustment range 50°-190°C inlet Ø1/2" F outlet Ø3/8" F cap.length. 1200 mm nich. Ø5x95 mm bulb complete with knob, lid, fittings and various accessories Code Qt. Description 052833 1 Pipe fitting , 052834 1 Pipe fitting , 054267 1 Gas valve; minisit , 054268 1 Knob , 054270 1 Pipe fitting , 054271 2 Gasket , 054272 6 Screw , 054273 1 Ignition cable; 1000 mm , 056835 1 Pipe fitting , 0C1753 2 Screw; m4x30 , 0C8410 1 Piezo igniter with lid	
056688	MINISIT gas valve adjustment range 110°-190°C inlet Ø1/2" F outlet Ø3/8" F cap.length. 1050 mm nich. bulb Ø6x105 mm complete with 2 corner flanges Ø1/2" F	
056689	MINISIT gas valve adjustment range 110°-190°C inlet Ø1/2" F outlet Ø3/8" F thermocouple connection M9x1 cap.length. 1050 mm nich. bulb Ø6x105 mm complete with knob, cover, fittings and various accessories Code Qt. Description 052834 1 Pipe fitting , 054268 1 Knob , 054271 1 Gasket , 054272 2 Screw , 054273 1 Ignition cable; 1000 mm , 056835 1 Pipe fitting , 058496 1 Gas valve; 110-190 c, minisit , 0C1753 2 Screw; m4x30 , 0C8410 1 Piezo igniter with lid	
056833	MINISIT gas valve adjustment range 100°-340°C inlet Ø1/2" F outlet Ø3/8" F thermocouple connection M9x1 cap.length. 1050 mm nich. bulb Ø5x70 mm	
0G2402	MINISIT gas valve adjustment range 100°-340°C inlet Ø1/2" F outlet Ø3/8" F cap.length. 1050 mm nich. bulb Ø4x72 mm	
054267	MINISIT gas valve adjustment range 50°-190°C inlet Ø1/2" F outlet Ø3/8" F thermocouple connection M9x1 cap.length. 1200 mm nich. bulb Ø5x95 mm	



Safety Gas Valves

Code	Spare Part Description	Picture
003655	MINISIT gas valve adjustment range 110°-190°C inlet Ø1/2"F outlet Ø3/8"F thermocouple connection M9x1 cap.length. 1050 mm nich. bulb Ø6x105 mm	
058496	MINISIT gas valve adjustment range 110°-190°C inlet Ø1/2"F outlet Ø3/8"F thermocouple connection M9x1 cap.length. 1050 mm nich. bulb Ø6x105 mm	
003334	EUROSIT gas valve adjustment range 110°-190°C inlet Ø3/8"F outlet Ø3/8"F cap.length. 1000 mm bulb Ø4x202 mm	
056009	Sealing cap for 3/8" inlet and outlet	
0C6235	EUROSIT gas valve adjustment range 80-320°C inlet Ø3/8"F outlet Ø3/8"F thermocouple connection M9x1 cap. length 1000 mm bulb Ø4x72 mm	
0G2294	EUROSIT gas valve oven adjustment range 100°-340°C inlet Ø3/8"F outlet Ø3/8"F thermocouple connection M9x1 length cap. 1050 mm bulb Ø4x72 mm	
054268	MINISIT knob	



Safety Gas Valves

Code	Spare Part Description	Picture
054271	MINISIT sealing ring	
0CB766	Thermostatic element for MINISIT valve 60-200°C capillary length 1200 mm bulb Ø5x95mm nich.	
0CB767	Thermostatic element for MINISIT valve 100-200°C capillary length 1050 mm bulb Ø6x105 mm	
056592	Thermostatic element for MINISIT valve 100-340°C capillary length 1050 mm bulb Ø5x70 mm nich.	
052668	Fitting for bicone Ø 16 mm MINISIT	
056835	1/2" inlet elbow fitting for MINISIT	
054270	3/8" outlet elbow fitting for MINISIT	
057543	ELETTROSIT gas valve inlet Ø3/4"F outlet Ø3/4"F power supply 230V 50Hz long buttons pilot connection and lateral thermocouple	



Safety Gas Valves

Code	Spare Part Description	Picture
055446	820 NOVA inlet-outlet gas valve Ø1/2" F thermocouple connection M9x1 power supply 230V 50Hz	
006182	820 NOVA inlet-outlet gas valve Ø1/2" F power supply 230V 60Hz thermocouple connection M9x1	
002903	820 NOVA inlet-outlet gas valve Ø1/2" F 230V 50Hz power supply without slow ignition level	
002606	820 NOVA mV inlet-outlet gas valve Ø1/2" FF thermocouple connection M9x1 power supply via two-wire thermopile	
0C2408	822 NOVA inlet-outlet gas valve Ø1/2" FF thermocouple connection M9x1 regulation field. pressure 5÷50 mbar power supply 24V 50 Hz ambient temperature 0÷70 °C	
002714	Gas valve 836 TANDEM inlet-outlet Ø1/2" F power supply 230V 50Hz - 27mA rectified regulation range. pressure 2÷50 mbar ambient temperature 0÷60 °C	
0K5838	830 TANDEM inlet-outlet gas valve Ø1/2" F power supply 230V 50Hz flow regulator blind screw ambient temperature 0÷60 °C Code Qt. Description 059474 1 Plug; for wash arm , 0G6549 1 Gas valve; 220-240v 50hz , 0G7343 1 Plug solenoid valve;4-pole; kit	



Safety Gas Valves

Code	Spare Part Description	Picture
0C7600	840 SIGMA inlet-outlet gas valve Ø 3/4" M power supply 230V 50Hz pressure regulation range 2-50mbar	
0C9642	Double valve coil 840 SIGMA 230V 50Hz	
002340	830 TANDEM inlet-outlet gas valve Ø1/2" F power supply 230V 50Hz regulation range. pressure 3÷50 mbar ambient temperature 0÷60 °C	
005526	830 TANDEM inlet-outlet gas valve Ø1/2" F regulation field. pressure 3÷50 mbar power supply 24V 50Hz ambient temperature 0÷60 °C	
0K3020	SIT 820 NOVA valve coil 220÷240 V 50 Hz	
059305	Gas valve extension	
059326	Gas valve gasket	
003209	Tap protection gasket	



Safety Gas Valves

Code	Spare Part Description	Picture
0C8085	Electrical connector with cable	
054539	Electric ignition contact without cables for ELETROSIT, SIT 820 NOVA	
056601	Electric ignition contact with 920 mm cable for ELETROSIT and SIT 820 NOVA	
002452	Valve coil 830 Tandem	
003704	Knob Ø 30 mm	
002607	Thermopile 588 mm	
0C5249	Mertik gas valve 30-110°C thermocouple connection M9x1 3/8" connections ignition cable/bulb and capillary for N900 bain-marie	
0C5248	Mertik gas valve 110-190°C thermocouple connection M9x1 3/8" connections ignition cable/bulb and capillary for N700-N900 fryer	



Safety Gas Valves

Code	Spare Part Description	Picture
0C5245	Mertik gas valve 100-340°C thermocouple connection M9x1 3/8" connections ignition cable/bulb and capillary for bratt pan PR700-N900	
0C5250	Mertik gas valve 55-280°C thermocouple connection M9x1 3/8" connections ignition cable/bulb and capillary for N900 static ovens	
0C5246	Mertik gas valve 100-340°C thermocouple connection M9x1 3/8" connections ignition cable/bulb and capillary for cookers and fry tops N900	
0C5247	Mertik gas valve 100-340°C thermocouple connection M9x1 3/8" connections ignition cable/bulb and capillary for N700-N900 cookers	
006465	Mertik knob gasket dim. Ø 39 mm h 4.8 mm	
0C0625	Sealing cap for Mertik inlet and outlet 3/8	
0C5400	Mertik valve knob adapter	



Safety Gas Valves

Code	Spare Part Description	Picture
0C6134	Idle screw not drilled	
0G8684	Magnetic group for Mertik valves L=32 mm Ø upper: 14 mm Ø lower: 19 mm	
0C5481	Minimum screw Ø 0.80 mm	
006466	Minimum screw Ø 0.90 mm	
006467	Minimum screw Ø 1.00 mm	
006651	Minimum screw Ø 1.10 mm	



Safety Gas Valves

Code	Spare Part Description	Picture
006652	Minimum screw Ø 1.25 mm	
006475	Minimum screw Ø 1.30 mm	
0C1734	Minimum screw Ø 1.50 mm	
0C4156	Minimum screw Ø 1.75 mm	
006653	Minimum screw Ø 1.90 mm	
006654	Minimum screw Ø 2.00 mm	



Safety Gas Valves

Code	Spare Part Description	Picture
006472	Minimum screw Ø 2.25 mm	
00C1735	Minimum screw Ø 2.60 mm	

Safety Thermostats

Code	Spare Part Description	Picture
00C1147	Single-phase thermostat 150°C Bulb Ø6X74 mm Capillary 1700 mm 0.5A 12V	
004912	Single-phase thermostat 130°C Bulb Ø6X130 mm Capillary 870 mm 16A 250V	
00C1000	Single-phase thermostat 210°C Bulb Ø6X75 mm Capillary 1250 mm 0.5A 12V	
00C4279	Single-phase thermostat 230°C Bulb Ø6X87 mm Capillary 900 mm 0.5A 12V	



Safety Thermostats

Code	Spare Part Description	Picture
005680	Single-phase thermostat 338°C Bulb Ø11X6 mm Capillary 900 mm 20A 400V	
002711	Single-phase thermostat 150°C Bulb Ø6X74 mm Capillary 1700 mm 20A 400V	
058164	Single-phase thermostat 230°C bulb Ø6X130 mm covered capillary 1000 mm 16A, 250V with thermocouple wiring	
053012	Single-phase thermostat 235°C bulb Ø5X100 mm capillary 1000 mm 15A 250V	
005931	Single-phase thermostat 250°C Capillary 900 mm Bulb Ø6X87 mm 0.5A, 12V	
0A5435	Single-phase thermostat 245°C Capillary 1100 mm Bulb Ø6X87 mm 0.5A, 12V	
002730	Single-phase thermostat 338°C Bulb Ø11X6 mm Capillary 900 mm 20A 400V	



Safety Thermostats

Code	Spare Part Description	Picture
003594	Single-phase thermostat 360°C Bulb Ø6X79 mm Capillary 1500 mm 0.5A 12V	
004354	Single-phase thermostat 240°C Bulb Ø6X79 mm Capillary 2000 mm 0.5A 12V	
0C0999	Single-phase thermostat 260°C Bulb Ø6X75 mm Capillary 1250 mm 0.5A 12V	
007042	Single-phase thermostat 338°C Bulb Ø6X39 mm Capillary 900 mm 20A 400V	
004269	Single-phase thermostat 360°C Bulb Ø4X120 mm Capillary 900 mm 0.5A, 12V	
006433	Three-phase thermostat 150°C Bulb Ø6X73 mm Capillary 1730 mm 0.5A 12V	



Safety Thermostats

Code	Spare Part Description	Picture
005295	Three-phase thermostat 170°C Bulb Ø6X87 mm Capillary 900 mm 0.5A 12V	
0C4463	Three-phase thermostat 230°C Bulb Ø6X87 mm Capillary 900 mm 20A 400V	
0C2983	Three-phase thermostat 140°C Bulb Ø6X87 mm Capillary 900 mm 20A 400V	
004742	Three-phase thermostat 170°C Bulb Ø6X87 mm Capillary 900 mm 20A 400V	
003120	Three-phase thermostat 240°C bulb Ø6X100 mm covered capillary 900 mm 10A 400V gland fitting M10x1	
004472	Three-phase thermostat 245°C Bulb Ø6X87 mm Capillary 2700 mm 20A 400V	
005941	Three-phase thermostat 250°C Bulb Ø6X87 mm Capillary 900 mm 20A 400V	



Safety Thermostats

Code	Spare Part Description	Picture
006307	Three-phase thermostat 270°C Bulb Ø6X87 mm Capillary 900 mm 20A 400V	
004921	Three-phase thermostat 293°C Bulb Ø4X120 mm Capillary 900 mm 10A 400V	
006282	Three-phase thermostat 245°C Bulb Ø6X87 mm Capillary 900 mm 0.5A 12V	
053183	Three-phase thermostat 285°C Bulb Ø6X157 mm Capillary 940 mm 0.5A 12V	
006826	Three-phase thermostat 350°C Bulb Ø6X79 mm Capillary 1500 mm 20A 400V	
0C0270	Three-phase thermostat 350°C Bulb Ø3X190 mm Capillary 900 mm 10A 400V	
004919	Three-phase thermostat 350°C Bulb Ø3X190 mm Capillary 1120 mm 10A 400V	



Safety Thermostats

Code	Spare Part Description	Picture
004600	Three-phase thermostat 360°C Bulb Ø6X79 mm Capillary 1200 mm 0.5A 12V	
006314	Positive safety thermostat, it opens the contacts in capillary breaking events, min. probe temperature -10°C, max. body temperature 125°C, min. folding radius of capillary 5mm	

Spark Plugs

Code	Spare Part Description	Picture
052610	Spark plug Ø 6x44mm electrode L=16.6x2 mm connection Ø 4x 11 mm	
059380	Spark plug Ø 6x44mm electrode L=8x2 mm connection Ø 4x 11 mm	
054336	Spark plug Ø 7x44mm electrode L=14x2 mm faston connection Ø 2.4 mm	
0A2164	Spark plug Ø 7/10 mm Length 52 mm	
002637	Spark plug Ø 9 x 60 mm connection Ø 6 mm	



Spark Plugs

Code	Spare Part Description	Picture
004970	Spark plug Ø 6 x 32 mm cable with sheath L=750 mm connection Ø 2.5 mm	
054099	Spark plug Ø 5+8x52mm electrode L=0.7x5 mm faston connection 2.8x0.8 mm	
0H6803	Spark plug Ø 9 x 60 mm connection Ø 6 mm	
003556	Spark plug Ø 9 x 60 mm with protective tubes Ø 6 mm connection Code Qt. Description 0A5168 1 Spark plug; 9x60 mm , 0C0247 1 Sheath; 1 pz=70 mm , 0C0248 1 Silicone hose; 1pc=70mm	
006023	Cable assembly for FCV/G 10 1/1 oven spark plugs	
006024	Cable assembly for FCV/G 10 2/1 oven spark plugs	
002638	Flame detection candle Ø 9 mm Length 60 mm connection Ø 4 mm	
0PRC1G	Spark plug Ø 7x45mm Total length 65 mm connection M4x1 mm	

Genuine Replacement Parts

Switches

Code	Spare Part Description	Picture
0E5132	0-1 pos switch and button 3 control positions - 3 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	
0C6245	Switch 0-7 pos 8 control positions - 5 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	
0C0084	Switch with card and LED lights 0-9 pos 10 control positions -1 pole contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm Cable length 500mm connections with connector plug	
0K5063	Switch with connector 0-1 pos 2 control positions -4 poles contacts with rating 32A-250V D shaft Ø 6x4.6 mm spindle length 23 mm Cable length 2400mm screw connections version with potentiometer	
0E5131	0-1 pos switch 2 control positions - 4 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	
0K8614	Switch 0-2 pos 3 control positions - 5 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	
0E5222	Switch 0-1 pos 2 control positions - 6 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm faston connections 6.3x0.8mm	



Switches

Code	Spare Part Description	Picture
0G3298	Cam switch with 0-1 pos connector 2 control positions -2 poles contacts with capacity 16A-250V crescent pin Ø 6x4.6 mm shaft length 23 mm cable length 2400mm connections with connector plug version with potentiometer	
0KI631	9-position switch with terminal type faston serie 250, 16A 250V	
099274	Green illuminated two-pole switch, without frame	
049063	Press Switch with click	
0L2066	three-phase line disconnecter/switch, designed for DIN 46277 coupling, compliance with IEC 60947 standard, AC-21A current up to 125 A, AC-23A power up to 45 Kw	

Thermocouples

Code	Spare Part Description	Picture
0G1120	Thermocouple M8x1, L=450 mm	
0G2906	Thermocouple M8x1, L=550 mm	



Thermocouples

Code	Spare Part Description	Picture
0K5730	Thermocouple M8x1, L=1200 mm	
027317	Thermocouple M9x1, L=500 mm	
025031	Thermocouple M9x1 aluminized tip, L=600 mm	
027350	Thermocouple M9x1, L=1000 mm	
020094	Thermocouple M9x1 aluminized tip, L=1200 mm	
059064	Thermocouple M9x1, L=1500 mm	
0C1634	Thermocouple M9x1, L=1900 mm	
0K5688	Thermocouple M8x1 joint M8x1, L=600 mm	
0U2960	Thermocouple M8x1 joint M8x1, L=1000 mm	
025677	Thermocouple M9x1 joint M8x1, L=600 mm	
0C0202	Thermocouple M8x1 aluminized tip, L=750 mm	
051119	Thermocouple M8x1 aluminized tip, L=1500 mm	



Thermocouples

Code	Spare Part Description	Picture
004942	Thermocouple M9x1 L=500 mm	
057781	Thermocouple M9x1 L=600 mm	
003281	Thermocouple M9x1 L=1200 mm	
0M0893	Thermocouple M9x1 L=1500 mm	
0H6253	Thermocouple M10x1 L=850 mm	
0H6252	Thermocouple M10x1 L=1500 mm	
051635	Interrupted thermocouple M9x1 L=1000mm Cable length 1000 mm	
0C3162	Interrupted thermocouple M9x1 QUICK OFF L=1000 mm Cable length 700 mm	
0CA280	Interrupted thermocouple M9x1 QUICK OFF L=730 mm Cable length 500 mm	



Thermocouples

Code	Spare Part Description	Picture
0C3197	Interrupted thermocouple M9x1 L=1000 mm Cable length 850 mm	
002784	Interrupted thermocouple M9x1 L=1000 mm Cable length 600 mm	
0CBCX2	Interrupted thermocouple M9x1 NORMAL L=1450 mm Cable length 600 mm Code Qt. Description 055032 1 Extension thermocouple; m9x1, l=60 cm , 0C7716 1 Thermocouple; l. 1450 m9x1	
0C7716	Interrupted thermocouple M9x1 NORMAL L=1450 mm Cable length 700 mm	
0CA188	Interrupted thermocouple M9x1 NORMAL L=1700 mm Cable length 200 mm	
004955	Thermocouple M8x1 L=600 mm Joint M6x1	
0S0055	Universal thermocouple L=900 mm Threaded pilot joint M6x0.75 (A513) Complete with adapters (6 pcs)	
0S0056	Universal thermocouple L=1200 mm joint for threaded pilot M6x0.75 (A513) Complete with adapters (6 pcs)	



Thermocouples

Code	Spare Part Description	Picture
052163	Thermocouple M9x1 L=1000 mm Joint M8x1	
0U1115	Universal thermocouple L=900 mm Complete with 4 fittings (M10x1; 11/32" - M10x1 milled; M8x1 - M9x1 milled; 7/16"), bushings, adapters and spacers	
052814	Thermocouple M9x1 Lenght=850mm	

Accessories for Thermocouples

Code	Spare Part Description	Picture
055032	Thermocouple extension M9x1 L=600 mm Female nut M9x1	
0K3024	Interrupted connection ASA M 11/32	
005687	Interrupted fitting M9x1	



Accessories for Thermocouples

Code	Spare Part Description	Picture
055033	Joint thermocouple nut M8x1	
0CB504	ASA 11/32 thread thermocouple fitting	

Thermostats

Code	Spare Part Description	Picture
0C6234	Min/Max sensor temperature -10/370°C	
054323	Single-phase thermostat 0-300°C Bulb Ø3.5x190 mm Capillary 1500 mm 15A 230V Knob pin Ø6x4.6 mm	
051142	Single-phase thermostat 30-90°C Bulb Ø6x174 mm Capillary 980 mm 16A 380V Knob pin Ø6x4.6 mm	
033716	Single-phase thermostat 30-90°C Bulb Ø6x100 mm Capillary 960 mm 16A 230V Knob pin Ø6x4.6 mm	
002109	Single-phase thermostat 50-260°C with auxiliary switch Bulb Ø4x115 mm capillary 1300 mm 10A 400V Knob pin Ø6x4.6 mm	



Thermostats

Code	Spare Part Description	Picture
003262	Single-phase thermostat 30-90°C Bulb Ø6x130 mm Capillary 1500 mm 16A 380V Knob pin Ø6x4.6 mm	
0E5032	Single-phase thermostat 30-110°C Bulb Ø3x197 mm Capillary 3000 mm 16A 230V Knob pin Ø6x4.6 mm	
0S3251	Single-phase thermostat 30-110°C bulb Ø5x80 mm capillary 980 mm 16A 230V knob pin Ø6x4.6 mm	
031480	Single-phase thermostat 60-175°C Bulb Ø3x226 mm Capillary 870 mm Knob pin Ø6x4.6 mm	
056384	Single-phase thermostat 50-296°C capillary 1000 mm bulb Ø3x219 mm 16A 380V knob pin Ø6x4.6 mm	
057937	Single-phase thermostat 50-260°C Capillary 900 mm Bulb Ø3x219 mm 16A 380V Knob pin Ø6x4.6 mm	
051360	Single-phase thermostat 50-260°C Bulb Ø4x115 mm Capillary 1200 mm 16A 250V Knob pin Ø6x4.6 mm	



Thermostats

Code	Spare Part Description	Picture
002602	Single-phase thermostat 90-185°C 0.5A 12V Bulb Ø4x230 mm Capillary 1300 mm Knob pin Ø6x4.6 mm	
052330	Single-phase thermostat 90-185°C with auxiliary switch Bulb Ø4x229 mm Capillary 2350 mm 16A 380V Knob pin Ø6x4.6 mm	
058163	Single-phase thermostat 95-190°C bulb Ø6x135 mm covered capillary 900 mm 16A, 250V knob pin Ø6x4.6 mm gland fitting M10x1	
050412	Single-phase thermostat 90-185°C 16A 250V Bulb Ø4x230 mm Capillary 1300 mm Knob pin Ø6x4.6 mm	
003049	Single-phase thermostat 90-185°C with auxiliary switch Bulb Ø4x229 mm Capillary 2350 mm 16A 380V Knob pin Ø6x4.6 mm	
004911	Three-phase thermostat 30-110°C bulb Ø6x130 mm capillary 900 mm; 10A 400V knob pin Ø6x4.6 mm gland fitting M9x1	
032858	Three-phase thermostat 30-110°C bulb Ø6x130 mm capillary 1200 mm; 10A 400V knob pin Ø6x4.6 mm	



Thermostats

Code	Spare Part Description	Picture
0A2206	Three-phase thermostat 50-320°C Bulb Ø3x219 mm Capillary 900 mm 16A, 380V Knob pin Ø6x4.6 mm	
055996	Three-phase thermostat 50-300°C Bulb Ø2.5x330 mm Capillary 1150 mm 16A 380V Knob pin Ø6x4.6 mm	
052099	Three-phase thermostat 60-320°C Bulb Ø4X130 mm Capillary 1300 mm 16A 380V Knob pin Ø6X4.6 mm	
0H6233	Three-phase thermostat 95-180°C bulb Ø6X133 mm capillary 1800 mm 16A 230V knob pin Ø6X4.6 mm, gland fitting M9x1	
052000	Three-phase thermostat 30-90°C Bulb Ø6x175 mm Capillary 870 mm 16A 380V Knob pin Ø6x4.6 mm	
0H6217	Three-phase thermostat 50-300°C Bulb Ø6x80 mm Capillary 1740 mm 16A, 230V Knob pin Ø6x4.6 mm	
005940	Three-phase thermostat 60 - 185°C Bulb Ø4X231 mm Capillary 1200 mm 10A 400V Knob pin Ø6X4.6 mm	



Thermostats

Code	Spare Part Description	Picture
0C7528	Three-phase thermostat 90 - 230°C Bulb Ø4X131 mm Capillary 1250 mm 10A 400V Knob pin Ø6X4.6 mm	
059235	Three-phase thermostat 100 - 285°C Bulb Ø3X225 mm Capillary 1150 mm 10A 400V Knob pin Ø6X4.6 mm	
052916	Three-phase thermostat 100-300°C Bulb Ø6X80 mm Capillary 1150 mm 10A 400V Knob pin Ø6X4.6 mm	
051361	Three-phase thermostat 60-185°C Bulb Ø4X231 mm Capillary 2600 mm 16A 380V Knob pin Ø6X4.6 mm	
004363	Three-phase thermostat 115 - 300°C Bulb Ø3X144 mm Capillary 1150 mm 10A 400V Knob pin Ø6X4.6 mm	
004862	Three-phase thermostat 140°C Bulb Ø6X87 mm Capillary 900 mm 20A 400V	

Water Columns


Code	Spare Part Description	Picture
0C9108	Adjustable water column for kitchen series 700-900 complete with fixing plates (extension tubes not included) H=700	
0S0350	Universal adjustable water column with horizontal tap, 250 mm articulated spout Complete with: gaskets, washer and locknuts H= 550 mm	
0S0134	1/2" screw for 8x20 broach connection	
0S1001	Knob with Blue insert; 8X20mm connection	
0C5240	Extension for water column series 900 dim. Ø 1/2" G x 244 mm dim. Ø 1/2" G x 394 mm	
0C5241	Extension for water column series 700 dim. Ø 1/2" G x 173 mm dim. Ø 1/2" G x 698 mm	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Genuine Replacement Parts

Water Columns

Code	Spare Part Description	Picture
025260	Column knob	
0C6826	External support for water column series 700-900 dim. 44x55x266 h mm	
0C3108	Tap kit with 200 mm spout complete with 7x7 square connection screw, 1/2" thread	
058967	Dispensing spout Ø 18x200 mm	
0S0719	Dispensing spout Ø 18x300 mm	
0C2963	Square connection screw 7x7 1/2" thread for HD900 (2005)	
0S0948	French O-Ring R12 (lot 50pcs) Code Qt. Description 0S0947 50 O-ring; francese r12	

Water Gas Steam Valves

Code	Spare Part Description	Picture
0CA947	Ball water valve Ø1" FF Aluminum lever, PN40 heavy series	
002033	½" FF ball water valve Aluminum lever, PN50	
056843	3/8" FF butterfly water ball valve in aluminium, PN40	
0K7222	Gas/water ball valve Ø3/4" FF Aluminum butterfly PN40 heavy series DIN-DVGW approved	
0A5258	Ball water valve Ø3/8" MF Aluminum lever, PN40 heavy series	
0C9658	Ball water valve Ø3/8" FF Aluminum butterfly complete with pin, nut and bracket Code Qt. Description 0C6504 1 Pivot support; for tap , 0C6612 1 Nut; m8x1 , 0C9425 1 Pivot; m5 , 0C9490 1 Water valve	
0S2530	Ø3/4" FF 3-way ball water valve, aluminum lever	
058647	½" FF PN40 ball water valve with 10x7.5mm pin	



Water Gas Steam Valves

Code	Spare Part Description	Picture
0S0143	Hexagonal type steam valve with 1" 1/4F connection	
008019	Angled safety group for steam Ø 1 1/4" M calibration pressure 0.5 bar Spring safety valve and pressure gauge cock complete with valve accessories	
017055	Pressure gauge for pans Ø 1/4" M in chromed brass Ø 52.5 mm with Ø 3/8" adapter scale from 0 to 1 bar	
0S0141	Ø 3/8 M pressure gauge valve	
0S2411	Vertical safety group for steam 3/4" calibration pressure 0.5 bar Spring safety valve and pressure gauge tap complete with accessories for valve H 185 mm	
051566	Ø 3/8" depression valve	
0K3442	Ø 3/4" depression valve	



Water Gas Steam Valves

Code	Spare Part Description	Picture
0C9635	Ball valve 3/8" S2000 + Extension + Hose holder. Anti-clockwise opening. Range of use -55/+150°C. Extension pin mounted on cap with elastic pin. 3/8-1/2 fitting hermetically mounted. WRAS approved seals.	
0C8648	3/8" ball valve + extension + hose holder. Brass pin and cap. Hermetically mounted hose holder. Anti-clockwise opening, pin diameter 10mm, flared inlet/outlet diameters of the 8/12mm.	
0G2763	Electric gas valve 840 SIGMA ø3/4", Pi max 60mbar, Po 2-50mbar, EV1 230V-50Hz 9,2VA, EV2 230V-50Hz 2,8VA, Tamb 0-60°	
0CBCP7	Steam exhaust valve kit For 100-150L pots N900 range (PNC 206279) Includes: Automatic valve, cap and hose	
0S3250	Round type angle steam valve with 1" M connection	

Water Taps

Code	Spare Part Description	Picture
0S1037	Drain tap with conical seal and safety swivel connection Ø 1 1/2" F	
0CA949	GBM drain tap with O Ring swivel connection Ø 2" F	



Water Taps

Code	Spare Part Description	Picture
0S0287	Athermal handle for 2" drain taps	
0S1034	Drain tap with conical seal and fixed connection safety Ø 1"¼ F	
0S0568	Athermal handle for 1"¼, 1"½ drain taps	
0C3142	O-rings (package of 3 pcs) for 1"¼, 1" ½ drain taps	
0S2227	GBM drain tap with conical seal swivel connection Ø 2"F MOCA certified	
052907	Drain tap with Dutch connection M68x3 internal hole Ø 50 mm	
053159	Conical seal drain cock with Dutch connection: M78x3 mm	
0S2118	Grease for taps with o-rings 100 g NSFH1 certification	



Water Taps

Code	Spare Part Description	Picture
0S1145	Food grease for conical seal taps, 2 x 45 g tubes Code Qt. Description 0S1144 2 Grease; klubersynth uhl; 45 g	
0C7121	Single hole filling tap with 1/2"F and 3/8"M swivel spout complete with no. 2 flexible Code Qt. Description 0C4530 1 Flange , 0C4531 1 Connection; for flexible hose , 0G2937 1 Tap; l=120mm , 0S1253 2 O-ring; 3043 nbr , 0S1254 2 Screw; m6x16	
0S0724	3/8" foot operated tap Double control lever L=255mm with locking lever Under-sink installation Description: Flexible hose 3/8"M 1/2"F Ø12x850 mm	
0S1336	3/4" screw for single-hole tap with 7x7 mm connection	
0S1067	Athermal handle for M78x3 drain tap	
0S2277	Food grease for conical seal taps 1 kg	
0C9506	Aluminum anti-seize lubricating grease 500 g	
0C4530	Flange dim. 90x70 mm	



Water Taps

Code	Spare Part Description	Picture
0C4531	Ø45 mm connection for 3/8" hoses	
0S0247	Knob with blue insert 7x7 mm connection	
0S0246	Knob with red insert 7x7 mm connection	
0S1035	Drain tap with conical seal and fixed connection safety Ø 1 1/2" F	
0S0286	O-ring for drain tap Ø 2"F for TECNO and GBM type (pack of 3 pcs)	
0S2807	Single hole tap with swivel spout for filling Ø 1/2" F pots	
004986	Fiber gasket for Ø 2" drain tap	
0C1450	Water level tap composed of tap body, 3/8" screw, tap handwheel, M4X9 brass screw	

Brass Solenoid Valves

Code	Spare Part Description	Picture
0C1148	2-way solenoid valve 1/2" FF 230/240V 50-60Hz for water min/max temperature -10/+90°C min/max pressure 0.2 / 16 bar coil type BDV 230/240V 50-60Hz 16VA	
0K5341	2-way 1/4" FF 230V 50Hz solenoid valve for water min/max temperature -10 / +90°C min/max pressure 0.35 / 20 bar coil type ZA10A 9W 230V 50Hz 14VA	
0C1121	2-way 3/4" FF 230V 50-60Hz solenoid valve for water min/max temperature -10 / +90°C min/max pressure 0.2 / 16 bar coil type BDA 220/230V 50-60Hz 14.5VA	
0E2200	2-way 3/4" FF 24V 50Hz solenoid valve for water/steam min/max temperature -10 / +140°C min/max pressure 0.35 / 3.5 bar coil type MXX-HT 24V 50Hz	
0E5974	2-way 3/4" FF 230V 50Hz solenoid valve for hot water/steam min/max temperature -10 / +140°C min/max steam pressure 0.35 / 3.5 bar min/max hot water pressure 0.35 / 10 bar coil type MXX-HT 230V 50Hz 10.5W	
0L1481	2-way 3/4" FF 24V 50-60Hz solenoid valve for steam min/max temperature +60 / +170°C min/max pressure 0.4 / 6 bar coil type Z534A 24V 50-60Hz 14VA	
0L0537	2-way solenoid valve 3/8" FF 230V 50-60Hz for water min/max temperature -10 / +90°C min/max pressure 0.35 / 16 bar coil type ZB14A 230V 50-60Hz 12VA	
0L2656	2-way solenoid valve 3/8" FF 208-240V 50-60Hz for water min/max temperature -10 / +140°C min/max pressure 0.35 / 16 bar coil type ZB14Y 208-240V 50-60Hz 12VA	
0L2850	2-way 3/8" FF 240V 50-60Hz solenoid valve for water min/max temperature -10 / +140°C min/max pressure 0.35 / 16 bar coil type ZB10A 240V 50-60Hz 12VA 4W	



Brass Solenoid Valves

Code	Spare Part Description	Picture
0K8129	2-way 3/4" FF 24V 60Hz solenoid valve for hot water/steam min/max temperature -10 / +140°C min/max steam pressure 0.35 /3.5 bar min/max hot water pressure 0.35 /10 bar coil type MXX-HT 24V 60Hz 10.5W	
0L1482	2-way 3/4" FF 230V 50-60Hz solenoid valve for steam min/max temperature +60 / +170°C min/max pressure 0.4 /6 bar coil type Z534A 230V 50-60Hz 14VA	
0L2516	2-way 3/8" FF 24V 50-60Hz solenoid valve for water min/max temperature -10 / +140°C min/max pressure 0.35 /16 bar coil type ZB14A 24V 50-60Hz 12VA 4W	
0L2857	2-way solenoid valve 3/8" FF 200V 50-60Hz for water min/max temperature -10 / +140°C min/max pressure 0.35 /20 bar coil type ZB14A 200V 50-60Hz 12VA	
0L0423	2-way solenoid valve 3/8" FF 230V 50-60Hz for water min/max temperature 0 / +140°C min/max pressure 0.35 /16 bar coil type ZB14A 230V 50-60Hz 12VA 4W	
003778	2-way 3/4" FF solenoid valve 24V AC 50-60Hz for water temperature min/max 0 / +130°C pressure min/max 0.3 /10 bar coil type BA2 24V AC 50-60Hz 11VA	
0CBAYD	2-way solenoid valve 1/2"-1.1-4.5 FF 230V 50Hz for water min/max temperature -10 / +130°C min/max pressure 0 / 6 bar coil 220/230 V 50/60 Hz	

Contactors

Code	Spare Part Description	Picture
0KV051	Mini contactor Screw fixing method on OMEGA bar Model: K1-09D01; Coil power supply: 400V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 9A/4kW; Rated load AC1 690V: 20A; Cont. Aux.: 1 NC; Cont. amperage aux. AC15 400V: 2A	
088557	Mini contactor Screw fixing method on OMEGA bar Model: K1-09D10; Coil power supply: 230V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 9A/4kW; Rated load AC1 690V: 20A; Cont. Aux.: 1 NO; Cont. amperage aux. AC15 400V: 2A	
0KZ813	Contactor Fixing Way: Screw and DIN Top Hat Rail Model: K2-09A10; Coil power supply: 24V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 9A/4kW; Rated load AC1 690V: 25A; Cont. Aux.: 1 NO; Cont. amperage aux. AC15 400V: 4A	
0H7051	Contactor Fixing Way: Screw and DIN Top Hat Rail Model: K2-12A00-40; Coil power supply: 230V/50Hz; Contacts: 4 NO; Rated load AC3 400V: 12A / 5.5kW; Rated load AC1 690V: 25A	
0K3383	Contactor Fixing Way: Screw and DIN Top Hat Rail Model: K2-12A01; Coil power supply: 230V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 12A / 5.5kW; Rated load AC1 690V: 25A; Cont. Aux.: 1 NC; Cont. amperage aux. AC15 400V: 4A	
006879	Contactor Fixing Way: Screw and DIN Top Hat Rail Model: K2-12A10; Coil power supply: 230V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 12A / 5.5kW; Rated load AC1 690V: 25A; Cont. Aux.: 1 NO; Cont. amperage aux. AC15 400V: 4A	



Contactors

Code	Spare Part Description	Picture
0KJ216	Contactor Fixing Way: Screw and DIN Top Hat Rail Model: K2-12A10; Coil power supply: 400V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 12A / 5.5kW; Rated load AC1 690V: 25A; Cont. Aux.: 1 NO; Cont. amperage aux. AC15 400V: 4A	
0KZ812	Contactor Fixing Way: Screw and DIN Top Hat Rail Model: K2-16A10; Coil power supply: 24V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 16A / 7.5kW; Rated load AC1 690V: 25A; Cont. Aux.: 1 NO; Cont. amperage aux. AC15 400V: 4A	
0K3384	Contactor Fixing Way: Screw and DIN Top Hat Rail Model: K2-23A01; Coil power supply: 230V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 23A/11kW; Rated load AC1 690V: 45A; Cont. Aux.: 1 NC; Cont. amperage aux. AC15 400V: 4A	
0C9763	Contactor Fixing Way: Screw and DIN Top Hat Rail Model: K2-23A01; Coil power supply: 230V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 23A/11kW; Rated load AC1 690V: 45A; Cont. Aux.: 1 NO; Cont. amperage aux. AC15 400V: 4A Code Qt. Description 046995 1 Auxiliary contact , 0C9762 1 Instruction foil contactor , 0L0355 1 Contactor; 220-240v 50hz/240-264v 60hz	
0K9124	Contactor Fixing Way: Screw and DIN Top Hat Rail Model: K2-23A10; Coil power supply: 24V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 23A/11kW; Rated load AC1 690V: 45A; Cont. Aux.: 1 NO; Cont. amperage aux. AC15 400V: 4A	
0KJ217	Contactor Fixing Way: Screw and DIN Top Hat Rail Model: K2-23A10; Coil power supply: 400V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 23A/11kW; Rated load AC1 690V: 45A; Cont. Aux.: 1 NO; Cont. amperage aux. AC15 400V: 4A	



Contactors

Code	Spare Part Description	Picture
0C2247	Contacteur Fixing Way: Screw and DIN Top Hat Rail Model: K2-30A00-40; Coil power supply: 230V/50Hz; Contacts: 4 NO; Rated load AC3 400V: 30A/15kW; Rated load AC1 690V: 50A	
0KV658	Contacteur Fixing Way: Screw and DIN Top Hat Rail Model: K2-30A10; Coil power supply 230V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 30A/15kW; Rated load AC1 690V: 50A; Cont. Aux.: 1 NO; Cont. amperage aux. AC15 400V: 4A	
0C7622	Contacteur Fixing Way: Screw and DIN Top Hat Rail Model: K3-10A00-40; Coil power supply 230V/50Hz; Contacts: 4 NO; Rated load AC3 400V: 10A/4kW	
0L0285	Contacteur Fixing Way: Screw and DIN Top Hat Rail Model: K3-10A01; Coil power supply 230V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 10A/4kW; Rated load AC1 690V: 25A; Cont. Aux.: 1 NC; Cont. amperage aux. AC15 400V: 4A	
088477	Contacteur Fixing Way: Screw and DIN Top Hat Rail Model: K3-10A10; Coil power supply 230V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 10A/4kW; Rated load AC1 690V: 25A; Cont. Aux.: 1 NO; Cont. amperage aux. AC15 400V: 4A	
0L0354	Contacteur Fixing Way: Screw and DIN Top Hat Rail Model: K3-14A10; Coil power supply 230V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 14A / 5.5kW; Rated load AC1 690V: 25A; Cont. Aux.: 1 NO; Cont. amperage aux. AC15 400V: 4A	



Contactors

Code	Spare Part Description	Picture
0L0360	Contacteur Fixing Way: Screw and DIN Top Hat Rail Model: K3-14A1024; Coil power supply: 24V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 14A / 5.5kW; Rated load AC1 690V: 25A; Cont. Aux.: 1 NO; Cont. amperage aux. AC15 400V: 4A	
0K9132	Contacteur Fixing Way: Screw and DIN Top Hat Rail Model: K3-22A10; Coil power supply 230V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 22A/11kW; Rated load AC1 690V: 32A; Cont. Aux.: 1 NO; Cont. amperage aux. AC15 400V: 2A	
0L0355	Contacteur Fixing Way: Screw and DIN Top Hat Rail Model: K3-24A00; Coil power supply 230V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 24A/11kW; Rated load AC1 690V: 50A	
0L0361	Contacteur Fixing Way: Screw and DIN Top Hat Rail Model: K3-24A00; Coil power supply 24V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 24V/50Hz; Rated load AC1 690V: 50A	
007080	Contacteur Fixing Way: Screw and DIN Top Hat Rail Model: K3-32A00; Coil power supply 230V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 32A/15kW; Rated load AC1 690V: 65A	
007104	Contacteur Fixing Way: Screw and DIN Top Hat Rail Model: K3-40A00; Coil power supply 230V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 40A / 18.5kW; Rated load AC1 690V: 80A	



Contactors

Code	Spare Part Description	Picture
0C2244	Contacteur Fixing Way: Screw and DIN Top Hat Rail Model: K3-50A00; Coil power supply 230V/50Hz; Contacts: 3 NO; Rated load AC3 400V: 50A/22kW; Rated load AC1 690V: 110A	
0G9210	Contacteur Fixing method: Screw and DIN Top Hat Rail Model: K3-18NBX; Coil power supply: 230V/50Hz; Contacts: 4 NO; Rated load AC3 400V: 18A / 7.5kW; Rated load AC1 690V: 32A Auxiliary contactor amperage AC15 400V: 3A	
0K8700	Auxiliary contact Adaptable to models: K2 Model: HA01 red; Cont. Aux.: 1NC; Cont. amperage aux. AC15 400V: 3A	
048497	Auxiliary contact Adaptable to models: K2 Model: HA10 green; Cont. Aux.: 1NO; Cont. amperage aux. AC15 400V: 3A	
0G4291	Auxiliary contact Adaptable to models: from K3-24A up to K4-74A Model: HB11; Cont. Aux.: 1NO / 1NC; Cont. amperage aux. AC15 400V: 2A	
047046	Auxiliary contact Adaptable to models: K2 / K3 Model: HN01 red; Cont. Aux.: 1NC; Cont. amperage aux. AC15 400V: 2A	



Genuine Replacement Parts

Contactors

Code	Spare Part Description	Picture
046995	Auxiliary contact Adaptable to models: K2 / K3 Model: HN10 green; Cont. Aux.: 1NO; Cont. amperage aux. AC15 400V: 2A	
0G4645	Contactor with Varistor, 3 Pole with Auxiliary Contact, 220-240V 50HZ	
0D6869	Contactor 220V, 50/60Hz, 40A, 3P1NO	
0G4646	Contactor, 220-240 Volt Coil, 50/60Hz, 3 Pole, 24 Amp.	
0L0286	Current AC1 400V 40-60°C: 25A, 17.3kW; Current AC1 400V 90°C: 14A; Current AC3 400V 40-90°C: 10A, 4kW; 180-210V at 50Hz; 200- 240V at 60Hz	
0L3008	Current AC1 400V 40-60°C: 65A, 45kW; Current AC1 400V 90°C: 40A; Current AC3 400V 40-90°C: 32A, 15kW; 22-24 at 50Hz; 24-27V at 60Hz	

Cords for Tray Conveyors

Code	Spare Part Description	Picture
0E3584	Rope for tray conveyor belt with core Ø 15 mm rope (sold by the linear metre)	



Cords for Tray Conveyors

Code	Spare Part Description	Picture
0HB073	Rope for tray conveyor belt with core Ø 12 mm rope (sold by the linear metre)	
0E3762	Rope for tray conveyor belt with core Ø rope 15 mm (60m reel)	
0S3222	Rope for tray conveyor belt without core Ø rope 15 mm (50m reel)	
0S1230	Cord for tray conveyor belt without core Ø rope 15 mm (sold by the linear metre)	

External Dosing Systems for Dishwashers

Code	Spare Part Description	Picture
0S0669	Peristaltic pump for detergent mod. PR4 with volumetric dosage adjustment, santoprene tube, absorption 3.5 Watt 230V 50Hz Pressure: 0.1bar; Flow rate: 4 l/h Accessories supplied: fixing bracket, injection fitting, suction pipe, delivery pipe, bottom filter for single-tank machines	
0S0670	Peristaltic pump for detergent model PA6 with conductivity probe and santoprene tube. Absorption: 3.5 W Power supply: 230V, 50Hz Pressure: 0.1bar; Flow rate: 6 l/h; Equipped with: fixing bracket, injection fitting, suction pipe, delivery pipe and bottom filter and conductivity probe for tunnel machines	
0S0671	PR1 model peristaltic rinse aid pump with volumetric dosage adjustment and sekobrill tube. Absorption: 3.5 W Power supply: 230V, 50Hz Pressure: 3 bar; Flow rate: 1l/h equipped with: fixing bracket, suction hose, delivery hose, bottom filter, injection fitting with non-return valve, hose fitting Ø 6-8 mm for single-tank machines	
0S3138	WareDose 35 dosing system Microprocessor control with LCD display. Conductivity or timed detergent dosing. Speed or timed rinse aid dosing. Detergent pump: santoprene tube flow rate 9 l/h Rinse aid pump: SekoBril tube flow rate 1.5 l/h 3 bar Max absorptio	



External Dosing Systems for Dishwashers

Code	Spare Part Description	Picture
049419	Santoprene tube for detergent	
0S2121	Santoprene hose for detergent with BCK PVDF connection for dispenser 0S1986 6.25X10.65mm	
0S2817	conductivity probe for Twindose 40	

Accessories for External Dosing Systems

Code	Spare Part Description	Picture
0S0674	Detergent tank inlet steel injection fitting (PR4 and PA6)	
0S0675	Low-profile injection fitting for detergent tank inlet (PR4 and PA6) lot of 5pcs	
049358	Injection fitting with non-return valve for rinse aid (PR1)	
0S1249	Hose fitting for PR1 rinse aid injector, pack of 5 pieces	



Accessories for External Dosing Systems

Code	Spare Part Description	Picture
0S0677	Suction lance with level probe for Twindose 40 with EPDM non-return valve used on all products except those based on sanitizing chlorine	
0S0676	Suction lance with level probe for Twindose 40 with non-return valve in FPM used on sanitizing chlorine-based products	
049801	Detergent injector	
0L2071	Injector fixing ring nut	
049359	Transparent PVC hose for detergent 4x6mm length. 4m	
0S2100	Transparent PE hose for detergent 4x6mm 50m hank	
0L0481	Tube L=2660Mm; Øe=6mm; Blue	
0S1028	Bottom filter with stainless steel weight attached for 4 mm diameter tube	



Accessories for External Dosing Systems

Code	Spare Part Description	Picture
0S2772	Transparent PVC hose for detergent 4x6mm 100 m hank	
0L5181	TRANSPARENT PE HOSE FOR DETERGENT Ø 4x6 MM SOLD BY THE METER	
0L4643	GRAY PE HOSE FOR DETERGENT Ø 4x6 MM SOLD BY THE METER	
0S2387	TRANSPARENT PE HOSE FOR DETERGENT Ø 4x6 MM SET 100MT	
0L4642	Light blue PE hose for rinse aid 4x6mm sold by the metre	
0S2848	Sekobril tube for rinse aid for dispenser 0S0671 and 0S0672	
0S2847	Santoprene hose for dispenser cleaner 0S0669, 0S0670 and 0S0672	
0S3085	Light blue PE hose for rinse aid 4x6mm, 100m hank	

Inlet and Drain Water Pipes

Code	Spare Part Description	Picture
0L1887	Smooth rubber loading hose internal Ø 10 mm external Ø 17 mm yellow galvanized brass ring nut Ø 3/4"FF Operating pressure 10bar Temperature 90°C Connections: straight+90° length. 2000 mm, WRAS compliant	
0C8316	Internal rubber loading hose Ø 10mm external Ø 16mm nylon ring nut Ø 3/4"FF Operating pressure 10bar Temperature 90°C Connections: straight+90°, length. 1500 mm WRAS and VDE compliant	
061488	Gasket Ø 3/4"	
0L1031	WRC compliant smooth rubber loading hose Ø 3/4"FF internal Ø 15 mm external Ø 25 mm length. 2000 mm	
0S2210	WRC compliant smooth rubber loading hose Ø 3/4"FF internal Ø 15 mm external Ø 25 mm length. 2500 mm	
0S2214	WRC compliant smooth rubber loading hose Ø 3/4"FF internal Ø 15 mm external Ø 25 mm length. 3000 mm	
0C3359	Internal stainless steel braided loading hose Ø 19 mm, external Ø 28 mm nickel-plated brass ring nut Ø 3/4"FF max pressure 25bar, temperature 100°C connections: straight length. 2000 mm	
060933	Smooth rubber loading hose internal Ø 13mm external Ø 25mm nickel-plated brass ring nut Ø 3/4"FF operating pressure 10bar Temperature 90°C connections: straight length. 1500 mm	



Inlet and Drain Water Pipes

Code	Spare Part Description	Picture
0C8327	Internal rubber loading hose Ø 13mm external Ø 20mm nylon ring nut Ø 3/4"FF Operating pressure 10bar Temperature 90°C Connections: straight+90° length. 2100 mm WRAS and VDE compliant	
069571	Internal stainless steel braided charging hose Ø 10 mm, external Ø 14 mm nickel-plated brass ring nut Ø 3/4"FF max pressure 25bar Temperature 100°C connections: straight+90° length. 1500 mm	
0S0733	Internal stainless steel braided loading hose Ø 13mm, external Ø 19mm nickel-plated brass ring nut Ø 3/4"FF pressure length. 1500 mm	
049540	Internal stainless steel braided loading hose Ø 13mm, external Ø 19mm nickel-plated brass ring nut Ø 3/4"FF pressure length. 2100 mm	
0S1231	Internal stainless steel braided loading hose Ø 19 mm, external Ø 28 mm nickel-plated brass ring nut Ø 3/4"FF max pressure 15bar, temperature 100°C connections straight+90° length. 1500 mm	
0S1095	18/10 stainless steel hose for shower group transparent PVC covering swivel connections Ø1/2" MF L=1050 mm	
0L5288	18/10 stainless steel hose for shower group transparent PVC covering swivel connections Ø1/2" FF L=1100 mm	
0S1094	18/10 stainless steel hose L=1200 mm	



Inlet and Drain Water Pipes

Code	Spare Part Description	Picture
047894	Plasticized drain pipe made of shock-proof reinforced spiral PVC, resistant to high temperatures and chemical aggression	
048818	Plasticized drain hose in PVC, shock-proof reinforcement spiral, resistant to high temperatures and chemical aggression, smooth internal surface, internal sleeve Ø 35/40, internal pipe Ø 35 length. 1600 mm	
0S1155	Stainless steel spiral hose with swivel connections Ø1/2" FF L=1050 mm	
0L4552	Flexible drain hose with 90° polypropylene connection, internal sleeve Ø 35/40, internal pipe Ø 22.5 length. 1600 mm	
047465	Plasticized drain hose in PVC, shock-proof reinforcement spiral, resistant to high temperatures and chemical aggression, smooth internal surface, internal sleeve Ø 35/40, internal pipe Ø 35 length. 1000 mm	
0S2682	Flexible polypropylene drain hose, internal sleeve Ø 35/40, internal pipe Ø 22.5 length. 1600 mm	
0S3035	Flexible polypropylene drain hose internal sleeve Ø 28/35 internal pipe Ø 28 length. 3000 mm	
048845	PVC pump drain hose special model resistant to temp. max 80°C and chemical attack, inside sleeve Ø 18/28 inside tube Ø18 length. 2100 mm	

Internal Dosing Systems for Dishwashers

Code	Spare Part Description	Picture
0L4295	Rinse aid dispenser, flow rate adjustment screw from 0 to 4 cm ³ /cycle complete with hose fittings, bottom filter with steel bushing and tube	
0HA055	Rinse aid dispenser type 1000	
0HA056	Type 3000 rinse aid dispenser with filter	
0S0706	Peristaltic rinse aid pump mod. NBR 0.4 flow rate adjustment t/p: 0.4 l/h pressure: 3bar Power supply: 230V- 50Hz complete with: 2 m of suction hose, 2 m of delivery hose, injection fitting with non-return valve for rinse aid, ROHS certification	
0S2787	Peristaltic rinse aid pump mod. NPG -04 flow rate: 0.4 l/h pressure: 3 bar Electrical supply: 230 V - 50/60 Hz complete with: 4 m of 4x6 PE pipe, 2.66 m of 4x6 cross-linked PEHD pipe, filter and weight of bottom, ROHS certified rinse aid injection valve	
0S2782	Peristaltic detergent pump mod. NPG -3 flow rate: 3 l/h pressure: 0.1 bar Electrical supply: 230V - 50/60 Hz complete with: 4 m of PE 4x6 pipe, 1.6 m of PE 4x6 pipe, filter and bottom weight, ROHS certified bulkhead	
0S2781	Peristaltic detergent pump mod. NBR 3 flow rate regulator t/p: 3 l/h pressure: 0.1 bar Electrical supply: 230V - 50 Hz complete with: 4 m of PE 4x6 pipe, 1.6 m of PE 4x6 pipe, adjustable peristaltic connection wiring, filter and weight of bottom, ROHS 247 certification	

Accessories for Internal Dosing Systems

Code	Spare Part Description	Picture
0R0081	Diaphragm for type 3000 dispenser	
0HA092	Diaphragm for type 1000 dispenser	
0R0083	Small valve for 1000/3000 sets nr. 5 pieces Code Qt. Description 0R0082 5 Valve	
0HA067	Suction filter for type 3000 dispenser	
049418	Sekobril tube for rinse aid	
0L5079	Sekobril hose for rinse aid Quick connections for 4x6mm hoses in PE material (code 0L0481 and 0S3085)	
0L5076	Santoprene hose for detergent Quick connections for 4x6mm hoses in PE material (code 0S2100)	

Magnetic Coils for Solenoid Valves

Code	Spare Part Description	Picture
0S2268	Magnetic coil type Z610A 230V 50-60Hz	
0S1612	Magnetic coil type Z610A 24VAC 10VA 50-60Hz	
0PRE91	Magnetic coil type ZA34A 230V 50HZ 14VA housing Ø 14mm for OCBAYD solenoid valve	
0CA882	Magnetic coil 24V DC 50Hz 15W type BC2 for solenoid valve 003778	
0S2269	Magnetic coil type ZB10A 230V 50-60Hz 4W	
0S2270	Magnetic coil type ZB10A 24V 50-60Hz 4W	



Magnetic Coils for Solenoid Valves

Code	Spare Part Description	Picture
0CA930	Magnetic coil type BA2 24V AC 50Hz 11VA For solenoid valve 003778	
0PRDTN	Magnetic coil 16A 230VAC 50/60Hz Type BDV for solenoid valve 0C1148	
0PRDTO	Magnetic coil 14.5A 24VAC 50/60Hz Type BDA	

Pressure Switches

Code	Spare Part Description	Picture
0PRQ12	PRESSURE SWITCH 1st level pressure range: 28/12 mbar; Connection size: 6mm; Diameter Size: 58mm; Photo type A	
0PRAC3	PRESSURE SWITCH 1st level pressure range: 35/17 mbar; Connection size: 6mm; Diameter Size: 58mm; Photo type A	
0PRG28	PRESSURE SWITCH 1st level pressure range: 46/26 mbar; Connection size: 6mm; Diameter Size: 58mm; Photo type A	
0S2723	PRESSURE SWITCH 1st level pressure range: 50/20 mbar; Connection size: 6mm; Diameter Size: 58mm; Maximum operating temperature: 85°C; Photo type A	



Pressure Switches

Code	Spare Part Description	Picture
0PRZ46	PRESSURE SWITCH 1st level pressure range: 55/30 mbar; Connection size: 6mm; Diameter Size: 58mm; Maximum operating temperature: 85°C; Photo type A	
069434	PRESSURE SWITCH 1st level pressure range: 55/35 mbar; Connection size: 6mm; Diameter Size: 58mm; Maximum operating temperature: 85°C; Photo type A	
049485	Dishwashing pressure switch kit Code Qt. Description 049413 1 Support , 0L0048 1 Pressure switch	
0PRAD3	PRESSURE SWITCH 1st level pressure range: 60/25 mbar; Connection size: 6mm; Diameter Size: 58mm; Photo type A	
0PRA7E	PRESSURE SWITCH 1st level pressure range: 75/35 mbar; Connection size: 6mm; Diameter Size: 58mm; Maximum operating temperature: 85°C; Photo type A	
0PRY05	PRESSURE SWITCH 1st level pressure range: 90/35 mbar; Connection size: 6mm; Diameter Size: 58mm; Maximum operating temperature: 85°C; Photo type A	
0PRX78	PRESSURE SWITCH 1st level pressure range: 110/60 mbar; Connection size: 6mm; Diameter Size: 58mm; Maximum operating temperature: 85°C; Photo type A	
0G2646	PRESSURE SWITCH 1st level pressure range: 110/70 mbar; Connection size: 6mm; Diameter Size: 58mm; Maximum operating temperature: 85°C; Photo type A	
0S2724	PRESSURE SWITCH 1st level pressure range: 123/75 mbar; Connection size: 6mm; Diameter Size: 58mm; Maximum operating temperature: 85°C; Photo type A	
0PRG23	PRESSURE SWITCH 1st level pressure range: 125/105 mbar; Connection size: 6mm; Diameter Size: 58mm; Photo type A	
0PRPDX	PRESSURE SWITCH 1st level pressure range: 165/140 mbar; Connection size: 6mm; Diameter Size: 58mm; Photo type A	
0PRX71	PRESSURE SWITCH 1st level pressure range: 180/70 mbar; Connection size: 6mm; Diameter Size: 58mm; Photo type A	



Pressure Switches

Code	Spare Part Description	Picture
048267	PRESSURE SWITCH 1st level pressure range: 240/130 mbar; Connection size: 6mm; Diameter Size: 58mm; Maximum operating temperature: 85°C; Photo type A Code Qt. Description 049413 1 Support , 0L0599 1 Pressure switch	
0S2725	PRESSURE SWITCH 1st level pressure range: 250/40 mbar; Connection size: 6mm; Diameter Size: 58mm; Maximum operating temperature: 85°C; Photo type A	
075660	PRESSURE SWITCH 1st level pressure range: 310/180 mbar; Connection size: 6mm; Diameter Size: 58mm; Photo type A	
0S2355	PRESSURE SWITCH 1st level pressure range: 340/200 mbar; Connection size: 6mm; Diameter Size: 58mm; Photo type A	
0KZ785	PRESSURE SWITCH 1st level pressure range: 40/15 mbar; Connection size: 6mm; Diameter Size: 58mm; Photo type B	
0KZ786	PRESSURE SWITCH 1st level pressure range: 60/35 mbar; Connection size: 6mm; Diameter Size: 55mm; Photo type B	
049881	PRESSURE SWITCH 1st level pressure range: 60/20-110 mbar; Connection size: 6mm; Diameter Size: 58mm; Photo type B	
049058	PRESSURE SWITCH 1st level pressure range: 110/55 mbar; Connection size: 6mm; Diameter Size: 58mm; Photo type B	



Pressure Switches

Code	Spare Part Description	Picture
049775	PRESSURE SWITCH 1st level pressure range: 180/80 mbar; Connection size: 6mm; Diameter Size: 58mm; Photo type B	
049620	PRESSURE SWITCH 1st level pressure range: 250/130 mbar; Connection size: 6mm; Diameter Size: 58mm; Photo type B	
0C0872	PRESSURE SWITCH 1st level pressure range: 320/200 mbar; Connection size: 6mm; Diameter Size: 55mm; Maximum operating temperature: 85°C; Photo type B	
0S2726	PRESSURE SWITCH 1st level pressure range: 28/13 mbar; 2nd level pressure range: 65/50 mbar; Connection size: 6mm; Diameter Size: 84mm; Photo type C	
0RT319	PRESSURE SWITCH 1st level pressure range: 35/20 mbar; 2nd level pressure range: 80/60 mba; Connection size: 6mm; Diameter Size: 84mm; Photo type D	
0E3731	PRESSURE SWITCH 1st level pressure range: 40/15 mbar; 2nd level pressure range: 55/35 mbar; Connection size: 6mm; Diameter Size: 84mm; Photo type C	
0K7146	PRESSURE SWITCH 1st level pressure range: 60/20 mbar; 2nd level pressure range: 100/30 mbar; Connection size: 6mm; Diameter Size: 84mm; Photo type D	
049081	PRESSURE SWITCH 1st level pressure range: 165/135 mbar; 2nd level pressure range: 110/55 mbar; Connection size: 6mm; Diameter Size: 84mm; Photo type C	
0S2727	PRESSURE SWITCH 1st level pressure range: 40/15 mbar; 2nd level pressure range: 120/60 mbar; 3rd level pressure range: 150/95 mbar; Connection size: 6mm; Diameter size: 84mm	



Pressure Switches

Code	Spare Part Description	Picture
0RT108	PRESSURE SWITCH 1st level pressure range: 40/25 mbar; 2nd level pressure range: 57/42 mbar; 3rd level pressure range: 125/105 mbar; Connection size: 6mm; Diameter size: 79mm	
0RT313	PRESSURE SWITCH 1st level pressure range: 40/25 mbar; 2nd level pressure range: 92/77 mbar; 3rd level pressure range: 160/140 mbar; Connection size: 6mm; Diameter size: 79mm	
0S2728	PRESSURE SWITCH 1st level pressure range: 50/30 mbar; 2nd level pressure range: 50/30 mbar; 3rd level pressure range: 145/80 mbar; Connection size: 6mm; Diameter size: 84mm	
0S3220	Pressure switch Pressure range 1st level: 60/305 mbar; Connection size: 6mm; Diameter size: 58mm; Photo type A	
0PRQJ3	Pressure switch Pressure range 1st level: 230/260 mbar; Connection size: 6mm; Diameter size: 58mm; Maximum operating temperature: 85°C; Photo type A	

Siphons - Drains - Overflows

Code	Spare Part Description	Picture
0S1335	Single Ø 1½" plastic siphon	
069821	Single Ø 2" plastic siphon	
0S0905	Double siphon Ø 1½" in plastic	



Siphons - Drains - Overflows

Code	Spare Part Description	Picture
033601	Double siphon Ø 2" in plastic	
0C9489	Stainless steel overflow pipe Ø 40 mm for drains Ø 1 1/2 H=180 mm	
069656	Overflow tube Ø 40 mm in chromed brass H=295 mm	
049759	Overflow tube Ø 50 mm in chromed brass H=280 mm	
0S0119	Stainless steel overflow tube Ø 50 mm H=270 mm	
0S0118	Overflow pipe Ø 50 mm in stainless steel H=295 mm	
069654	Drain waste Ø 40 mm in chromed brass 1 1/2" connection	
069816	Drain waste Ø 50 mm in chromed brass with 2" connection	



Siphons - Drains - Overflows

Code	Spare Part Description	Picture
033607	Drain drain Ø 50 mm, plastic body and steel filter, 2" connection	
0S1319	Drain waste Ø 50 mm, plastic body and steel filter, 1 1/2" connection with 2" adapter	
0S3339	Overflow pipe Ø 45 mm in plastic and stainless steel for waste code 0S3344 H=200 mm	
0S3340	Overflow pipe Ø 45 mm in plastic and stainless steel for waste code 0S3344 H=250 mm	
0S3341	Overflow pipe Ø 45 mm in plastic and stainless steel for waste code 0S3344 H=300 mm	
0S3343	Overflow pipe Ø 45 mm in plastic and stainless steel for waste code 0S3344 H=350 mm	
0S3344	Stainless steel drain plug Ø 45 mm, 1 1/2" connection	

Solenoid Valves

Code	Spare Part Description	Picture
055350	Single solenoid valve 90° inlet Ø 3/4" free outlet Ø 10 mm blue reducer 1lt/min max temperature 90°C coil 220/240 V 50/60 Hz	
055444	Double solenoid valve 90° inlet Ø 3/4" free outlet Ø 10 mm blue reducer 1lt/min max temperature 90°C coil 220/240 V 50/60 Hz	



Solenoid Valves

Code	Spare Part Description	Picture
002712	Triple solenoid valve 90° Inlet Ø 3/4" free Outlet Ø 10 mm Red reducer 0.25 l/min Max temperature 90°C Coil 220/240 V 50/60 Hz	
048178	Single solenoid valve 90° Inlet Ø 3/4" 20 l/min Outlet Ø 14 mm free Max temperature 90°C Coil 220/240 V 50/60 Hz	
0E5070	Single 24V solenoid valve 180° inlet Ø 3/4" free outlet Ø 14mm free max temperature 90°C coil 24 V 50 Hz	
002753	Single solenoid valve 180° inlet Ø 3/4" free outlet Ø 10 mm blue reducer 1lt/min max temperature 90°C coil 220/240 V 50/60 Hz	
047536	Double solenoid valve 180° Inlet Ø 3/4" 20 l/min Outlet Ø 10 mm Black reducer 5 l/min Max temperature 90°C Coil 220/240 V 50/60 Hz	
0F0001	Triple solenoid valve 180° inlet Ø 3/4" outlet Ø 10 mm reducer yellow 2.5 l/min - red 0.25 l/min max temperature 90°C coil 220/240 V 50/60 Hz	



Solenoid Valves

Code	Spare Part Description	Picture
049230	Double solenoid valve 90° Inlet Ø 3/4" 14 l/min Outlet Ø 14 mm free Max temperature 90°C Coil 220/240 V 50/60 Hz	
048180	24V double solenoid valve 180° inlet Ø 3/4" free outlet Ø 14mm free max temperature 90°C coil 24 V 50 Hz	
0C1933	Single 90° solenoid valve inlet Ø 3/4" outlet Ø 10 mm power connection P5 blue max temperature 90°C coil 220/240 V 50/60 Hz	
0C6137	Double solenoid valve 90° inlet Ø 3/4" outlet Ø 10 mm reducer 8lt/min - 0.6 l/min power connection P5 blue-orange max temperature 90°C coil 220/240 V 50/60 Hz	
0C2240	Triple 90° solenoid valve inlet Ø 3/4" outlet Ø 10 mm reducer 1.2lt/min-0.25 l/min power connection P5 orange-grey-blue max temperature 90°C coil 220/240 V 50/60 Hz	
049626	Single solenoid valve 90° inlet Ø 3/4" 10 l/min outlet Ø 14 mm free P5 power supply connection orange max temperature 90°C coil 220/240 V 50/60 Hz	



Solenoid Valves

Code	Spare Part Description	Picture
049439	Double outlet solenoid valve 90° inlet Ø 3/4" 20 l/min outlet Ø 14 mm free P5 power supply connection orange-green max temperature 90°C coil 220/240 V 50/60 Hz	
0C3254	Single solenoid valve 180° inlet Ø 3/4" outlet Ø 10 mm power connection P5 blue max temperature 90°C coil 220/240 V 50/60 Hz	
0C5517	Double solenoid valve 180° inlet Ø 3/4" outlet Ø 10 mm reducer 5lt/min - 0.25 l/min power connection P5 orange-grey max temperature 90°C coil 220/240 V 50/60 Hz	
0C1934	Triple solenoid valve 180° inlet Ø 3/4" outlet Ø 10 mm reducer 1.2lt/min- 0.25 l/min power connection P5 orange-grey-blue max temperature 90°C coil 220/240 V 50/60 Hz	
0L3446	Single solenoid valve 180° inlet Ø 3/4" outlet Ø 14 mm power connection P5 orange max temperature 90°C coil 220/240 V 50/60 Hz	
049668	Solenoid valve double outlet 180° inlet Ø 3/4" 20 l/min outlet Ø 14 mm free power connection P5 orange-green max temperature 90°C coil 220/240 V 50/60 Hz	



Solenoid Valves

Code	Spare Part Description	Picture
0L3444	Triple outlet solenoid valve 90° inlet Ø 3/4" outlet Ø 14 mm reducer red 0.25 l/min - white power connection P5 orange-green-white max temperature 90°C coil 220/240 V 50/60 Hz	
0L4427	3/8" solenoid valve, 230V 50-60Hz, brass body with nickel plating treatment, internal components in brass and stainless steel, operating range: 0.35-20bar, internal diameter 13.5mm, fluid temperature range -10/+ 140°C	
0C6081	1-way solenoid valve with inlet filter and galvanised steel fixing bracket, 180° displacement, 220-240V/50-60Hz, flow rate: 0.25 l/min, operating pressure 0.2-10bar, terminals with faston 6.3x0.8 pitch 12.5, water operating temperatures 15 to 90°C	
0S1650	Single solenoid valve 90° inlet Ø 3/4" free outlet Ø 10 mm free max temperature 90°C coil 220/240 V 50/60 Hz	
0S1656	Single solenoid valve 90° inlet Ø 3/4" free outlet Ø 14 mm free max temperature 90°C coil 220/240 V 50/60 Hz	
0S2569	Single solenoid valve 180° inlet Ø 3/4" free outlet Ø 10 mm free max temperature 90°C coil 220/240 V 50/60 Hz	



Solenoid Valves

Code	Spare Part Description	Picture
0S2570	Single solenoid valve 180° inlet Ø 3/4" free outlet Ø 14mm free max temperature 90°C coil 220/240 V 50/60 Hz	
0S3342	Single solenoid valve 24V 180° inlet Ø 3/4" free outlet Ø 14mm free max temperature 90°C coil 24 V 50 Hz	
0S2571	Double solenoid valve 90° inlet Ø 3/4" free outlet Ø 10 mm free max temperature 90°C coil 220/240 V 50/60 Hz	
0S1657	Double solenoid valve 90° inlet Ø 3/4" free outlet Ø 14mm free max temperature 90°C coil 220/240 V 50/60 Hz	
0S1654	Double solenoid valve 180° inlet Ø 3/4" free outlet Ø 10 mm free max temperature 90°C coil 220/240 V 50/60 Hz	
0S1652	Triple solenoid valve 90° inlet Ø 3/4" free outlet Ø 10 mm free max temperature 90°C coil 220/240 V 50/60 Hz	



Solenoid Valves

Code	Spare Part Description	Picture
0S1655	Triple solenoid valve 180° inlet Ø 3/4" free outlet Ø 10 mm free max temperature 90°C coil 220/240 V 50/60 Hz	
0S2545	Red output flow rate reducer 0.25l/min	
0S2546	Orange output flow rate reducer 0.5l/min	
0S2547	White output flow rate reducer 0.8l/min	
0S2548	Celestial outlet flow rate reducer 1l/min	
0S2549	Brown output flow rate reducer 1.2l/min	



Solenoid Valves

Code	Spare Part Description	Picture
0S2550	Output flow reducer light brown 1.5l/min	
0S2551	Yellow output flow rate reducer 2.5l/min	
0S2552	Dark green output flow rate reducer 3.4l/min	
0S2553	Black output flow rate reducer 5l/min	
0S2538	Red inlet flow reducer 3l/min	
0S2539	Yellow inlet flow reducer 5.5l/min	



Solenoid Valves

Code	Spare Part Description	Picture
0S2540	Gray inlet flow reducer 6l/min	
0S2541	White inlet flow reducer 10l/min	
0S2542	Bronze inlet flow rate reducer 12l/min	
0S2543	Light brown inlet flow reducer 16l/min	
0S2544	Bright red inlet flow reducer 20l/min	

Taps

Code	Spare Part Description	Picture
0S1238	Cartridge for Euro type single lever taps diameter 40mm square connection 10x10.5 mm	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Genuine Replacement Parts

Taps

Code	Spare Part Description	Picture
0S0346	Cartridge for single-lever taps type CX42 8x7 and 9x9 square connection for mixer taps 037616 and 037617	
0S2218	Cartridge for single-lever Euro-type taps with square connection 10x10.5 for shower group 0S0956 and 0S0894	
0S1239	Cartridge for single-lever taps type AX38 square connection 10x10.5	
0S0146	U type dispensing spout Ø18X300M	
0S0063	3/4" screws for single and double hole groups	
0S0343	Leverage black clinic	
0S1340	Cartridge for single-lever taps diameter 47mm square connection 10x10.5 mm for mixer taps 0S0863 and 0S1457	
0PE631	self-closing tap ca. 15 sec, thread 1/2" L 95mm	



Taps

Code	Spare Part Description	Picture
0S3300	Swivel spout L= 200mm	
0S3299	Swivel spout L= 250mm	

Water Columns for Counters (K-series)

Code	Spare Part Description	Picture
0S3139	90° pot filling column 360° rotatable Stainless steel and brass body. Dim. 637x814mm. Fixing hole 3/4"G. Water connection 1/2"G U-shaped spout dim. 18x300x30mm DVGW Hygiene compliant	

Cables and Plugs

Code	Spare Part Description	Picture
037983	Spiral cable with SCHUKO plug 3 wires x 1.5 mm ² Length 950-3000mm Protection degree IP44	
0A3010	Spiral cable 3 wires x 1.5 mm ² Length 750-3000mm	
0KL080	Cable with SCHUKO plug 3 wires x 1 mm ² Length 2400mm	



Cables and Plugs

Code	Spare Part Description	Picture
0S3065	Cable with SCHUKO plug 90° 3 wires x 1.5 mm ² Length 2400mm	
0SPLHV 04.SF0034.001	Three-phase straight mobile plug No. of poles: 3P+N+E 16A Nominal voltage 380-415V Dimensions: 153mm Ø68mm Protection degree IP54	

Fuses

Code	Spare Part Description	Picture
0W3499 471900442	Rapid fuse Ø 5x20mm 0.32A 250V	
002750	Rapid fuse Ø 5x20mm 0.4A 250V	
0G5814	Rapid fuse Ø 5x20mm 1A 250V	
0A8438	Rapid fuse Ø 5x20mm 2A 250V	
058869	Rapid fuse Ø 5x20mm 10A 250V	



Fuses

Code	Spare Part Description	Picture
058871	Rapid fuse Ø 5x20mm 6.3A 250V	
005136	Rapid fuse Ø 5x20mm 16A 250V	
0D0467	Ceramic fuse Ø 5x20mm 0.8A 400V	
0L3432	Ceramic fuse Ø 5x20mm 1A 250V	
0E2697 471875011	Ceramic fuse Ø 5x20mm 1.25A 250V	
0L3433	Ceramic fuse Ø 5x20mm 2A 250V	
0W1VCY 471875023	Ceramic fuse Ø 5x20mm 3.15A 250V	
0L3434	Ceramic fuse Ø 5x20mm 5A 250V	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Genuine Replacement Parts

Fuses

Code	Spare Part Description	Picture
0L3435	Ceramic fuse Ø 5x20mm 6.3A 250V	
0L3083	Ceramic fuse Ø 5x20mm 10A 250V	
086317	Ceramic fuse Ø 5x20mm 16A 250V	
047131	Ceramic fuse Ø 10x38mm 25A 500V	
048995	Ceramic fuse Ø 10x38mm 1A 500V	
003669	Ceramic fuse Ø 10x38mm 2A 500V	
003670	Ceramic fuse Ø 10x38mm 6A 500V	

Lighting

Code	Spare Part Description	Picture
054840	Clear tubular lamp 25 W small socket E14 230 V	
0PRZFI	40W halogen lamp small E14 fitting 230V for temperatures even above 300°C	
0S2260	40 W halogen lamp with G9 230 V connection for temperatures up to 300°C	
0S2518	4 W LED lamp with G9 connection 3000 °K 230V	
0S2385	Halogen infrared lamp 200W R7S connection 235 V dim. L 185.7mm Ø 7 mm	
0S2587	Halogen infrared lamp 350W R7S connection 235 V dim. L 185.7mm Ø 9.6mm	
0PR505	Halogen infrared lamp 500W R7S connection 235 V dim. L 220.6mm Ø 11mm	
0S0596	Light olive lamp 40 W small socket E14 230 V for max temperatures 300°C	
0CB661	10W halogen lamp with G4 12 V connection	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Genuine Replacement Parts

Lighting

Code	Spare Part Description	Picture
0S1957	10W LED lamp R7S connection lumen 1200 light 2700K 230V 50/60Hz dim. Ø22x118mm	
0S1918	250 W infrared lamp with E27 230 V connection, light colour	
0PE645	Ceiling light for extractor hoods with halogen connection complete with 40 W halogen bulb, G9 230V connection	
0PE842	Tubular fluorescent lamp 18 W T8 class II Power supply 230V(I) 50/60Hz Length 590mm	
032276	1x36W fluorescent ceiling light with protection no. 1 lamp 36 W dim. 1257x65x124 mm pnc 644834	
033804	Ceiling light for extractor hoods with 40 W bulb and glass globe, E14 bulb connection, max temperature 300°C	
004160	Lamp holder for bulbs with E14 screw connection	
004163	Glass globe	



Lighting

Code	Spare Part Description	Picture
0H7035	Clear tubular lamp 15 W small socket E14 230 V	
0S2862	Halogen lamp 150 W connection R7S 230 V dim. L 118 mm	
0S2803	Lampholder with R7S 10A/250V connection in metal material Adaptable to lamps of any length Sold individually	
0S2977	Ceiling light 1x36 W LED nr. 1 LED lamp 18 W Degree of protection IP65 dim. 1250x125x136 mm PNC 644836	
0S3075	10W LED lamp R7S connection lumen 1350 light 3000K 220/240V 50/60Hz dim. Ø16x118mm	
0S3022	1x8 W LED ceiling light IP65 protection rating dim. 650x55x115 mm max power 18W PNC 644835	
0S3040	LED tubular lamp 8 W, T8 class II 4000K Cold white Power supply 220V/240V(I) 50/60Hz Length 600mm	
0S2979	LED tubular lamp 18 W, T8 class II 4000K Cold white Power supply 220V/240V(I) 50/60Hz Length 1200mm	
0S3017	Stainless steel food warmer lamp holder Diameter 260mm Adjustable cable length 980/1980mm 250W lamp code 0S1918 included	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Genuine Replacement Parts

Lighting

Code	Spare Part Description	Picture
0S3103	Stainless steel heating lamp Diameter 180mm Adjustable cable length 980/1980mm 250W lamp code 0S1918 included	
0S3130	LED lamp 4W 230V G9 fitting Ø16X50.5MM NEUTRAL light 4000°K	
0S3162	Ceiling light 1x36W polycarbonate body with watertight protection. No. 1 lamp 36 W dim. 1300x97x92 mm Complete with lamp code 0S3039	
0PRD0P	Germicidal lamp 15W G13 fitting Length 435mm	
0S3151	Germicidal lamp 15W G13 fitting Length 450mm	
0S3190	Germicidal lamp 18W G13 fitting Length 610mm	
093949	Germicidal lamp 18W 2G11 fitting Length 226mm	
0PRW7B	Germicidal lamp 15W E27 fitting for knife cabinets	
0S3287	16W LED tubular lamp (equivalent to 36W fluorescent) Direct power supply at 230V (No ballast) 4000K, G5 socket Length 849mm	
0S3286	16W LED tubular lamp (equivalent to 36W fluorescent) Direct power supply at 230V (No ballast) 4000K, G5 socket Length 1150mm	



Lighting

Code	Spare Part Description	Picture
0S3326	20W halogen lamp with G4 socket, 12V, for temperatures up to 450°C	
0PRQHV	20W halogen lamp GU 5.3 socket 12V	
0S3293	15.5W LED tubular lamp (equivalent to 36W fluorescent) Direct power supply at 230V (No ballast) 4000K, G13 fitting Length 1200mm	
0S3253	28.6W LED ceiling light, polycarbonate body with waterproof protection. 4100lm, temp. 4000K. IP65 protection rating, dim. 1250x96x87 mm.	
0S3266	LED strip 24V 14.4W Length 5 meters Temp. 6500K Cold White Dimmable Rear adhesive: 3M	
0S3264	Transformer 100W 24V Dim. 295x43x29,5mm	
0S3265	Anodized aluminum profile Length 2 meters Reduced height: < 7 mm With satin polycarbonate diffuser For strips up to 15W/m The package includes: 1 diffuser 4 fixing clips 2 closing caps	
0PE172	Quartz infrared lamp 500 W Length 505x10mm threaded connection 2.23A 230/240V For shelf with heating element	
0S3356	150W infrared lamp with R7S fitting, 230V, dim. L 118mm	

Quartz Heating Elements

Code	Spare Part Description	Picture
0S3321	Quartz resistor 310W 115V Dimensions: ø11mm x 455mm Faston connection M 6.3mm	
0S3322	Quartz resistor 400W 115V Dimensions: ø11.5mm x 285mm Faston connection M 6.3mm	
0S3323	Quartz resistance 480W 115V Dimensions: ø10mm x 365mm Faston connection M 6.3mm	
0S3324	Quartz resistor 500W 115V Dimensions: ø10mm x 373mm Faston connection M 6.3mm	
0SR773	Quartz resistor 500W 115V Dimensions: ø11.5mm x 390mm	
0SR611	Quartz resistor 600W 115V Dimensions: ø12mm x 390mm	
0PRS3J	Quartz resistance 920W 115V Dimensions: ø11mm x 428mm Faston connection M 6.3mm	

Switches

Code	Spare Part Description	Picture
0SP312 04.BA0024.001	BLACK SINGLE-POLE SWITCH I-O, TEMPLATE 11X30MM	
004110	GREEN SINGLE-POLE SWITCH, LIGHTED, TEMPLATE 11X30MM	
053810	GREEN BIPOLAR SWITCH I-O LUM. DIM. 22X30MM	



Switches

Code	Spare Part Description	Picture
004158	GREEN BIPOLAR SWITCH I-O LUM. DIM. 22X30MM	
053837	GREEN BIPOLAR SWITCH II LUM. TEMPLATE 22X30MM	
054552	GREEN BIPOLAR SWITCH WITH LIGHTING, TEMPLATE 22X30MM	
0K8650	GREEN BIPOLAR SWITCH, LIGHTED, TEMPLATE 22X30MM	
056880	ORANGE BIPOLAR SWITCH I-O LUM. DIM. 22X30MM	
082390	WHITE BIPOLAR SWITCH I-O LUM. DIM. 22X30MM	
0S3227	RED BIPOLAR SWITCH I-O LUM. DIMA 22X30MM	
005899	RED BIPOLAR SWITCH I-O LUM. DIMA 22X30MM	



Genuine Replacement Parts

Switches

Code	Spare Part Description	Picture
099275	WHITE BIPOLAR SWITCH I-II LUM. DIM. 25X27MM	
092131	BIPOLAR WHITE SWITCH, LIGHTED, 25X27MM DIAGRAM	
082337	GREEN BIPOLAR SWITCH, LIGHTED, 25MM DIMENSION	
054518	GREEN BIPOLAR SWITCH, LIGHTED, 25MM DIMENSION	

Accessories for Cold Rooms

Code	Spare Part Description	Picture
092602	Ventilated crawl space profile for cells dim. mm 40x70 length. 1860 mm	
092604	Ventilated crawl space profile for cells dim. mm 40x70 length. 2660 mm	
092606	Ventilated crawl space profile for cells dim. mm 40x70 length. 3460 mm	



Accessories for Cold Rooms

Code	Spare Part Description	Picture
092603	Ventilated crawl space profile for cells dim. mm 40x70 length. 2260 mm	
092605	Ventilated crawl space profile for cells dim. mm 40x70 length. 3060 mm	
095414	Anti-panic label	

Anti-Acid Filter Driers

Code	Spare Part Description	Picture
0S1900	Solid cartridge filter driers 100% molecular sieve SAE flare connections Description: Filter drier; Type: 4305/2; SAE FLARE connections: 1/4"; Volume (cm³): 80; PS(bar) 45; TS (°C) min -40 max +60	
0S1823	Solid cartridge filter driers 100% molecular sieve SAE flare connections Description: Filter drier; Type: 4305/3; SAE FLARE connections: 3/8"; Volume (cm³): 80; PS(bar) 45; TS (°C) min -40 max +60	
0S2211	Solid cartridge filter driers 100% molecular sieve SAE flare connections Description: Filter drier; Type: 4308/2; SAE FLARE connections: 1/4"; Volume (cm³): 130; PS(bar) 45; TS (°C) min -40 max +60	



Anti-Acid Filter Driers

Code	Spare Part Description	Picture
0S1498	Solid cartridge filter driers 100% molecular sieve SAE flare connections Description: Filter drier; Type: 4308/3; SAE FLARE connections: 3/8"; Volume (cm³): 130; PS(bar) 45; TS (°C) min -40 max +60	
0S2212	Solid cartridge filter driers 100% molecular sieve SAE flare connections Description: Filter drier; Type: 4316/3; SAE FLARE connections: 3/8"; Volume (cm³): 250; PS(bar) 45; TS (°C) min -40 max +60	
0S2213	Solid cartridge filter driers 100% molecular sieve SAE flare connections Description: Filter drier; Type: 4316/4; SAE FLARE connections: 1/2"; Volume (cm³): 250; PS(bar) 45; TS (°C) min -40 max +60	
092142	Solid cartridge filter driers 100% molecular sieve SAE flare connections Description: Filter drier; Type: DML 304; SAE FLARE connections: 1/2"; Volume (cm³): 330; PS(bar) 46; TS (°C) min -40 max +70	
089791	Solid cartridge filter driers 100% molecular sieve SAE flare connections Description: Filter drier; Type: DML 305; SAE FLARE connections: 3/8"; Volume (cm³): 330; PS(bar) 46; TS (°C) min -40 max +70	
089669	Solid cartridge filter driers 100% molecular sieve solder connections Description: Filter drier; Type: 4303/2S; Connections ODS Ø (in-mm) 1/4", ODM Ø (in-mm) 3/8"; Volume (cm³): 50; PS(bar) 45; TS (°C) min -40 max +80	
0S1497	Solid cartridge filter driers 100% molecular sieve solder connections Description: Filter drier; Type: 4308/M10S; Connections ODS Ø (in-mm) 10, ODM Ø (in-mm) 12; Volume (cm³): 130; PS(bar) 45; TS (°C) min -40 max +80	
092143	Solid cartridge filter driers 100% molecular sieve solder connections Description: Filter drier; Type: DML307S; Connections ODS Ø (in-mm) 22, ODM Ø (in-mm); Volume (cm³): 330; PS(bar) 46; TS (°C) min -40 max +70	
0S3269	Solid cartridge filter driers 100% molecular sieve with humidity indicator, solder connections Type: DI305N/2S; ODS connections Ø (in-mm) 1/4"; Volume (cm³): 80; PS (bar) 50; TS (°C) min -40 max +80	
0S3270	Solid cartridge filter driers 100% molecular sieve with humidity indicator, solder connections Type: DI305N/3S; ODS connections Ø (in-mm) 3/8"; Volume (cm³): 80; PS (bar) 50; TS (°C) min -40 max +80	



Anti-Acid Filter Driers

Code	Spare Part Description	Picture
0S3271	Solid cartridge filter driers 100% molecular sieve with humidity indicator, solder connections Type: DI308N/2S; ODS connections Ø (in-mm) 1/4"; Volume (cm³): 130; PS (bar) 50; TS (°C) min -40 max +80	
0S3272	Solid cartridge filter driers 100% molecular sieve with humidity indicator, solder connections Type: DI308N/3S; ODS connections Ø (in-mm) 3/8"; Volume (cm³): 130; PS (bar) 50; TS (°C) min -40 max +80	
0S3273	Solid cartridge filter driers 100% molecular sieve with humidity indicator, solder connections Type: DI316N/3S; ODS connections Ø (in-mm) 3/8"; Volume (cm³): 250; PS (bar) 50; TS (°C) min -40 max +80	
0S2987	DML 052 filter drier	

Castors

Code	Spare Part Description	Picture
095795	Wheels for ecostoreHP Premium refrigerated/freezer tables, height 150 mm; Recommended quantities: ► for tables with 2 and 3 compartments: 2 pieces 095795 and 2 pieces 095796 ► for tables with 4 compartments: 3 pieces 095795 and 2 pieces 095796 Compatible with: 1 wheel with brake	
095796	Wheels for ecostoreHP Premium refrigerated/freezer tables, height 150 mm; Recommended quantities: ► for tables with 2 and 3 compartments: 2 pieces 095795 and 2 pieces 095796 ► for tables with 4 compartments: 3 pieces 095795 and 2 pieces 095796 Compatible with: 1 wheel without brake	

Cold Room Handles

Code	Spare Part Description	Picture
0S3061	Internal handle for cell Model 500TN Dimensions 79x145mm Hole spacing 110mm For door thickness up to 180mm	



Genuine Replacement Parts

Cold Room Handles

Code	Spare Part Description	Picture
0S3062	External handle for cell Model 500TN Dimensions 200x110mm Hole spacing 110mm	
095610	Complete handle for standard Misa cells from 2013. Includes internal handle, external handle, spacers, and key. For door thicknesses of 70-80mm.	
094730	Complete handle For blast chillers 120-180-200kg Complete with internal handle, external handle and spacers Hole spacing 82x41mm For door thickness 50-150mm	
0S3330	Complete handle. Includes internal handle, external handle, spacers, and key. Reversible right or left. Bolt adjustment +/- 6mm. For door thicknesses of 50-140mm.	

Digital Thermoregulators

Code	Spare Part Description	Picture
0S1642	Digital thermoregulator mod. ICPLUS 902 NTC-PTC; Aliment.(V) 12; Input: 1 NTC/PTC; Output: 1 RELAY; External dimensions LxHxD (mm)78.6x37x59; Hole dimensions LxH (mm) 71x29	
0S1644	Digital thermoregulator mod. ICPLUS 902 J/K PT100; Aliment.(V) 12; Input: 1 PT100 / TC (J,K); Output: 2 RELAYS; External dimensions LxHxD (mm)78.6x37x59; Hole dimensions LxH (mm) 71x29	
0S1645	Digital thermoregulator mod. ICPLUS 902 J/K PT100 ; Food (V) 24; Input: 1 PT100 / TC (J,K); Output: 1 RELAY; External dimensions LxHxD (mm)78.6x37x59; Hole dimensions LxH (mm) 71x29	
0S1643	Termoregolatore digitale mod. ICPLUS 915 NTC-PTC; Aliment.(V) 230; Input: 2 NTC / PTC; Output: 2 RELÉ; Dimensioni est LxHxD (mm)78,6x37x59; Dimensioni foro LxH (mm) 71x29	



Digital Thermoregulators

Code	Spare Part Description	Picture
0S1743	Termoregolatore digitale mod. IDPLUS 902 NTC-PTC; Aliment.(V) 12; Input: 1 NTC / PTC / PT1000; Output: 1 RELÉ; Dimensioni est LxHxD (mm)74x32x59; Dimensioni foro LxH (mm) 71x29	
0S1742	Termoregolatore digitale mod. IDPLUS 902 NTC-PTC ; Aliment.(V) 230; Input:1 NTC / PTC / PT1000; Output: 1 RELÉ; Dimensioni est LxHxD (mm)74x32x59; Dimensioni foro LxH (mm) 71x29	
0S1453	Termoregolatore digitale mod. IDPLUS 961 NTC-PTC ; Aliment.(V) 230; Input:2 NTC / PTC / PT1000; Output: 1 RELÉ; Dimensioni est LxHxD (mm)74x32x59; Dimensioni foro LxH (mm) 71x29	
0S2136	Termoregolatore digitale mod. IDPLUS 971 NTC-PTC; Aliment.(V) 230; Input:2 NTC / PTC / PT1000; Output: 1 RELÉ; Dimensioni est LxHxD (mm)74x32x59; Dimensioni foro LxH (mm) 71x29	
0S1454	Digital thermoregulator mod. IDPLUS 974 NTC-PTC; Food (V) 230; Input: 2 NTC/PTC/PT1000; Output: 3 RELAYS; External dimensions LxHxD (mm)74x32x59; Hole dimensions LxH (mm) 71x29	
0G8687	Digital thermoregulator mod. IDPLUS 974 NTC-PTC; Aliment.(V) 12; Input: 2 NTC/PTC/PT1000; Output: 3 RELAYS; External dimensions LxHxD (mm)74x32x59; Hole dimensions LxH (mm) 71x29	
090074	Digital thermoregulator mod. IS 972 LX; Output: telephone connection with EWEM 233; Dimensions LxHxD (mm)74x32x30	
099224	Digital thermoregulator mod. EWEM 233; Food (V) 230; Input: 2 NTC/PTC; Output: 3 RELAYS; Dimensions LxHxD (mm)70x85x53	
099221	Digital thermoregulator mod. IS 974 LX; Output: telephone connection with EWEM 243; Dimensions LxHxD (mm)74x32x30	



Digital Thermoregulators

Code	Spare Part Description	Picture
091189	Digital thermoregulator mod. EWEM 243; Food (V) 230; Input: 2 NTC/PTC; Output: 4 RELAYS; Dimensions LxHxD (mm)70x85x53	
091207	Digital thermoregulator mod. 10 poles connection cable; Dimensions LxHxD (mm)1000	
0S1891	Digital thermoregulator mod. EMPLUS600; Food (V) 230; Input: 1 NTC/PTC; Dimensions LxHxD (mm)74x32x59; Dimensions LxH (mm) 71x29	
092235	Thermoregulator mod. IR33 - IRELF0EN22 analog input for 2 probes: PTC/NTC digital output: 3 outputs on 250v relay (two 8A, one 5A) serial port output: TTL connections on phoenix connector not included dim. 71x29mm drilling template dim. 76.2x34.4x depth 65mm Power supply 230v (+/-10%) 50/60Hz	
091642	Thermoregulator mod. IR33 -IRELC0HN21 analog input for 2 probes: PTC/NTC digital output: 4 outputs on 250v relay (one 12A, two 8A, one 4A) serial port output: TTL connections on phoenix connector not included dim. 71x29mm drilling template dim. 76.2x34.4x depth 65mm Power supply 230v (+/-10%) 50/60Hz	
091609	Thermoregulator mod. IR33 - IRELF0EN21 analog input for 2 probes: PTC/NTC digital output: 3 outputs on 250v relay (two 8A, one 5A) serial port output: TTL connections on phoenix connector not included dim. 71x29mm drilling template dim. 76.2x34.4x depth 65mm Power supply 230v (+/-10%) 50/60Hz	
092355	Thermoregulator mod. IR33 - IRELF0HN21 analog input for 2 probes: PTC/NTC digital output: 3 outputs on 250v relay (two 4A and one 12A) serial port output: TTL connections on phoenix connector not included dim. 71x29mm drilling template dim. 76.2x34.4x depth 79mm Power supply 230v (+/-10%) 50/60Hz Software function: condenser cleaning alarm, condenser fan failure alarm, defrost due to unit shutdown, low humidity	
0S3018	Thermoregulator Mod. IJF LARGE - IJFPLA5N00S0083 analogue inputs for 4 probes: PTC/NTC/PT1000 digital output: 7 outputs on 250V relay (one 30A, four 8A, one 10A, one 10A) BMS serial port output (RS485) NFC connectivity connections on phoenix connector not included dim. 138.5x29mm drilling template dim. 163.2x39.6x depth 84.2mm Power supply 230v (+/-10%) 50/60Hz	



Digital Thermoregulators


Code	Spare Part Description	Picture
091103	Thermoregulator DIXELL XW10L -5P1C0, complete with IP65 gasket and steel front painting.	
091015	Thermoregulator DIXELL XW30L complete with gasket, IP65 and steel-coloured front painting, 230V 50/60Hz, depth 48 mm, 1 relay output 20A for compressor - faston 6.3 mm, 1 relay output 8A for fans - faston 6.3 mm, 1 relay output 8A for light - faston 6.3 mm, 2 NTC probes (not included) - faston 2.8 mm, front dimension 185x38 mm, drilling template 150x31 mm	
09A1NM	Carel IJF Small thermoregulator assembly + Zero-Cross Firmware	
0PRZA1	Thermoregulator mod. EASY -PJEZC0H000 analog input for 2 probes: PTC/NTC digital output: 3 outputs on 230v relay (one 2HP, two 8A) dim. 71x29mm drilling template dim. 81x36x depth 58mm Power supply 230v (+/-10%) 50/60Hz	

Accessories for Thermoregulators

Code	Spare Part Description	Picture
092597	Complete IR33 front mask	
091684	5-way connector, pitch 5.08, 90° screw connection no. (8 to 12)	
092662	8-way connector, pitch 5.08, 90° screw connection no. (1 to 8)	



Accessories for Thermoregulators

Code	Spare Part Description	Picture
092663	3-way connector, pitch 5.08, straight screw connection no. (13 to 15)	
091682	4-way connector, pitch 5.08, 90° screw connection no. (9 to 12)	
092665	5-way connector, pitch 5.08, 90° screw connection no. (8 to 12)	
092664	7-way connector, 5.08 pitch, straight screw connection	
092360	NTC sensor for IR series length. 2000 mm	
099743	Small 3-way connector with 90° screw connection	
099742	2-way connector, 5.08 pitch, 90° screw connection	
099741	5-way connector, pitch 5.08, 90° screw connection	
099740	7-way connector, pitch 5.08, 90° screw connection	



Accessories for Thermoregulators

Code	Spare Part Description	Picture
088998	3-way connector, 5.08 pitch, 90° screw connection	
097616	2-way connector, pitch 5.08. 90° screw connection	
097578	3-way connector, pitch 3.50. 90° screw connection	
097617	5-way connector, pitch 5.08. 90° screw connection	
092174	NTC sensor silicone cable with 6x20 mm AISI304 bulb Terminal with stripped wires length 2000 mm	
092176	NTC sensor silicone cable with 6x20 mm AISI304 bulb Terminal with stripped wires length 4000 mm	
092178	NTC sensor silicone cable with bulb 6x40 mm AISI304 Terminal with stripped wires length 1500 mm	



Accessories for Thermoregulators

Code	Spare Part Description	Picture
096125	NTC sensor silicone cable with bulb 6x40 mm AISI304 Terminal with stripped wires length 3000 mm	
092182	NTC sensor silicone cable with bulb 6x40 mm AISI304 Terminal with stripped wires length 2000 mm	
092180	NTC sensor with silicone cable and 6x40 mm AISI304 bulb	
083833	Transformer for thermoregulators powered by 12 V power supply: 220/12 V-3 VA dim. 44x45x33 mm	
091101	PTC sensor silicone cable with 6x40 mm bulb Terminal with stripped wires temperature range -30+80°C length 1200 mm	
0S0302	PTC sensor silicone cable with bulb 6x40 mm Terminal with stripped wires temperature range -30+80°C length 1500 mm	
0A9600	PTC sensor silicone cable with bulb 6x40 mm Terminal with stripped wires temperature range -50+105°C length 2500 mm	
0S2565	PTC sensor 1kOhm silicone cable with bulb 6x20 mm Terminal with stripped wires temperature range -40+105°C length 5000 mm	

Fan Motors and Timers

Code	Spare Part Description	Picture
094755	Defrost timer daily cycle from 1 to 12 defrosts adjustable fan delay INTC/PTC power supply 230V 50Hz dim.mm 72x88x70h	
0S0562	Pentavalent motor fan 5 different types of fixing with cable Rpm 1300/1550 Output/input power 16/65W 230/240 V 50-60Hz	
0S0563	Pentavalent motor fan 5 different types of fixing with cable Rpm 1300/1550 Output/input power 25/95W 230/240 V 50-60Hz	
0S0561	Pentavalent motor fan 5 different types of fixing with cable Rpm 1300/1550 Output/input power 10/38W 230/240 V 50-60Hz	
0S1119	Pentavalent motor fan 5 different types of fixing with cable Rpm 1300/1550 Output/input power 18/73W 230/240 V 50-60Hz	
087168	Multipurpose motor for fan with long shaft (46mm), 5 different types of fixing with cable Rpm 1300/1550 Output/input power 25/95W 230/240 V 50-60Hz, IP42, suitable for use at low and high temperatures (-40 °C/+150°C)	
099646	Fan motor equipped with heat-shrinkable sheath, 3000mm long wiring, 3 Fastons + 1 eyelet connectors	



Fan Motors and Timers

Code	Spare Part Description	Picture
084745	Motor 230/50-60 10/38W VN10-20/1832 NET2T10ZVN042	
088603	Fan motor assembly with fast-on extension, cable length 1850mm, 3 terminals code 639712700 (AMP 350547-1) and 1 eyelet terminal code IAZ. 439872900 (AMP 34145)	
085674	Motor with high temperature lubrication system -40° / +150°C, VN10-20, 230/240V, 50/60Hz, 0,23A, 10/38W, 1300/1500rpm, counterclockwise	
094829	Consisting of AC axial fan and protection grid d.350, 3 terminals + 1 for ground connection, cable length 1600mm.	
088013	Motor ELCO 4-010-1602 3BTM 45-40/1 230V 50HZ	

Hermetic Compressors

Code	Spare Part Description	Picture
093267	Compressor mod. EMT6144Z; Power (Volt/Ph/Hz) 220-240/1/50; 5.20cm ³ ; Engine type: CSIR	



Hermetic Compressors

Code	Spare Part Description	Picture
093207	Compressor mod. EMT6160Z; Power (Volt/Ph/Hz) 220-240/1/50; 6.76cm ³ ; Engine type: CSIR	
093206	Compressor mod. EMT6170Z; Power (Volt/Ph/Hz) 220-240/1/50; 7.69cm ³ ; Engine type: CSIR	
093379	Compressor mod. NEK6187Z; Power (Volt/Ph/Hz) 220-240/1/50; 10.00cm ³ ; Engine type: CSIR	
093297	Compressor mod. NEK6210Z; Power (Volt/Ph/Hz) 220-240/1/50; 14.30cm ³ ; Engine type: CSIR	
093484	Compressor mod. NEK6214Z; Power (Volt/Ph/Hz) 220-240/1/50; 14.30cm ³ ; Engine type: CSIR	
092312	Compressor mod. NT6215Z; Power (Volt/Ph/Hz) 220-240/1/50; 17.40cm ³ ; Engine type: CSIR	



Hermetic Compressors

Code	Spare Part Description	Picture
093454	Compressor mod. NJ6220Z; Power (Volt/Ph/Hz) 220-240/1/50; 26.20cm ³ ; Engine type: CSIR	
093474	Compressor mod. NJ6226Z; Power (Volt/Ph/Hz) 220-240/1/50; 34.37cm ³ ; Engine type: CSR	
092337	Compressor mod. EMT6144GK; Power (Volt/Ph/Hz) 220-240/1/50; 3.97cm ³ ; Engine type: CSIR	
0S1499	Compressor mod. EMT6152GK; Power (Volt/Ph/Hz) 220-240/1/50; 4.50cm ³ ; Engine type: CSIR	
093208	Compressor mod. EMT6165GK; Power (Volt/Ph/Hz) 220-240/1/50; 5.20cm ³ ; Engine type: CSIR	
093373	Compressor mod. NEK6181GK; Power (Volt/Ph/Hz) 220-240/1/50; 7.28cm ³ ; Engine type: CSIR	



Hermetic Compressors

Code	Spare Part Description	Picture
093377	Compressor mod. NEK6210GK; Power (Volt/Ph/Hz) 220-240/1/50; 8.77cm ³ ; Engine type: CSIR	
091161	Compressor mod. NEK6213GK; Power (Volt/Ph/Hz) 220-240/1/50; 12.12cm ³ ; Engine type: CSIR	
092239	Compressor mod. NEK6217GK; Power (Volt/Ph/Hz) 220-240/1/50; 14.30cm ³ ; Engine type: CSIR	
0S1824	Compressor mod. NJ9226GK; Power (Volt/Ph/Hz) 220-240/1/50; 21.70cm ³ ; Engine type: CSIR	
093426	Compressor mod. EMT6152U; Power (Volt/Ph/Hz) 220-240/1/50; 5.19cm ³ ; Power: 1/4; Engine type: CSIR; Application: MBP; Brand: EMBRACO	
093425	Compressor mod. EMT6144U; Power (Volt/Ph/Hz) 220-240/1/50; 4.50cm ³ ; Power: 1/5; Engine type: CSIR; Application: HMBP; Brand: EMBRACO	
0S2611	Compressor mod. NEK2150U; Power (Volt/Ph/Hz) 220-240/1/50; 13.54cm ³ ; Power: 1/2; Engine type: CSIR; Application: LBP; Brand: EMBRACO	
0S1922	Compressor mod. NEK2160U; Power (Volt/Ph/Hz) 220-240/1/50; 16.80cm ³ ; Power: 3/4; Engine type: CSR; Application: LBP; Brand: EMBRACO	



Hermetic Compressors

Code	Spare Part Description	Picture
093727	Compressor mod. NT2160U; Power (Volt/Ph/Hz) 220-240/1/50; 17.40cm ³ ; Power: 3/4; Engine type: CSR; Application: LBP; Brand: EMBRACO	
0S1960	Compressor mod. NT2170U; Power (Volt/Ph/Hz) 220-240/1/50; 20.40cm ³ ; Power: 3/4; Engine type: CSR; Application: LBP; Brand: EMBRACO	
0S2612	Compressor mod. SC21CNX2A; Power (Volt/Ph/Hz) 220-240/1/50; 20.95cm ³ ; Power: 1; Engine type: CSIR; Application: LBP; Brand: SECOP	
0S2613	Compressor mod. TL5CN; Power (Volt/Ph/Hz) 220-240/1/50; 5.08cm ³ ; Power: 1/5; Engine type: CSIR; Application: LMBP; Brand: SECOP	
0S1936	Compressor mod. HVY57AA; Power (Volt/Ph/Hz) 220-240/1/50; 5.76cm ³ ; Power: 1/9; Engine type: RSIR; Application: LBP; Brand: CUBIGEL	
0S2098	Compressor mod. EMT40CLP; Power (Volt/Ph/Hz) 220-240/1/50; 7.23cm ³ ; Power: 1/8; Engine type: RSIR; Application: LBP; Brand: EMBRACO	
0S1959	Compressor mod. HQM80AA; Power (Volt/Ph/Hz) 220-240/1/50; 8.10cm ³ ; Power: 1/7; Engine type: RSIR; Application: LBP; Brand: CUBIGEL	
0S2531	Compressor mod. N1112Y; Power (Volt/Ph/Hz) 220-240/1/50; 8.10cm ³ ; Power: 1/5; Engine type: RSCR; Application: LBP; Brand: JIAXIPERA	
0S2186	Compressor mod. EMX40CLC; Power (Volt/Ph/Hz) 220-240/1/50; 7.23cm ³ ; Power: 1/7; Engine type: RSCR; Application: LBP; Brand: EMBRACO	
0S2614	Compressor mod. EMX55CLC; Power (Volt/Ph/Hz) 220-240/1/50; 9.04cm ³ ; Power: 1/6; Engine type: RSCR; Application: LBP; Brand: EMBRACO	
0S2615	Compressor mod. EMYE70CLP; Power (Volt/Ph/Hz) 220-240/1/50; 11.14cm ³ ; Power: 1/4; Engine type: RSCR; Application: LBP; Brand: EMBRACO	



Hermetic Compressors

Code	Spare Part Description	Picture
093374	Compressor mod. NEK2134GK; Power (Volt/Ph/Hz) 220-240/1/50; 8.78cm ³	
093630	Compressor mod. NEK2150GK; Power (Volt/Ph/Hz) 220-240/1/50; 12.12cm ³	
093787	Compressor mod. NT2168GK; Power (Volt/Ph/Hz) 220-240/1/50; 14.50cm ³	
092785	Compressor mod. NT2178GK; Power (Volt/Ph/Hz) 220-240/1/50; 17.40cm ³	
093735	Compressor mod. NT2180GK; Power (Volt/Ph/Hz) 220-240/1/50; 20.40cm ³	
093424	Compressor mod. NT2192GK; Power (Volt/Ph/Hz) 220-240/1/50; 22.40cm ³	



Hermetic Compressors

Code	Spare Part Description	Picture
084076	Compressor mod. NJ2192GK; Power (Volt/Ph/Hz) 220-240/1/50; 26.00cm ³	
085097	Compressor mod. NJ2212GK; Power (Volt/Ph/Hz) 220-240/1/50; 34.37cm ³	
085501	Compressor mod. GL45TB; Power (Volt/Ph/Hz) 220-240/1/50; 4.50cm ³ ; Power: 1/6; Engine type: CSIR; * Excluding rubbers and spacers cod. 0S0604	
083718	Compressor mod. GL90TB; Power (Volt/Ph/Hz) 220-240/1/50; 8.85cm ³ ; Power: 1/4; Engine type: CSIR; * Excluding rubbers and spacers cod. 0S0604	
083752	Compressor mod. GP12TB; Power (Volt/Ph/Hz) 220-240/1/50; 12.00cm ³ ; Power: 3/8; Engine type: CSIR; * Excluding rubbers and spacers cod. 0S0604	
0T3259	Compressor mod. ML45TB; Power (Volt/Ph/Hz) 220-240/1/50; 4.50cm ³ ; Power: 1/5; Engine type: CSIR	
0S3353	Compressor model ML45TG; Power supply (Volts/Ph/Hz) 220-240/1/50/60HZ; 4.50cm ³ ; Power: 1/5; Motor type: CSIR	
0T3290	Compressor mod. ML90TB; Power (Volt/Ph/Hz) 220-240/1/50; 8.85cm ³ ; Power: 3/8; Engine type: CSIR * Excluding rubbers and spacers cod. 0S0604	



Hermetic Compressors

Code	Spare Part Description	Picture
0T3261	Compressor mod. MX18TB; Power (Volt/Ph/Hz) 220-240/1/50; 18.39cm ³ ; Power: 7/8; Engine type: CSR * Excluding rubbers and spacers cod. 0S0604	
0A9615	Compressor mod. MP14FB; Power (Volt/Ph/Hz) 220-240/1/50; 14.00cm ³ ; Power: 1/2; Engine type: CSIR * Excluding rubbers and spacers cod. 0S0604	
092289	Compressor mod. MX23FB; Power (Volt/Ph/Hz) 220-240/1/50; 23.20cm ³ ; Power: 7/8; Engine type: CSR	
0A9727	Compressor mod. MS34FB; Power (Volt/Ph/Hz) 220-240/1/50; 34.42cm ³ ; Power: 1; Engine type: CSR	
0S3331	Compressor model NEU2155U; Power supply (Volts/Ph/Hz) 220-240/1/50; 13.54cm ³ ; Power: 3/4; Motor type: CSIR; Application: LBP; Brand: EMBRACO	
094840	Compressor model NEU2168U; Power supply (Volts/Ph/Hz) 220-240/1/50; 16.80 cm ³ ; Power: 3/4; Motor type: CSCR; Application: LBP; Brand: EMBRACO	

Accessories for Compressors

Code	Spare Part Description	Picture
0A8764	Starting capacitor; 50F; 260V; 50Hz	



Accessories for Compressors

Code	Spare Part Description	Picture
082640	Starting capacitor; 80F; 330V; 50/60Hz	
0A9228	Starting capacitor; 72/88F; 330V; 50/60Hz	
083449	Cable starting capacitor with faston; 88/108F; 330V; 50/60Hz	
099747	Cable inrush capacitor with eyelet; 88/108F; 330V; 50/60Hz	
083406	Running capacitor; 5F; 420V; 50/60Hz	
083156	Running capacitor; 16F; 400V; 50/60Hz	
087201	Running capacitor; 20F; 450V; 50/60Hz	
0S0604	Rubbers and spacers for Cubigel compressors	



Accessories for Compressors

Code	Spare Part Description	Picture
097094	Starting capacitor; 52F; 330V; 50Hz	

Hermetic Condensing Units

Code	Spare Part Description	Picture
0S0762	Cond. unit hermetic mod HA007Y1101; EMT6160Z 6.8cm ³ compressor; 1 fan; Power consumption 250W; dim. 450x300x270mm; connections: 6x10mm	
0S0764	Cond. unit hermetic mod HA007Y1111; EMT6160Z 6.8cm ³ compressor; 1 fan; Power consumption 250W; dim. 450x300x270mm; connections: 6x10mm	
0S0765	Cond. unit hermetic mod HA010Y1041; NEK6187Z 10cm ³ compressor; 1 fan; Power consumption 323W; dim. 480x330x295mm; connections: 6x10mm	
0S2187	Cond. unit hermetic mod HA017Y1081; Compressor NEU6214Z 16.8cm ³ ; 1 fan; Power consumption 527W; dim. 490x385x295mm; connections: 6x10mm	
0S0770	Cond. unit hermetic mod HA005Z1101; EMT6165GK compressor 5.2cm ³ ; 1 fan; Power consumption 328W; dim. 450x300x270mm; connections: 6x10mm	
0S0771	Cond. unit hermetic mod HA007Z1051; NEK6181GK compressor 7.3cm ³ ; 1 fan; Power consumption 415W; dim. 480x330x295mm; connections: 6x10mm	



Hermetic Condensing Units

Code	Spare Part Description	Picture
0S0772	Cond. unit hermetic mod HA009Z1051; NEK6210GK 8.8cm ³ compressor; 1 fan; Power consumption 486W; dim. 480x330x295mm; connections: 6x10mm	
0S1906	Cond. unit hermetic mod HA004Z1211; EMT6152GK 4.5cm ³ compressor; 1 fan; Power consumption 281W; dim. 450x300x270mm; connections: 6x10mm	
0S0774	Cond. unit hermetic mod HA005Z1111; EMT6165GK compressor 5.2cm ³ ; 1 fan; Power consumption 328W; dim. 450x300x270mm; connections: 6x10mm	
0S0775	Cond. unit hermetic mod HA007Z1041; NEK6181GK compressor 7.3cm ³ ; 1 fan; Power consumption 415W; dim. 480x330x295mm; connections: 6x10mm	
0S0776	Cond. unit hermetic mod HA009Z1041; NEK6210GK 8.8cm ³ compressor; 1 fan; Power consumption 486W; dim. 480x330x295mm; connections: 6x10mm	
0S2471	Cond. unit hermetic mod HA012Z1081; NEV6215GK 12.1cm ³ compressor; 1 fan; Power consumption 660W; dim. 490x385x295mm; connections: 6x10mm	
0S1033	Cond. unit hermetic mod HA017Z1111; NT6222GK 17.4cm ³ compressor; 1 fan; Power consumption 905W; dim. 490x385x345mm; connections: 6x12mm	
0S1388	Cond. unit hermetic mod HA021Z1011; Compressor NJ9226GK 21.7cm ³ ; 1 fan; Power consumption 1032W; dim. 490x385x345mm; connections: 10x12mm	



Hermetic Condensing Units

Code	Spare Part Description	Picture
0S1387	Cond. unit hermetic mod HA021Z2012; Compressor NJ9226GS 21.7cm ³ ; 2 fan; Power consumption 1028W; dim. 490x700x346mm; connections: 10x12mm	
0S0982	Cond. unit hermetic mod LA009Z1051; NEK2134GK 8.8cm ³ compressor; 1 fan; Power consumption 411W; dim. 480x330x295mm; connections: 6x10mm	
0S0983	Cond. unit hermetic mod LA017Z1111; NT2178GK 17.4cm ³ compressor; 1 fan; Power consumption 641W; dim. 500x330x295mm; connections: 6x10mm	
0S2117	Cond. unit hermetic mod LA020Z1111; NT2180GK 20.4cm ³ compressor; 1 fan; Power consumption 832W; dim. 500x330x295mm; connections: 6x10mm	
0S2217	Cond. unit hermetic mod LA026Z1011; Compressor NJ2192GK 26.1cm ³ ; 1 fan; Power consumption 1037W; dim. 490x385x345mm; connections: 10x12mm	
0S1625	Cond. unit hermetic model LUCEN34A; Compressor NJ2212GK 34.37cm ³ ; 2 fan; Power consumption 1373W; dim. 490x700x346mm; connections: 10x12mm	
0S0767	Cond. unit hermetic mod CGP12TB3N; GP12TB 12cm ³ compressor; 1 fan; Power consumption 602W; dim. 425x350x270mm; connections: 1/4"x3/8"mm	
0S0768	Cond. unit hermetic mod CGP14TB3N; GP14TB 14cm ³ compressor; 1 fan; Power consumption 665W; dim. 425x350x270mm; connections: 1/4"x3/8"mm	



Hermetic Condensing Units

Code	Spare Part Description	Picture
0S0777	Cond. unit hermetic mod CML60TB3N; ML60TB 5.67cm ³ compressor; 1 fan; Power consumption 477W; dim. 425x330x245mm; connections: 1/4"x3/8"mm	
0S0778	Cond. unit hermetic mod CML80TB3N; ML80TB 7.57cm ³ compressor; 1 fan; Power consumption 570W; dim. 450x355x270mm; connections: 1/4"x3/8"mm	
0S0779	Cond. unit hermetic model CML90TB3N; ML90TB 8.85cm ³ compressor; 1 fan; Power absorbed 700W; dim. 425x355x270mm; connections: 1/4"x3/8"mm	
0S0783	Cond. unit hermetic mod CMS34FB3N; MS34FB compressor 34.32cm ³ ; 1 fan; Power absorbed 1220W; dim. 545x425x350mm; connections: 3/8"x5/8"mm	
0S2785	Cond. unit hermetic mod HA004Z1111; EMT6144GK compressor 3.97cm ³ ; 1 fan; Power consumption 252W; dim. 450x300x270mm; connections: 6x10mm	
0S2986	Cond. unit hermetic mod HA012Z1091; Compressor HA012Z1091 12.1cm ³ ; 1 fan; Power consumption 674W; dim. 490x385x295mm; connections: 6x10mm	

Pressure Switches

Code	Spare Part Description	Picture
094584	High pressure switch Cut in: 16.6 bar - Cut out: 17.8 bar	
085088	High pressure switch Cut in: 23.5 bar - Cut out: 30 bar	



Pressure Switches

Code	Spare Part Description	Picture
096201	High pressure switch Cut in: 24 bar - Cut out: 31 bar	
097776	High pressure switch Cut out: 8-42 bar Differential: 4-10 bar Automatic reset	
092698	High/low pressure switch Cut in: 0.2-7.5 bar - Cut out: 8-32 bar Automatic reset	

Tangential Fans

Code	Spare Part Description	Picture
081795	Tangential fan Power: 17W 230V/50HZ Motor position: DX Roller size: Ø 45X120mm Operating temperature: 0° +60°C	
082730	Tangential fan Power: 35W 230V/50HZ Motor position: SX Roller size: Ø 45X300mm Operating temperature: 0° +60°C	
0PRR94	Tangential fan Power: 19W 230V/50HZ Motor position: DX Roller size: Ø 60X180mm Operating temperature: -30° +100°C	
005204	Tangential fan Power: 17W 230V/50HZ Motor position: DX Roller size: Ø 60X180mm Operating temperature: -30° +100°C	
033070	Tangential fan Power: 21W 230V/50HZ Motor position: SX Roller size: Ø 60X180mm Operating temperature: 0° +60°C	



Tangential Fans

Code	Spare Part Description	Picture
0G6480	Tangential fan Power: 45W 230V/50HZ Motor position: Central Roller size: Ø 60X180X180mm Operating temperature: -30° +100°C	
0K5059	Tangential fan Power: 22W 230V/50HZ Motor position: DX Roller size: Ø 65X240mm Operating temperature: 0° +60°C	
0G2982	Tangential fan Power: 45W 230V/50HZ Motor position: DX Roller size: Ø 65X300mm Operating temperature: 0° +60°C	

Thermostatic Valves and Orifices

Code	Spare Part Description	Picture
083758	T2/TE2 thermostatic expansion valves CARD X CARD Thermostatic element with bulb holder, without orifice, filter and unions Valve type: TN2; Pressure equalization: internal ½"; Capillary length m: 1.5; Flare inlet connections 3/8", Flare outlet 1/2" Working range (Range N -40 to + 10°C) without MOP; Danfoss code : 068Z3542; Refrigerant gas: R134a	
0S1391	T2/TE2 thermostatic expansion valves CARD X CARD Thermostatic element with bulb holder, without orifice, filter and unions Valve type: TS2; Pressure equalization: internal ½" ; Capillary length m: 1.5; Flare inlet connections 3/8", Flare outlet 1/2" Working range (Range N -40 to + 10°C) without MOP; Danfoss code : 068Z3400; Refrigerant gas: R404a/R507	
0S1393	T2/TE2 thermostatic expansion valves CARD X CARD Thermostatic element with bulb holder, without orifice, filter and unions Valve type: TES2; Pressure equalization: external ½" x ¼"; Capillary length m: 1.5; Flare inlet connections 3/8", Flare outlet 1/2" Working range (Range N -40 to + 10°C) without MOP; Danfoss code: 068Z3403; Refrigerant gas: R404a/R507	
0A9508	T2/TE2 thermostatic expansion valves CARD X CARD Thermostatic element with bulb holder, without orifice, filter and unions Valve type: TS2; Pressure equalization: internal; Length Capillary m: 1.5; Flare inlet connections 3/8", Flare outlet 1/2" Working range (NL range -40 to -15°C) MOP -10°C; Danfoss code: 068Z3408; Refrigerant gas: R404a/R507	



Thermostatic Valves and Orifices

Code	Spare Part Description	Picture
0S1932	T2/TE2 thermostatic expansion valves BRAZING CARD Thermostatic element with bulb holder, without orifice, filter and unions Valve type: TEX2; Pressure equalization: external 12x6mm; Length Capillary m: 1.5; Flare inlet connections 3/8", Flare outlet 1/2" Working range (Range N -40 to + 10°C) without MOP; Danfoss code: 068Z3305; Refrigerant gas: R22	
0KW895	T2/TE2 thermostatic expansion valves BRAZING CARD Thermostatic element with bulb holder, without orifice, filter and unions Valve type: TN2; Pressure equalization: internal 1/2" ; Capillary length m: 1.5; Flare inlet connections 3/8", Flare outlet 1/2" Working range (Range N -40 to + 10°C) without MOP; Danfoss code : 068Z3383; Refrigerant gas: R134a	
0T5187	T2/TE2 thermostatic expansion valves BRAZING CARD Thermostatic element with bulb holder, without orifice, filter and unions Valve type: TES2; Pressure equalization: external 1/2" x 1/4"; Capillary length m: 1.5; Flare inlet connections 3/8", Flare outlet 1/2" Working range (Range N -40 to + 10°C) without MOP; Danfoss code: 068Z3415; Refrigerant gas: R404a/R507	
0S3042	T2/TE2 thermostatic expansion valves BRAZING CARD Thermostatic element with bulb holder, without orifice, filter and unions Valve type: T2; Pressure equalization: internal; Length Capillary m: 1.5; Flare inlet connections 10mm, Flare outlet 12mm Working range (Range N -40 to + 10°C) without MOP; Danfoss code: 068Z3808; Refrigerant gas: R452A	
0S2333	Orifices for thermostatic expansion valve CARD X CARD Valve type: T2-TE2; Port Type: 0X; Danfoss code: 068-2002	
084084	Orifices for thermostatic expansion valve CARD X CARD Valve type: T2-TE2; Port Type: 00; Danfoss code: 068-2003	
083404	Orifices for thermostatic expansion valve CARD X CARD Valve type: T2-TE2; Ports type: 02; Danfoss code: 068-2015	



Thermostatic Valves and Orifices

Code	Spare Part Description	Picture
0S2334	Orifices for thermostatic expansion valve CARD X CARD Valve type: T2-TE2; Ports type: 03; Danfoss code: 068-2006	
0L2379	Orifices for thermostatic expansion valve CARD X CARD Valve type: T2-TE2; Ports type: 04; Danfoss code: 068-2007	
0T5165	Orifices for thermostatic expansion valve CARD X CARD Valve type: T2-TE2; Port type: 01; Danfoss code: 068-2010	
0S3043	Orifices for thermostatic expansion valve CARD X CARD Valve type: T2-TE2; Port Type: 0X; Danfoss code: 068-2089	
088475	Thermostatic Valve, range NL,-40/-15, mop-10 or.6 068U2782	

Genuine Replacement Parts, Accessories and Consumables Catalogue
Accessories and Consumables

Bundles

Code	Spare Part Description	Picture
CS0002	GRILL BUNDLE FOR OVENS WITH C22 AND C25 BUNDLE	
CS0004	BURNER OC0127 AND FLAME SPREADER OC0129 BUNDLE	
CS0005	BURNER OC0126 AND FLAME SPREADER OC0128 BUNDLE	
CS0006	DETERGENT BUNDLE OS2092 (2PCS)+OS2094 (1PCS)	
CS0007	DETERGENT BUNDLE OS2093 (2PCS)+OS2904 (1PCS)	
CS0008	DETERGENT BUNDLE OS2394 (2PCS) + OS2395 (2PCS)	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

Bundles

Code	Spare Part Description	Picture
CS0009	LAB PACK water analysis case complete with: • Conductivity meter/pH meter code OS2889 • Manual chloride analysis instrument (approximately 200 tests) code OS0585 • Electrode preservation solution code OS2383 • Total and partial carbonate hardness kit code OS1701 • Carbonate analysis, set of 100 test sticks, code OS2916 • Total iron analysis, set of 100 test sticks, code OS2917 • Plastic case dim 500x380x195mm code OS2954 *The components may not be delivered in a single solution Code Qt. Description OS0585 1 Tt chloride test kit chemical kit; adr&imgd&iata limited quantity, OS1701 1 Carbonate and total hardness test adr &imgd &iata exempted quantity, OS2383 1 Solution, OS2889 1 Conductivity meter ph-meter, OS2916 1 Carbonates chemical analysis; 100 test sticks, OS2917 1 Iron chemical analysis; 100 test sticks, OS2954 1 Tools case; abs dim. 500x380x195mm	
CS000A	DETERGENT BUNDLE OS2394 (2PCS) + OS2395 (4PCS)	

Router/Hub/Boards

Code	Spare Part Description	Picture
OCK635	Connectivity Wi-Fi Board (Niu-Hacl) Internet Connection: Cable Connection From Hub To Local Router (Connection Is Not Required When Using Skyduo* Only) Appliances Connection To Hub: Wi-Fi Q.Ty: 1 Per Appliance	
OCB931	Connectivity Ethernet Board Oven (Niu-Lan) For Ovens+Rack Type Dishwashers Internet Connection: Cable Connection From Hub To Local Router (Connection Is Not Required When Using Skyduo* Only) Appliances Connection To Hub: Cable (Ethernet) Q.Ty: 1 Per Appliance	

Blast Chiller Probes

Code	Spare Part Description	Picture
OPRRNX	Sensor Probe for Blast Chiller Freezer for Blast Chillers 6-20 Gn	



Blast Chiller Probes

Code	Spare Part Description	Picture
OPRRNY	6 Sensor Probe For Blast Chiller Freezer For Blast Chillers 6-20 Gn	
OPRRNZ	3 Single-Sensor Probe For Blast Chiller Freezer Ideal When It Is Required To Have Multipoint Testing Not Recommended For Continuous Usage	

Castors

Code	Spare Part Description	Picture
OPRRQ1	4 wheels in Aisi 304 for 6 GN 1/1 oven superimposed on blast chiller ideal for cleaning behind the oven 2 swivel wheels with brake and 2 fixed wheels without brake if mounted on gas ovens requires flexible hose	
OPRRRJ	4 Wheels For 6-10 Gn 1/1 Blast Chiller Freezer Ideal For Cleaning Behind The Blast Chiller Freezer 2 Swivelling Wheels With Brakes And 2 Fixed Wheels Without Brakes	
OPRRRK	Wheels For 10 Gn 2/1 Blast Chiller Freezer Ideal For Cleaning Behind The Blast Chiller Freezer 2 Swivelling Wheels With Brakes And 2 Fixed Wheels Without Brakes	
093279	Swivelling Wheel For 10 Gn 2/1 Blast Chiller Freezer Ideal For Cleaning Behind The Blast Chiller Freezer	

Detergents for Automatic Washing

Code	Spare Part Description	Picture
0S2395	C22 Cleaning Tab Disposable detergent tablets for SkyLine ovens Professional detergent for new generation ovens with automatic washing system. Suitable for all types of water. Packaging: 1 drum of 100 65g tablets. each	



Detergents for Automatic Washing

Code	Spare Part Description	Picture
0S2394	C25 Rinse & Descale tab 2in1 rinse aid and descaler in disposable tablets for Skyline ovens Professional 2in1 rinse aid and descaler in disposable tablets for new generation ovens with automatic washing system. Suitable for all types of water. Packaging: 1 drum of 50 30g tablets. each	
0S2282	C20 Extra Strong Detergent for ovens detergent for ovens with automatic washing system. Packaging: 1 pack of 2 5L cans	
0S2283	C21 Extra Strong Rinse aid for ovens rinse aid for ovens with automatic washing system. Packaging: 1 pack of 2 5L cans	
0S2347	Metal wall support for 5l canisters Compatibility: suitable for 0S2282 and 0S2283	
0S2559	Detergent tank support to attach to the open base Compatibility: suitable for 0S2282 and 0S2283	

Feet

Code	Spare Part Description	Picture
0CA753	Adjustable Flanged Foot For 6&10 Gn - 100-130Mm In Aisi 304	
0PRRRL	Kit with 4 flanged feet h=150	

Gas Conversion Kits




Code	Spare Part Description	Picture
0S2983	Kit for Conversion from LPG to Methane Gas In case of transformation of 6 Gn 1/1 or 6 Gn 2/1 ovens from methane to LPG, the chimney is also required	
0S2984	Kit for Conversion from Methane Gas to LPG In case of transformation of 6 Gn 1/1 or 6 Gn 2/1 ovens from methane to LPG, a chimney is also required	

GN Grids and Trays

Code	Spare Part Description	Picture
0S1875	Aluminum tray with non-stick coating ▶ reduce cooking time by up to 10% and energy consumption by up to 8% ▶ reduce the weight loss of food by 2-4% compared to traditional methods, obtaining juicier foods ▶ improve the operations ▶ it is recommended to use plastic spatulas in order to extend the life of the special coating ▶ it is recommended not to wash the tray in the pot washer with granules dim. GN: GN 1/2 LxDxH (mm) 325x265x20	
0S1876	Aluminum tray with non-stick coating ▶ reduce cooking time by up to 10% and energy consumption by up to 8% ▶ reduce the weight loss of food by 2-4% compared to traditional methods, obtaining juicier foods ▶ improve the operations ▶ it is recommended to use plastic spatulas in order to extend the life of the special coating ▶ it is recommended not to wash the tray in the pot washer with granules dim. GN: GN 1/2 LxDxH (mm) 325x265x40	
0S1877	Aluminum tray with non-stick coating ▶ reduce cooking time by up to 10% and energy consumption by up to 8% ▶ reduce the weight loss of food by 2-4% compared to traditional methods, obtaining juicier foods ▶ improve the operations ▶ it is recommended to use plastic spatulas in order to extend the life of the special coating ▶ it is recommended not to wash the tray in the pot washer with granules dim. GN: GN 1/2 LxDxH (mm) 325x265x60	
0S1872	Aluminum tray with non-stick coating ▶ reduce cooking time by up to 10% and energy consumption by up to 8% ▶ reduce the weight loss of food by 2-4% compared to traditional methods, obtaining juicier foods ▶ improve the operations ▶ it is recommended to use plastic spatulas in order to extend the life of the special coating ▶ it is recommended not to wash the tray in the pot washer with granules dim. GN: GN 1/1 LxDxH (mm) 530x325x20	
0S1873	Aluminum tray with non-stick coating ▶ reduce cooking time by up to 10% and energy consumption by up to 8% ▶ reduce the weight loss of food by 2-4% compared to traditional methods, obtaining juicier foods ▶ improve the operations ▶ it is recommended to use plastic spatulas in order to extend the life of the special coating ▶ it is recommended not to wash the tray in the pot washer with granules dim. GN: GN 1/1 LxDxH (mm) 530x325x40	



GN Grids and Trays

Code	Spare Part Description	Picture
0S1874	Aluminum tray with non-stick coating ► reduce cooking time by up to 10% and energy consumption by up to 8% ► reduce the weight loss of food by 2-4% compared to traditional methods, obtaining juicier foods ► improve the operations ► it is recommended to use plastic spatulas in order to extend the life of the special coating ► it is recommended not to wash the tray in the pot washer with granules dim. GN: GN 1/1 LxDxH (mm) 530x325x60	
0S1878	Aluminum grill with non-stick coating ideal for improving the cooking of steaks (it is not necessary to preheat the grill) it is recommended to use plastic spatulas in order to extend the life of the special coating ► it is advisable not to wash the tray in the pot washer with granules size . GN: GN 1/1 LxDxH (mm) 530x325x12	
0S1894	Smooth/ribbed aluminum plate with non-stick coating for various cooking needs: dual use of the plate, with the ribbed side for grilling and the smooth side for various baking and toasting. ► it is recommended to use plastic spatulas in order to extend the life of the special coating ► it is recommended not to wash the tray in the pot washer with granules dim. GN: GN 1/1 LxDxH (mm) 530x325x5	
0C8526	Non-stick coated aluminum egg tray for 8 eggs with non-stick coating. Ideal for an automatic egg cooking process; It can also be used for pancakes, burgers, omelettes, quiches and other round-shaped food. ► it is recommended to use plastic spatulas in order to extend the life of the special coating ► it is recommended not to wash the tray in the pot washer with granules dim. GN: GN 1/1 LxDxH (mm) 530x325x12	
0S1992	AISI 304 steel potato grill GN 1/1 for 28 potatoes dim. GN: GN 1/1 LxDxH (mm) 530x325x85	
0C8525	GN 1/1 silicone-coated baguette tray made of perforated aluminum with silicone coating. Ideal for cooking 4 pieces of baguette weighing 290g each. GN: GN 1/1 LxDxH (mm) 530x325x14	
0S0868	GN 1/1 oven grill in AISI 304 steel suitable for supporting irregular containers or plates to be heated dim. GN: GN 1/1 LxDxH (mm) 530x325x12	
003189	GN 2/1 oven grill in AISI 304 steel with splashback on 3 sides: 2 on the long sides and 1 on the short side; suitable for longitudinal ovens dim. GN: GN 2/1 LxDxH (mm) 530x650x25	



GN Grids and Trays

Code	Spare Part Description	Picture
0C6037	GN 1/1 frying baskets in AISI 304 steel ideal for frying pre-cooked frozen foods (fries, chicken nuggets, crab claws); set 2pcs dim. GN: GN 1/1 LxDxH (mm) 530x325x40	
0C7013	Chicken grills in AISI 304 steel, ideal for obtaining perfect browning and excellent cooking results thanks to the distribution of the chickens on the grill: 4 or 8 chickens per grill. dim. GN: GN 1/2 LxDxH (mm) 265x325x140 Load: 4 chickens	
0S0869	Chicken grills in AISI 304 steel, ideal for obtaining perfect browning and excellent cooking results thanks to the distribution of the chickens on the grill: 4 or 8 chickens per grill. dim. GN: GN 1/1 LxDxH (mm) 530x325x140 Load: 8 chickens	
0S2480	Duck grill PNC 922362 dim. GN: GN 1/1 LxDxH (mm) 530x325x258 Load: 8 ducks	
0S2513	Non-stick perforated diamond grill ideal for grilled steaks, improves cooking and preheating is not necessary dim. GN: GN 1/1 LxDxH (mm) 530x325x14	
0S2514	Tray for traditional cooking, ideal for braised meats, ragù and other traditional cooking. GN: GN 1/1 LxDxH (mm) 530x325x100	
0S2515	Non-stick tray for dehydration cycle ideal for: dehydrating fruit and vegetables without using baking paper dim. GN: GN 1/1 LxDxH (mm) 530x325 Height: 20mm	
0S2516	Non-stick tray for dehydration cycle ideal for: dehydrating fruit and vegetables without using baking paper dim. GN: GN 1/1 LxDxH (mm) 530x325 Height: flat	



GN Grids and Trays

Code	Spare Part Description	Picture
0S1752	GN 1/1 fat collection tray in AISI 304 ideal for easy collection of fats thanks to the particular integrated stainless steel drain pipe. Including drain hose and lid. dim. GN: GN 1/1 LxDxH (mm) 530x325x40 Height: 40mm	
0S1993	GN 1/1 fat collection tray in AISI 304 ideal for easy collection of fats thanks to the particular integrated stainless steel drain pipe. Including drain hose and lid. dim. GN: GN 1/1 LxDxH (mm) 530x325x100 Height: 100mm	
0S2622	GN 2/1 fat collection tray in AISI 304 ideal for easy collection of fats thanks to the particular integrated stainless steel drain pipe. Including drain hose and lid. dim. GN: GN 2/1 LxDxH (mm) 650x530x60 Height: 60mm	
0C8634	GN 1/1 aluminum pastry tray with two edges for bakery-pastry shops dim. GN: GN 1/1 LxDxH (mm) 530x325x10	
0S1747	Universal skewer grill GN 1/1 in AISI 304 ideal for the preparation of all types of kebab, tandoor grill, churrasco, yakitori and any other type of cooking with skewers. dim. GN: GN 1/1 LxWxH (mm) 530x325x55 Skewers: 4 long skewers	
0S1748	Universal skewer grill GN 1/1 in AISI 304 ideal for the preparation of all types of kebab, tandoor grill, churrasco, yakitori and any other type of cooking with skewers. dim. GN: GN 1/1 LxDxH (mm) 530x325x55 Skewers: 6 short skewers	
0S1750	Long skewer set 4pcs LxWxH (mm) 615x5	
0S1751	Short skewer set 6pcs LxWxH (mm) 352x5	
0S1749	Universal GN 1/1 skewer grill in AISI 304 not including skewers dim. GN: GN 1/1 LxDxH (mm) 530x325x55	
0CBAP1	Multifunctional hook with 2 hooks in AISI 304 The hook must be hung on the grill (0S0868 or 003189) and placed on the highest level of the tray rack Hook length: 300mm Maximum weight: 15kg	



GN Grids and Trays

Code	Spare Part Description	Picture
0CB819	Kit of 6 non-stick U-Pans - Gn 1/1 H=40mm	
0CB818	Kit of 6 non-stick U-Pans - Gn 1/1 H=20mm	
0CB820	Kit of 6 non-stick U-Pans - Gn 1/1 H=60mm	
0S3008	Perforated tray GN 2/1 In stainless steel with step WxD (mm) 650x530 Height (mm) 100	

GN Inox Basins

Code	Spare Part Description	Picture
0S1733	GN 1/1 pan In stainless steel with step WxD (mm) 530x325 Height (mm) 100	
0S1455	GN 1/1 pan In stainless steel with step WxD (mm) 530x325 Height (mm) 150	
0S0900	GN 1/2 pan In stainless steel with step WxD (mm) 325x265 Height (mm) 65	
0S2167	GN 1/2 pan In stainless steel with step WxD (mm) 325x265 Height (mm) 100	



GN Inox Basins

Code	Spare Part Description	Picture
0S2168	GN 1/2 pan In stainless steel with step WxD (mm) 325x265 Height (mm) 150	
0S2195	GN 1/3 pan In stainless steel with step WxD (mm) 325x175 Height (mm) 65	
0S2196	GN 1/3 pan In stainless steel with step WxD (mm) 325x175 Height (mm) 100	
0S2107	GN 1/3 pan In stainless steel with step WxD (mm) 325x175 Height (mm) 150	
0S2197	GN 1/4 pan In stainless steel with step WxD (mm) 265x162 Height (mm) 100	
0S2198	GN 1/4 pan In stainless steel with step WxD (mm) 265x162 Height (mm) 150	
0S2199	GN 1/6 pan In stainless steel with step WxD (mm) 176x162 Height (mm) 100	



GN Inox Basins

Code	Spare Part Description	Picture
0S2200	GN 1/6 pan In stainless steel with step WxD (mm) 176x162 Height (mm) 150	
0G4461	GN 1/9 pan In stainless steel with step WxD (mm) 176x108 Height (mm) 65	
0S2067	GN 1/9 pan In stainless steel with step WxD (mm) 176x108 Height (mm) 100	

GN Plastic Basins

Code	Spare Part Description	Picture
0S2918	GN 1/1 tray In polypropylene WxD (mm) 530x325 Height (mm) 65	
0S2919	GN 1/1 tray In polypropylene WxD (mm) 530x325 Height (mm) 100	
0S2920	GN 1/1 tray In polypropylene WxD (mm) 530x325 Height (mm) 150	
0S2921	GN 1/1 tray In polypropylene WxD (mm) 530x325 Height (mm) 200	
0S2922	GN 1/2 tray In polypropylene WxD (mm) 325x265 Height (mm) 65	
0S2923	GN 1/2 tray In polypropylene WxD (mm) 325x265 Height (mm) 100	
0S2924	GN 1/2 tray In polypropylene WxD (mm) 325x265 Height (mm) 150	
0S2925	GN 1/2 tray In polypropylene WxD (mm) 325x265 Height (mm) 200	



GN Plastic Basins

Code	Spare Part Description	Picture
0S2926	GN 1/3 tray In polypropylene WxD (mm) 325x175 Height (mm) 65	
0S2927	GN 1/3 tray In polypropylene WxD (mm) 325x175 Height (mm) 100	
0S2928	GN 1/3 tray In polypropylene WxD (mm) 325x175 Height (mm) 150	
0S2929	GN 1/3 tray In polypropylene WxD (mm) 325x175 Height (mm) 200	
0S2930	GN 1/4 pan In polypropylene WxD (mm) 265x162 Height (mm) 65	
0S2931	GN 1/4 pan In polypropylene WxD (mm) 265x162 Height (mm) 100	
0S2932	GN 1/4 pan In polypropylene WxD (mm) 265x162 Height (mm) 150	
0S2933	GN 1/4 pan In polypropylene WxD (mm) 265x162 Height (mm) 200	
0S2934	GN 1/6 tray In polypropylene WxD (mm) 176x162 Height (mm) 65	
0S2935	GN 1/6 pan In polypropylene WxD (mm) 176x162 Height (mm) 100	
0S2936	GN 1/6 pan In polypropylene WxD (mm) 176x162 Height (mm) 150	
0S2937	GN 1/6 pan In polypropylene WxD (mm) 176x162 Height (mm) 200	
0S2938	GN 1/9 pan In polypropylene WxD (mm) 176x108 Height (mm) 65	
0S2939	GN 1/9 pan In polypropylene WxD (mm) 176x108 Height (mm) 100	

Accessories for Basins

Code	Spare Part Description	Picture
0S1916	Coperchio in acciaio inox per bacinelle Dimensione GN: Coperchio GN 1/1	
0PR975	Coperchio in acciaio inox per bacinelle Dimensione GN: Coperchio GN 1/2	
0S2106	Coperchio in acciaio inox per bacinelle Dimensione GN: Coperchio GN 1/3	
0S1917	Stainless steel lid for GN size containers: GN 1/4 lid	
0S2202	Stainless steel lid for GN size containers: GN 1/6 lid	
0S2068	Stainless steel lid for GN size containers: GN 1/9 lid	
0S2940	Polypropylene lid for GN size containers: GN 1/1 lid	
0S2941	Polypropylene lid for GN size containers: GN 1/2 lid	
0S2942	Polypropylene lid for GN size containers: GN 1/3 lid	
0S2943	Polypropylene lid for GN size containers: GN 1/4 lid	
0S2944	Polypropylene lid for GN size containers: GN 1/6 lid	
0S2945	Polypropylene lid for GN size containers: GN 1/9 lid	



Accessories for Basins

Code	Spare Part Description	Picture
088951	Stainless steel supports for pans Dim. GN: GN 1/1 LxDxH (mm) 528x20x30	
0A8155	Stainless steel supports for GN size containers: GN 1/2 LxDxH (mm) 328x22x15	

GN Stainless Steel Trays

Code	Spare Part Description	Picture
0S1964	GN 2/1 tray In stainless steel with step WxD (mm) 650x530 Height (mm) 20	
0S1965	GN 2/1 tray In stainless steel with step WxD (mm) 650x530 Height (mm) 40	
0S1966	GN 2/1 tray In stainless steel with step WxD (mm) 650x530 Height (mm) 65	
0S1967	GN 1/1 tray In stainless steel with step WxD (mm) 530x325 Height (mm) 20	
0S1048	GN 1/1 tray In stainless steel with step WxD (mm) 530x325 Height (mm) 40	
0S1968	GN 1/1 tray In stainless steel with step WxD (mm) 530x325 Height (mm) 65	



GN Stainless Steel Trays

Code	Spare Part Description	Picture
0S0991	GN 1/2 tray Stainless steel with step WxD (mm) 325x265 Height (mm) 20	
0S0954	GN 1/2 tray Stainless steel with step WxD (mm) 325x265 Height (mm) 40	
0S1969	Perforated tray GN 2/1 In stainless steel with step WxD (mm) 650x530 Height (mm) 20	
0S1970	Perforated tray GN 2/1 In stainless steel with step WxD (mm) 650x530 Height (mm) 40	
0S1232	Perforated tray GN 2/1 In stainless steel with step WxD (mm) 650x530 Height (mm) 65	
0S1971	Perforated tray GN 1/1 In stainless steel with step WxD (mm) 530x325 Height (mm) 20	
0S1972	Perforated tray GN 1/1 In stainless steel with step WxD (mm) 530x325 Height (mm) 40	
0S0899	Perforated tray GN 1/1 In stainless steel with step WxD (mm) 530x325 Height (mm) 65	



GN Stainless Steel Trays

Code	Spare Part Description	Picture
0S2201	Perforated tray GN 1/1 In stainless steel with step WxD (mm) 530x325 Height (mm) 100	

Grease Filters


Code	Spare Part Description	Picture
006310	Grease filter for convection and conv./steam ovens Facilitates cleaning operations after cooking fatty foods. Dishwasher safe. Oven type: 6 GN 1/1 LxDxH (mm) 450x360x30	
005918	Grease filter for convection and conv./steam ovens Facilitates cleaning operations after cooking fatty foods. Dishwasher safe. Oven type: 10 GN 1/1 - 10 GN 2/1 20 GN 1/1 - 20 GN 2/1 WxDxH (mm) 582x460x45 ▶ Note: for 20 GN ovens use 2 pieces	
003774	Grease filter for convection and conv./steam ovens Facilitates cleaning operations after cooking fatty foods. Dishwasher safe. Suitable for crosswise ovens. Oven type: 10 GN 1/1 - 10 GN 2/1 crosswise WxDxH (mm) 580x450x80 ▶ Note: for 20 GN ovens use 2 pieces	
056044	Grease filter for convection and conv./steam ovens Facilitates cleaning operations after cooking fatty foods. Dishwasher safe. Suitable for crosswise ovens. Oven type: 20 GN 1/1 WxDxH (mm) 483x598x51 ▶ Note: for 20 GN ovens use 2 pieces	



Grease Filters

Code	Spare Part Description	Picture
056045	Grease filter for convection and conv./steam ovens Facilitates cleaning operations after cooking fatty foods. Dishwasher safe. Suitable for crosswise ovens. Oven type: 20 GN 2/1 WxDxH (mm) 678x598x51 ▶ Note: for 20 GN ovens use 2 pieces	

Grids and Trays for Bakery - Pastry

Code	Spare Part Description	Picture
0S1754	AISI 304 steel oven grill for bread and pastry making WxDxH (mm) 600x400x12	
0S0587	Perforated aluminum non-stick baguette pan with silicone coating; ideal for preparing 5 pieces of baguettes with a max. length. 600 mm WxDxH (mm) 600x400x38	
0S0588	Flat perforated aluminum baking/pastry tray; ideal for "light" baked pastries (e.g. cream puffs) WxDxH (mm) 600x400x20	
0S0936	Smooth flat baking/pastry tray in aluminium, ideal for baking and pastry making WxDxH (mm) 600x400x20	
0S2585	Smooth/ribbed aluminum plate with non-stick coating for various cooking needs: dual use of the plate, with the ribbed side for grilling and the smooth side for various baking and toasting. WxDxH (mm) 600x400x20	

Grids and Trays for Convection Ovens

Code	Spare Part Description	Picture
054846	GN 2/3 grill in chromed steel for FCF2 oven WxDxH (mm) 354x325x20	
0S0901	GN 2/3 tray in AISI 304 steel with flat edges and capacity from 2lt to 4lt dim. GN: GN 2/3 LxDxH (mm) 354x325x20 Capacity (l): 2	
0S0926	GN 2/3 tray in AISI 304 steel with flat edges and capacity from 2lt to 4lt dim. GN: GN 2/3 LxDxH (mm) 354x325x40 Capacity (l): 4	
0CB009	GN 2/3 enamelled tray dim. GN: GN 2/3 LxDxH (mm) 354x325x20 Capacity (l): 2	
055428	AISI 304 GN 1/1 steel grill with splashback on the short sides and one on the long side WxDxH (mm) 530x325x30 Height (mm) 30	
0C3029	Enamelled tray for oven FCF4 WxDxH (mm) 422x370x20	
0C3028	Enamelled tray for oven FCF4 WxDxH (mm) 422x370x33	
0C3030	Stainless steel grill for FCF4 oven WxDxH (mm) 422x370x8	
0KB698	GN 1/2 stainless steel tray for 3 GN 1/2 combi oven dim. GN: GN 1/2 LxDxH (mm) 325x265x40	
0KI553	GN 1/2 perforated stainless steel tray for 3 GN 1/2 combi oven dim. GN: GN 1/2 LxDxH (mm) 325x265x40	



Grids and Trays for Convection Ovens

Code	Spare Part Description	Picture
0KI275	GN 1/2 flat non-stick pan for 3 GN 1/2 combi oven dim. GN: GN 1/2 LxDxH (mm) 325x265x5	
0KD893	GN 1/2 grill in AISI 304 steel for 3 GN 1/2 combi oven dim. GN: GN 1/2 LxDxH (mm) 325x265x5	

Oven Probes

Code	Spare Part Description	Picture
0S0668	Oven probe kit, suitable for cross convection ovens, 6-10 GN 1/1, Probe size: 675 x Ø4 mm	
0S2343	Oven probe kit, suitable for cross convection ovens, 10 GN 2/1. Needle size: 1300 x Ø4 mm	
0S2344	Oven probe kit, suitable for transverse convection ovens, 20 GN 1/1-2/1. Needle size: 1120 x Ø4 mm	
0PRRPB	Single point USB probe to be used in addition to the standard core probe, also suitable for high temperature cooking	

Professional Tool Supplies

Code	Spare Part Description	Picture
0PE648	Magnetic tool holder bar Length 300mm	

Smokers and Accessories

Code	Spare Part Description	Picture
0S1753	Volcano smoker in AISI 304 ideal for: ▶ smoking fish, pork, chicken, beef, cheese, vegetables, bread (using wood chips and dried spices) ▶ low temperature cooking with the typical flavor of smoking ▶ The desired amount of smoke can be adjusted (registered design @ EPO) Compatible with: all ovens WxDxH (mm) 220x220x85	
0S2602	Wooden pellets to be used as essence for Volcano smokers, for food use. American carob: one of the favorite flavors of the Texan panorama, it infuses the meat with a robust smoked flavour. Ideal for cattle, poultry and fish. Description: Carob essence Weight: 450 g	
0S2603	Wooden pellets to be used as essence for Volcano smokers, for food use. North American walnut: with a strong flavour, it is suitable for use on many types of meat. Ideal for cattle, poultry, pork and vegetables. Description: Walnut essence Weight: 450 g	
0S2604	Wooden pellets to be used as essence for Volcano smokers, for food use. Sugar maple: light and with a sweet aftertaste. Ideal for beef, pork, bread making/cakes and vegetables. Description: Maple essence Weight: 450 g	
0S2605	Wooden pellets to be used as essence for Volcano smokers, for food use. Cherry: with a rich and intense aroma, cherry is ideal for smoking lovers. Ideal for beef, poultry, pork and bread/cake making. Description: Cherry essence Weight: 450 g	
0S2606	Wooden pellets to be used as essence for Volcano smokers, for food use Melo: offers a sweet and light fragrance that emphasizes delicate meats. Ideal for poultry, pork, baking/cakes and vegetables. Description: Apple tree essence Weight: 450 g	
0S1919	Gas burner suitable for lighting charcoal in the smoker Description: Gas burner	

Sous-vide Cooking

Code	Spare Part Description	Picture
0S1532	SMOOTH bags for vacuum COOKING - thickness 80 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 121°C (121°C maximum for 1h) Format (mm) 150X300 Pcs. 100	
0S1523	SMOOTH bags for vacuum COOKING - thickness 80 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 121°C (121°C maximum for 1h) Format (mm) 200x300 Pcs. 100	
0S2473	SMOOTH bags for vacuum COOKING - thickness 80 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 121°C (121°C maximum for 1h) Format (mm) 250x350 Pcs. 100	
0S2474	SMOOTH bags for vacuum COOKING - thickness 80 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 121°C (121°C maximum for 1h) Format (mm) 300x400 Pcs. 100	
0S1526	SMOOTH bags for vacuum COOKING - thickness 80 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 121°C (121°C maximum for 1h) Format (mm) 400x500 Pcs. 100	
0S2475	SMOOTH bags for vacuum COOKING - thickness 80 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 121°C (121°C maximum for 1h) Format (mm) 400x600 Pcs. 50	
0S2476	EMBOSED bags for vacuum COOKING - Thickness 90 microns ▶ for external suction packaging machines ▶ suitable for temperatures between -40° + 121°C (121°C maximum for 4h) Format (mm) 150X300 Pcs. 50	



Sous-vide Cooking

Code	Spare Part Description	Picture
0S2477	EMBOSED bags for vacuum COOKING - Thickness 90 microns ▶ for external suction packaging machines ▶ suitable for temperatures between -40° + 121°C (121°C maximum for 4h) Format (mm) 200x300 Pcs. 50	
0S2478	EMBOSED bags for vacuum COOKING - Thickness 90 microns ▶ for external suction packaging machines ▶ suitable for temperatures between -40° + 121°C (121°C maximum for 4h) Format (mm) 250x350 Pcs. 50	
0S2479	EMBOSED bags for vacuum COOKING - Thickness 90 microns ▶ for external suction packaging machines ▶ suitable for temperatures between -40° + 121°C (121°C maximum for 4h) Format (mm) 300x400 Pcs. 50	
0S1827	Silicone adhesive tape for sous vide cooking ▶ to be used with USB probe Quantity: Set of 57 pieces WxDxH (mm) 30x50x12	
0C8514	USB probe for sous vide cooking ▶ ideal for sous vide cooking, ensures that the correct temperature of the product is reached precisely without damaging the bag ▶ 1 mm in diameter, 60 mm in length and with a special diagonally pointed needle, designed to avoid bag breakage ▶ to be used with silicone adhesive tape cod. 0S1827 ▶ available only for air-o-steam Touchline and air-o-convect Touchline ovens WxDxH (mm) 160x170x90	

Sous-vide Storage

Code	Spare Part Description	Picture
0S3213	SMOOTH bags for vacuum STORAGE - thickness 90 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: dried mushrooms, sausages/sliced meats, soft cheese (Emmental type), fresh meat without bones, fish fillet, raw vegetables, cooked vegetables, shelled molluscs/crustaceans, shelled nuts, fresh fruit, cooked legumes, spices Format (mm) 150x200 Pcs. 100	



Sous-vide Storage

Code	Spare Part Description	Picture
0S1500	SMOOTH bags for vacuum STORAGE - thickness 90 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: dried mushrooms, sausages/sliced meats, soft cheese (Emmental type), fresh meat without bones, fish fillet, raw vegetables, cooked vegetables, shelled molluscs/crustaceans, shelled nuts, fresh fruit, cooked legumes, spices Format (mm) 200x300 Pcs. 100	
0S1503	SMOOTH bags for vacuum STORAGE - thickness 90 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: dried mushrooms, sausages/sliced meats, soft cheese (Emmental type), fresh meat without bones, fish fillet, raw vegetables, cooked vegetables, shelled molluscs/crustaceans, shelled nuts, fresh fruit, cooked legumes, spices Format (mm) 250x350 Pcs. 100	
0S1504	SMOOTH bags for vacuum STORAGE - thickness 90 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: dried mushrooms, sausages/sliced meats, soft cheese (Emmental type), fresh meat without bones, fish fillet, raw vegetables, cooked vegetables, shelled molluscs/crustaceans, shelled nuts, fresh fruit, cooked legumes, spices Format (mm) 250x400 Pcs. 100	
0S1501	SMOOTH bags for vacuum STORAGE - thickness 90 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: dried mushrooms, sausages/sliced meats, soft cheese (Emmental type), fresh meat without bones, fish fillet, raw vegetables, cooked vegetables, shelled molluscs/crustaceans, shelled nuts, fresh fruit, cooked legumes, spices Format (mm) 300x400 Pcs. 100	
0S1505	SMOOTH bags for vacuum STORAGE - thickness 90 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: dried mushrooms, sausages/sliced meats, soft cheese (Emmental type), fresh meat without bones, fish fillet, raw vegetables, cooked vegetables, shelled molluscs/crustaceans, shelled nuts, fresh fruit, cooked legumes, spices Format (mm) 300x500 Pcs. 100	
0S1506	SMOOTH bags for vacuum STORAGE - thickness 90 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: dried mushrooms, sausages/sliced meats, soft cheese (Emmental type), fresh meat without bones, fish fillet, raw vegetables, cooked vegetables, shelled molluscs/crustaceans, shelled nuts, fresh fruit, cooked legumes, spices Format (mm) 350x450 Pcs. 100	
0S2472	SMOOTH bags for vacuum STORAGE - thickness 90 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: dried mushrooms, sausages/sliced meats, soft cheese (Emmental type), fresh meat without bones, fish fillet, raw vegetables, cooked vegetables, shelled molluscs/crustaceans, shelled nuts, fresh fruit, cooked legumes, spices Format (mm) 400x500 Pcs. 50	



Sous-vide Storage

Code	Spare Part Description	Picture
0S1507	SMOOTH bags for vacuum STORAGE - thickness 90 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: dried mushrooms, sausages/sliced meats, soft cheese (Emmental type), fresh meat without bones, fish fillet, raw vegetables, cooked vegetables, shelled molluscs/crustaceans, shelled nuts, fresh fruit, cooked legumes, spices Format (mm) 400x600 Pcs. 100	
0S1531	SMOOTH bags for vacuum STORAGE - thickness 140 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: whole salami, seasoned slices with/without edges, matured cheese in pieces, fresh meat with bones, whole fish with bones, whole fish without bones, molluscs/crustaceans, nuts in shell, dried fruit, raw legumes Format (mm) 150X300 Pcs. 100	
0S1508	SMOOTH bags for vacuum STORAGE - thickness 140 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: whole salami, seasoned slices with/without edges, matured cheese in pieces, fresh meat with bones, whole fish with bones, whole fish without bones, molluscs/crustaceans, nuts in shell, dried fruit, raw legumes Format (mm) 200x300 Pcs. 100	
0S1510	SMOOTH bags for vacuum STORAGE - thickness 140 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: whole salami, seasoned slices with/without edges, matured cheese in pieces, fresh meat with bones, whole fish with bones, whole fish without bones, molluscs/crustaceans, nuts in shell, dried fruit, raw legumes Format (mm) 250x350 Pcs. 100	
0S1511	SMOOTH bags for vacuum STORAGE - thickness 140 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: whole salami, seasoned slices with/without edges, matured cheese in pieces, fresh meat with bones, whole fish with bones, whole fish without bones, molluscs/crustaceans, nuts in shell, dried fruit, raw legumes Format (mm) 250x400 Pcs. 100	
0S1512	SMOOTH bags for vacuum STORAGE - thickness 140 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: whole salami, seasoned slices with/without edges, matured cheese in pieces, fresh meat with bones, whole fish with bones, whole fish without bones, molluscs/crustaceans, nuts in shell, dried fruit, raw legumes Format (mm) 300x400 Pcs. 100	
0S1513	SMOOTH bags for vacuum STORAGE - thickness 140 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: whole salami, seasoned slices with/without edges, matured cheese in pieces, fresh meat with bones, whole fish with bones, whole fish without bones, molluscs/crustaceans, nuts in shell, dried fruit, raw legumes Format (mm) 300x500 Pcs. 100	



Sous-vide Storage

Code	Spare Part Description	Picture
0S1514	SMOOTH bags for vacuum STORAGE - thickness 140 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: whole salami, seasoned slices with/without edges, matured cheese in pieces, fresh meat with bones , whole fish with bones, whole fish without bones, molluscs/crustaceans, nuts in shell, dried fruit, raw legumes Format (mm) 350x450 Pcs. 100	
0S1515	SMOOTH bags for vacuum STORAGE - thickness 140 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: whole salami, seasoned slices with/without edges, matured cheese in pieces, fresh meat with bones , whole fish with bones, whole fish without bones, molluscs/crustaceans, nuts in shell, dried fruit, raw legumes Format (mm) 400x500 Pcs. 50	
0S1516	SMOOTH bags for vacuum STORAGE - thickness 140 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: whole salami, seasoned slices with/without edges, matured cheese in pieces, fresh meat with bones , whole fish with bones, whole fish without bones, molluscs/crustaceans, nuts in shell, dried fruit, raw legumes Format (mm) 400x600 Pcs. 50	
0S1509	SMOOTH bags for vacuum STORAGE - thickness 140 microns ▶ for bell-shaped packaging machines ▶ suitable for temperatures between -40° + 40°C ▶ ideal for: whole salami, seasoned slices with/without edges, matured cheese in pieces, fresh meat with bones , whole fish with bones, whole fish without bones, molluscs/crustaceans, nuts in shell, dried fruit, raw legumes Format (mm) 200x400 Pcs. 100	
0S1517	EMBOSSED bags for vacuum STORAGE - thickness 90 microns ▶ for external suction packaging machines ▶ suitable for temperatures between -40° + 40°C Format (mm) 200x300 Pcs. 100	
0S1518	EMBOSSED bags for vacuum STORAGE - thickness 90 microns ▶ for external suction packaging machines ▶ suitable for temperatures between -40° + 40°C Format (mm) 250x400 Pcs. 100	
0S1519	EMBOSSED bags for vacuum STORAGE - thickness 90 microns ▶ for external suction packaging machines ▶ suitable for temperatures between -40° + 40°C Format (mm) 300x400 Pcs. 100	



Sous-vide Storage

Code	Spare Part Description	Picture
0S1520	EMBOSED bags for vacuum STORAGE - thickness 90 microns ▶ for external suction packaging machines ▶ suitable for temperatures between -40° + 40°C Format (mm) 300x500 Pcs. 100	
0S1521	EMBOSED bags for vacuum STORAGE - thickness 90 microns ▶ for external suction packaging machines ▶ suitable for temperatures between -40° + 40°C Format (mm) 400x500 Pcs. 50	
0S1522	EMBOSED bags for vacuum STORAGE - thickness 90 microns ▶ for external suction packaging machines ▶ suitable for temperatures between -40° + 40°C Format (mm) 400x600 Pcs. 50	
0S2899	SMOOTH RECYCLABLE bags for vacuum STORAGE - thickness 100 microns ▶ for bell-shaped packaging machines ▶ ideal for rapid heating ▶ suitable for temperatures between -25° + 85°C Format (mm) 150x300 Pcs. 100	
0S2900	SMOOTH RECYCLABLE bags for vacuum STORAGE - thickness 100 microns ▶ for bell-shaped packaging machines ▶ ideal for rapid heating ▶ suitable for temperatures between -25° + 85°C Format (mm) 200x300 Pcs. 100	
0S2901	SMOOTH RECYCLABLE bags for vacuum STORAGE - thickness 100 microns ▶ for bell-shaped packaging machines ▶ ideal for rapid heating ▶ suitable for temperatures between -25° + 85°C Format (mm) 250x350 Pcs. 100	
0S2902	SMOOTH RECYCLABLE bags for vacuum STORAGE - thickness 100 microns ▶ for bell-shaped packaging machines ▶ ideal for rapid heating ▶ suitable for temperatures between -25° + 85°C Format (mm) 300x400 Pcs. 100	
0S2903	SMOOTH RECYCLABLE bags for vacuum STORAGE - thickness 100 microns ▶ for bell-shaped packaging machines ▶ ideal for rapid heating ▶ suitable for temperatures between -25° + 85°C Format (mm) 400x600 Pcs. 100	



Sous-vide Storage

Code	Spare Part Description	Picture
0S2788	SYV stainless steel valve for core probe allows you to detect the core temperature of the product subjected to vacuum cooking, creating an effective barrier to the passage of air at the crossing point of the probe needle with the bag ▶ Reusable infinite times ▶ Suitable for food contact, produced in stainless steel, silicone and food-grade Teflon ▶ Compatible with oven jar cooking ▶ Suitable for use in cooking and blast chilling processes from -20°C to 130°C. ▶ Suitable for bain-marie cooking processes up to 100°C. ▶ Suitable for steam oven cooking processes up to 130°C. Description:SYV valve for core probe	
0S1533	Stainless steel trays with lids for vacuum storage ▶ maximum lid sealing temperature: 90°C Description: Stainless steel trays with Tritan™ lid GN: 1/1 WxD (mm) 530 x 325 H (mm) 100 pcs. 1	
0S1534	Stainless steel trays with lids for vacuum storage ▶ maximum lid sealing temperature: 90°C Description: Stainless steel trays with Tritan™ lid GN: 1/1 WxD (mm) 530 x 325 H (mm) 150 pcs. 1	
0S1535	Stainless steel trays with lids for vacuum storage ▶ maximum lid sealing temperature: 90°C Description: Stainless steel trays with Tritan™ lid GN: 1/2 WxD (mm) 325 x 265 H (mm) 100 pcs. 1	
0S1536	Stainless steel trays with lids for vacuum storage ▶ maximum lid sealing temperature: 90°C Description: Stainless steel trays with Tritan™ lid GN: 1/2 WxD (mm) 325 x 265 H (mm) 150 pcs. 1	
0S1537	Stainless steel trays with lids for vacuum storage ▶ maximum lid sealing temperature: 90°C Description: Stainless steel trays with Tritan™ lid GN: 1/3 WxD (mm) 325 x 175 H (mm) 100 pcs. 1	
0S1538	Stainless steel trays with lids for vacuum storage ▶ maximum lid sealing temperature: 90°C Description: Stainless steel trays with Tritan™ lid GN: 1/3 WxD (mm) 325 x 175 H (mm) 150 pcs. 1	
0S2616	Tritan™ lid with gasket for stainless steel pans ▶ maximum lid sealing temperature: 90°C Description: Stainless steel pan with Tritan™ lid GN: 1/1 WxD (mm) 530 x 325 pcs. 1	
0S2617	Tritan™ lid with gasket for stainless steel pans ▶ maximum lid sealing temperature: 90°C Description: Stainless steel pan with Tritan™ lid GN: 1/2 WxD (mm) 325 x 265 pcs. 1	
0S2618	Tritan™ lid with gasket for stainless steel pans ▶ maximum lid sealing temperature: 90°C Description: Stainless steel pan with Tritan™ lid GN: 1/3 WxD (mm) 325 x 175 pcs. 1	
0S2619	Steel lid with gasket for stainless steel containers ▶ maximum lid sealing temperature: 90°C GN: 1/1 WxD (mm) 530 x 325 pcs. 1	



Sous-vide Storage

Code	Spare Part Description	Picture
0S2620	Steel lid with gasket for stainless steel containers ▶ maximum lid sealing temperature: 90°C GN: 1/2 WxD (mm) 325 x 265 pcs. 1	
0PRQXV	External vacuum hose on containers ▶ External vacuum device in plastic material complete with sleeve and connection Length (mm) 1140 Ø ext. (mm) 18 Ø internal. (mm) 12	
0PRRC6	Accessory for external vacuum ▶ Use with embossed bags Description: Easy Flat 35 pcs. 3	
0PRRC7	Accessory for external vacuum ▶ Use with embossed bags Description: Easy Flat 40 pcs. 3	
0PRRFG	Inclined stainless steel worktop for benchtop machines for vacuum packaging of liquids, complete with adjustment angle LxWxH (mm) 300x234x71	
0PRRFH	Inclined stainless steel worktop for benchtop machines for vacuum packaging of liquids, complete with adjustment angle LxWxH (mm) 400x280x66	
0PRQXR	Complete Bluetooth LP printer (1 ribbon and 1 label roll) 100-240V KIT	
0PRQXS	Start pack for tag kit printer (4 ribbons and 9 label rolls)	



Sous-vide Storage

Code	Spare Part Description	Picture
0PRQXT	Black ribbon Set of 4 pieces WxD (mm) 50x30 Length (m) 30	
0PRQXU	Label rolls Set of 9 pieces WxD (mm) 50x60 200 labels per roll	
0S2608	External vacuum hose kit with sleeve complete with quick connection fitting (0S2609) WxDxH (mm) L= 1350mm; Ø 22 mm ext. Ø 16mm internal pcs. 1	
0S2609	1/4" fitting with quick coupling compatible with Electrolux Professional packaging machines, Dito Sama Description: included in 0S2608 pcs. 1	
0S1543	Polyethylene tablets WxDxH (mm) 310x230x25 pcs. 1	
0S2188	High temperature adhesive label roll for HACCP printer Dimensions: 57mm x 12m pcs. 1	
0PRRVS	Set of gaskets (3px each, 9 in total) for the external vacuum valve cod. 0S2788	
0PRRVT	Replacement gaskets (set of 10 pieces) for the external vacuum valve cos 0S2788. This gasket is the one where the probe is inserted	

Thermal Covers

Code	Spare Part Description	Picture
0S1994	Thermal cover for tray holder structure Ideal for maintaining the temperature of food for up to 30 minutes. The particular strap closure guarantees easy use. Washable: Approved by ETL Sanitation (PNC 922364). Oven type: 10 GN 1/1 WxDxH (mm) 390x660x720	
0S1995	Thermal cover for tray holder structure Ideal for maintaining the temperature of food for up to 30 minutes. The particular strap closure guarantees easy use. Washable: Approved by ETL Sanitation (PNC 922366). Oven type: 10 GN 2/1 LxDxH (mm) 625x785x720	
0S1996	Thermal cover for tray holder structure Ideal for maintaining the temperature of food for up to 30 minutes. The particular strap closure guarantees easy use. Washable: Approved by ETL Sanitation (PNC 922365). Oven type: 20 GN 1/1 WxDxH (mm) 385x660x1560	
0S1997	Thermal cover for tray holder structure Ideal for maintaining the temperature of food for up to 30 minutes. The particular strap closure guarantees easy use. Washable: Approved by ETL Sanitation (PNC 922367). Oven type: 20 GN 2/1 WxDxH (mm) 625x785x1550	

Washing Systems

Code	Spare Part Description	Picture
006696	Concealed shower unit with retractable tube and accessories included for assembly in the oven Oven type: all WxDxH (mm) 300x250x120	



Washing Systems

Code	Spare Part Description	Picture
0S0662	External shower unit including connection to the external panel of the oven Oven type: all Tube length (mm) 2000	
003164	External shower group components included with code 0S0662 Description: Shower dispenser up to 08-2010	
0S1639	External shower group components included with code 0S0662 Description: Shower dispenser from 09-2010	
003167	External shower group components included with code 0S0662 Description: 1/2" black shower head	
0S0555	External shower group components included with code 0S0662 Description: Tap with knob without bracket	
0S0354	External shower unit including connection to the external panel of the oven Oven type: all Tube length (mm) 2000	



Washing Systems

Code	Spare Part Description	Picture
0S0323	External shower group components included with code 0S0354 Description: 1/2" black shower head	
0S0324	External shower group components included with code 0S0354 Description: Anchor bracket	
0S0325	External shower group components included with code 0S0354 Description: Flexible hose Ø 1/2" FF L=2000mm	

Water Treatment for Ovens

Code	Spare Part Description	Picture
0S1632	Purity Steam filter with MDU head recommended for all oven models from 6 GN 1/1 to 20 GN 2/1 Description: Purity STEAM 450 suitable for all oven models Steam: low use of steam	
0S1633	Purity Steam filter with MDU head recommended for all oven models from 6 GN 1/1 to 20 GN 2/1 Description: Purity STEAM 600 suitable for all oven models Steam: medium steam use	



Water Treatment for Ovens

Code	Spare Part Description	Picture
0S1634	Purity Steam filter with MDU head recommended for all oven models from 6 GN 1/1 to 20 GN 2/1 Description: Purity STEAM 1200 suitable for all oven models (PNC 920003) Steam: high steam usage	
0S1635	Purity Steam filter with MDU head recommended for all oven models from 6 GN 1/1 to 20 GN 2/1 Description: Replacement cartridge for Purity STEAM 450	
0S1636	Purity Steam filter with MDU head recommended for all oven models from 6 GN 1/1 to 20 GN 2/1 Description: Replacement cartridge for Purity STEAM 600	
0S1637	Purity Steam filter with MDU head recommended for all oven models from 6 GN 1/1 to 20 GN 2/1 Description: Replacement cartridge for Purity STEAM 1200	
0S2490	Purity C STEAM filter with liter counter recommended for 6 GN 1/1 and 10 GN 1/1 ovens with low steam use. Description: Replacement cartridge for Purity C500 STEAM	
0S2488	Purity C STEAM filter with liter counter recommended for 6 GN 1/1 and 10 GN 1/1 ovens with low steam use. Description: Replacement cartridge for Purity C1100 STEAM	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

Water Treatment for Ovens

Code	Spare Part Description	Picture
0S3239	Purity C STEAM filter with liter counter recommended for 6 GN 1/1 and 10 GN 1/1 ovens with low steam use. Description: Purity C500 STEAM kit suitable for 6 GN 1/1 and 10 GN 1/1 Steam: low use of steam Code Qt. Description 0S2489 1 Head for water filters with 4 levels of bypass, 0S2490 1 Cartridge for purity c 500 steam, 0S2555 1 Digital flow-meter for water filters	
0S3240	Purity C STEAM filter with liter counter recommended for 6 GN 1/1 and 10 GN 1/1 ovens with low steam use. Description: Purity C1100 STEAM kit suitable for 10 GN 1/1 Steam: medium steam use Code Qt. Description 0S2488 1 Cartridge for purity c 1100 steam, 0S2489 1 Head for water filters with 4 levels of bypass, 0S2555 1 Digital flow-meter for water filters	
0S1701	Total and partial carbonate hardness kit	

Accessories for Boiling Pans

Code	Spare Part Description	Picture
005585	1 sector colander Compatible with: 60 lt pot	
0CC044	Colander-vegetable colander 2 sectors Compatible with: 100 lt pot	
0CC043	Colander-vegetable colander 2 sectors Compatible with: 150 l pot	
038002	Handle for 2-sector colander-vegetable colander basket Compatible with: 2-sector colander	
0TT838	Colander/Vegetable Strainer 2 sectors Height 450mm Length 290+290mm Compatible with 150lt pot PNC accessory 206123	

Accessories for Bain-Marie

Code	Spare Part Description	Picture
004852	False perforated bottom in stainless steel Suitable for 400mm wide bain-marie; compatible with all models WxDxH (mm) 280x500x20 Compatible with: all models	
004858	False perforated bottom in stainless steel Suitable for 800mm wide bain-marie; compatible with all models WxDxH (mm) 490x600x20 Compatible with: all models	

Accessories for Braising Pans

Code	Spare Part Description	Picture
0CA640	Stainless steel lid for multifunctional bratt pans 400mm wide LxWxH (mm) 350x550x20 Compatible with: 900XP; EVO900; N900; ELCO900; HD900; 700XP; EVO700; N700; ELCO700; PR700; MD700; 600	
0CA641	Stainless steel lid for 800mm wide multifunctional bratt pans WxDxH (mm) 700x550x20 Compatible with: 900XP; EVO900; N900; ELCO900; HD900; 700XP; EVO700; N700; ELCO700; PR700; MD700; 600	

Castors

Code	Spare Part Description	Picture
0L2658	Set of 4 low wheels for dishwashers dim 80x62.6 mm H 20 mm	

Accessories for Electric Modular Cookers

Code	Spare Part Description	Picture
0CA622	Cast iron crosspieces Suitable for expanding the cooking area, usable only with square-shaped electric plates; set 2pcs LxDxH (mm) 270x115x25 Compatible with: 700XP; EVO700; N700; ELCO700	



Accessories for Electric Modular Cookers

Code	Spare Part Description	Picture
002012	Cast iron crosspiece Suitable for expanding the cooking area, can only be used with square-shaped electric plates; WxDxH (mm) 350x100x30 Compatible with: 900XP; EVO900; N900; ELCO900	

Accessories for Fry Tops

Code	Spare Part Description	Picture
0CC064	Scraper for smooth plate Suitable for cleaning all smooth plate fry tops complete with 2 blades 0C6241 WxDxH (mm) 400x150x50 Compatible with: All smooth plate fry tops	
0CB172	Scraper for ridged plate Suitable for cleaning ridged plate fry tops WxDxH (mm) 359x120x30 Compatible with: All ridged plate fry tops	
0C2519	Stainless steel blades for scraper For scraper 0CC064 Not suitable for chrome fry tops Set of 10 Compatible with: smooth plate fry tops	
0C6241	Stainless steel blades for scraper with beveled corners For scraper 0CC064 Suitable for chromed fry tops Set of 2 Compatible with: smooth chromed plate fry tops Code Qt. Description 056347 2 Scraper blade , 0C3529 1 Label	
006469	Stainless steel blade for scraper For scraper 0CC064 Suitable for multifunction bratt pans modular cooking One piece Compatible with: multifunction bratt pans modular cooking	
0C6384	Stainless steel cap For horizontal plate fry tops Suitable for keeping fats released from food on the plate ØxH (mm) Ø46x50 Compatible with: 900XP; EVO900; N900; ELCO900	



Accessories for Fry Tops

Code	Spare Part Description	Picture
0S1379	Brush with handle for hot surfaces Suitable for cleaning hot plates with a maximum temperature of 175° C Non-abrasive With handle in heat-resistant material Compatible with: All fry tops	
0S1380	Replacement sponge for brush Suitable for cleaning hot plates with a maximum temperature of 175° C Non-abrasive Quantity: Set 15 pcs	
0S1377	Water squeegee with handle for hot surfaces Suitable for cleaning hot plates with a maximum temperature of 175° C With wooden handle Compatible with: All fry tops	

Accessories for Fryers

Code	Spare Part Description	Picture
054948	Chromed basket for fryer Half basket for fryers with 7 l well WxDxH (mm) 100x325x120 Compatible with: 700XP; EVO700; N700; ELCO700; MD700; PR700	
004492	Chromed basket for fryer Whole basket for fryers with 7 l well WxDxH (mm) 225x325x90 Compatible with: 700XP; EVO700; N700; ELCO700; MD700; PR700	
054960	Chromed basket for fryer Half basket for fryers with 12 l well WxDxH (mm) 225x325x125 Compatible with: 700XP; EVO700; N700; ELCO700; MD700; PR700	
005933	Chromed basket for fryer Whole basket for fryers with 14-15 bowl, programmable electric fryers WxDxH (mm) 225x325x120 Compatible with: 900XP; EVO900; N900; ELCO900; HD900; 700XP; EVO700; N700; ELCO700; PR700	



Accessories for Fryers

Code	Spare Part Description	Picture
005974	Chromed baskets for fryers Pair of half baskets for monobloc fryers with 12 -14-15 bowl, programmable electric fryers WxDxH (mm) 100x325x120 Compatible with: 700XP; EVO700	
004499	Chromed basket for fryer Half basket for fryers with 34 l and 40 l wells WxDxH (mm) 270x260x120 Compatible with: 900XP; EVO900; N900; ELCO900; HD900; 700XP; EVO700; N700; ELCO700; PR700; MD700	
005180	Chromed basket for fryer Whole basket for 34 l and 40 l fryers WxDxH (mm) 620x330x80 Compatible with: 700XP; EVO700; N700; ELCO700; PR700	
0HB228	Stainless steel basket for fryer Stainless steel half basket WxDxH (mm) 340x130x140 Compatible with: N900; ELCO900; HD900 On request plastic handle 0C3723	
0HB229	Stainless steel basket for fryer Entire stainless steel basket WxDxH (mm) 340x280x140 Compatible with: N900; ELCO900; HD900 On request plastic handle 0C3723	
059327	Chromed basket for fryer Half basket for fryers with 20 l well WxDxH (mm) 330x158x122 Compatible with: N900; ELCO900; HD900	
059307	Chromed basket for fryer Whole basket for fryers with 20 l well WxDxH (mm) 333x338x122 Compatible with: N900; ELCO900; HD900	
0C9735	Chromed basket for fryer Half basket for fryers with 20-23 l well WxDxH (mm) 345x150x160 Compatible with: H900	



Accessories for Fryers

Code	Spare Part Description	Picture
006133	Chromed basket for fryer Half basket for fryers with 18-23 bowl, programmable electric fryers WxDxH (mm) 137x330x142 Compatible with: 900XP; EVO900; N900; ELCO900; HD900	
0CA823	Set of 2 chromed baskets for fryers with additional hook 2 half baskets for fryers with 18-23 bowls and programmable electric fryers - dim.137x330x142 - Compatible with 900XP; EVO900; N900; ELCO900; HD900	
006539	Chromed basket for fryer Whole basket for fryers with 18-23 bowls programmable electric fryers WxDxH (mm) 285x330x142 Compatible with: 900XP; EVO900; N900; ELCO900; HD900	
0CBCEH	Chromed basket for fryers with additional hook Half basket for fryers with 18-23 capacity programmable electric fryers - dim.137x330x142 - Compatible with 900XP; EVO900; N900; ELCO900; HD900	
0CA824	Chromed fryer basket with additional hook. Whole basket for fryers with 18-23 capacity programmable electric fryers - dim.285x330x142 - Compatible with 900XP; EVO900; N900; ELCO900; HD900	
053206	Chromed fryer basket Half basket for monobloc fryers with 36 l well WxDxH (mm) 134x260x120 Compatible with: MD700; PR700	
052683	Chromed basket for fryer Whole basket for monobloc fryers with 36 l well WxDxH (mm) 268x260x120 Compatible with: MD700; PR700	



Accessories for Fryers

Code	Spare Part Description	Picture
005704	Chromed basket for fryer Whole basket for fryers with 7 l well WxDxH (mm) 210x265x105 Compatible with: 600	
0C3723	Plastic handle for fryer basket Compatible with: 006133; 006539; 059307; 059327; 0HB228; 0HB229	
005932	Chromed grill for fryer tank bottom WxDxH (mm) 220x360x5 Compatible with: 700XP; EVO700; N700; ELCO700; MD700	
005965	Chromed grill for fryer tank bottom WxDxH (mm) 230x330x5 Compatible with: 700XP; EVO700; N700; ELCO700; MD700	
0C1743	Chromed grill for fryer tank bottom WxDxH (mm) 388x320x5 Compatible with: 900XP; EVO900; N900; ELCO900; HD900	
006130	Chromed grill for fryer tank bottom WxDxH (mm) 388x296x5 Compatible with: 900XP; EVO900; N900; ELCO900; HD900	
0C1859	Stainless steel deflector Suitable for monobloc fryers with 15 l "V" shaped tank. The use of the deflector located on the inclined part of the tank is to prevent the breaching or flour released from the products from depositing on the walls of the tank itself. and carbonize WxDxH (mm) 280x350x90 Compatible with: 900XP; EVO900; N900; ELCO900 700XP; EVO700; N700; ELCO700	
0C3717	Stainless steel deflector Suitable for monobloc fryers with 23 l "V" shaped tank. The use of the deflector located on the inclined part of the tank is to prevent the breaching or flour released by the products from depositing on the walls of the tank itself. and carbonize WxDxH (mm) 295x390x65 Compatible with: 900XP; EVO900; N900; ELCO900 700XP; EVO700	
0CA623	Stainless steel lid for fryer Suitable for fryer with 23 l tank WxDxH (mm) 550x375x1.5 Compatible with: 900XP; EVO900; N900; ELCO900	



Accessories for Fryers

Code	Spare Part Description	Picture
0CA776	Internal tank filter for 15 l fryer Suitable for collecting sediment in the tank for monobloc fryers WxDxH (mm) 58x368x114 Compatible with: 900XP; EVO900; N900; ELCO900; 700XP; EVO700; N700; ELCO700; PR700	
0CA777	Internal tank filter for 23 l fryer Suitable for collecting sediment in the tank for monobloc fryers WxDxH (mm) 61x384x126 Compatible with: 900XP; EVO900; N900; ELCO900	
0CA642	Brush for 15 l fryer Suitable for cleaning the fryer tank drain Ø 6mm WxDxH (mm) 668x228x6 Compatible with: 900XP; EVO900; N900; ELCO900; HD900; 700XP; EVO700; N700; ELCO700; PR700; MD700	
0CA643	Brush for 23 l fryer Suitable for cleaning the fryer tank drain Ø 6mm WxDxH (mm) 781x125x6 Compatible with: 900XP; EVO900; N900; ELCO900; HD900; 700XP; EVO700; N700; ELCO700; PR700; MD700	
006149	Polyester oil filter with stainless steel structure Consisting of: Polyester filter pcs. 1 Compatible with: 900XP; EVO900; N900; ELCO900	
006160	Polyester oil filter with stainless steel structure Consisting of: Stainless steel frame for filter pcs. 1 Compatible with: 900XP; EVO900; N900; ELCO900	
006161	Polyester oil filter with stainless steel structure Consisting of: Crosspiece for filter pcs. 2 Compatible with: 900XP; EVO900; N900; ELCO900	
0TH071	Polyester oil filter with stainless steel structure Consisting of: Hexagonal nut M4x3.2 pcs. 4 Compatible with: 900XP; EVO900; N900; ELCO900	



Accessories for Fryers

Code	Spare Part Description	Picture
0G1697	Polyester oil filter with stainless steel structure Consisting of: Flat washer pcs. 4 Compatible with: 900XP; EVO900; N900; ELCO900	
0C8556	Polyester oil filter with stainless steel structure Consisting of: Screw M4x14 pcs. 4 Compatible with: 900XP; EVO900; N900; ELCO900	
0C9119	Stainless steel oil filter For monobloc fryers (PNC 206359 - until 2016) WxDxH (mm) 242x490x50 Compatible with: 900XP; EVO900; N900; ELCO900	
0C9069	Stainless steel oil filter For monobloc fryers WxDxH (mm) 256x402x40 Compatible with: 700XP; EVO700; N700; ELCO700; PR700	
0CB343	Stainless steel pre-filter For 23 l fryers. Supplied as standard in all models with oil recirculation pump. WxDxH (mm) 242x514x151 Compatible with: 900XP; EVO900;	
0CB512	Advanced stainless steel filter system For 23 l fryers. Mandatory if using paper filters WxDxH (mm) 242x514x151 Compatible with: 900XP; EVO900;	
0CB513	Paper filters for advanced filtering system For 23 l fryers. Set of 100 pieces WxDxH (mm) 214x691x90 Compatible with: 900XP; EVO900;	



Accessories for Fryers

Code	Spare Part Description	Picture
0C7974	Oil drain extension Suitable for fryers with 23 l tank - 1"-270mm long WxDxH (mm) 30x400x30 Compatible with: 900XP; EVO900; 700XP; EVO700	
0C6282	Oil drain extension Suitable for fryers with 15 l 3/4" tank - 185mm long WxDxH (mm) 40x185x40 Compatible with: 900XP; EVO900; 700XP; EVO700	
0CB466	Extension for oil drain connection hose For 23 l fryers with oil recirculation pump. WxDxH (mm) 60x2292x60 Compatible with: 900XP; EVO900;	

Accessories for Gas Modular Cookers

Code	Spare Part Description	Picture
0CC022	Smooth food contact enamelling grill plate Suitable for direct cooking of food; The plate can only be installed on front burners WxDxH (mm) 300x340x55 Compatible with: 700XP; EVO700; N700; ELCO700	
0CC023	Ribbed food contact enamelling grill plate Suitable for direct cooking of food; The plate can only be installed on front burners WxDxH (mm) 300x340x60 Compatible with: 700XP; EVO700; N700; ELCO700	
0C4708	Smooth single-burner cast iron radiant plate Suitable for indirect cooking of food using pans WxDxH (mm) 285x329x50 Compatible with: 700XP; EVO700; N700; ELCO700	
002009	Smooth single-burner cast iron radiant plate Suitable for indirect cooking of food using pans WxDxH (mm) 350x350x30 Compatible with: 900XP; EVO900; N900; ELCO900; HD900	
0CC019	Smooth food contact enamelling grill plate Suitable for direct cooking of food equipped with fat collection channel WxDxH (mm) Compatible with: 900XP; EVO900; N900; ELCO900; HD900	




Accessories for Gas Modular Cookers

Code	Spare Part Description	Picture
0CC020	Ribbed food contact enamelling grill plate Suitable for direct cooking of food equipped with fat collection channel WxDxH (mm) 350x400x30 Compatible with: 900XP; EVO900; N900; ELCO900; HD900	
0C6770	Double-fire cast iron ribbed plate Suitable for direct cooking of food equipped with fat collection channel WxDxH (mm) 310x510x55 Compatible with: 600	
0C6771	Smooth dual-fire cast iron radiant plate Suitable for indirect cooking of food using pans WxDxH (mm) 310x510x55 Compatible with: 600	
026953	Cast iron disc for solid top ØxH (mm) 225x25 Compatible with: 900XP; EVO900; N900; ELCO900; HD900	
001158	Rim lifter	
0CA626	Wok pot support Stainless steel for open fire Ø 260mm ØxH (mm) Ø260x47 Compatible with: 900XP; EVO900; N900; ELCO900; HD900; 700XP; EVO700; N700; ELCO700; MD700; PR700; B700; 600	
0C1985	Cast iron pan support single burner grill Black enamelled finish WxDxH (mm) 394x360x50 Compatible with: 900XP; EVO900; N900; ELCO900	
0C1278	Stainless steel grid for single burner pan support WxDxH (mm) 398x370x35 Compatible with: 900XP; EVO900; N900; ELCO900	
0C6298	Stainless steel pan support double burner grill WxDxH (mm) 331x760x93 Compatible with: 900XP; N900* * from S/N 350...	



Accessories for Gas Modular Cookers

Code	Spare Part Description	Picture
0C0130	Stainless steel double burner pan support grill WxDxH (mm) 398x370x35 Compatible with: N900** ** up to S/N 349...	
0C0132	Cast iron grate for single burner pan support Black enamelled finish (PNC 206208 pair of grates) WxDxH (mm) 381x360x50 Compatible with: N900	
002437	Cast iron pan support single burner grill Black enamelled finish WxDxH (mm) 390x350x60 Compatible with: HD900	
0CB759	Stainless steel pan support double burner grill WxDxH (mm) 335x594x75 Compatible with: 700XP; EVO700; N700; ELCO700	
0C2526	Cast iron pan support single burner grill Black enamelled finish WxDxH (mm) 386x285x48 Compatible with: 700XP; EVO700; N700; ELCO700	
002436	Cast iron pan support single burner grill Black enamelled finish WxDxH (mm) 345x285x37 Compatible with: PR700	
004976	Cast iron pan support double burner grill Black enamelled finish WxDxH (mm) 320x530x40 Compatible with: 600	
0S2805	Chromed steel fire reduction grille Reduction grille 260x260 mm Compatible with: 900XP; EVO900; N900; ELCO900; HD900; 700XP; EVO700; N700; ELCO700; MD700; PR700; B700; 600	
0CBCCK	Ribbed single-burner cast iron plate For burners Ø 85 mm Suitable for direct cooking of food equipped with fat collection channel WxDxH (mm) 345x395x55 Compatible with: H900; P1000	



Accessories for Gas Modular Cookers

Code	Spare Part Description	Picture
0CBCCL	Double-fire cast iron ribbed plate For burners Ø 85 mm and Ø 103 mm Suitable for direct cooking of food equipped with fat collection channel WxDxH (mm) 395x695x55 Compatible with: H900; P1000	
0CB505	Disc for cooking plate. Compatible with: 700XP; EVO700; N700; ELCO700; MD700 ØxH (mm): 197x18	

Accessories for GourmeXpress - Cleaning

Code	Spare Part Description	Picture
0S2882	S02 Electrolux Professional Degreaser is a highly concentrated detergent specifically conceived for cleaning and removing grease from appliances, surfaces and floors. Recommended Dose: ready-to-use product. The bottle contains 750 ml.	
0D7015	Plate cleaning brush Suitable for high temperatures, removes solid residues and crumbs	
0S1779	Microfibre cloth for cleaning stainless steel surfaces set of 20pcs	
095782	Multipurpose brush Universal multipurpose brush with hard bristles Dimensions (mm) 100x100x260	
0S2985	Heat protection gloves Contact resistant up to 350 °C for a short period Size 10 EN 388, EN 407, EN 420	

Accessories for GourmeXpress - Cooking

Code	Spare Part Description	Picture
0CBCB8	Aluminum baking shovel with handle. Suitable for collecting food from the oven. Lightweight and practical to use Dim 410x300x60mm	
0CBCB7	Teflon-coated mesh tray. Non-stick surface. Perforated base to maximize the bottom browning of the food. Ideal for cooking pizza, focaccia and sandwiches. Dim 300x250x40mm	
0CBEB4	Teflon-coated tray. Non-stick surface. The rigid sides prevent food from spilling over the edges. The solid bottom prevents residue from falling into the oven. Ideal for cooking chicken wings and other appetizers. Dimensions: 300 x 250 x 40 mm.	
0CBCB9	Barcode scanner gun Allows reading and sending the recipe to the GourmeXpress oven. Dim 110x190x90mm	

Grids

Code	Spare Part Description	Picture
0CA629	AISI 304 steel rod grill for monobloc modular cooking 900 Suitable for direct cooking of food with AISI 304 steel rod grill For equipment 400-800mm wide WxDxH (mm) 324x635x57.5 Compatible with: 900XP and EVO900 1/2 module Quantity: 1 pc	
0CA627	AISI 304 steel rod grill for monobloc modular cooking 900 Suitable for direct cooking of food with AISI 304 steel rod grill For equipment 400-800mm wide WxDxH (mm) 360x635x57.5 Compatible with: 900XP and EVO900 1 module Quantity : set 2 pcs	
0CA631	AISI 304 steel rod grill for monobloc modular cooking 700 Suitable for direct cooking of food with AISI 304 steel rod grill For equipment 400-800mm wide WxDxH (mm) 324x473x57.5 Compatible with: 700XP and EVO700 1/2 module Quantity: 1 pc	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

Grids

Code	Spare Part Description	Picture
0CBAP7	AISI 304 steel rod grill for monobloc modular cooking 700 Suitable for direct cooking of food with AISI 304 steel rod grill For equipment 400-800mm wide WxDxH (mm) 360x473x57.5 Compatible with: 700XP and EVO700 1 module Quantity : set 2 pcs	
0CA634	Greedy grill in AISI 304 steel for modular top and monobloc cooking 700 Suitable for direct cooking of food with greedy grill in AISI 304 steel For 400 wide equipment Including scraper 0CA637 WxDxH (mm) 324x484.5x50 Compatible with: 700XP; EVO700	
0CA632	Greedy grill in AISI 304 steel for modular monobloc cooking 700 Suitable for direct cooking of food with greedy grill in AISI 304 steel For 800 wide equipment (contains 2 pieces for the entire surface of the grill) Including scraper 0CA637 WxDxH (mm) 361x484.5x50 Compatible with: 700XP; EVO700	
0CA630	Greedy grill in AISI 304 steel for modular monobloc cooking 900 Suitable for direct cooking of food with greedy grill in AISI 304 steel For 400 wide equipment Including scraper 0CA637 WxDxH (mm) 324x645.5x50 Compatible with: 900XP; EVO900	
0CA628	Greedy grill in AISI 304 steel for modular monobloc cooking 900 Suitable for direct cooking of food with greedy grill in AISI 304 steel For 800 wide equipment (contains 2 pieces for the entire surface of the grill) Including scraper 0CA637 WxDxH (mm) 361x645.5x50 Compatible with: 900XP; EVO900	
0C6878	Greedy grill in AISI 304 steel for modular cooking top 700 Suitable for direct cooking of food with greedy grill in AISI 304 steel WxDxH (mm) 335x533x50 Compatible with: 700XP; EVO700; N700; ELCO700; PR700	
0C6876	Greedy grill in AISI 304 steel for modular monobloc cooking 900 Suitable for direct cooking of food with greedy grill in AISI 304 steel WxDxH (mm) 363x656x50 Compatible with: N900; ELCO900	
0C6875	Greedy grill in AISI 304 steel for modular monobloc cooking 700 Suitable for direct cooking of food with greedy grill in AISI 304 steel WxDxH (mm) 364x491x50 Compatible with: N700; ELCO700	
0C9059	Cast iron grill for modular cooking top 700 Suitable for direct cooking of food with cast iron grill WxDxH (mm) 337x529x50 Compatible with: N700; ELCO700 Code Qt. Description 002272 2 Handgrip protection; øe=45mm øi=8,5mm , 053705 2 Dummy screw , 057728 2 Handgrip; ø max=28,5mm; hole=m8 , 0C8907 1 Grid-iron	

Accessories for Grills

Code	Spare Part Description	Picture
0C9150	AISI 304 steel scraper Suitable for cleaning the HP gas grill WxDxH (mm) 84x454x62 Compatible with: 900XP; EVO900 700XP; EVO700	
0CA819	AISI 304 steel scraper Suitable for cleaning the HP electric grill WxDxH (mm) 80x424x71 Compatible with: 900XP; EVO900 700XP; EVO700	
0CA637	AISI 304 steel scraper Suitable for cleaning greedy grills cod. 0CA628, 0CA630, 0CA632 Long handle grip WxDxH (mm) 110x490x30 Compatible with: universal	
0C5156	AISI 304 steel scraper Suitable for cleaning greedy grills cod. 0C6875 and 0C6876 Long handle grip WxDxH (mm) 88x440x40 Compatible with: N700; ELCO700 N900; ELCO900	
0C9974	AISI 304 steel scraper Suitable for cleaning the cast iron grill WxDxH (mm) 110x490x30 Compatible with: universal	
050859	Lava stone for grill Packaging: 5 kg pack	

Accessories for Induction

Code	Spare Part Description	Picture
0S2059	Stainless steel induction pot With stainless steel handle Ø 200mm. ØxH (mm) Ø200x350	
0S2060	Non-stick aluminum induction pan with stainless steel handle Ø 240mm. ØxH (mm) Ø240x400	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

Accessories for Induction

Code	Spare Part Description	Picture
0S2061	Non-stick aluminum induction pan with stainless steel handle Ø 280mm. ØxH (mm) Ø280x450	
0S2062	WOK pan for induction in stainless steel With stainless steel handle Ø 350mm. ØxH (mm) Ø350x100	
0CA638	WOK pan for induction in stainless steel With stainless steel handle Ø 360mm (PNC 911587) ØxH (mm) Ø360x100	
0T2024	Mild steel induction WOK pan with wooden handle Ø 360mm. ØxH (mm) Ø360x105	
0S3308	Stainless steel induction wok pan With stainless steel handle Ø 360mm. ØxH (mm) Ø360x100	
0S3309	Stainless steel non-stick induction wok pan With stainless steel handle Ø 360mm. ØxH (mm) Ø360x100	
0CA639	Lid for stainless steel WOK pot Ø 360mm. ØxH (mm) Ø360x40	
0S2064	Non-stick ribbed plate Suitable for direct cooking of food on induction hobs max cooking surface 260x330 WxDxH (mm) 465x275x50	
0S1606	Scraper for glass ceramic hobs WxDxH (mm) 45x10x135	
0S1071	Stainless steel blades For scraper 0S1606 - Set 5pcs WxDxH (mm) 42x1x22	
0S3025	Scraper blades code 0S3026 - Set of 10pcs	



Accessories for Induction

Code	Spare Part Description	Picture
0S3026	Scraper for smooth surfaces	

Accessories for Modular Cooking Ovens

Code	Spare Part Description	Picture
025020	GN 2/1 chromed grill for ovens Suitable for modular cooking ovens with splashback on the short side and anti-tipping block WxDxH (mm) 530x650x10 Compatible with: 900XP; EVO900; N900; ELCO900; HD900; 700XP; EVO700; N700; ELCO700; MD700; PR700; B700	
0C1722	Chromed grill for large ovens Suitable for large ovens, modular cooking with splashback on the long side and anti-tipping block WxDxH (mm) 972x687x70 Compatible with: 900XP; N900	
0C7336	GN 2/1 chromed grill for ovens Suitable for fan ovens. modular cooking with splashback on the long side and anti-tipping block WxDxH (mm) 660x512x37.5 Compatible with: 900XP; EVO900; N900; ELCO900; HD900; 700XP; EVO700; N700; ELCO700; MD700; PR700; B700	

Accessories for Pasta Cookers

Code	Spare Part Description	Picture
004874	Stainless steel basket for pasta cooker Whole basket with 2 handles WxDxH (mm) 230x360x240 Compatible with: 700XP; EVO700; N700; ELCO700; PR700	
0CBAGM	Stainless steel basket for pasta cooker, 1/2 basket with 2 handles WxDxH (mm) 220x170x240 Compatible with: 700XP; EVO700; N700; ELCO700; PR700	



Accessories for Pasta Cookers

Code	Spare Part Description	Picture
004873	Stainless steel basket for pasta cooker 1/2 longitudinal basket with handle on the short side WxDxH (mm) 105x350x265 Compatible with: 700XP; EVO700; N700; ELCO700; PR700	
0CB360	Stainless steel baskets for pasta cooker kit* Pair of 1/4 right and left baskets with handle WxDxH (mm) 105x160x240 Compatible with: 700XP; EVO700; N700; ELCO700; PR700 * Basket support grid cod. 0CB362	
0CB361	Stainless steel baskets for pasta cooker kit* Pair of 1/6 right and left baskets with handle WxDxH (mm) 105x105x240 Compatible with: 700XP; EVO700; N700; ELCO700; PR700 * Basket support grid cod. 0CB362	
056919	Stainless steel basket for pasta cooker 1/3 basket for "rapid system" pasta cooker with handle on the short side WxDxH (mm) 150x275x180 Compatible with: N700; ELCO700; PR700; MD700	
006886	Stainless steel basket for pasta cooker* Basket for pasta cooker with automatic lifter WxDxH (mm) 115x160x123 Compatible with: 700XP; EVO700; N700; ELCO700 * Basket support grid code. 0CA625	
0C9539	Stainless steel basket for pasta cooker* Basket for pasta cooker with automatic lifter WxDxH (mm) 105x320x123 Compatible with: 700XP; EVO700; N700; ELCO700 * Basket support grid code. 0CA625	
0CA806	Stainless steel baskets for pasta cooker kit Pair of 1/6 right and left baskets with handle WxDxH (mm) 130x130x215 Compatible with: 900XP; EVO900; N900; ELCO900 * Basket support grid code. 0C1902	



Accessories for Pasta Cookers

Code	Spare Part Description	Picture
0C1901	Stainless steel basket for pasta cooker 1/3 longitudinal basket with handle on the short side WxDxH (mm) 135x310x215 Compatible with: 900XP; EVO900; N900; ELCO900 * Basket support grid code. 0C1902	
0C1341	Stainless steel basket for pasta cooker Whole basket with 2 handles WxDxH (mm) 276x485x210 Compatible with: 900XP; EVO900; N900; ELCO900; HD900; PR700	
0C1339	Stainless steel basket for pasta cooker 1/2 basket with 2 handles (PNC 910513) WxDxH (mm) 275x230x210 Compatible with: 900XP; EVO900; N900; ELCO900; HD900; PR700	
0C1340	Stainless steel basket for pasta cooker 1/3 basket with 2 handles WxDxH (mm) 275x150x210 Compatible with: 900XP; EVO900; N900; ELCO900; HD900; PR700	
005809	Stainless steel basket for pasta cooker Whole basket with 2 handles WxDxH (mm) 290x290x200 Compatible with: 600	
0C6290	Stainless steel baskets for pasta cookers Pair of 1/2 baskets with two handles WxDxH (mm) 145x290x200 Compatible with: 600	
0C6291	Stainless steel baskets for pasta cooker kit 1/4 right and left baskets with handle (4 pieces) WxDxH (mm) 140x140x200 Compatible with: 600	



Accessories for Pasta Cookers

Code	Spare Part Description	Picture
057728	Athermal black bakelite handle Dimensions (mm) Ø 28.5 x 90mm, M8 connection	
056917	Stainless steel basket for pasta cooker 1/3 round basket with handle Ø 170mm Ø x H (mm) 170x180 Compatible with: 900XP; EVO900; ELCO900; EVO700; ELCO700; HD900; MD700; N700; N900 PR700	
056918	Stainless steel basket for pasta cooker 1/6 round basket with handle Ø 135mm Ø x H (mm) 135x180 Compatible with: 900XP; EVO900; ELCO900; EVO700; ELCO700; HD900; MD700; N700; N900 PR700	
0C1338	Universal athermal handle in black bakelite WxDxH (mm) 125x29x18 (L=125)	
0CA751	Athermal handle kit in black polyamide 66 (30%) - knob with insert WxDxH (mm) 132x37x17 (L=132)	
0CBAP2	Basket support for pasta cooker line 700 to be used with basket 004873 P x H (mm) 290x85	
0C6831	Stainless steel support for round baskets Suitable for 6 1/6 round baskets (056918) to be used to fix the baskets during cooking WxDxH (mm) 330x535x10 Compatible with: 900XP; EVO900; N900; ELCO900	



Accessories for Pasta Cookers

Code	Spare Part Description	Picture
0CB362	Stainless steel bottom grill Support for pasta cooker baskets H 240 mm WxDxH (mm) 230x350x60 Compatible with: 700XP; EVO700; N700; ELCO700; PR700	
004876	Stainless steel bottom grill Support for pasta cooker baskets H 265 mm WxDxH (mm) 230x350x30 Compatible with: 700XP; EVO700; N700; ELCO700; PR700	
056922	Stainless steel bottom grill Support for pasta cooker baskets WxDxH (mm) 290x500x115 Compatible with: 900XP; EVO900; N900; ELCO900; HD900; PR700 H 180MM	
0C1902	Stainless steel bottom grill Support for pasta cooker baskets WxDxH (mm) 295x505x80 Compatible with: 900XP; EVO900; N900; ELCO900 H 215 MM	
0CA788	Stainless steel lid for pasta cooker WxDxH (mm) 250x450x50 Compatible with: 700XP; EVO700; N700; ELCO700; PR700	
0CA789	Stainless steel lid for pasta cooker WxDxH (mm) 300x700x100 Compatible with: 900XP; EVO900; N900; ELCO900	
0CBCMT	The kit contains: 2 pieces code 0C1901 1/3 1 piece code 0C1340 1/3 with 2 handles	

Accessories for Speedelight - Cleaning

Code	Spare Part Description	Picture
0S2292	C41 HI-TEMP RAPID DEGREASER. Suitable for cleaning plates and grills with high temperature surfaces (max 175°C). Pack of 6 1l bottles (includes 1 spray bottle code 0S2331)	



Accessories for Speedelight - Cleaning

Code	Spare Part Description	Picture
0S2882	S02 Electrolux Professional Degreaser is a highly concentrated detergent specifically conceived for cleaning and removing grease from appliances, surfaces and floors. Recommended Dose: ready-to-use product. The bottle contains 750 ml.	
0S2331	Sprayer with extension for C41 HI-TEMP RAPID DEGREASER Description: Sprayer with extension for C41 RAPID GREASE Code Qt. Description OS1800 1 Pump, OS2058 1 Extension tube; cm.21	
0D4024	Silicone protection mat for glass-ceramic plate. Indicated to protect the glass during cleaning from the upper plate (to be used only during maintenance) WxDxH (mm) 240x240x5	
0D7015	Plate cleaning brush Suitable for high temperatures, removes solid residues and crumbs	

Accessories for Speedelight - Cooking

Code	Spare Part Description	Picture
0CBAKJ	NSF food grade non-stick paper for Speedelight Extraordinary cooking results thanks to its non-stick properties which maintain the freshness and fragrance of foods. Keeps the plate clean by eliminating food residues and grease. Reusable several times and dishwasher safe. Dimensions (mm) 215x400 Quantity: packs of 24 sheets	
0CB905	Teflon-coated tray for Speedelight Flat PTFE tray resistant up to 260°C WxDxH (mm) 272x272x9.5	



Accessories for Speedelight - Cooking

Code	Spare Part Description	Picture
0C9500	Corrugated plate in Teflon-coated aluminum Suitable for machines designed for the insertion of corrugation WxDxH (mm) 213x203x4	
0D4063	Silicone Griddle Spatula Versatile for multiple uses	
0CB904	Slim metal cleaning brush For non-ferrous metals and delicate surfaces WxDxH (mm) 215x65x21.5	
0CB903	Slim brush for cleaning delicate surfaces Without abrasion, also suitable for electrical parts WxDxH (mm) 215x65x21.5	
0CA736	Removable Teflon flat plate. To facilitate cleaning and maintenance	
0CBB4H	Sandwich bags suitable for Speedelight and all the other Sandwich cooking plates/surfaces: 500pcs	

Chemical Products

Code	Spare Part Description	Picture
0S2975	Spray lubricant for the food sector; it is particularly suitable for food preparation equipment such as slicers, meat mincers... It is also applicable on aluminium, stainless steel and all plastic materials. If in contact, the product does not pose any risk to health, it is non-toxic and harmless to the skin. 1 can of 300ml	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

Chemical Products

Code	Spare Part Description	Picture
0D8030	Food grease suitable for accidental contact with food and for greasing mechanical devices (bearings, reducers, gears); water resistant 1 pack of 400 g	
0S2308	Sparkle metal pickler Foaming product that allows you to instantly pickle, restore, clean and polish all metal surfaces, making them immediately shiny. It does not stain and prevents corrosion and oxidation	
0S2277	Food grease for conical seal taps 1 kg	
0S1145	Food grease for conical seal taps, 2 x 45 g tubes Code Qt. Description 0S1144 2 Grease; klubersynth uh1; 45 g	
0S2118	Grease for taps with o-rings 100 g NSFH1 certification	
0S0327	High temperature lubricating grease suitable for bearings 1 pack. from 1 kg	
003363	Spray grease for high temperatures 1 pack. from 500 g	



Chemical Products

Code	Spare Part Description	Picture
0S2819	Grease for gas taps 1 pack. from 750 g	
0C9506	Aluminum anti-seize lubricating grease 500 g	
005256	Conductive silicone compound for FCV ovens applicable for boiler probes 1 tube of 100 g	
0S2275	Food fat for Speedelight 1 tube of 50 g	
0S2826	Spray grease for Speedelight. NSF certified for food equipment. Recommended to lubricate the top plate release mechanism once a year or after 66000 cooking cycles. Operating temperature from - 30°C to + 1100°C 1 500ml can	
0W4112 96011019	Grease Molykote 44 Medium High temperature lubricating grease Ideal for bearings and supports on steam ironers 1 pack. from 1kg	
059611	Single-component adhesive sealant for covering joints of stainless steel appliances, gray color pack. of 310ml	



Chemical Products

Code	Spare Part Description	Picture
0CB101	Red silicone adhesive sealant Max temperature 300° C pack. of 310ml	
0CB051	Red silicone adhesive sealant for Speedelight Max temperature 300° C pack. of 300ml	
006083	Adhesive sealant for oven gaskets pack. of 90ml	
0S2680	Adhesion promoter Sika Aktivator-205 flac. 250ml	
0D1250	Transparent silicone adhesive sealant	
0C0074	PACTAN HT 6076 polyurethane anthracite adhesive sealant	
0D6223	Adhesive sealant for glass-ceramic hobs NOVASIL S 76 Ideal for thermaline induction hobs	



Chemical Products

Code	Spare Part Description	Picture
006101	Corrosion inhibitor kit also used for indirect gas cookware 10 sachets of "trisodium phosphate" (5 pairs) Code Qt. Description 0C1876 5 Water additive against corrosion;2 bag	
0S0939	ISO46 Hydraulic Oil 1 pack. from 1l	
0S0940	ISO46 Hydraulic Oil 1 pack. of 5l	
0S2607	ISO32 Hydraulic Oil 1 pack. from 1l	
0S0941	ISO32 Hydraulic Oil 1 pack. of 5l	
0K4525	STABURAGS NBU 30 PTM is an assembly grease containing a solid lubricant composed of mineral oil and barium complex soap. The grease is water resistant and offers reliable protection against tribocorrosion (fretting corrosion) and resists water and steam up to 160°C. It facilitates the assembly of springs, bolts, flange and all those coupled metal-to-metal components, it protects the assembled components from oxidation and corrosion throughout their entire use even in the presence of high static friction loads. It also facilitates disassembly even after very long periods.	



Chemical Products

Code	Spare Part Description	Picture
0SECF8	Electrode cleaning solution 500ml bottle	
005866	Adhesive sealant for fixing dishwasher modules, 310ml pack	
0S3181	Hydraulic Oil ISO100 GREENSTAR HS 100 1 pack of 5l	
0KC414	BIO granules for pot washers Granuldisk ideal for pot washers with biodegradable granule washing system 1 pack of 10Kg	

Detergency

Code	Spare Part Description	Picture
0S3023	Detergent tablets for fryers particularly suitable for cleaning the tanks, baskets and steel surfaces of the fryer. 1 pack of 25 tablets	
0S2980	TOPMATIC HYDRO liquid dishwasher detergent particularly suitable for hard and very hard water 1 pack. of 4 5l cans	



Detergency

Code	Spare Part Description	Picture
0SZ895	SUPER TRUMP liquid dishwasher detergent particularly suitable for soft and medium hard water, recommended for dishwashing systems with demineralizers 1 pack. of 4 5l cans	
0S2389	DIP-IT PLUS granular detergent for dishwashers and linen. Whitening action for dishes and bleaching action for fabrics. Also suitable for non-ferrous surfaces and soft metals. 1 pack of 6 2.4 kg cans	
0SZ896	Universal neutral pH rinse aid CLEAR DRY CLASSIC particularly suitable for hard water 1 pack. of 2 5l canisters	
0S0845	Universal neutral pH rinse aid CLEAR DRY N particularly suitable for all types of water hardness 1 pack. of 2 5l canisters	
0S1615	Acid-based rinse aid CLEAR DRY HD IT particularly suitable for very hard water 1 pack. of 2 5l canisters	
0S0842	Neutral liquid detergent TABOR LIMONE product for manual dishwashing 1 pack. of 4 5l cans	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

Detergency

Code	Spare Part Description	Picture
0S2504	C50 Sanitizing descaler, product suitable for ice makers and refrigerated dispensers 1 pack. of 4 bottles of 1l	
0S1764	Bactericidal disinfectant tablets Suitable for cleaning and sanitization maintenance. Universal for all dishwashers. Ideal for disinfecting work surfaces, floors, walls, equipment and machinery. Pack of 6pcs x 1kg. Sellable only in Italy.	
0S2712	Ready-to-use disinfectant detergent SANIALC ULTRA. It ensures rapid disinfectant action on all hard surfaces that come into contact with food, such as preparation tables, cutting boards, slicers, etc. without the need for rinsing. Contains no residue. 1 pack of 6 bottles of 750ml	
0S1779	Microfibre cloth for cleaning stainless steel surfaces set of 20pcs	
0S0841	Rapid degreaser GREASE CUTTER PLUS product suitable for ovens, cooking plates and chrome fry tops 1 pack. of 4 5l cans	
0S2711	Ready-to-use sanitizing disinfectant degreaser SANI ACTIVE Also ideal for surfaces in contact with food 1 pack. of 6 bottles of 750ml	
0S2797	VITRO CARE glass ceramic cleaner Removes food, grease and water residues on induction and glass ceramic hobs. Concentrated, just a few drops 1 pack. of 12 bottles of 300ml Code Qt. Description 0S2794 12 Detergent; 300ml	



Detergency

Code	Spare Part Description	Picture
0S2384	REGAIN alkaline degreasing detergent Suitable for automatic washing of extraction systems 1 pack. of 2 5l canisters	
0KZL56	Granuldisk pot washer granules	
0S0994	Universal ammonia-based cleaner SPRAY CLEANER for metal surfaces, ceramic tiles, glass 1 pack. of 12 cans of 500ml	
0S0995	SS POLISH & CLEANER polishing detergent for stainless steel and other metal surfaces 1 pack. of 12 cans of 500ml	
0S0060	Clean Spray detergent for removing grease, oil, dirt from adhesive, silicone, wax... 1 can of 500ml	
0S2399	Granulate for cutlery dryer 1 pack. from 9 kg	



Detergency

Code	Spare Part Description	Picture
0S2292	C41 HI-TEMP RAPID DEGREASER. Suitable for cleaning plates and grills with high temperature surfaces (max 175°C). Pack of 6 1l bottles (includes 1 spray bottle code 0S2331)	

Electrolux Professional Descaling

Code	Spare Part Description	Picture
0S2362	C30 Multipurpose descaler ► effectively removes encrustations and limescale deposits from washing equipment and boilers of any professional equipment ► regular use of C30 Multipurpose descaler keeps performance unchanged over time, slowing down the natural wear of the equipment itself. ► thanks to its low foaming power, C30 Multipurpose descaler is particularly suitable for cleaning boilers and equipment with an automatic descaling device. ► its neutral fragrance makes use more pleasant. Packaging: 1 pack. with 2 5lt canisters	

Electrolux Professional Detergents for Cooking Plates

Code	Spare Part Description	Picture
0S2292	C41 HI-TEMP RAPID DEGREASER. Suitable for cleaning plates and grills with high temperature surfaces (max 175°C). Pack of 6 1l bottles (includes 1 spray bottle code 0S2331)	
0S2331	Sprayer with extension for C41 HI-TEMP RAPID DEGREASER Description: Sprayer with extension for C41 RAPID GREASE Code Qt. Description 0S1800 1 Pump, 0S2058 1 Extension tube; cm.21	

Electrolux Professional Detergents for Coffee Machines

Code	Spare Part Description	Picture
0SPO27	U01 Cleaning Tablets for Espresso Machine 120Pcs	
0SPO28	U02 Cleaning Tablets for Standard Espresso Coffee Machines 100Pcs	
0SPO29	U03 Milk Frother Detergent 1Lt	

Electrolux Professional Detergents for Dishwashers

Code	Spare Part Description	Picture
0S2092	Professional dishwasher detergent C11 Detergent for dishwashers ▶ ideal for any type of dishware such as ceramics, porcelain, glass, crystal and metal ▶ suitable for removing caffeine and theine deposits from cups and teapots ▶ the delicate fragrance reduces the unpleasant odor sometimes present in dishwashers ▶ particularly suitable for restaurants that prepare fish-based dishes ▶ suitable for hard and medium hard water Packaging: 1 pack. with two 5lt canisters	
0S2281	Professional dishwasher detergent C11 Detergent for dishwashers ▶ ideal for any type of dishware such as ceramics, porcelain, glass, crystal and metal ▶ suitable for removing caffeine and theine deposits from cups and teapots ▶ the delicate fragrance reduces the unpleasant odor sometimes present in dishwashers ▶ particularly suitable for restaurants that prepare fish-based dishes ▶ suitable for hard and medium hard water Packaging: 1 20lt can	



Electrolux Professional Detergents for Dishwashers

Code	Spare Part Description	Picture
0S2093	Professional dishwasher detergent ECO C13 ECO Detergent for dishwashers ▶ ideal for any type of dishware such as ceramics, porcelain, glass, crystal and metal ▶ the special "Eco-Formula" without phosphate, EDTA and NTA content guarantees a product with low environmental impact ▶ easily eliminates dried food residues and any type of dirt ▶ particularly suitable for fresh water and suitable for systems with osmosis and demineralizers Packaging: 1 pack. with two 5lt canisters	
0S2094	Professional rinse aid for dishwashers C12 Rinse aid for dishwashers ▶ rinse aid additive for rinsing in the dishwasher ▶ guarantees shiny and dry dishes ▶ ideal for ceramics, porcelain, glass and crystal ▶ specific formula for hard water ▶ pH: 2 - 2.5 Packaging: 1 pack. with two 5lt canisters	

Electrolux Professional Detergents for Equipment and Surfaces

Code	Spare Part Description	Picture
0S2881	S01 Stainless Steel Surface Polisher ▶ Ideal for polishing any stainless steel surface, ensuring a flawless finish ▶ Effective up to a maximum temperature of 50°C ▶ Complete with spray bottle Pack of 6 x 750 ml bottles	
0S2883	S03 Alcohol Base Detergent ▶ Specific formula for cleaning and sanitising all surfaces such as: worktops, sinks, equipment components and kitchen utensils ▶ Effective up to a maximum temperature of 50°C ▶ Complete with spray bottle Pack of 6 x 750 ml bottles	
0S2884	S04 Glasses & Hard Surfaces Cleaner ▶ Specific formula for cleaning induction hobs, glass ceramic, marble, and any glass surface. ▶ Effective up to a maximum temperature of 50°C. ▶ Complete with spray bottle. Pack of 6 x 750 ml bottles.	



Electrolux Professional Detergents for Equipment and Surfaces

Code	Spare Part Description	Picture
0S3257	S05 Multipurpose Degreaser ▶ Multipurpose degreaser developed for cleaning all surfaces ▶ Also ideal for use as a pre-treatment ▶ Effective up to a maximum temperature of 50°C ▶ Complete with spray bottle Pack of 6 x 750 ml bottles	

Electrolux Professional Detergents for Ovens, SpeedDelight and GourmeXpress

Code	Spare Part Description	Picture
0S2882	S02 Electrolux Professional Degreaser is a highly concentrated detergent specifically conceived for cleaning and removing grease from appliances, surfaces and floors. Recommended Dose: ready-to-use product. The bottle contains 750 ml.	


Electrolux Professional Liquid Detergents for Ovens

Code	Spare Part Description	Picture
0S2282	C20 Extra Strong Detergent for ovens detergent for ovens with automatic washing system. Packaging: 1 pack of 2 5L cans	
0S2283	C21 Extra Strong Rinse aid for ovens rinse aid for ovens with automatic washing system. Packaging: 1 pack of 2 5L cans	

Electrolux Professional Powder Detergents for Ovens

Code	Spare Part Description	Picture
0S2394	C25 Rinse & Descale tab 2in1 rinse aid and descaler in disposable tablets for Skyline ovens Professional 2in1 rinse aid and descaler in disposable tablets for new generation ovens with automatic washing system. Suitable for all types of water. Packaging: 1 drum of 50 30g tablets. each	
0S2395	C22 Cleaning Tab Disposable detergent tablets for SkyLine ovens Professional detergent for new generation ovens with automatic washing system. Suitable for all types of water. Packaging: 1 drum of 100 65g tablets. each	

Baskets for Pot Washers

Code	Spare Part Description	Picture
0E3564	Stainless steel basket for pot washer WxDxH (mm) 700x630x590 Compatible with: pot washer	
0E3563	Stainless steel basket for pot washer WxDxH (mm) 1300x630x590 Compatible with: pot washer	
049664	Stainless steel basket for pot washer WxDxH (mm) 688x716x100 Compatible with: hood and pot washer	
049692	Set of 4 wheels for pot washer basket Description: Ø 40 x 18 mm Compatible with: 049664, 0L3583	



Baskets for Pot Washers



Code	Spare Part Description	Picture
0L3583	Reinforced stainless steel basket for pot washer WxDxH (mm) 688x716x100 Compatible with: pot washer	
049709	Stainless steel basket for pot washer WxDxH (mm) 1351x716x100 Compatible with: pot washer	
0L3582	Reinforced stainless steel basket for pot washer WxDxH (mm) 1351x716x100 Compatible with: pot washer	
075690	Stainless steel grid for basins and trays WxDxH (mm) 500x500x110 Compatible with: for all pot washer baskets	
0L2014	Stainless steel wire basket for pizza plates, trays and small utensils; WxDxH (mm) 535x550x103 Compatible with: front opening	
0L2441	Stainless steel wire basket for small tools WxDxH (mm) 535x550x103 Compatible with: front opening	

Accessories for Baskets

Code	Spare Part Description	Picture
048892	Green separator for 16 glasses max Ø 100 mm Compatible with: blue basket code. 048796	



Accessories for Baskets

Code	Spare Part Description	Picture
0S0572	Green separator for 16 glasses max Ø 100 mm Pack of: Set of 15 pieces Compatible with: blue basket cod. 048796	
048951	Green separator with tilter for 16 glasses max Ø 100mm with inclined bottom Compatible with: blue basket cod. 048796	
0S0963	Green separator with tilter for 16 glasses max Ø 100mm with inclined bottom Pack of: Set of 8 pieces Compatible with: blue basket code. 048796 Code Qt. Description 048951 8 Green insert for 16 glasses; dia.100mm	
048953	Blue separator for 25 glasses max Ø 80mm Compatible with: blue basket cod. 048796	
0S0573	Blue separator for 25 glasses max Ø 80mm Pack of: Set of 15 pieces Compatible with: blue basket cod. 048796	
048952	Blue separator with tilter for 25 glasses max Ø 80mm with inclined bottom Compatible with: blue basket cod. 048796	



Accessories for Baskets

Code	Spare Part Description	Picture
0S0964	Blue separator with tilter for 25 glasses max Ø 80mm with inclined bottom Pack of: Set of 8 pieces Compatible with: blue basket code. 048796 Code Qt. Description 048952 8 Blu insert for 25 glasses; dia.80mm	
048955	Yellow separator for 36 glasses max Ø 70mm Compatible with: blue basket code. 048796	
0S0574	Yellow separator for 36 glasses max Ø 70mm Pack of: Set of 15 pieces Compatible with: blue basket code. 048796	
048954	Yellow separator with tilter for 36 glasses max Ø 70mm with inclined bottom Compatible with: blue basket cod. 048796	
048948	Brown separator for 49 glasses max Ø 60mm Compatible with: blue basket code. 048796	
0S0575	Brown separator for 49 glasses max Ø 60mm Pack of: Set of 15 pieces Compatible with: blue basket cod. 048796	
048949	Red separator for 64 glasses max Ø 50mm Compatible with: blue basket code. 048796	



Accessories for Baskets

Code	Spare Part Description	Picture
0S0576	Red separator for 64 glasses max Ø 50mm Pack of: Set of 15 pieces Compatible with: blue basket cod. 048796	
048950	Blue ring indicated to increase the height of the glass basket by 50mm 048796 WxDxH (mm) 500x500x60 Compatible with: blue basket cod. 048796	
0S0571	Blue ring suitable for increasing the height of the glass basket by 50mm 048796 Pack of: Set of 12 pieces Compatible with: blue basket cod. 048796	
048946	Wire insert for plates suitable for holding 16 dinner plates or 16 soup plates on a universal blue basket cod. 048796 Compatible with: blue basket code. 048796	
048947	Wire insert for pizza plates suitable for holding 12 pizza plates Ø max 320mm on universal blue basket cod. 048796 Compatible with: blue basket code. 048796	
069399	Wire insert for cups suitable for tilting cups or cups on blue basket 048796 Compatible with: blue basket cod. 048796	
0S0860	Cover grid in AISI 304 steel suitable for blocking small or light objects on blue basket 048796 WxDxH (mm) 458x458x10 Compatible with: blue basket cod. 048796	
0L4546	Stainless steel wire insert for 6 trays suitable for flattened symmetrically shaped tray basket WxDxH (mm) 457x457x113 Compatible with: basket cod. 0L4545	
0S2528	Stainless steel wire insert for 10 trays suitable for flat open-sided tray basket WxDxH (mm) 452x452x100 Compatible with: basket cod. 0S2583	



Accessories for Baskets

Code	Spare Part Description	Picture
048959	Stainless steel wire insert for 5 insulated trays suitable for insulated tray basket with flattened open side LxWxH (mm) 452x452x193 Compatible with: basket cod. 048962	
0S3140	Basket trolley 500x500 Polyethylene base Stainless steel pivoting wheels	
0S3141	Basket trolley 500x500 Stainless steel base Stainless steel pivoting wheels Maximum load 100kg	
0S3142	Basket trolley 500x500 Stainless steel base with handle Stainless steel pivoting wheels Also ideal for transporting kitchen utensils Maximum load 150kg	

Baskets for HeroDry

Code	Spare Part Description	Picture
0L5273	Basket For Herodry	
0L5274	Cup holder for HeroDry basket	

Electrolux Professional Detergents for Dishwashers

Code	Spare Part Description	Picture
0S2092	Professional dishwasher detergent C11 Detergent for dishwashers ▶ ideal for any type of dishware such as ceramics, porcelain, glass, crystal and metal ▶ suitable for removing caffeine and theine deposits from cups and teapots ▶ the delicate fragrance reduces the unpleasant odor sometimes present in dishwashers ▶ particularly suitable for restaurants that prepare fish-based dishes ▶ suitable for hard and medium hard water Packaging: 1 pack. with two 5lt canisters	
0S2281	Professional dishwasher detergent C11 Detergent for dishwashers ▶ ideal for any type of dishware such as ceramics, porcelain, glass, crystal and metal ▶ suitable for removing caffeine and theine deposits from cups and teapots ▶ the delicate fragrance reduces the unpleasant odor sometimes present in dishwashers ▶ particularly suitable for restaurants that prepare fish-based dishes ▶ suitable for hard and medium hard water Packaging: 1 20lt can	
0S2094	Professional rinse aid for dishwashers C12 Rinse aid for dishwashers ▶ rinse aid additive for rinsing in the dishwasher ▶ guarantees shiny and dry dishes ▶ ideal for ceramics, porcelain, glass and crystal ▶ specific formula for hard water ▶ pH: 2 - 2.5 Packaging: 1 pack. with two 5lt canisters	
0S2093	Professional dishwasher detergent ECO C13 ECO Detergent for dishwashers ▶ ideal for any type of dishware such as ceramics, porcelain, glass, crystal and metal ▶ the special "Eco-Formula" without phosphate, EDTA and NTA content guarantees a product with low environmental impact ▶ easily eliminates dried food residues and any type of dirt ▶ particularly suitable for fresh water and suitable for systems with osmosis and demineralizers Packaging: 1 pack. with two 5lt canisters	
0S2362	C30 Multipurpose descaler ▶ effectively removes encrustations and limescale deposits from washing equipment and boilers of any professional equipment ▶ regular use of C30 Multipurpose descaler keeps performance unchanged over time, slowing down the natural wear of the equipment itself. ▶ thanks to its low foaming power, C30 Multipurpose descaler is particularly suitable for cleaning boilers and equipment with an automatic descaling device. ▶ its neutral fragrance makes use more pleasant. Packaging: 1 pack. with 2 5lt canisters	
0S2904	Professional rinse aid for dishwashers C15 ECO Rinse Aid for Dishwasher ▶ Ideal for all types of dishes: ceramic, porcelain, glass, crystal, metal and plastic ▶ Neutral pH 6.5 - 7 ▶ Removes limescale from dishes, leaving a perfectly shiny surface ▶ Reduces limescale deposits in the machine ▶ Guarantees perfectly clean and dry crockery ▶ Perfect drying results, without further manual steps ▶ Particularly suitable for fresh water and systems with osmosis and demineralizers ▶ Tested in the field by Experts and Customers ▶ Eco-friendly chemical product low environmental impact thanks to the use of surfactants of vegetable origin ▶ Ergonomic packaging consisting of 2 5-litre cans to facilitate use and storage Packaging: 1 pack. with two 5lt canisters	

External Dosing Systems For Dishwashers

Code	Spare Part Description	Picture
0S3027	Peristaltic detergent pump with santoprene hose kit For TWINDOSE 40 (0S0672)	
0S3028	Peristaltic rinse aid pump with sekobril tube kit For TWINDOSE 40 (0S0672)	
0S3085	Light blue PE hose for rinse aid 4x6mm, 100m hank	

Accessories For External Dosing Systems

Code	Spare Part Description	Picture
049356	Bottom filter with ceramic weight connection for Ø 4 mm tube	

Foot Mixer Taps

Code	Spare Part Description	Picture
0S1755	1/2" foot operated tap Single control lever L=160mm hot and cold water Floor or wall installation	
0L1695	1/2" foot operated tap Single control lever L=160mm hot and cold water Floor or wall installation Description: Swivel spout 1/2" L=220mm with riser (code 0S1849)	
0L1696	1/2" foot operated tap Single control lever L=160mm hot and cold water Floor or wall installation Description: Flexible hose 1/2"FF Ø14x1000 mm (for tap 0S1755)	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

Foot Mixer Taps

Code	Spare Part Description	Picture
0S1407	1/2" foot operated tap Single control lever L=160mm hot and cold water Floor or wall installation Description: Swivel spout 1/2" L=180mm without riser	
0S0721	3/8" foot operated tap Double control lever L=165mm hot and cold water Floor installation	
0S1059	3/8" foot tap Double control lever L=165mm hot and cold water Floor installation Description: Flexible hose 3/8"M 1/2"F for spout L=1000 mm	
0S0962	3/8" foot operated tap Double control lever L=255mm with locking lever Under-sink installation	
0S0723	3/8" foot tap Double control lever L=255mm with locking lever Under-sink installation Description: Flexible hose 3/8"M 1/2"F for spout; Ø12x1200 mm 1 piece for tap 0S0962	
0S0722	3/8" foot operated tap Double control lever L=255mm with locking lever Under-sink installation Description: floor support bracket for 0S0962	
0S0351	Foot operated tap 1/2"FL=245mm Double control lever complete with: Spout Ø 18x250mm 1100mm flexible hose Floor installation	
0S0352	Delivery spout Ø18x250 mm connection Ø 1/2"MA=250 mm B=175 mm	
0S0061	3/8" foot tap L=310mm Single control lever complete with: Spout Ø 18x200mm 1100 mm flexible hose Under-shelf installation	



Foot Mixer Taps

Code	Spare Part Description	Picture
032865	Pedal tap 3/8" L=310mm Single control lever complete with: Spout Ø 18x200mm 1100 mm flexible hose Under-shelf installation Description: Mixer block for pedal tap 0S0061	
0S2328	Pedal tap 3/8" L=310mm Single control lever complete with: Spout Ø 18x200mm Flexible hose 1100 mm Under-shelf installation Description: AISI 304 bracket for pedal tap 0S0061	
0S0967	Pedal tap 3/8"FL=330mm Double control lever with locking lever Undersink installation C=3/8"F	
0S3260	Pedal tap 1/2"FL=350mm Double control lever with locking lever Under sink installation C= 1/2"F	
0S0876	MIDIREEL washing group in AISI 304 steel Wall version with automatic rewriter water connection Ø1/2"G EPDM rubber hose 6 m NITO1 shower head I (m)= 6	
0S1263	MIDIREEL washing group in AISI 304 steel Wall version with automatic rewriter water connection Ø1/2"G EPDM rubber hose 6 m NITO1 shower head Description: Regulator nozzle	
0S2487	MIDIREEL washing group in AISI 304 steel Wall-mounted version with automatic rewriter water connection Ø1/2"G EPDM rubber hose 6 m shower head NITO1 Description: EPDM rubber hose for MIDIREel 6m	
0L1300	MIDIREEL washing unit in AISI 304 steel Wall version with automatic rewriter water connection Ø1/2"G EPDM rubber hose 6 m NITO1 shower head Description: EPDM rubber hose for MIDIREel 6m	

Mixer Taps and Shower Groups

Code	Spare Part Description	Picture
0S1244	Single hole clinical lever tap water connection Ø1/2" fixing hole Ø 52mm dispensing spout Ø 20x320 mm	
0S0863	Single hole clinical lever tap water connection Ø1/2"G fixing hole Ø3/4" dispensing spout Ø 25x225 mm	
0S0864	Single hole clinical lever tap water connection Ø1/2"G fixing hole Ø3/4" dispensing spout Ø 25x275 mm	
0S2839	Single hole clinical lever tap with extractable hand shower from 70 to 80cm Ø1/2"G water connection Ø42mm fixing hole 220mm spout	
0S0862	Single hole tap with knobs water connection Ø 1/2"G fixing hole Ø3/4"G spout Ø 25x300 mm	
033125	Two-hole tap with knobs water connection Ø3/4"G center distance 155mm fixing hole Ø3/4"G delivery spout Ø 25x300 mm	



Mixer Taps and Shower Groups

Code	Spare Part Description	Picture
0S1457	Two-hole clinical lever tap water connection Ø3/4"G center distance 155mm fixing hole Ø3/4"G delivery spout 270mm	
0S1472	Wall-mounted double-hole tap with water connection knobs Ø1/2"G center distance 155 mm spout Ø 25x300 mm	
0S1250	Two-hole wall-mounted clinical lever tap with water connection Ø 1/2"G center distance 150mm spout 200mm	
0S2809	Two-hole wall-mounted clinical lever tap with water connection Ø1/2"G 150mm spacing, 300mm spout	
0S1436	Single hole infrared tap water connection Ø1/2" fixing hole Ø 35mm dispensing spout Ø 45x102mm Power supply 220V/6V with external power supply	
0S2511	Single hole infrared tap water connection Ø1/2" fixing hole Ø 35mm dispensing spout Ø 45x102mm Battery powered (4pcs AA LI x1.5V included)	
0S0092	Single hole tap with knobs water connection Ø 1/2"F fixing hole Ø 30-32 mm spout Ø18x300 mm	



Mixer Taps and Shower Groups

Code	Spare Part Description	Picture
0S0096	Two-hole tap with knobs water connection Ø 1/2" M center distance 160 mm fixing hole Ø 22 mm spout Ø18x300 mm	
0S0097	Two-hole tap with knobs water connection Ø 3/4" M center distance 160 mm fixing hole Ø 22 mm spout Ø18x300 mm	
0S2846	Single hole clinical lever tap connection Ø G3/8" F fixing hole Ø 56.5 mm spout spout cast 230 mm	
037616	Single hole clinical lever tap connection Ø 1/2" F fixing hole Ø 32-34 mm spout spout cast 250 mm	
0S0341	Two-hole clinical lever tap connection Ø 3/4" M center distance 155 mm fixing hole Ø 22 mm spout spout 250 mm	
037617	Single hole shower unit with clinical lever tap connection Ø 1/2" M fixing hole Ø 30-32 mm spout spout 250 mm height of flexible hose from the surface h=1265mm	



Mixer Taps and Shower Groups

Code	Spare Part Description	Picture
0S1579	Single hole tap with clinical lever shower group connection Ø 3/4" M spout spout 250 mm	
0S0342	Two-hole shower unit with clinical lever tap connection Ø 3/4" M fixing hole Ø 30-32 mm spout spout 250 mm flexible hose height from the surface h=1265mm	
0S1365	Two-hole tap with clinical lever and shower unit connection Ø 3/4" M connection center distance 155 mm spout spout 250 mm	
0S0956	JOLLY single hole shower mixer with lever tap connection Ø1/2"G fixing hole Ø35-36mm, spout Ø 24x200mm flexible hose height from the surface h=950mm	
0S0347	Black shower head	
069968	Single hole shower group with clinical lever tap Ø3/8"F connection with 8x20 broach knobs, flexible hose height from the surface h=1250mm	



Mixer Taps and Shower Groups

Code	Spare Part Description	Picture
0S0894	MOLLY single-lever shower mixer, connection Ø3/8" FH=400 mm	
0S0895	MOLLY single-lever shower mixer, connection Ø1/2" FH=400 mm	
0S3145	Single hole tap with clinical lever with 100mm riser, water connection Ø1/2"G, fixing hole Ø3/4" spout Ø 25x245 mm	
0S3146	Single-hole clinical lever tap with 100mm riser, water connection Ø1/2"G, fixing hole Ø3/4" spout Ø 25x295 mm	
0S3303	Two-hole shower set with wall-mounted tap, connection Ø 3/4" M, fixing hole G1/2" M, spout with 250 mm outlet, height of flexible hose from the tap h=1000mm	
0S3302	Wall mounted two-hole tap and shower group connection, Ø 3/4" M connection, 145 mm centre distance, 250 mm spout	

Accessories for Water Taps and Shower Groups

Code	Spare Part Description	Picture
0L0699	Gray clinical lever length 220 mm Compatible with: 0S1244, 0S0863, 0S0864, 0S1457	
0S0597	Shower group	
0S1212	Shower group base	
0S2572	Mignon shower group	
0S0348	Hose	
0S0349	Support spring	
0S2990	Top class shower group 0S2990 Shower group with tap H=1200mm	
0S3299	Swivel spout L= 250mm	



Accessories for Water Taps and Shower Groups

Code	Spare Part Description	Picture
0S3300	Swivel spout L= 200mm	
0S3150	Single-hole shower set with knobs and Top Class knob tap, water connection Ø 3/8"GF, spout L=250 mm, flexible hose height h=1250 mm, complete with: - shower set with tap code 0S2990 - single-hole mixer with knobs code 0S3354	

Plastic Baskets 500x250mm

Code	Spare Part Description	Picture
0S1161	Basic basket for cups and glasses for universal use WxDxH (mm) 500x250x80 Compatible with: glasswasher, undercounter, front opening, hood	
0S1163	Glass basket for 14 glasses height. max 100mm Ø max 70mm WxDxH (mm) 500x250x90 Compatible with: glasswasher, undercounter, front opening, hood Code Qt. Description 0S1161 1 Basket; 250x500x80h , 0S1166 1 Separator insert; 14 section	
0L5555	Glass basket for 14 glasses max height 100mm Ø max 70mm WxDxH (mm) 500x250x125 Compatible with: glass washers, undercounter, front opening, hood	
0S1164	Glass basket for 14 glasses height. max 140mm Ø max 70mm WxDxH (mm) 500x250x125 Compatible with: glasswasher, undercounter, front opening, hood Code Qt. Description 0S1161 1 Basket; 250x500x80h , 0S1168 1 Separator insert; 14 section; blu	
0S1165	Saucer basket for 24 saucers WxDxH (mm) 500x250x115 Compatible with: glasswasher, undercounter, front opening, hood Code Qt. Description 0S1161 1 Basket; 250x500x80h , 0S1170 1 Separator insert	



Plastic Baskets 500x250mm

Code	Spare Part Description	Picture
0S1166	Green glass separator suitable for holding up to 14 glasses h max 100mm on basket cod. 0S1161 WxDxH (mm) 500x250x10 Compatible with: basic basket cod. 0S1161	
0S1168	Blue glass separator suitable for holding up to 14 glasses h max 140mm on basket cod. 0S1161 WxDxH (mm) 500x250x45 Compatible with: basic basket cod. 0S1161	
0S1170	Saucer separator suitable for holding up to 24 saucers on basket cod. 0S1161 WxDxH (mm) 500x250x35 Compatible with: basic basket cod. 0S1161	

Plastic Baskets 500x500mm

Code	Spare Part Description	Picture
048891	Green basket for soup plates for 12 soup plates - Ø max 240mm WxDxH (mm) 500x500x105 Compatible with: undertable, front opening, hood, dragged basket	
0L1965	Green basket for soup plates for 12 soup plates - Ø max 240mm Pack of Set of 5 pieces Compatible with: undertable, front opening, hood, dragged basket	
048960	Blue basket for dinner/soup plates for 16 soup plates or 16 dinner plates Ø max 240 mm - with rilsan insert WxDxH (mm) 500x500x105 Compatible with: undertable, front opening, hood, dragged basket	
048795	Yellow basket for dinner plates for 18 dinner plates - Ø max 240mm WxDxH (mm) 500x500x105 Compatible with: undertable, front opening, hood, dragged basket	
0L1964	Yellow basket for dinner plates for 18 dinner plates - Ø max 240mm Pack of 5-piece set Compatible with: undertable, front opening, hood, dragged basket	



Plastic Baskets 500x500mm

Code	Spare Part Description	Picture
068692	Gray basket for plates/soup plates for 18 dinner plates or 16 soup plates Ø max 240mm for 9 serving plates 450x370mm WxDxH (mm) 500x500x105 Compatible with: undertable, front opening, hood, dragged basket	
0S0944	Gray basket for plates/soup plates for 18 dinner plates or 16 soup plates Ø max 240mm for 9 serving plates 450x370mm Pack of 5-piece set Compatible with: undertable, front opening, hood, dragged basket Code Qt. Description 068692 5 Grey dish basket; 18 plates; ø max 240mm; 500x500x105mm	
048961	Blue basket for pizza plates for 12 pizza plates Ø max 320mm (for undercounter dishwashers Ø max 300mm; for larger plates use code 049895) with rilsan insert WxDxH (mm) 500x500x105 Compatible with: undertable, front opening, hood, basket dragged	
048796	Blue basket for universal use with wide mesh WxDxH (mm) 500x500x105 Compatible with: undercounter, front opening, hood, dragged basket	
0L1961	Blue basket for universal use with wide mesh Pack of 5-piece set Compatible with: undercounter, front opening, canopy, dragged basket	
048964	Blue basket for cups or cups for 20 cups or 24 cups with rilsan insert with inclined bottom WxDxH (mm) 500x500x105 Compatible with: undertable, front opening, hood, dragged basket	
048797	Brown narrow mesh cutlery basket WxDxH (mm) 500x500x105 Compatible with: undertable, front opening, hood, dragged basket	
0L1962	Brown narrow-mesh cutlery basket Pack of 5-piece set Compatible with: undertable, front opening, hood, dragged basket	
048965	Blue cutlery basket complete with 16 cutlery containers WxDxH (mm) 500x500x105 Compatible with: undertable, front opening, hood, dragged basket	



Plastic Baskets 500x500mm

Code	Spare Part Description	Picture
0L1813	Yellow containers for cutlery, pack of 4 pieces WxDxH (mm) 113x113x123mm. Bottom 88,4x88,4mm. Compatible with: undercounter, front opening, hoodtype, racktype.	
0S1131	Gray cutlery container with 8 compartments for all types of cutlery WxDxH (mm) 485x230x146 Compatible with: universal for all models	
048890	Red open-sided tray basket for 7 trays with dim. max 530x370mm WxDxH (mm) 500x500x105 Compatible with: dragged basket	
0L1963	Red open-sided tray basket for 7 trays with dim. max 530x370mm Pack of Set of 5 pieces Compatible with: dragged basket	
048962	Red open-sided tray basket for 5 trays with dim. max 530x370mm complete with stainless steel insert WxDxH (mm) 500x500x195 Compatible with: dragged basket	
0S2583	Red open-sided tray basket for 10 trays with dim. max 530x370mm complete with stainless steel insert WxDxH (mm) 500x500x125 Code Qt. Description 048958 1 Trays basket; smooth , 0C6415 2 Clamp; 200x3.6 nylon , 0S2528 1 Basket insert for 10 tray	
068701	Red basket for symmetrically shaped trays for 6 trays with dim. max 530x370mm WxDxH (mm) 538x504x110 Compatible with: front opening, canopy, dragged basket	
0L4545	Red basket for GN1/1 trays with symmetrical shapes for 6 trays with dim. max 530x325mm WxDxH (mm) 500x500x105 Compatible with: dragged basket	
0S0318	Blue glass basket for 16 glasses height. max 70mm Ø max 100mm WxDxH (mm) 500x500x105 Compatible with: undertable, front opening, hood, dragged basket	



Plastic Baskets 500x500mm

Code	Spare Part Description	Picture
048968	Blue basket for glasses with inclined bottom for 16 glasses max height 100mm Ø max 100mm LxDxH (mm) 500x500x155 Compatible with: undertable, front opening, hood, dragged basket	
048971	Blue basket for glasses with inclined bottom for 16 glasses max height 150mm Ø max 100mm LxDxH (mm) 500x500x205 Compatible with: undertable, front opening, hood, dragged basket	
048974	Blue basket for glasses with inclined bottom for 16 glasses max height 200mm Ø max 100mm LxDxH (mm) 500x500x255 Compatible with: undertable, front opening, hood, dragged basket	
048969	Blue basket for glasses with inclined bottom for 25 glasses max height 100mm Ø max 80mm LxDxH (mm) 500x500x155 Compatible with: undertable, front opening, hood, dragged basket	
048972	Blue basket for glasses with inclined bottom for 25 glasses max height 150mm Ø max 80mm LxDxH (mm) 500x500x205 Compatible with: undertable, front opening, hood, dragged basket	
048975	Blue basket for glasses with inclined bottom for 25 glasses max height 200mm Ø max 80mm LxDxH (mm) 500x500x255 Compatible with: undertable, front opening, hood, dragged basket	
048970	Blue basket for glasses with inclined bottom for 36 glasses max height 100mm Ø max 70mm LxDxH (mm) 500x500x155 Compatible with: undertable, front opening, hood, dragged basket	
048973	Blue basket for glasses with inclined bottom for 36 glasses max height 150mm Ø max 70mm LxDxH (mm) 500x500x205 Compatible with: undertable, front opening, hood, dragged basket	
048976	Blue basket for glasses with inclined bottom for 36 glasses max height 200mm Ø max 70mm LxDxH (mm) 500x500x255 Compatible with: undertable, front opening, hood, dragged basket	



Plastic Baskets 500x500mm

Code	Spare Part Description	Picture
048966	Blue basket for glasses with flat bottom for 49 glasses max height 70mm Ø max 60mm LxDxH (mm) 500x500x105 Compatible with: undertable, front opening, hood, dragged basket	
048967	Blue basket for glasses with flat bottom for 64 glasses max height 70mm Ø max 50mm LxDxH (mm) 500x500x105 Compatible with: undertable, front opening, hood, dragged basket	
048963	Red basket for trays. For 5 GN 1/1 trays Compatible with: undercounter WxDxH (mm): 538x504x110	

Plastic Baskets 600X500mm

Code	Spare Part Description	Picture
0S3191	Grey basket for flat/soup plates for 24 flat plates up to Ø 24cm or 22 soup/serving plates Dim. 600x500x120mm Compatible with pastry undercounter and dragged basket	
0S3192	Grey tray basket for 12 trays up to 47cm long or 10 GN trays up to 53cm long Dim. 600x500x120mm Compatible with pastry undercounter and dragged basket	
0S3193	Flat grey basket with wide mesh. For universal use such as cups, bowls, pans, etc.. 2 cutlery containers included Dim. 600x500x120mm Compatible with pastry undercounter and dragged basket	

Plastic Baskets for Glasswashers

Code	Spare Part Description	Picture
0S2177	Round plastic basket suitable for glasses and cups ØxH (mm) Ø350x160 Compatible with: glasswashers	
0S2178	Round plastic basket suitable for glasses and cups ØxH (mm) Ø380x170 Compatible with: glasswashers	
0S2179	Round plastic basket suitable for glasses and cups ØxH (mm) Ø400x180 Compatible with: glasswashers	

Accessories for Plastic Baskets - Glasswashers

Code	Spare Part Description	Picture
0S2105	Square container for plastic cutlery WxDxH (mm) 113x113x130mm. Bottom 89x89mm. Compatible with: plastic baskets for glasswashers.	
0S2104	Insert for 12 plastic saucers WxDxH (mm) 290x290x75 Compatible with: plastic baskets for glasswashers	
0S2215	Slanted insert for plastic glasses Compatible with: glass basket 0L3731 new	

Rubber Collar for Waste Disposal

Code	Spare Part Description	Picture
0PE213	Rubber collar for waste disposal Ø table hole (mm) 190 Ø external top (mm) 250 H (mm) 100	
0S2793	Rubber collar for waste disposal Ø table hole (mm) 205 Ø external top (mm) 235 H (mm) 55	
069318	Rubber collar for waste disposal Ø table hole (mm) 230 Ø external top (mm) 282 H (mm) 93	
0S3355	Crescent scraper for clearing Suitable for cleaning baking trays, plates and trays	
0SECFE	Natural silicone scraper blade Thickness 5mm	

Shower Groups

Code	Spare Part Description	Picture
0S1990	Single hole shower unit with clinical lever tap water connection Ø 3/8"GF fixing hole Ø 3/4"G spout Ø 25x175mm flexible hose height from the surface h=600mm	
0S1182	Single hole tap with clinical lever and shower connection Ø1/2" F connection spout Ø 20x275 mm	



Shower Groups

Code	Spare Part Description	Picture
0S1461	Two-hole shower unit with clinical lever tap water connection Ø3/4"G center distance 155mm fixing hole Ø3/4"G spout spout 330mm flexible hose height from the surface h=1030mm	
0S0920	Two-hole tap with clinical lever and shower connection 3/4"G spout spout 330mm	
0L0643	Two-hole shower unit with knobs water connection Ø3/4"G center distance 155mm fixing hole Ø3/4" flexible hose height from the surface h=1100mm	
0S1465	Two-hole shower group with knobs and knob tap water connection Ø3/4"G center distance 155mm fixing hole Ø 29mm spout Ø 25x225 mm flexible hose height from the surface h=1200mm	
0S1036	Single hole shower group with knobs water connection Ø1/2"G fixing hole Ø 3/4"G flexible hose height from the surface h=1080mm	
0S0951	Single hole shower group with knobs water connection Ø1/2"G fixing hole Ø 3/4"G flexible hose height from the surface h=1080mm with non-return valve	



Shower Groups

Code	Spare Part Description	Picture
0S2838	Single hole shower group with knobs and knob tap water connection Ø 3/8"G fixing hole Ø 29mm spout L=250mm flexible hose height from the surface h=448mm	
0S3206	Shower group STYL single-com. shower counter G3/4"x50, flexible G1/2". Plastics, metals and rubbers that come into contact with drinking water from this product comply with DVGW Hygiene. Barrel height 100.	

Accessories for Shower Groups

Code	Spare Part Description	Picture
0L0640	Black shower head 1/2" M connection	
0PRRDS	Black shower head 1/2" M connection Standard type multi-hole dispenser (14 l/min) shower effect	
0S3216	Multi-hole shower effect aerator Complete with O-ring seal Included in code 0PRRDS Compatible with code 0L0640	

Wall Washing Units

Code	Spare Part Description	Picture
0S0877	MAXIREEL washing group in AISI 304 steel wall version with automatic rewinder water connection Ø1/2"G EPDM rubber hose 10 m standard shower head L (m) = 10	



Wall Washing Units

Code	Spare Part Description	Picture
0L0821	MAXIREEL washing group in AISI 304 steel wall version with automatic rewinder water connection Ø1/2"G EPDM rubber hose 10 m standard shower head Description: EPDM rubber hose for MAXIReel 10m	
0S1857	MAXIREEL washing group in AISI 304 steel with NITO 2 shower group wall version with automatic rewinder water connection Ø1/2"G EPDM rubber hose 10 m NITO2 shower head L (m)= 10	
0S0878	MAXIREEL washing group in AISI 304 steel with standard shower group wall version with automatic rewinder water connection Ø1/2"G EPDM rubber hose 15 m standard shower head L (m) = 15	
0S0785	MAXIREEL washing group in AISI 304 steel with standard shower group wall version with automatic rewinder water connection Ø1/2"G EPDM rubber hose 15 m standard shower head Description: EPDM rubber hose for MAXIReel 15m with K reel connection	
0S1856	MAXIREEL washing group with NITO 2 shower group wall version with automatic rewinder water connection Ø1/2"G EPDM rubber hose NITO2 shower head L(m)= 15	
0S1923	MAXIREEL washing group with NITO 2 shower group wall version with automatic rewinder water connection Ø1/2"G EPDM rubber hose NITO2 shower head L(m)= 20	
0S1924	MAXIREEL washing group with NITO 2 shower group wall version with automatic rewinder water connection Ø1/2"G EPDM rubber hose NITO2 shower head Description: EPDM rubber hose for MAXIReel 20m with M 1/2"G connection	



Wall Washing Units

Code	Spare Part Description	Picture
0S1132	NITO 2 water gun	
0S1858	Extension for NITO 1 and NITO 2 water guns	
0S1384	NITO 1 water gun	

Water Treatment

Code	Spare Part Description	Picture
0S2695	MAXI automatic water softener with cabinet ▶ with AUTOTROL 255 Logix 740 valve ▶ max flow rate 1500lt/h ▶ 230V 50/60Hz power supply ▶ 24lt fiberglass cylinder with 17lt of cationic resins suitable for softening ▶ 50kg salt container ▶ water connections Ø 3 /4" ▶ min/max pressure 2-8 bar ▶ temperature 4-25°C ▶ 2.7 kg of salt for regeneration ▶ operating capacity 5040lt 20°f ▶ anti-flooding device WxDxH (mm) 320x500x1120	
0S0801	PURITY 1200 CLEAN FILTER SYSTEM with partial demineralization including filter cartridge. ▶ connections: inlet 1" - outlet 3/4" ▶ min./max inlet pressure: 2-6 bar ▶ operating temperature 4°-60°C ▶ capacity: 13000lt at 10° KH ▶ PNC 864017 ØxH (mm) Ø288x550	
0S0803	PURITY 1200 CLEAN EXTRA FILTER with total demineralization including filter cartridge. ▶ connections: inlet 1" - outlet 3/4" ▶ min./max inlet pressure: 2-6 bar ▶ operating temperature 4°-60°C ▶ capacity: 5000lt at 10° KH ▶ PNC 864367 ØxH (mm) Ø288x550	



Water Treatment

Code	Spare Part Description	Picture
0S0802	PURITY 1200 CLEAN FILTER SYSTEM with partial demineralization including filter cartridge. ▶ connections: inlet 1" - outlet 3/4" ▶ min./max inlet pressure: 2-6 bar ▶ operating temperature 4°-60°C ▶ capacity: 13000lt at 10° KH ▶ PNC 864017 Description: Filter cartridge for PURITY 1200 CLEAN	
0S0804	PURITY 1200 CLEAN EXTRA FILTER with total demineralization including filter cartridge. ▶ connections: inlet 1" - outlet 3/4" ▶ min./max inlet pressure: 2-6 bar ▶ operating temperature 4°-60°C ▶ capacity: 5000lt at 10° KH ▶ PNC 864367 Description: Filter cartridge for PURITY 1200 CLEAN EXTRA	
0S2556	PURITY 1200 CLEAN EXTRA FILTER with total demineralization including filter cartridge. ▶ connections: inlet 1" - outlet 3/4" ▶ min./max inlet pressure: 2-6 bar ▶ operating temperature 4°-60°C ▶ capacity: 5000lt at 10° KH ▶ PNC 864367 Description: Liter counter (PNC 864468)	
0S3147	Automatic GIX TEMPO water softeners with Autotrol 255 Logix 740 valve Cabin (RC): Salt insertion, cleaning and maintenance easier. Anti-flooding and overflow incorporated. AISI 304 cylinder: 8 lt; Resins per cylinder: 5.6 lt; Max flow rate: 1500 lt/h; Bri	
0S3288	Automatic GIX VOLUMETRIC water softeners with Autotrol 255 Logix 740 valve. Enclosure (RC): Easier salt addition, cleaning and maintenance. Built-in anti-flooding and overflow. AISI 304 cylinder: 8 lt; Resins per cylinder: 5.5 lt; Max flow rate: 1500 lt/h; Brine: 20 kg; Salt per regeneration cycle: 1.0 kg; Electrical power supply: 230V 50/60 Hz; Water connections: Ø 3/4" G; Min/max pressure: 2-8 bar; Water supply temp.: 4-25°C; LxDxH: 275x450x540 mm	

Wire Baskets 500x500mm

Code	Spare Part Description	Picture
0S0057	Plastic-coated steel wire basket for dishes for 18 dishes suitable for fixed jet dishwashers WxDxH (mm) 500x500x93 Compatible with: old undertables and hood	



Wire Baskets 500x500mm

Code	Spare Part Description	Picture
0S1045	Description: Corner for baskets in plastic-coated steel wire. Pack of: Set of 20 pieces Code Qt. Description 0S1047 20 Plastic angle slide for wire basket	
0S0058	Plastic-coated steel wire basket for glasses, cutlery and glasses suitable for fixed jet dishwashers WxDxH (mm) 500x500x100 Compatible with: old undertables and hood	
0S0861	Rilsan wire basket for wine glasses height. max 270mm Ø max 104mm LxDxH (mm) 500x500x246 Compatible with: undertable and hood	
049895	AISI 304 steel wire basket for 12 pizza plates max Ø 320mm WxDxH (mm) 500x500x105 Compatible with: undertable, front opening and hood	
0S2180	Multifunctional Rilsan wire basket complete with insert for cups, plates, saucers and cutlery container WxDxH (mm) 500x500x200 Compatible with: undertable, front opening and hood	

Wire Baskets for Glasswashers

Code	Spare Part Description	Picture
049069	Rilsan wire basket for glasses for LB/WT/GW models 1-2 LxDxH (mm) 395x395x100 Compatible with: glasswashers	
0S2173	Rilsan wire basket for glasses WxDxH (mm) 395x395x115 Compatible with: glasswashers	



Wire Baskets for Glasswashers

Code	Spare Part Description	Picture
049365	Rilsan wire basket for glasses suitable for long-stemmed glasses WxDxH (mm) 395x395x200 Compatible with: glasswashers	
049367	Rilsan wire basket for glasses with inclined bottom for 16 glasses for LB/WT/GW models 1-2 WxDxH (mm) 395x395x200 Compatible with: glasswashers	
049364	Rilsan wire basket for dishes suitable for holding up to 16 plates Ø 190mm 8 plates Ø 240mm for GW 2 models WxDxH (mm) 395x395x100 Compatible with: GW2 glasswashers	
049366	Multifunction Rilsan wire basket complete with insert for saucers and cutlery container for LB/WT/GW models 1-2 LxDxH (mm) 395x395x100 Compatible with: glasswashers	
049269	Round Rilsan wire basket for glasses suitable for glasses with square frame ØxH (mm) Ø400x140 Compatible with: glasswashers	
0L4313	Accessories for wire basket cod. 049269 Dim. (mm) Ø400x140 Description: round wire basket	
0L4314	Accessories for wire basket cod. 049269 Dim. (mm) 400x400 Description: square wire frame	
069563	Rilsan wire basket for glasses for LTB 11-12-22 models (not compatible with LB/WT/GW 1-2 models) WxDxH (mm) 382x382x105 Compatible with: glasswashers	



Wire Baskets for Glasswashers

Code	Spare Part Description	Picture
0R0068	Rilsan wire basket for glasses with inclined bottom WxDxH (mm) 350x350x180 Compatible with: glasswashers	

Accessories for Wire Baskets

Code	Spare Part Description	Picture
049071	Rilsan wire insert for saucers suitable for holding up to 14 saucers WxDxH (mm) 352x110x100 Compatible with: glasswashers	
049369	Rilsan wire insert for plates for 7 saucers max Ø 240mm; for wire basket WxDxH (mm) 327x240x100 Compatible with: glasswashers	
049368	Inclined Rilsan wire insert for cups for wire basket cod. 049069 WxDxH (mm) 373x265x32 Compatible with: glasswashers	
0S2174	Square plastic basket for glasses suitable for glasses and cups WxDxH (mm) 350x350x150 Compatible with: glasswashers	
0S2175	Square plastic basket for glasses suitable for glasses and cups WxDxH (mm) 380x380x150 Compatible with: glasswashers	
0S1130	Square plastic basket for glasses suitable for glasses and cups WxDxH (mm) 400x400x150 Compatible with: glasswashers	



Accessories for Wire Baskets

Code	Spare Part Description	Picture
0L3731	Square plastic basket for glasses suitable for glasses and cups with protected corners WxDxH (mm) 400x400x130 Compatible with: glasswashers	
0S2176	Square plastic basket for dishes suitable for dishes WxDxH (mm) 400x400x110 Compatible with: glasswashers	

B2000 - B3000

Code	Spare Part Description	Picture
650132 8FRJ650132	Stainless steel crusher tube with 353 mm blades for B3000 bayonet connection	
650133 8FRJ650133	Stainless steel crusher tube with 453 mm blades for B3000 bayonet connection	
650134 8FRJ650134	Stainless steel crusher tube with 553 mm blades for B3000 bayonet connection	
650135 8FRJ650135	Stainless steel crusher tube with 653 mm blades for B3000 bayonet connection	



B2000 - B3000

Code	Spare Part Description	Picture
653578 8FRJ653578	Reinforced stainless steel whisk for B3000 portable mixer, bayonet connection	
653294 8FRJ653294	Stand for B3000 portable mixer	
653292 8FRJ653292	Adjustable guides for containers/pots diam. from 375 to 650 mm. To be used in combination with the support code. 653294	
0D6297	Plastic wall holder for Bermixer and tools	
0D7068	Stainless steel crusher tube with 353 mm blades for B3000 clip attachment	
0D7069	Stainless steel crusher tube with 453 mm blades for B3000 clip attachment	
0D7070	Stainless steel crusher tube with 553 mm blades for B3000 clip attachment	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

B2000 - B3000

Code	Spare Part Description	Picture
0D7071	Stainless steel crusher tube with 653 mm blades for B3000 clip attachment	

BE5

Code	Spare Part Description	Picture
653295 8FRJ653295	5 l stainless steel tank for BE5	
653765 8FRJ653765	Spiral stainless steel hook (only for BE5)	
653781 8FRJ653781	BPA-free CLOSED protection shield for BE5 without K-mount	
653782 8FRJ653782	BPA free CLOSED protective shield for BE5 with K mount	

Genuine Replacement Parts, Accessories and Consumables Catalogue
Accessories and Consumables

BE8

Code	Spare Part Description	Picture
653766 8FRJ653766	1 stainless steel tank for BE8	
653769 8FRJ653769	Stainless steel whisk for BE8	
653768 8FRJ653768	Stainless steel spatula for BE8	
653767 8FRJ653767	Spiral stainless steel hook for BE8	

BMX60 - BMXE60 - XBE60

Code	Spare Part Description	Picture
650129 8FRJ650129	60 l stainless steel tank for BMX60-BMXE60-XBE60	
653084 8FRJ653084	Spiral stainless steel hook for BMX60-BMXE60-XBE60	



BMX60 - BMXE60 - XBE60

Code	Spare Part Description	Picture
653083 8FRJ653083	Spatula for BMX60-BMXE60-XBE60	
653086 8FRJ653086	Stainless steel whip for BMX60-BMXE60-XBE60	
653097 8FRJ653097	Reinforced stainless steel whip for BMX60-BMXE60-XBE60	
653442 8FRJ653442	Scraper for 60 lt tank BMX60-BMXE60-XBE60	
650127 8FRJ650127	40 l reduction kit (bowl, hook, spatula and whisk) for 60/80 l mixer BMX60-BMXE60-XBE60-BMXE80-XBE80	
0D7798	40 l stainless steel tank for reduction kit 650127	
0D0463	Hook for reduction kit 650127	



BMX60 - BMXE60 - XBE60

Code	Spare Part Description	Picture
0D0462	Spatula for reduction kit 650127	
0H1010	Stainless steel whisk for reduction kit 650127	

BMXE80 - XBE80

Code	Spare Part Description	Picture
650130 8FRJ650130	80 l stainless steel tank for BMXE80-XBE80	
653133 8FRJ653133	Spiral stainless steel hook for BMXE80-XBE80	
653135 8FRJ653135	Spatula for BMXE80-XBE80	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

BMXE80 - XBE80

Code	Spare Part Description	Picture
653134 8FRJ653134	Stainless steel whip for BMXE80-XBE80	
653443 8FRJ653443	Scraper for 60 lt tank BMX60-BMXE60-XBE60	
650131 8FRJ650131	60 l reduction kit (bowl, hook, spatula and whisk) for 80 l BMXE80-XBE80 mixer	

CT6/10 - DTA - CF4

Code	Spare Part Description	Picture
653100 8FRJ653100	6 mm blade block for CT6 slice cutter	
653099 8FRJ653099	6 mm guide carriage for CT6 slice cutter	

Ditomix

Code	Spare Part Description	Picture
653508 8FRJ653508	5 l stainless steel tank (only for DITOMIX5)	

Emix

Code	Spare Part Description	Picture
653754 8FRJ653754	5 l stainless steel tank only for Emix	
653755 8FRJ653755	Stainless steel semi-spiral hook 5 l (only for Emix)	
653756 8FRJ653756	Stainless steel spatula for Emix-DITOMIX-BE5	
653757 8FRJ653757	Stainless steel whisk for Emix-Ditomix-BE5	
653043 8EXT653043	60 mm meat mincer for machines with K-type accessory socket (12mm square socket). Aluminum body complete with 1 stainless steel disc with 6 mm diameter holes	
653044 8EXT653044	Kit of 3 discs with Ø holes 3 - 4.5 - 8 mm for meat mincer	
0C9122	Pasta accessories kit with K-type connection Complete with three accessories: 0D4201 for lasagne/puff pastry 9pos. from 2.5 to 0.3 mm 0D4202 for fettuccine/tagliatelle 6 mm 0D4203 for tagliolini 1.5 mm	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

Emix

Code	Spare Part Description	Picture
0D4200	Spaghetti accessory Type K attachment for 2 mm spaghetti - PNC 653298	
0D4201	Puff pastry accessory Type K attachment for lasagne/puff pastry 9pos. 2.5 to 0.3 mm - PNC 653296	
0D4202	Fettuccine accessory Type K connection For 6 mm fettuccine/tagliatelle	
0D4203	Tagliolini accessory Type K attachment for 1.5 mm tagliolini	

K120/KE120 - K120S/KE120S

Code	Spare Part Description	Picture
653872 8FRJ653872	Smooth blade knife group for 11.5 l cutter mixer usable without scraper	
653299 8FRJ653299	Knurled knife group for cutter mixer 11.5 l	
653538 8FRJ653538	Serrated meat knife unit for cutter mixer 11.5 l (use at speeds up to 1500 rpm)	



K120/KE120 - K120S/KE120S

Code	Spare Part Description	Picture
650060 8FRJ650060	Knife group with micro-toothed blade for 11.5 lt mixer cutter.	
650073 8FRJ650073	11.5 liter stainless steel tank. for cutter mixer K120S-KE120S	
650059 8FRJ650059	Scraper for mixer cutter K120S and KE120S use only with the microtoothed blade knife group 650060	

K180/KE180 - K180S/KE180S

Code	Spare Part Description	Picture
653119 8FRJ653119	Smooth blade knife group for cutter mixer 17.5 l	
653120 8FRJ653120	Knurled knife group for cutter mixer 17.5 l	
653539 8FRJ653539	Serrated meat knife unit for cutter mixer 17.5 l (use at speeds up to 1500 rpm)	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

K180/KE180 - K180S/KE180S

Code	Spare Part Description	Picture
650047 8FRJ650047	Knife group with micro-toothed blade for 17.5 lt mixer cutter.	
650074 8FRJ650074	17.5 liter stainless steel tank. for cutter mixer K180S-KE180S	
650046 8FRJ650046	Scraper for mixer cutter K180S and KE180S Use only with the microtoothed blade knife group 650047	

K25 - K35 - K45 -K 55 -K70

Code	Spare Part Description	Picture
0DF214	Smooth blade knife group for K35	
653875 8FRJ653875	Smooth blade knife group for TRK45 cutter mixer	
653877 8FRJ653877	Micro-serrated blade knife group specific for emulsions for TRK45 cutter mixer	
653876 8FRJ653876	Micro-serrated blade knife group for TRK45 cutter mixer	
653878 8FRJ653878	Smooth blade knife group for TRK55 cutter mixer	



K25 - K35 - K45 -K 55 -K70

Code	Spare Part Description	Picture
653879 8FRJ653879	Micro-serrated blade knife group for TRK55 cutter mixer	
653874 8FRJ653874	Micro-serrated blade knife group for TRK70 cutter mixer	
653881 8FRJ653881	Smooth blade knife assembly for TRK70 cutter mixer	
653882 8FRJ653882	Micro-serrated blade knife group specifically for emulsions for TRK70 cutter mixer	

MB40 - MBE40

Code	Spare Part Description	Picture
650128 8FRJ650128	40 l stainless steel tank for MB-MBE40	
653092 8FRJ653092	Hook for MB-MBE40	
653093 8FRJ653093	Spatula for MB-MBE40	
653094 8FRJ653094	Fine stainless steel whisk for emulsions for MB-MBE40	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

MB40 - MBE40

Code	Spare Part Description	Picture
653127 8FRJ653127	Reinforced stainless steel whisk for MB-MBE	
650126 8FRJ650126	20 l reduction kit (bowl, hook, spatula and whisk) for 40 l MB-MBE40 mixer	
0D7872	20 l stainless steel tank for reduction kit 650126	
0KQ303	Hook for reduction kit 650126	
0KQ302	Spatula for reduction kit 650126	
0KJ061	Stainless steel whisk for reduction kit 650126	
650186 8FRJ650186	MB-MBE40 40 liter tank scraper	



MB40 - MBE40

Code	Spare Part Description	Picture
653585 8FRJ653585	Trolley for 40/60/80 liter tank (cannot be used if the wheel kit frame code 653552 is installed)	

Mini Green

Code	Spare Part Description	Picture
0D8296	RD2 2 mm stainless steel grating disc	
653003 8FRJ653003	RD3 3 mm stainless steel grating disc	
653004 8FRJ653004	RD4 4 mm stainless steel grating disc	
653005 8FRJ653005	RD7 7 mm stainless steel grating disc	
653171 8FRJ653171	ED2 Disc for sticks - 2 mm stainless steel matches	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

Mini Green

Code	Spare Part Description	Picture
653006 8FRJ653006	ED4 Disc for sticks - 4 mm stainless steel matches	
650214 8FRJ650214	TD2 2 mm stainless steel slice disc	
650215 8FRJ650215	TD3 3 mm stainless steel slice disc	
650216 8FRJ650216	TD5 5 mm stainless steel slice disc	
650217 8FRJ650217	TD7 7 mm stainless steel slice disc	
650218 8FRJ650218	WD2 2 mm stainless steel wavy slice disc	
653632 8FRJ653632	Container for 1 cutting disc (Ø 175 mm and 205 mm)	

Multigreen

Code	Spare Part Description	Picture
653145 8FRJ653145	Accessory set for cutter function: - 2.5 l ABS bowl with lid and smooth blade knife unit	



Genuine Replacement Parts, Accessories and Consumables Catalogue
Accessories and Consumables

Multigreen

Code	Spare Part Description	Picture
653146 8FRJ653146	Smooth blade knife group for Multigreen/K25	
650035 8FRJ650035	Knife group with micro-toothed blade for Multigreen/K25	
653488 8FRJ653488	2.5 l ABS bowl for Multigreen cutter mixer	
0DF013	Transparent polycarbonate cover for vegetable cutters (K25 and Multigreen)	
0D6447	Plastic knife holder also suitable for wall mounting	
0DF054	2.5 l stainless steel bowl for Multigreen cutter-mixer	
0DF063	"Fresh cut" hopper with safety lever	

RC14

Code	Spare Part Description	Picture
653022 8FRJ653022	Cutting blocks sticks 8x8 mm (chips)	
653023 8FRJ653023	Cutting blocks sticks 10x10 mm (chips)	
653024 8FRJ653024	Cutting blocks sticks 12x12 mm (chips)	
653018 8FRJ653018	Cutting blocks sticks 14x14 mm (chips)	
653503 8FRJ653503	4 mm puff pastry cutting blocks (chips)	
653504 8FRJ653504	6 mm puff pastry cutting blocks (chips)	



RC14

Code	Spare Part Description	Picture
653505 8FRJ653505	8 mm puff pastry cutting blocks (chips)	

Speedy Mixer

Code	Spare Part Description	Picture
0PR950	Stainless steel tube with 150 mm blades for Speedy Mixer	
0PR951	Stainless steel tube with 200 mm blades for Speedy Mixer	
0PRB64	Stainless steel tube with 250 mm blades for Speedy Mixer	
650057 8FRJ650057	Variable Speed Speedy Mixer Whisk	
0PRPXN	Emulsion tube with 250 mm blade for Speedy Mixer	
0PRPXO	Stainless steel wall support for Speedy Mixer	



Speedy Mixer

Code	Spare Part Description	Picture
0PRAL5	Motor body 250W Black color, Variable speed	

T10E - T15E

Code	Spare Part Description	Picture
653203 8FRJ653203	Abrasive disc for T10E-T15E	
653205 8FRJ653205	Abrasive disc for large onions T10E-T15E	
653184 8FRJ653184	Abrasive disc for onions, shallots and garlic (not suitable for models with abrasive cylinder) T10E-T15E	
653204 8FRJ653204	Knife disc for T10E-T15E (not suitable for models with abrasive cylinder)	
0KQ570	Set of 10 knives	



T10E - T15E

Code	Spare Part Description	Picture
653058 8FRJ653058	Disc for washing and brushing vegetables T10E-T15E	
653208 8FRJ653208	Centrifuge basket for T10E only	
653209 8FRJ653209	Centrifuge basket for T15E only	

T5S - T5E/T5M - T8E/T8M

Code	Spare Part Description	Picture
653182 8FRJ653182	Abrasive disc for T5S	
653183 8FRJ653183	Knife disc for T5S	
653057 8FRJ653057	Washing disc with brushes for T5S	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

T5S - T5E/T5M - T8E/T8M

Code	Spare Part Description	Picture
653784 8FRJ653784	Filter table with support surface for 5/10/15 kg peelers complete with: - extractable shelf with handle and waste container with filter	
653316 8FRJ653316	Abrasive disc for T5E-T5M-T8E-T8M	
653486 8FRJ653486	Mussel cleaning disc for T5E-T5M-T8E-T8M	
653314 8FRJ653314	Filter basket only for T5E-T5M	
653514 8FRJ653514	Filter basket for T8E-T8M potato peeler and T5E-T5M-T8E-T8M mussel cleaner	
653315 8FRJ653315	Vegetable spinner basket only for T5E	



T5S - T5E/T5M - T8E/T8M

Code	Spare Part Description	Picture
653496 8FRJ653496	Stainless steel stand for peelers and mussel cleaners T5E-T5M-T8E-T8M	
653515 8FRJ653515	Kit for peeling vegetables on the T5M mussel cleaner. Includes bowl with handles and abrasive disc	
653495 8FRJ653495	Vegetable spinner basket only for T8E	

Ti25 - T25E

Code	Spare Part Description	Picture
653506 8FRJ653506	Abrasive disc for Ti25-T25E	
653302 8FRJ653302	Wheeled tank with handle and filter only for T25E	
653509 8FRJ653509	Device to facilitate the dilution of waste only for T25E	

TR260

Code	Spare Part Description	Picture
650150 8FRJ650150	J302N 2 mm stainless steel Julienne disc	
650151 8FRJ650151	J303N 3 mm stainless steel Julienne disc	
650152 8FRJ650152	J304N 4 mm stainless steel Julienne disc	
650153 8FRJ650153	J307N 7 mm stainless steel Julienne disc	
650154 8FRJ650154	J309N 9 mm stainless steel Julienne disc	
650148 8FRJ650148	P300 Stainless steel parmesan grater disc	
650149 8FRJ650149	K300 Stainless steel dumpling grater disc	



Genuine Replacement Parts, Accessories and Consumables Catalogue
Accessories and Consumables

TR260

Code	Spare Part Description	Picture
653198 8FRJ653198	AF306 Disc for 6x6 mm sticks	
653199 8FRJ653199	AF308 Disc for 8x8 mm sticks	
653200 8FRJ653200	AF310 Disc for 10x10 mm sticks	
653195 8FRJ653195	A302 Disc for sticks 2x2 mm	
653196 8FRJ653196	A303 Disc for sticks 3x3 mm	
653197 8FRJ653197	A304 Disc for 4x4 mm sticks	
650157 8FRJ650157	DJ607N Stainless steel Julienne disc for 7 mm corer for cabbage hopper, cap (only for TR260)	
653188 8FRJ653188	C301 Slicing disc 1 mm	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

TR260

Code	Spare Part Description	Picture
653172 8FRJ653172	C302 2 mm slice disc	
653173 8FRJ653173	C303 3 mm slice disc	
653189 8FRJ653189	C305 Slicing disc 5 mm curved knife with knurling for tomatoes	
653190 8FRJ653190	C306 6 mm slice disc	
653191 8FRJ653191	C308 8 mm slice disc	
653192 8FRJ653192	C310 10 mm slice disc	
653193 8FRJ653193	C316 Slicing disc 16 mm	
653009 8FRJ653009	D601 Coring slice disc 1 mm for cabbage hopper only for TR260)	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

TR260

Code	Spare Part Description	Picture
653227 8FRJ653227	D602 2 mm corer slice disc for cabbage hopper, cap (only for TR260)	
653228 8FRJ653228	D603 3 mm corer slice disc for cabbage hopper, cap (only for TR260)	
653217 8FRJ653217	C302W 2 mm slice disc for wavy cutting	
653218 8FRJ653218	C303W 3 mm slice disc for wavy cutting	
653219 8FRJ653219	C306W 6 mm slice disc for wavy cutting	
653051 8FRJ653051	MT310 Cube grid 10x10 mm for TR260	
653301 8FRJ653301	MT312 Cube grid 12x12 mm for TR260	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

TR260

Code	Spare Part Description	Picture
653052 8FRJ653052	MT316 Cube grid 16x16 mm for TR260	
653053 8FRJ653053	MT320 Cube grid 20x20 mm for TR260	
653054 8FRJ653054	MT325 Cube grid 25x25 mm for TR260	
653055 8FRJ653055	MT332 Cube grid 32x32 mm for TR260	
653212 8FRJ653212	Stainless steel disc holder (for discs diam. 300) to be fixed on support 653017 (only for TR260)	
653017 8FRJ653017	Stainless steel support with 4 wheels with brake h=730 mm (only for TR260)	
653224 8FRJ653224	Stainless steel trolley for GN 2/1 tray (tray excluded) recommended for collecting cut products to be positioned under the product outlet	

TR300

Code	Spare Part Description	Picture
653068 8FRJ653068	M310 Cube grid 10x10 mm for TR300	
653499 8FRJ653499	M312 Cube grid 12x12 mm for TR300	
653075 8FRJ653075	M316 Cube grid 16x16 mm for TR300	
653073 8FRJ653073	M320 Cube grid 20x20 mm for TR300	
653259 8FRJ653259	M332 Cube grid 32x32 mm for TR300	
653076 8FRJ653076	Chip cutting block 6x6 mm To be combined with the slice discs and ejector 653143 (only for TR300)	
653074 8FRJ653074	Chip cutting block 8x8 mm To be combined with the slice discs and ejector 653143 (only for TR300)	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

TR300

Code	Spare Part Description	Picture
653069 8FRJ653069	Chip cutting block 10x10 mm To be combined with the slice discs and ejector 653143 (only for TR300)	
653142 8FRJ653142	ES300 Universal ejector (no chips) for TR300	
653143 8FRJ653143	EF300 French Fries Ejector (For Fries Cutting Blocks Only)	

TrinityPro

Code	Spare Part Description	Picture
650213 8FRJ650213	C17X1 Stainless steel disc slices 1 mm	
650214 8FRJ650214	TD2 2 mm stainless steel slice disc	
650215 8FRJ650215	TD3 3 mm stainless steel slice disc	
650237 8FRJ650237	C17X4 Stainless steel disc slices 4 mm	



TrinityPro

Code	Spare Part Description	Picture
650216 8FRJ650216	TD5 5 mm stainless steel slice disc	
650217 8FRJ650217	TD7 7 mm stainless steel slice disc	
650218 8FRJ650218	WD2 2 mm stainless steel wavy slice disc	
650219 8FRJ650219	C17XW5 Stainless steel slice disc with 5 mm wavy blades	
650198 8FRJ650198	J172 Julienne stainless steel disc 2 mm	
650199 8FRJ650199	J173 3 mm julienne stainless steel disc	
650205 8FRJ650205	J174 4 mm julienne stainless steel disc	
650207 8FRJ650207	J177 Julienne stainless steel disc 7 mm	
650208 8FRJ650208	J17P Stainless steel grater disc for mature cheese 2 mm	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

TrinityPro

Code	Spare Part Description	Picture
650220 8FRJ650220	C17X8 Aluminum disc slices 8 mm Complete with locking screw code 0DF043	
650221 8FRJ650221	C17X10 Aluminum disc slices 10 mm Complete with locking screw code 0DF043	
650209 8FRJ650209	AS172 Stainless steel disc with 2 mm stick	
650210 8FRJ650210	AS174 Stainless steel disc with 4 mm stick	
650211 8FRJ650211	AS178 Stainless steel disc with 8 mm stick	
650232 9FRJ650232	Parmesan ejector disc	
650222 8FRJ650222	MT08 Cube grids (to be combined with slice discs) 8x8 mm	
650223 8FRJ650223	MT10 Cube grids (to be combined with slice discs) 10x10 mm	
650110 8FRJ650110	Cube grid cleaning comb Compatible with 5/8/10MM grids	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

TrinityPro

Code	Spare Part Description	Picture
650226 8FRJ650226	Knife group with micro-toothed blade for 2.6 liter cutter mixer	
650227 8FRJ650227	Smooth blade knife unit for TrinityPro - 2.6 liter bowl	
650228 8FRJ650228	Stainless steel bowl for 2.6 liter cutter mixer	
650229 8FRJ650229	Transparent copolyester bowl for 2.6 liter cutter mixer	
650230 8FRJ650230	Bowl scraper for 2.6 liter mixer cutter	
650117 8FRJ650117	Transparent lid for 2.6 liter mixer cutter	
650234 8FRJ650234	Smooth blade knife unit for 3.6 liter cutter mixer	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

TrinityPro

Code	Spare Part Description	Picture
650233 8FRJ650233	Knife group with micro-toothed blade for 3.6 liter cutter mixer	
650235 8FRJ650235	Stainless steel bowl for 3.6 liter cutter mixer	
650236 8FRJ650236	Bowl scraper for 3.6 liter mixer cutter	
650118 8FRJ650118	Transparent lid for 3.6 liter mixer cutter	
0DF043	Locking screw	
653632 8FRJ653632	Container for 1 cutting disc (Ø 175 mm and 205 mm)	

TRK45 - TRK55 -TRK 70

Code	Spare Part Description	Picture
650040 8FRJ650040	Knife group with micro-toothed blade specific for emulsions for TRK55 cutter mixer	
650099 8FRJ650099	Lid and bowl scraper for TRK45 cutter mixer	



TRK45 - TRK55 -TRK 70

Code	Spare Part Description	Picture
653589 8FRJ653589	4.5 l stainless steel bowl for TRK45 cutter mixer	
650102 8FRJ650102	Lid and bowl scraper for TRK55 cutter mixer	
653590 8FRJ653590	5.5 l stainless steel bowl for TRK55 cutter mixer	
650104 8FRJ650104	Lid and bowl scraper for TRK70 cutter mixer	
653593 8FRJ653593	7 l stainless steel bowl for TRK70 cutter mixer	
0D7971	Vegetable cutter conversion kit	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

TRK45 - TRK55 -TRK 70

Code	Spare Part Description	Picture
0D1250	Transparent silicone adhesive sealant	
653875 8FRJ653875	Smooth blade knife group for TRK45 cutter mixer	
653878 8FRJ653878	Smooth blade knife group for TRK55 cutter mixer	
653877 8FRJ653877	Micro-serrated blade knife group specific for emulsions for TRK45 cutter mixer	
653876 8FRJ653876	Micro-serrated blade knife group for TRK45 cutter mixer	
653879 8FRJ653879	Micro-serrated blade knife group for TRK55 cutter mixer	
653874 8FRJ653874	Micro-serrated blade knife group for TRK70 cutter mixer	
653882 8FRJ653882	Micro-serrated blade knife group specifically for emulsions for TRK70 cutter mixer	
653881 8FRJ653881	Smooth blade knife assembly for TRK70 cutter mixer	

TRS - TR210

Code	Spare Part Description	Picture
653773 8FRJ653773	J2X 2 mm stainless steel Julienne disc	



TRS - TR210

Code	Spare Part Description	Picture
653774 8FRJ653774	J3X 3 mm stainless steel Julienne disc	
653775 8FRJ653775	J4X 4 mm stainless steel Julienne disc	
653776 8FRJ653776	J7X 7 mm stainless steel Julienne disc for mozzarella	
653777 8FRJ653777	J9X 9 mm stainless steel Julienne disc for mozzarella	
653778 8FRJ653778	KX Stainless steel grater disc for dumplings and bread	
653779 8FRJ653779	PX Stainless steel grater disc for cheese and bread	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

TRS - TR210

Code	Spare Part Description	Picture
650166 8FRJ650166	AS2XX Disc for 2 mm stainless steel sticks	
650158 8FRJ650158	AS2X8X Stainless steel stick disc with 2x8 mm "S" blades (tagliatelle)	
650159 8FRJ650159	AS2X10X Stainless steel stick disc with "S" blades 2x10 mm (tagliatelle)	
650167 8FRJ650167	AS3XX Disc for 3 mm stainless steel sticks	
650077 8FRJ650077	AS4XX Disc for 4 mm stainless steel sticks	
650078 8FRJ650078	AS6XX Stainless steel stick disc with 6x6mm "S" blades (also suitable for French fries)	



TRS - TR210

Code	Spare Part Description	Picture
650079 8FRJ650079	AS8XX Stainless steel stick disc with 8x8mm "S" blades (also suitable for French fries)	
650080 8FRJ650080	AS10XX Stainless steel stick disc with 10x10mm "S" blades (also suitable for French fries)	
650081 8FRJ650081	C06SX Stainless steel slicing disc with 0.6 mm "S" blades (suitable for slicing or combining cubes with grids)	
650082 8FRJ650082	C1SX Stainless steel slicing disc with 1 mm "S" blades (suitable for slicing or combining cubes with grids)	
650083 8FRJ650083	C2SX Stainless steel slicing disc with 2 mm "S" blades (suitable for slicing or combining cubes with grids)	
650084 8FRJ650084	C3SX Stainless steel slicing disc with 3 mm "S" blades (suitable for slicing or combining cubes with grids)	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

TRS - TR210

Code	Spare Part Description	Picture
650085 8FRJ650085	C4SX Stainless steel slicing disc with 4 mm "S" blades (suitable for slicing or combining cubes with grids)	
650086 8FRJ650086	C5SX Stainless steel slice disc with "S" blades and 5 mm presser (suitable for slicing or combining cubes with grids)	
650087 8FRJ650087	C6SX Stainless steel slice disc with "S" blades and 6 mm presser (suitable for slicing or combining cubes with grids)	
650088 8FRJ650088	C8SX Stainless steel slice disc with "S" blades and 8 mm presser (suitable for slicing or combining cubes with grids)	
650160 8FRJ650160	C10SX Stainless steel slice disc with "S" blades with 10 mm MOZZARELLA presser (suitable for slicing or combining cubes with grids)	
650161 8FRJ650161	C12SX Stainless steel slice disc with "S" blades with 12 mm presser (suitable for slicing or combining cubes with grids)	



TRS - TR210

Code	Spare Part Description	Picture
650165 8FRJ650165	C13SX Stainless steel slice disc with "S" blades and 13 mm presser (suitable for slicing or combining cubes with grids)	
650089 8FRJ650089	C2WX Stainless steel disc with 2 mm "S" wavy blades (suitable for slicing or combining cubes with grids)	
650090 8FRJ650090	C3WX Stainless steel disc with 3 mm "S" wavy blades (suitable for slicing or combining cubes with grids)	
650091 8FRJ650091	C6WX Stainless steel disc with 6 mm "S" wavy blades (suitable for slicing or combining cubes with grids)	
650162 8FRJ650162	C8WX Stainless steel disc with wavy "S" blades with 8 mm presser (suitable for slicing or combining cubes with grids)	
650164 8FRJ650164	C10WX Stainless steel disc with wavy "S" blades with 10 mm presser (suitable for slicing or combining cubes with grids)	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

TRS - TR210

Code	Spare Part Description	Picture
653566 8FRJ653566	MT05T Grid for 5x5 mm stainless steel cubes to be combined with smooth (C) and wavy (CW) blade slice discs	
653567 8FRJ653567	MT08T Grid for 8x8 mm stainless steel cubes to be combined with smooth (C) and wavy (CW) blade slice discs	
653568 8FRJ653568	MT10T Grid for 10x10 mm stainless steel cubes to be combined with smooth (C) and wavy (CW) blade slice discs	
653569 8FRJ653569	MT12T Grid for 12x12 mm stainless steel cubes to be combined with smooth (C) and wavy (CW) blade slice discs	
653570 8FRJ653570	MT20T Grid for 20x20 mm stainless steel cubes to be combined with smooth (C) and wavy (CW) blade slice discs	
650115 8FRJ650115	C10 Aluminum slice disc, with 10 mm presser	



TRS - TR210

Code	Spare Part Description	Picture
650116 8FRJ650116	C8 Aluminum slice disc, with 8 mm presser	
653571 8FRJ653571	FT06 6x6 mm stainless steel chip strip grid to be combined with smooth (C) and wavy (CW) blade slice discs	
653572 8FRJ653572	FT08 8x8 mm stainless steel strip grid to be combined with smooth (C) and wavy (CW) blade slice discs	
653573 8FRJ653573	FT10 10x10 mm stainless steel strip grid to be combined with smooth (C) and wavy (CW) blade slice discs	
653772 8FRJ653772	Ejector disk	
653283 8FRJ653283	Stainless steel trolley with support surface, folding shelves, lower shelf and disc rack for TRK and TRS bench models	
650065 8FRJ650065	Stainless steel trolley for GN 2/1 tray (tray excluded) for TR210. Recommended for collecting cut products, to be positioned under the product outlet	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

TRS - TR210

Code	Spare Part Description	Picture
653632 8FRJ653632	Container for 1 cutting disc (Ø 175 mm and 205 mm)	

XBM10 - XBE10

Code	Spare Part Description	Picture
653276 8FRJ653276	10 l stainless steel tank for XBM10 -XBE10	
653269 8FRJ653269	Stainless steel whisk for XBM10-XBE10	
653267 8FRJ653267	Spatula for XBM10-XBE10	
653268 8FRJ653268	Hook for XBM10-XBE10	

XBM20 - XBE20 - XBB20

Code	Spare Part Description	Picture
650121 8FRJ650121	20 l stainless steel tank for XBM20-XBE20-XBB20	
653114 8FRJ653114	Hook for XBM20-XBE20-XBB20	
653116 8FRJ653116	Spatula for XBM20-XBE20-XBB20	
653109 8FRJ653109	Stainless steel whisk for XBM20-XBE20-XBB20	
653254 8FRJ653254	Reinforced stainless steel whisk for XBM20-XBE20-XBB20	
653434 8FRJ653434	Steel table with shelf for 20 liter planetary mixers (excluding XBB20)	
650122 8FRJ650122	10 liter reduction kit (bowl, hook, spatula and whisk) for 20 liter mixer XBM20 -XBE20-XBB20	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

XBM20 - XBE20 - XBB20

Code	Spare Part Description	Picture
0D7870	10 l stainless steel tank for reduction kit 650122	
0KQ278	Hook for reduction kit 650122-4	
0KQ277	Spatula for reduction kit 650122-4	
0H1017	Stainless steel whisk for reduction kit 650122-4	
653562 8FRJ653562	Trolley for 20/30 liter tank (cannot be used if the wheel kit frame code 653552 is installed on the XB)	
653552 8FRJ653552	3-wheel frame to be fixed to 20/30/40 lt mixers (XB models only)	

XBM30 - XBE30 - XBB30

Code	Spare Part Description	Picture
650123 8FRJ650123	30 l stainless steel tank for XBM30-XBE30-XBB30	
653161 8FRJ653161	Hook for XBM30-XBE30-XBB30	
653165 8FRJ653165	Spatula for XBM30-XBE30-XBB30	
653166 8FRJ653166	Stainless steel whisk for XBM30-XBE30-XBB30	
653253 8FRJ653253	Reinforced stainless steel whisk for XBM30-XBE30-XBB30	
650124 8FRJ650124	10 liter reduction kit (bowl, hook, spatula and whisk) for 30 liter mixer XBM30-XBE30-XBB30	
0D7871	10 l stainless steel tank for reduction kit 650124	
650125 8FRJ650125	20 L reduction kit (bowl, hook, spatula and whisk) for 30 L mixer XBM30 -XBE30-XBB30	



XBM30 - XBE30 - XBB30

Code	Spare Part Description	Picture
0D7813	20 l stainless steel tank for reduction kit 650125	

Accessories For Planetary Mixers

Code	Spare Part Description	Picture
653720 8EXT653720	70 mm aluminum meat mincer (MMH70) with H-type connection	
653724 8EXT653724	82 mm aluminum meat mincer (MMH82) with H-type connection	
653721 8EXT653721	"Enterprise" aluminum grinding kit for 70 mm meat mincer	
653726 8EXT653726	"Enterprise" aluminum grinding kit for 82 mm meat mincer	
653722 8EXT653722	"Enterprise" stainless steel grinding kit for 70 mm meat mincer	



Accessories For Planetary Mixers

Code	Spare Part Description	Picture
653725 8EXT653725	"Enterprise" stainless steel grinding kit for 82 mm meat mincer	
653723 8EXT653723	"1/2 Hunger" stainless steel grinding kit for 70 mm meat mincer	
653727 8EXT653727	"1/2 Hunger" stainless steel grinding kit for 82 mm meat mincer	
653187 8FRJ653187	Puree/food mill with H-type attachment mod. P200 complete with 3 stainless steel sieves of 1.5-3-6 mm	
653225 8FRJ653225	Vegetable cutter with H-type connection mod.CX21D complete with ejector (without discs) detachable transmission	

Accessories for Dynamic Preparation

Code	Spare Part Description	Picture
0S3137	Manual bench can opener Dimensions 180x80mm Maximum height 550mm	

Accessories for Cold Rooms

Code	Spare Part Description	Picture
092010	Ideal for reducing heat loss when opening the cell doors - dim. Door hole width 610/700 (mm) Door hole height 1900 (mm)	
0S1813	Ideal for reducing heat loss when opening the cell doors - dim. Door hole width 800 (mm) Door hole height 1900 (mm)	
092509	Ideal for reducing heat loss when opening the cell doors - dim. Door hole width 950 (mm) Door hole height 1900 (mm)	
0S2116	Ideal for reducing heat loss when opening the cell doors - dim. Door hole width 1174 (mm) Door hole height 2000 (mm)	
0S2372	Ideal for reducing heat loss when opening the cell doors - dim. Door hole width 1174 (mm) Door hole height 2400 (mm)	
0S2373	Ideal for reducing heat loss when opening the cell doors - dim. Door hole width 1574 (mm) Door hole height 2400 (mm)	
097575	Ideal for reducing heat loss when opening the cell doors - dim. Door hole width 1574 (mm) Door hole height 2800 (mm)	
0S2374	Ideal for reducing heat loss when opening the cell doors - dim. Door hole width 1974 (mm) Door hole height 2800 (mm)	
097573	Ideal for reducing heat loss when opening the cell doors - dim. Door hole width 1974 (mm) Door hole height 3200 (mm)	
097574	Ideal for reducing heat loss when opening the cell doors - dim. Door hole width 2374 (mm) Door hole height 3200 (mm)	

Accessories for Breeding Station

Code	Spare Part Description	Picture
095791	Cleaning kit Complete cleaning kit Kit contents: 095780 Universal brush Ø 110 mm 095781 Hard plastic spatula 095846 Pipe cleaners with nylon bristles Ø 9 mm Code Qt. Description 095779 4 Nylon brush, 095780 1 Round brush, 095781 1 Scraper	



Accessories for Breeding Station

Code	Spare Part Description	Picture
095780	Universal round brush with hard bristles; Ø 110	
095781	Hard plastic spatula; 100x250	
095846	Pipe cleaners with nylon bristles Ø 9 mm Code Qt. Description 095779 4 Nylon brush	
095782	Multipurpose brush Universal multipurpose brush with hard bristles Dimensions (mm) 100x100x260	
095815	Chicken breeding basket Ergonomic handling for optimal shaking Dimensions (mm) 286x358x96	
094869	White breeding tray Dimensions (mm) 580x350x170	
094861	Gray breeding tray Dimensions (mm) 580x350x170	
095806	White Breeding Pan Lid Description: White lid	



Accessories for Breeding Station

Code	Spare Part Description	Picture
096110	Crumb collector Description: to be used with trays codes 094869 and 094861	
095783	Conical stainless steel chicken washing basket Dimensions (mm) Ø230 / Ø179	
095680	Stainless steel chicken washing basket Dimensions (mm) Ø220	
095400	Collar for wash baskets to be used with baskets codes 095783 and 095680	
095753	Sieve basket for flour filtering Dimensions (mm) Ø250	
094903	Removable sink filter diam 160mm	
095687	Removable sink filter diam 225mm	



Accessories for Breeding Station

Code	Spare Part Description	Picture
095758	Storage tray for refrigerated area Dimensions (mm) 410x240x330	
095580	Collecting tray for dough balls Dimensions (mm) 410x240x330	
095788	Left hopper with wide discharge and grate	
095789	Right hopper with wide discharge and grate	
095681	Extended breeding tray support assembly WxDxH (mm) 662x370x150	
095682	Inclined breeding tray support assembly WxDxH (mm) 650x450x360	
094856	Suction filter with handle WxDxH (mm) 580x190x64	
09A1K9	Molded cap for breeding tray Description: to be used with trays codes 094869 and 094861	

Anti-Vibration Plates

Code	Spare Part Description	Picture
0S2762	Anti-vibration plates Rubber and composite material. Superior shock-absorbing effect compared to cork or solid rubber plates. Resistant to oil and humidity. Maximum load: 3.5 kg/cm2 LxDxH (mm) 50x50x22 Pack of: 5 pieces Code Qt. Description 0S3254 5 Rubber bumper; 50x50x22mm	
0S2763	Anti-vibration plates Rubber and composite material. Superior shock-absorbing effect compared to cork or solid rubber plates. Resistant to oil and humidity. Maximum load: 3.5 kg/cm2 LxDxH (mm) 76x76x22 Pack of: 10 pieces	
0S2764	Anti-vibration plates Rubber and composite material. Superior shock-absorbing effect compared to cork or solid rubber plates. Resistant to oil and humidity. Maximum load: 3.5 kg/cm2 LxDxH (mm) 101x101x22 Pack of: 5 pieces	
0S2765	Anti-vibration plates Rubber and composite material. Superior shock-absorbing effect compared to cork or solid rubber plates. Resistant to oil and humidity. Maximum load: 3.5 kg/cm2 LxDxH (mm) 152x152x22 Pack of: 5 pieces	
0S2766	Anti-vibration plates Rubber and composite material. Superior shock-absorbing effect compared to cork or solid rubber plates. Resistant to oil and humidity. Maximum load: 3.5 kg/cm2 LxDxH (mm) 457x457x22 Pack of: 1 piece	

Basins


Code	Spare Part Description	Picture
082468	PVC tray GN 2/1 h=200mm WxDxH (mm) 530x650x200 GN: 2/1	
095466	Plastic tray GN 1/1 h=65mm WxDxH (mm) 530x325x65 GN: 1/1	
087024	Plastic tray GN 1/1 h=100mm WxDxH (mm) 530x325x100 GN: 1/1	



Basins

Code	Spare Part Description	Picture
095467	Plastic tray GN 1/1 h=150mm WxDxH (mm) 530x325x150 GN: 1/1	
080702	Plastic fish tray GN 1/1 h=200mm without false bottom cod. 080901 WxDxH (mm) 530x325x200 GN: 1/1	
080901	False bottom in AISI 304 steel for fish bowl cod. 080702 WxDxH (mm) 457x255x5 Compatible: 080702	
0A8858	PVC fish tray h=210mm without false bottom cod. 0A8860 WxDxH (mm) 400x600x210	
0A8860	False bottom in AISI 304 steel for fish bowl cod. 0A8858 WxDxH (mm) 381x581x21 Compatible: 0A8858	

Castors

Code	Spare Part Description	Picture
0S1070	Kit of 4 projecting wheels (two with brake) Diam. 100mm, (PNC 855030) With 40x40mm square expansion Compatible with: Refrigerated tables Code Qt. Description 033655 4 Plastic square expander; 40x40 , 033656 2 Castor with brake , 033657 2 Castor without brake	
0S2631	Kit of 2 swivel wheels Kit of 2 wheels (one with brake) for fridge Compatible with: fridge cabinets	
0S2598	Kit of 4 swivel wheels Kit of 4 swivel wheels (2 with brakes) for refrigerator cabinets, diam. 125mm (PNC 881002) Compatible with: refrigerator cabinets; not for models with glass door and remote	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

Castors


Code	Spare Part Description	Picture
0S2633	Kit of 4 swivel wheels Kit of 4 swivel wheels (2 with brake) diam. 50 mm Compatible with: refrigerator cabinets; not for remote models	
0S2630	Kit of 6 swivel wheels Kit of 6 swivel wheels (2 with brake) diam. 50 mm Compatible with: Double door refrigerator cabinets, not for remote models	
0S2632	4 wheel kit 4 wheel kit for 250 lt table/saladette Compatible with: 250 lt table/saladette	

Grids

Code	Spare Part Description	Picture
082307	Chromed grille for Slim models with upstand on one side WxDxH (mm) 530x530x40	
082729	White Rilsan grill GN 1/1 with 4 feet H= 20mm WxDxH (mm) 325x530x20	
082885	GN 2/1 white Rilsan grill with splashback on the short side and anti-tipping block WxDxH (mm) 530x650x20	
081883	AISI 304 GN 2/1 steel grill with splashback on the short side and anti-tipping block WxDxH (mm) 530x650x40	
083595	White rilsan grid WxDxH (mm) 400x600x6	
083615	GN 1/1 gray rilsan grill with 4 feet H=25mm WxDxH (mm) 325x530x25	



Grids



Code	Spare Part Description	Picture
093252	GN 2/1 gray rilsan grill with splashback on the short side WxDxH (mm) 530x650x40	
083734	Gray rilsan grill with splashback on the long side for prostore WxDxH (mm) 400x530x20	
083785	GN 2/1 gray Rilsan grill with splashback on the long side WxDxH (mm) 530x650x40	
083911	Gray Rilsan grill with backsplash on one side WxDxH (mm) 530x530x60	
094105	Gray rilsan grill for Prostore 900 / 720lt ice cream parlor models with splashback on the long side WxDxH (mm) 530x700x40	
095010	AISI 304 steel grill for Prostore 470lt with splashback on the long side WxDxH (mm) 530x700x40	
099619	Gray Rilsan grill for 400lt wine fridge with splashback on the long side WxDxH (mm) 430x600x35	
099876	Gray Rilsan grill for 160lt refrigerator shelf lower part of the cell WxDxH (mm) 475x275x8.5	
095643	Gray rilsan grid for undercounter refrigerator 160lt cell shelf WxDxH (mm) 530x410x8.5	
095644	Gray Rilsan grill for undercounter refrigerator 160lt shelf lower part of cell WxDxH (mm) 475x175x6	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

Grids

Code	Spare Part Description	Picture
0PRAX6	Reinforced stainless steel grill for PASTRY LINE refrigerators WxDxH (mm) 600x800x25 Material: reinforced stainless steel	
0PRAX7	Reinforced stainless steel grill for PASTRY LINE refrigerators WxDxH (mm) 600x800x25 Material: rilsan	
0PRAY1	Stainless steel grid for PASTRY LINE refrigerator tables WxDxH (mm) 400x600x10 Material: stainless steel	
0PRAY2	Rilsan grid for PASTRY LINE refrigerator tables WxDxH (mm) 400x600x10 Material: rilsan	
0A8650	White rilsan grill for 400lt refrigerator shelf for cell WxDxH (mm) 410x600x2	
095009	Stainless steel grill for Prostore 470lt with splashback on the short side WxDxH (mm) 442x520x40	
094169	Gray Rilsan grill for Prostore 470lt with splashback on the short side WxDxH (mm) 442x520x40	
095008	AISI 304 GN 2/1 steel grill with splashback on the long side WxDxH (mm) 650x530x20	
0A8876	Perforated shelf GN 2/1 perforated shelf for bottles WxDxH (mm) 530x650x15	
087222	Meat hook with 4 hooks WxDxH (mm) 530x650x40	



Genuine Replacement Parts, Accessories and Consumables Catalogue

Accessories and Consumables

Grids

Code	Spare Part Description	Picture
095231	Gray rislan grill GN 1/1 Ecostore HP & CL table top WxDxH (mm): 325x530x9	
0S3211	AISI 304 steel grill without upstand LxDxH (mm) 530x530x6	
032407	Meat hook with 4 hooks LxDxH (mm) 530x650x40	

Modular Shelving

Code	Spare Part Description	Picture
0IM002	FLOOR; 1500X373MM; Material: Aluminium	
0IM000	FLOOR; 1700X373MM; Material: Aluminium	
0IM001	FLOOR; 1700X475MM; Material: Aluminium	
0IM041	FLOOR; 1700X577MM; Material: Aluminium	
0IM058	FLOOR; 2000X475MM; Material: Aluminium	
0IM054	CENTRAL STAND; 1550x373; Material: Aluminium	
0IM055	CENTRAL STAND; 1700x373; Material: Aluminium	
0IM056	CENTRAL STAND; 1700x475; Material: Aluminium	



Modular Shelving

Code	Spare Part Description	Picture
0IM059	CENTRAL STAND; 2000x373; Material: Aluminium	
0IM005	Grilled Shelf; 373X708mm; Plastic	
0IM006	Grilled Shelf; 373X798mm; Plastic	
0IM007	Grilled Shelf; 373X886mm; Plastic	
0IM008	Grilled Shelf; 373X974mm; Plastic	
0IM009	Grilled Shelf; 373X1062mm; Plastic	
0IM010	Grilled Shelf; 737X1152mm; Plastic	
0IM013	Grilled Shelf; 373X1505mm; Plastic	
0IM046	SHELF; 475X708MM; Polyethylene	
0IM047	SHELF; 475X798MM; Polyethylene	
0IM048	SHELF; 475X886MM; Polyethylene	
0IM037	SHELF; 475X974MM; Polyethylene	
0IM049	SHELF; 475X1062MM; Polyethylene	
0IM050	SHELF; 475X1152MM; Polyethylene	
0IM051	SHELF; 475X1240MM; Polyethylene	



Modular Shelving

Code	Spare Part Description	Picture
0IM043	SHELF; 1330X475MM; Polyethylene	
0IM042	SHELF; 1505X475MM; Polyethylene	
0IM014	Joint Profile; 373mm; For Angle	
0IM015	Joint Profile; 475mm; For Angle	
0IM039	Joint; L=577mm	
0IM06H	JOINTS FOR CORNER SHELVES	
0IM06D	FLOOR; 1550X373MM; Aluminum	
0IM06B	FLOOR; 1700X475MM; Aluminum	
0IM06E	CENTRAL STAND; 1550X373; Aluminum	
0IM06I	CENTRAL FLOOR;1700X373; Aluminum	
0IM06J	POLYETHYLENE GRID DIM 88X373MM	
0IM06K	POLYETHYLENE GRID DIM 88X475MM	
0IM06L	POLYETHYLENE GRID DIM 88X577MM	



Modular Shelving

Code	Spare Part Description	Picture
0IM06F	GRILLED SHELF; 373X708MM; ALU/POLY	
0IM06G	GRILLED SHELF; 373X798MM; ALU/POLY	
0IM06P	GRILLED SHELF; 373X974MM; ALU/POLY	
0IM06Q	GRILLED SHELF; 475X532MM; ALU/POLY	
0IM06Z	GRILLED SHELF; 475X708MM; ALU/POLY	
0IM06A	Complete Shelf attachment 4pcs right/left kit Code Qt. Description 0IM016 2 Connection; left/right	
0IM070	CENTRAL FLOOR LAMP; 1700X475; Aluminum	

Shelf Guides

Code	Spare Part Description	Picture
093849	Stainless steel guide for Ecostore models kit consisting of right and left guide Compatible with: ecostore; NPT; NAU Length: 645.5 mm Steel type: AISI 304 Code Qt. Description 093358 1 Sliding runner; left aisi 304 l=645,5mm, 093359 1 Sliding runner; right aisi 304 l=645,5mm	
097444	Stainless steel guide for Ecostore models kit consisting of right and left guide Compatible with: ecostore; NPT; NAU Length: 645.5 mm Steel type: AISI 430 Code Qt. Description 093250 1 Guide; left aisi 430 l=645.5mm , 093251 1 Guide; right aisi 430 l=645.5mm	
097627	Stainless steel guide for Ecostore models kit consisting of right and left guide Compatible with: ecostore; HP; CL and BL Length: 530.40mm Steel type: AISI 430	



Shelf Guides

Code	Spare Part Description	Picture
093851	Stainless steel guide for Heavy Duty models set 2pcs DX and SX 650-1400 lt Compatible with: HD; PT 3; 650-1400 liters Length: 621.0 mm Code Qt. Description 0A9680 2 Runner; 621x20mm; aisi304; rh/lh	
093852	Stainless steel guide for Heavy Duty models set 2pcs DX and SX 550-1100lt Compatible with: HD; PT S; 550-1100 liters Length: 526.0 mm Code Qt. Description 0A9708 2 Runner; 526x20mm; aisi304	
093853	Sliding guide for Prostore models set of 2pcs right and left Compatible with: Prostore Length: 466.0 mm Code Qt. Description 082304 2 Runner; 466x20mm; aisi304	
093850	Sliding guide for Standard Benefit models set of 2pcs right and left Compatible with: Standard Benefit Length: 581.0 mm Code Qt. Description 082263 2 Runner; 581x20 mm; aisi304	

Wire Baskets

Code	Spare Part Description	Picture
082536	Chromed wire basket GN 2/1 h= 150 mm WxDxH (mm) 530x650x150 GN: 2/1	
082794	Gray rilsan wire basket GN 1/1 h= 150 mm WxDxH (mm) 530x325x150 GN: 1/1	

Measuring Gauges

Code	Spare Part Description	Picture
0S2342	Instrument for testing and tightness of gas and water systems Testo 324 kit	
0S0390	Flexible glass fiber thermocouple Length 1500 mm (use only with adapter 0S1019) measuring range -50 ÷ +400°C	
0S2231	3/8" and 3/4" high pressure fitting	
0S2232	1/2" and 1" high pressure fitting	
0S2233	2 m hose with FF quick coupling	
0S0918	Digital carbon monoxide detector Testo 317-3 Instrument that signals the presence of CO concentrations	
0S3217	Testo 270 BT cooking oil tester Tool for measuring oil quality and temperature. Bluetooth for connection to the testo Smart App. Oil working temperature from +40 to +200 °C Protection class IP65 and waterproof and can be washed under running water. Battery life approximately 25h (500 measurements). Battery type: 2xAAA Complete with washable case	



Measuring Gauges

Code	Spare Part Description	Picture
0S0830	Testo 410-2 Vane Anemometer Air velocity meter with Ø40mm vane sensor for relative humidity and room temperature. Measuring range from 0.4 to 20m/s; from 0 to 100%RH and from -10 to + 50 °C. Including protective cap, test protocol and batteries.	
0S2108	Testo 510 gas micromanometer differential pressure gauge with temperature compensated sensor. Measuring range from 0 to 100 hPa Including protective cap, test protocol and batteries.	
0S2470	Testo 606/2 hygrometer instrument for measuring humidity in wood and materials using a tip sensor. It also measures humidity in ambient air to check goods storage and drying conditions. Measuring range -10°C to +50°C Batteries: 2 AAA (included)	
0S0831	Tachometer Testo 460 instrument for measuring rotation speed with protective cap, test protocol Measuring range from 100 to 29,999 rpm Batteries included	
0S0832	Surface thermometer Testo 810 Air and surface thermometer with infrared sensor and laser pointer Measuring range: air from -10 to +50 °C IR surfaces from -30 to +300°C Including protective cap, test protocol and batteries	
0S1984	SAVERIS 2 T2 WI-FI data logger. With display and 2 ports for NTC temperature probes. Use it to measure temperatures and door contacts in warehouses, cold rooms, and work environments. The temperature or door contact values detected by the connectable probes are reliably displayed even after long periods of time and transmitted via WLAN directly to the Testo Cloud (saveris.net online database. Notice: a user license has to be already active). Using your internet-connected smartphone, tablet, or PC, you can access these measurement values anytime, anywhere.	
0S1985	Aluminum tube probe - IP65	
0S1745	Testo 316-3 refrigerant gas leak detector	



Measuring Gauges

Code	Spare Part Description	Picture
0S0837	Testo 316-4 refrigerant gas leak detector	
0S1265	Refrigerant exchange sensor for all the most common refrigerant gases: CFC, HCFC, HFC	
0S1282	FLUKE 117 digital multimeter	
0S1456	FLUKE 323 current clamp	
0S1152	probe for flat surfaces -60°..+400°C (code 0602.1993)	
0S1158	waterproof immersion-penetration probe -50°..+400°C (code 0602.1293)	
0S1400	ultra-fast probe for mixed surfaces -50°..+300°C (code 0602.0393)	
0S1401	waterproof surface probe with small measurement terminal (TC type K) -60°....+1000°C	



Measuring Gauges

Code	Spare Part Description	Picture
0S1118	TX2000 Microwave Detector Instrument for detecting microwave leakage is a robust and compact instrument, with a unique RF power measurement range designed to operate in the 2.45 GHz frequency range. The instrument is calibrated and has an international calibration certificate	
0S2400	Plastic suitcase	
0K7904	Analog liter counter Kit	
0S0478	Water pressure gauge	
0S0480	Gas pressure gauge	
0S0586	Hardness analysis manual instrument (about 300 tests)	
0S2255	Replacement pH electrode for 0S2245 meter	



Measuring Gauges

Code	Spare Part Description	Picture
0S0585	Manual instrument for Chloride Analysis (about 200 tests)	
0S2246	Buffer solution pH 7.01 HI70007P	
0S2247	Buffer solution pH 4.01 HI70004P	
0S2248	Conductivity solution at 1413 S/cm HI70031P	
0S1707	HI70032P 1382 ppm TDS solution	
0S2968	Environmental measurement instrument with differential pressure sensor Testo 440Dp Differential pressure sensor included, for Pitot tube measurements and filter monitoring. Ideal for regulating ventilation and air conditioning systems, monitoring air quality or analyzing comfort, thanks to the countless combination possibilities with the right digital probes (which can be ordered separately). Up to 3 probes can be connected simultaneously: a Bluetooth probe, a cable probe and a K-type thermocouple temperature probe. Technical data: - measuring ranges from -150 to +150 hPa (resolution 0.01 hPa) - temp. working temperature -20°C to +50°C - weight 250 g - dim.mm 154x65x32h The kit contains: - flexible connection tube - 3 AA batteries - USB cable - testing protocol.	



Measuring Gauges

Code	Spare Part Description	Picture
0S0904	Testo infrared printer Complete with 1 roll of thermal paper and 4 AA batteries	
0S2970	Testo 549i Bluetooth high pressure gauge Measurement of high and low pressure. Ideal for maintenance and fault identification of air conditioning and refrigeration systems. Through the Testo Smart App it also allows you to automatically calculate the evaporation and condensation temperatures. Bluetooth® with range up to 100m. 3 x AAA batteries and test protocol included.	
0S2113	Testo 510i Bluetooth differential pressure gauge Suitable for measuring pressure tightness testing and for flow calculation. Can also be used via the Testo Smart App for Smartphones and Tablets. Bluetooth® with range up to 100m. 3 x AAA batteries and test protocol included.	
0S2610	Testo 330-1 LL V3 kit combustion analyzer The instrument is a multi-function Bluetooth smoke combustion analyzer capable of carrying out all types of measurements on heating systems; equipped with a high resolution color display, with graphic representation of the measurements and measurement menus that are easy to consult. Memory of up to 500,000 measurements. Prepared for the UNI 10845 fine draft external probe.	
0S2972	Testo 300 Next Level combustion analyzer KIT *Without printer	
0S2831	Digital manometer unit Testo 550S BLUETOOTH Kit	
0S2967	Testo Smart Probes Bluetooth Refrigeration Kit The kit includes: - 2 testo 115i clamp thermometers code 0S2971 - 2 testo 549i high pressure meters code. 0S2970 - 1 text Smart Case	
0S2731	Data Logger 175 T3 with display for measuring temperature, two ports for connecting external thermocouple probes (type T or type K). Particularly convenient for frequent or continuous measurements are the memory, for 1 million measurement values, and the battery life, which can reach up to 3 years.	
0S2853	Data Logger 176 T4 with display for measuring temperature, four ports for connecting external thermocouple probes (type TK and J). Particularly convenient for frequent or continuous measurements are the memory, for 2 million measurement values, and the battery life, which can reach up to 8 years.	



Measuring Gauges

Code	Spare Part Description	Picture
0S2732	USB cable for PC connection	
0S2234	Flexible air probe	
0S2854	Type K temperature probe TC connector and fiberglass insulation for quick and easy temperature measurement.	
0S2579	Ethernet LAN cable tester	
0S2804	Digital refractometer Instrument for analyzing sugar content in foods and drinks. Suitable for correct installation and verification of any anomalies in cold drink dispensers, slush machines, cold creams and soft ice cream. Reports results with an accuracy of +/-0.2% Brix. The glass prism and stainless steel measuring cell are easy to clean. Watertight, IP65 protection. Complete with batteries and user manual.	
0S2744	Electronic scale with 5kg capacity	
0S2745	Electronic scale with 5kg capacity	
0S2746	Electronic scale with 5kg capacity	



Measuring Gauges

Code	Spare Part Description	Picture
0S1756	Electronic scale with 30kg capacity	
0SR805	Stainless steel goods support surface Capacity 10kg; 2g division	
0SR806	Stainless steel goods support surface Capacity 20kg; division 2-5gr	
0S2364	Stainless steel goods support surface Capacity 40kg; 5g division	
CS0009	LAB PACK water analysis case complete with: • Conductivity meter/pH meter code 0S2889 • Manual chloride analysis instrument (approximately 200 tests) code 0S0585 • Electrode preservation solution code 0S2383 • Total and partial carbonate hardness kit code 0S1701 • Carbonate analysis, set of 100 test sticks, code 0S2916 • Total iron analysis, set of 100 test sticks, code 0S2917 • Plastic case dim 500x380x195mm code 0S2954 *The components may not be delivered in a single solution Code Qt. Description 0S0585 1 Tt chloride test kit chemical kit; adr&img&iata limited quantity, 0S1701 1 Carbonate and total hardness test adr & img & iata exempted quantity, 0S2383 1 Solution, 0S2889 1 Conductivity meter ph-meter, 0S2916 1 Carbonates chemical analysis; 100 test sticks, 0S2917 1 Iron chemical analysis; 100 test sticks, 0S2954 1 Tools case; abs dim. 500x380x195mm	
0S2957	BASIC KIT water analysis case complete with: • Portable, waterproof PH, EC, TDS and temperature meter, cod. 0S2245 • Kit for total and partial hardness from carbonates cod. 0S1701 • Carbonate analysis, set of 100 test sticks, cod. 0S2916 • Total iron analysis, set of 100 test sticks, cod. 0S2917 • Plastic case dim 370x270x85mm cod. 0S2955 Code Qt. Description 0S1701 1 Carbonate and total hardness test adr & img & iata exempted quantity, 0S2245 1 Measurer, 0S2916 1 Carbonates chemical analysis; 100 test sticks, 0S2917 1 Iron chemical analysis; 100 test sticks, 0S2955 1 Tools case; abs dim. 370x270x85mm	



Measuring Gauges

Code	Spare Part Description	Picture
0S2383	Electrode storage solution 230 ml bottle	
0S2889	Conductivity meter/ph meter complete with probe and buffer solutions measuring range: 0÷ 3999 S/cm	
0S2992	High pressure probe 0...25 bar for Testo 312-4 for pressure tests on water/gas systems	
0S3014	Digital Refrigerant Scale with Smart Valve Bluetooth® Kit Testo 560i Automatic and precise charging of refrigerant based on superheat, subcooling and target weight thanks to the smart valve. Wireless connection and operation with manifolds and Smart App via Bluetooth. All measured values for the charging process with saving of measured values in the Smart App. Easy to handle thanks to the practical carrying handle and durable plastic case. Resolution 10g, maximum load 100kg.	
0S3015	Bluetooth® refrigerant valve Wireless connection and operation with Testo manifolds and Smart App via Bluetooth. Compatible with testo 560i, Testo 557s/550s/550i and testo 557 /550 manifolds, Testo Smart Probes 115i/549i/605i and the Testo Smart App for Android and iOS	
0S3011	Testo 104-IR digital thermometer with penetration and infrared probe 2-point laser sensor with 10:1 focusing Complete with removable penetration probe Probe measuring range from -50 to +250 °C, resolution 0.1°C. Infrared measuring range from -30 to +250 °C, resolution 0.1°C. Certified to European standard EN 13485 and HACCP compliant Waterproof (IP65) Dimensions 178 x 48 x 23 mm Complete with 2 AAA batteries and testing protocol	
0S3091	Differential pressure measuring instrument Testo 512-1 Fast, simple and precise differential pressure measurement. You can use it to check the gas pressure in the burners, check the filters and make Pitot tube measurements in the ventilation duct. It ensures reliable and highly precise measurement results. Can be connected to the Testo Smart App. Technical data: - measuring ranges from 0 to 200 hPa (resolution 0.001/0.1 hPa) - temp. working temperature -20°C to +50°C - weight 190 g - dim.mm 146x60x28h The kit also contains: - Transport case - flexible connection tube - 3 AA batteries - testing protocol	



Measuring Gauges

Code	Spare Part Description	Picture
0S3092	Testo 925 digital thermometer connectable to the Smart App. Thermometer with one channel designed for TYPE K probes 3-digit liquid crystal display measuring range: from -50° to +1000°C backlit display, possibility of printing the measured data. Dim. 135 x 60 x 28 mm Complete with: Type K TC probe Case, 3 AA batteries, Test protocol.	
0S3093	Smart Testo 570s digital pressure gauge kit with 4-way valve block, Bluetooth and intelligent error analysis via Smart App, is ideal for wireless measurements on refrigeration circuit systems. All probes connect automatically to the manifold via Bluetooth. - The current 40 refrigerant liquids (including A3 and A2L) are already registered in the instrument with the possibility of free updating. Measuring ranges: from -1 to 60 bar; Temperature: -50°C to +150°C; Pressure resolution 0.01 bar Protection class: IP54 Complete with: - 2 testo 115i wireless clamp thermometric probes (code 0S2971) - 1 testo 552i wireless vacuum probe (code - rigid ABS case with shaped interior - testo Smart App (free download) - testing protocol and instruction manual	
0S1344	Testo 108 Digital Thermometer Suitable for temperature measurements in the food industry. Waterproof, protection class IP67. HACCP compliant, EN 13485 certified. Dimensions 140x60x24mm Complete with: - penetration temperature probe (TC type T) -50 to +300 °C - soft case - batteries (3 x AAA) - test protocol	
0S3189	EC Waterproof Meter Pocket-sized instrument for measuring water conductivity. Multi-level display, integrated temperature sensor and automatic calibration. Scale: EC from 0 to 2000 S/cm, Temp from 0 to 50°C Resolution: EC 1 S/cm , Temp. 0.1°C Accuracy:	
0S1583	Universal vacuum and charging kit with digital manifold and 100 kg scale Supports over 50 refrigerant gases Small size and extremely easy to transport Equipped with: - Tool trolley - Double stage vacuum pump 46 lt/min - FOX300 digital manifold complete wi	
0S2888	180 lt/min double stage high vacuum pump with solenoid valve and analogue vacuum gauge Professional line: High reliability, High efficiency, lightweight, IP54 protection rating, Non-combustible (R32-R1234yf). Equipped with: - Mineral oil bottle - carrying	



Measuring Gauges

Code	Spare Part Description	Picture
0S1585	46 lt/min double stage high vacuum pump with solenoid valve and analogue vacuum gauge Professional line: High reliability, High efficiency, lightweight, IP54 protection rating, Non-combustible (R32-R1234yf). Equipped with: - Mineral oil bottle - carrying	
0S3237	198 lt/min double stage high vacuum pump with BT connection to Smart App Fully automatic system evacuation process with integrated maintenance test. Safe to use even with flammable refrigerants of classes A3 and A2L. Non-return valve to prevent vacuum loss	
0S3218	Testo 108 Digital Food Thermometer	
0S3221	Bluetooth laser distance meter for App connection. Ideal for measuring distances and determining surfaces and volumes. Complete with case and batteries (AAA). Technical data: • measurement capacity from 50 mm to 100 m. • min. displayed unit 1 mm • weight	
0S3276	Mini Data logger 174T kit Instrument that monitors the temperature of foods, ensuring constant monitoring of the cold chain. With the help of software it is possible to program and read the temperature data logger, as well as analyse the data on the PC. For this purpose Testo offers a version of the ComSoft Basic software that can be downloaded free of charge. Complete with USB-C interface for data transfer to the PC, wall bracket, battery (2 x CR 2032 lithium) and test protocol. Data memory for 16,000 temperature values. Waterproof according to IP 65, HACCP compliant and certified according to EN 12830. Measuring range from -30 to + 70°C. Accuracy +/- 0.5 °C. Resolution 0.1 °C. Measuring cycle 1 min-24h. Dimensions 60 x 38 x 18.5 mm.	
0S3247	Portable vacuum switch. Vacuum measurement to check pump status and/or leaks in vacuum machines. Can be inserted inside the bell jar. Memory capacity: 20 tests. USB connection to a computer for data viewing and saving. USB rechargeable battery.	



Measuring Gauges

Code	Spare Part Description	Picture
0S3258	Testo 558S Digital Manifold Kit, the Bluetooth manifold for commissioning, servicing and maintaining systems. - Touchscreen display - App integration via Bluetooth for quick and easy control with on-site documentation - Refrigerant updates in the instrument via App - 4-way valve block for quick and efficient operation - The external Bluetooth vacuum probe supports evacuation of the system with an extremely precise measurement level. - Batteries rechargeable via USB-C - Degree of protection: IP54 Measuring range: - Pressure: -1 ... 60 bar - Temperature: -50 ... +150 °C - Vacuum: Measuring range 0 to 20,000 microns, Accuracy (10 microns + 10 % of mv) (100 to 1000 microns) Package contents: - 558S 4-way digital manifold - 2 Bluetooth clamp probes - 1 external BT vacuum probe - Rechargeable battery - USB-C cable - Case and test protocol	
0S3305	TESTO 162 T2 WI-FI Data Logger Connection to the testo Smart App with display for measuring temperature, two ports for connecting NTC temperature probes. Notifications: Push, email or SMS Includes: - USB cable - wall bracket with lock, batteries and test protocol. IP65 Measuring range: -30... +150 °C Memory 10,000 measurement values/channel Dim. mm 95 x 75 x 30.5" Paid cloud license required.	

Ppe

Code	Spare Part Description	Picture
0SE422	Blue washable filter mask with White logo	
0S2659	Protective visor Face shield with visor	
0S2653	Clear Goggles Safety glasses that has an indirect ventilation system that prevents fog, moisture and dust. UV protection certificate EN170, EN166 Class II PPE OX3000 transparent safety glasses	



Ppe

Code	Spare Part Description	Picture
0S2667	White 3M protective suit with PE hood size XL	
0S2668	White 3M protection suit with PE hood size 2XL	
0S2654	Infrared medical thermometer	
0S2675	High thickness blue nitrile glove size M	
0S2676	High thickness blue nitrile glove size L	
0S2677	High thickness blue nitrile glove size XL	
0S2640	Disposable nitrile gloves size L	



Genuine Replacement Parts, Accessories and Consumables Catalogue
Accessories and Consumables

Ppe

Code	Spare Part Description	Picture
0S2641	Disposable nitrile gloves size XL	
0S2662	Seat covers in HDPE 10m	
0S2663	Seat covers in LDPE BIO 13m	
0S2664	Protection film	
0S2665	Knob	
0S2666	Van interior protection kit (5pcs set)	
0S2672	White Tyvek HDPE coverall with hood, size 2XL	
0S2985	Heat protection gloves Contact resistant up to 350 °C for a short period Size 10 EN 388, EN 407, EN 420	
0SZ251	Black washable filter mask with logo	

Genuine Replacement Parts, Accessories and Consumables Catalogue


Accessories and Consumables

Tools

Code	Spare Part Description	Picture
0G6126	THERMA nozzle wrench in stainless steel used to remove/apply nozzles on pilot burners of Therma hobs	
0ST071	Clamping pliers for Speedelight upper plate	
0CB287	Oven fan extractor kit Code Qt. Description 0C8138 4 Screw; m6x25 , 0CK536 1 Idraulic puller for oven fan, 0CK617 1 Flange for hub blocking d30 , 0CK618 1 Threaded flange for extractor	
0S2336	1 Essentia maintenance sticker set 50 sheets/750 stickers Ø 35mm	
0ST072	Ratchet pliers for cannon cable. RJ45 Professional ratchet model Built-in wire stripper and wire cutter Uniform pressure and complete closing of the pliers to obtain optimal crimping Including screwdriver to release the ratchet if necessary For PLUG: 4/4 - 6/4 - 6/6 - 8 /8	
0ST017	Three-arm extractor 160x130 mm; M19 Narrow or wide interchangeable hook ends lock automatically. Self-tightening: by lever effect, the arms forcefully tighten the piece to be extracted. This makes the extraction process particularly safe.	
0CK86U	Flange for extractor kit To be used with extractor code 0ST017 Suitable for Skyline oven fans.	
0W4857 94081008	Belt tension meter Tool for obtaining the correct tension of transmission belts Suitable for any type of belt Sensitive from 20 to 600Hz Complete with unidirectional microphone and ABS case	
0CK638	OnE platform connectivity HUB (SIM version)	
0CK639	OneE platform connectivity HUB (LAN version)	



Tools

Code	Spare Part Description	Picture
0S2864	Set of 10 pcs of "Electrolux Professional" maintenance stickers	
0S3050	GourmeXpress Connector Extractor Removes male and female contacts from MATE-N-LOK Universal connectors	
0C0069	Spacer for glass ceramic support pack. of 8 pcs Code Qt. Description 0C5419 10 Spacer	
006451	Aluminized tape Length 50m Width 50mm	
0S1830	Eurover 2000 glass wool (roll format) used to insulate oven chambers, pasta cooker tanks, pots etc. covered on both sides with 15 micron thick aluminum foil Thickness 30 mm density 30 kg/m3 dim. 6000x850 mm	
0S3304	12pcs Gas Nozzle Reamer Set for Diameters (mm): 0.5/0.6/0.7/0.8/0.9 1.0/1.1/1.2/1.4/1.6/1.8/2.0 Complete with support	

Trolleys

Code	Spare Part Description	Picture
0S2578	Tool trolley case (tools excluded). Case in high thickness polypropylene 465x255x352mm, injection moulded. Great resistance to corrosive substances, impacts and high and low temperatures. The injection technique allows to obtain a constant thickness of the shell material, especially in the corners. Details: 2 metal lid support arms 2 key locks 3 metal rear hinges - Bottom with removable and adjustable dividers - Ergonomic rubber-coated handle - Name tag - Document holder area - Provision for an additional third panel	
0S1288	Tool assortment kit. Contents: • 2 flat screwdrivers, short type: 0.6x3.5x25mm - 1.2x6.5x25mm • 2 cross screwdrivers, blade length 25mm: PH1-PH2 • 1/4" nut driver in chrome-plated steel with flexible blade, 150mm • TORX screwdriver set (8 pcs), round-section blade, sizes TX10-15-20-25-27-30-40-45 • Insulated shank screwdriver set (5 pcs): 3 flat screwdrivers (2.5-4-6.5) and 2 cross screwdrivers (PH1-PH2) • Insulated shank flat screwdriver 1.2x8mm • 1/2" socket wrench set (32 pcs): 1 reversible ratchet handle, 2 extensions (100 and 150mm), 1 universal joint, 12 hex sockets from 4 to 12mm, 1 handle for sockets, 1 adaptor socket, 14 bits: PR1, 2, 3 • Hex key set (9 pcs) in chrome-vanadium steel, ball end, sizes 1.5-2-2.5-3-4-5-6-8-10mm • Through box spanner set (3 pcs) in chrome-vanadium steel, with hex and bi-hex heads, sizes 7-8-13mm • Ratcheting combination wrench set (6 pcs) with reinforced bi-hex head in chrome-vanadium steel, lengths from 135 to 250mm, sizes 8-10-12-13-17-19mm • Ratcheting combination wrench with reinforced bi-hex head in chrome-vanadium steel, length 286mm, size 22mm • Diagonal cutting pliers in steel, compliant with DIN ISO 5749, length 140mm • VDE insulated bent nose pliers, compliant with IEC 900:1997 and VDE 680/201, half-round 45° jaws, length 200mm, weight 185g • Adjustable pliers in chrome-vanadium steel, 7-position adjustment, 250mm, weight 350g • "Wrench pliers" in chrome-vanadium steel, 200mm, maximum opening 6-46mm, weight 550g • External circlip pliers with 90° tips, for circlips Ø16-60mm, length 165mm • Straight tweezers in alloy steel, polished nickel-plated, length 145mm, weight 25g • Medium cutter complete with 2 spare blades • Work scissors in special blued steel with plastic-coated handles • Adhesive tape • Blacksmith's hammer in C45 induction-hardened steel, DIN 1193 standard • Clogged panel for removing dust residues • Microactive cloth in special microfiber, high resistance, washable up to 90°C, size 360x320mm • Oval-shaped carpenter's pencil, length 180mm	



Trolleys

Code	Spare Part Description	Picture
0S2265	Tool trolley case (tools not included) High thickness polypropylene case, injection molded. High resistance to corrosive substances, impacts and high and low temperatures. The injection technique allows to obtain a constant thickness of the material of th	

Automatic Water Softeners

Code	Spare Part Description	Picture
0S1945	TIME automatic water softeners with ALIA valve AISI 304 cylinder: 5 lt; Resins per cylinder: 3.5 lt; Max flow rate: 1500 l/h; Brine: 10 kg; Salt for regeneration cycle: 0.6 kg; Food Electric: 230V 50/60 Hz; Water connections: Ø 3/4" G; Min/max pressure: 2-8 bar; Supply H2O temp.: 4-30°C; WxDxH: 230x360x460 mm	
0S1947	TIME automatic water softeners with ALIA valve AISI 304 cylinder: 12 lt; Resins per cylinder: 8.5 lt; Max flow rate: 1500 l/h; Brine: 25 kg; Salt for regeneration cycle: 1.5 kg; Food Electric: 230V 50/60 Hz; Water connections: Ø 3/4" G; Min/max pressure: 2-8 bar; Supply H2O temp.: 4-30°C; WxDxH: 285x405x595 mm	
0S2457	GIX TIME automatic water softeners with Autotrol 255 Logix 740 valve AISI 304 cylinder: 5 lt; Resins per cylinder: 3.5 lt; Max flow rate: 1500 l/h; Brine: 10 kg; Salt for regeneration cycle: 0.6 kg; Food Electric: 230V 50/60 Hz; Water connections: Ø 3/4" G; Min/max pressure: 2-8 bar; Supply H2O temp.: 4-25°C; WxDxH: 230x385x515 mm	
002454	GIX TIME automatic water softeners with Autotrol 255 Logix 740 valve - PNC 921305 - *water softener covered with stainless steel panels AISI 304 cylinder: 8 lt; Resins per cylinder: 5.6 lt; Max flow rate: 1500 l/h; Brine: 20 kg; Salt for regeneration cycle: 1.0 kg; Food Electric: 230V 50/60 Hz; Water connections: Ø 3/4" G; Min/max pressure: 2-8 bar; Supply H2O temp.: 4-25°C; WxDxH: 245x450x540 mm	



Automatic Water Softeners

Code	Spare Part Description	Picture
0S2458	GIX TIME automatic water softeners with Autotrol 255 Logix 740 valve AISI 304 cylinder: 12 lt; Resins per cylinder: 8.5 lt; Max flow rate: 1500 l/h; Brine: 25 kg; Salt for regeneration cycle: 1.4 kg; Food Electric: 230V 50/60 Hz; Water connections: Ø 3/4" G; Min/max pressure: 2-8 bar; Supply H2O temp.: 4-25°C; WxDxH: 285x425x650 mm	
0S2694	Automatic TIME water softeners with cabin with Autotrol 255 Logix 740 valve Fiberglass cylinder: 12 lt; Resins per cylinder: 8.5 lt; Max flow rate: 1500 l/h; Brine: 25 kg; Salt for regeneration cycle: 1.4 kg; Food Electric: 230V 50/60 Hz; Water connections: Ø 3/4" G; Min/max pressure: 2-8 bar; Supply H2O temp.: 4-25°C; WxDxH: 320x500x660 mm	
0S2459	LARGE VOLUMETRIC SERIES automatic water softeners with Autotrol 255 Logix 760 valve Fiberglass cylinder: 50 lt 10"x44"; Resins per cylinder: 35 lt; Max flow rate: 1500 l/h; Brine: 120 kg; Salt for regeneration cycle: 7.2 kg; Food Electric: 230V 50/60 Hz; Water connections: Ø 3/4" G; Min/max pressure: 2-8 bar; Supply H2O temp.: 4-25°C; WxDxH: cylinder: Ø271x1300mm brine: Ø541x810mm	
0S2460	LARGE VOLUMETRIC SERIES automatic water softeners with Autotrol 255 Logix 760 valve Fiberglass cylinder: 84 lt 13"x44"; Resins per cylinder: 59 lt; Max flow rate: 1500 l/h; Brine: 120 kg; Salt for regeneration cycle: 12.2 kg; Food Electric: 230V 50/60 Hz; Water connections: Ø 3/4" G; Min/max pressure: 2-8 bar; Supply H2O temp.: 4-25°C; WxDxH: cylinder: Ø360x1300mm brine: Ø541x810mm	
0S2696	Automatic VOLUMETRIC water softeners with cabin with Autotrol 255 Logix 760 valve Fiberglass cylinder: 12 lt; Resins per cylinder: 8.5 lt; Max flow rate: 1500 l/h; Brine: 25 kg; Salt for regeneration cycle: 1.4 kg; Food Electric: 230V 50/60 Hz; Water connections: Ø 3/4" G; Min/max pressure: 2-8 bar; Supply H2O temp.: 4-25°C; WxDxH: 320x500x660 mm	
0S2697	Automatic VOLUMETRIC water softeners with cabin with Autotrol 255 Logix 760 valve Fiberglass cylinder: 24 lt; Resins per cylinder: 17 lt; Max flow rate: 1500 l/h; Brine: 50 kg; Salt for regeneration cycle: 2.7 kg; Food Electric: 230V 50/60 Hz; Water connections: Ø 3/4" G; Min/max pressure: 2-8 bar; Supply H2O temp.: 4-25°C; WxDxH: 320x500x1120 mm	
0S2536	TIME automatic water softeners with 368 valve AISI 304 cylinder: 5 lt; Resins per cylinder: 3.5 lt; Max flow rate: 1500 l/h; Brine: 10 kg; Salt for regeneration cycle: 0.6 kg; Food Electric: 230V 50/60 Hz; Water connections: Ø 3/4" G; Min/max pressure: 2-8 bar; Supply H2O temp.: 6-25°C; WxDxH: 230x350x415 mm	



Automatic Water Softeners

Code	Spare Part Description	Picture
0S2535	TIME automatic water softeners with 368 valve AISI 304 cylinder: 12 lt; Resins per cylinder: 9 lt; Max flow rate: 1500 l/h; Brine: 25 kg; Salt for regeneration cycle: 1.5 kg; Food Electric: 230V 50/60 Hz; Water connections: Ø 3/4" G; Min/max pressure: 2-8 bar; Supply H2O temp.: 6-25°C; WxDxH: 285x400x550 mm	
0S2599	Water Softener	
0S3086	Automatic TIMED water softener that can be fed with hot water up to 70°C Resins per cylinder: 10lt Max flow rate: 1000lt/h Brine: 35kg Salt for regeneration: 1.4kg Power supply: 230V 50/60Hz Water connections: Ø 1" F/G Min/max pressure: 1.5-7 bar H2O supply temp.: 4-70°C Dimensions: 245x450x600mm	
0S3087	Automatic TIME water softener that can be fed with hot water up to 70°C Resins per cylinder: 22lt Max flow rate: 1800lt/h Brine: 75kg Salt for regeneration: 2.5kg Power supply: 230V 50/60Hz Water connections: Ø 1" F/G Pressure min/max: 1.5-7 bar Temp H2O supply: 4-70°C Dimensions: 200x188x1040mm	
0S3148	Automatic TIMED water softeners with ALIA valve Cabin (RC): Salt insertion, cleaning and maintenance easier. Anti-flooding and overflow incorporated. AISI 304 cylinder: 8 lt; Resins per cylinder: 5.6 lt; Max flow rate: 1500 lt/h; Brine: 20 kg; Salt per re	
0S3147	Automatic GIX TEMPO water softeners with Autotrol 255 Logix 740 valve Cabin (RC): Salt insertion, cleaning and maintenance easier. Anti-flooding and overflow incorporated. AISI 304 cylinder: 8 lt; Resins per cylinder: 5.6 lt; Max flow rate: 1500 lt/h; Bri	



Automatic Water Softeners

Code	Spare Part Description	Picture
0S3267	Automatic TIMED water softeners with 368 valve. AISI 304 cylinder: 8 lt; Resins per cylinder: 5.5 lt; Max flow rate: 1500 lt/h; Brine: 20 kg; Salt per regeneration cycle: 1.0 kg; Power supply: 230V 50/60 Hz; Water connections: Ø 3/4" G; Min/max pressure: 2-8 bar; Water supply temp.: 6-25°C; LxDxH: 275x445x450 mm enclosure (REK): Salt addition, easier cleaning and maintenance. Built-in anti-flooding and overflow.	
0S3288	Automatic GIX VOLUMETRIC water softeners with Autotrol 255 Logix 740 valve. Enclosure (RC): Easier salt addition, cleaning and maintenance. Built-in anti-flooding and overflow. AISI 304 cylinder: 8 lt; Resins per cylinder: 5.5 lt; Max flow rate: 1500 lt/h; Brine: 20 kg; Salt per regeneration cycle: 1.0 kg; Electrical power supply: 230V 50/60 Hz; Water connections: Ø 3/4" G; Min/max pressure: 2-8 bar; Water supply temp.: 4-25°C; LxDxH: 275x450x540 mm	
0S3332	Automatic water softeners LARGE SERIES PERFORMA VOLUMETRIC with Autotrol 268 Logix 760 valve Fiberglass tank: 24 lt 8"x35"; Resins per tank: 17 lt; Max flow rate: 4000 lt/h; Brine: 80 kg; Salt per regeneration cycle: 2.7 kg; Power supply: 230V 50/60 Hz; Water connections: Ø 1" G; Min/max pressure: 2-8 bar; Water supply temp.: 4-25°C; LxDxH: tank: Ø219x1060mm brine: Ø480x660mm	
0S3333	Automatic water softeners LARGE SERIES PERFORMA VOLUMETRIC with Autotrol 268 Logix 760 valve Fiberglass tank: 50 lt 10"x44"; Resins per tank: 35 lt; Max flow rate: 4000 lt/h; Brine: 120 kg; Salt per regeneration cycle: 7.2 kg; Power supply: 230V 50/60 Hz; Water connections: Ø 1" G; Min/max pressure: 2-8 bar; Water supply temp.: 4-25°C; LxDxH: tank: Ø271x1300mm brine: Ø541x810mm	
0S3334	Automatic water softeners LARGE SERIES PERFORMA VOLUMETRIC with Autotrol 268 Logix 760 valve Fiberglass tank: 84 lt 13"x44"; Resins per tank: 59 lt; Max flow rate: 4000 lt/h; Brine: 120 kg; Salt per regeneration cycle: 12.2 kg; Power supply: 230V 50/60 Hz; Water connections: Ø 1" G; Min/max pressure: 2-8 bar; Water supply temp.: 4-25°C; LxDxH: tank: Ø360x1300mm brine: Ø541x810mm	
0S3335	Automatic water softeners LARGE SERIES PERFORMA TIME with Autotrol 268 Logix 740 valve Fiberglass tank: 24 lt 8"x35"; Resins per tank: 17 lt; Max flow rate: 4000 lt/h; Brine: 80 kg; Salt per regeneration cycle: 2.7 kg; Power supply: 230V 50/60 Hz; Water connections: Ø 1" G; Min/max pressure: 2-8 bar; Water supply temp.: 4-25°C; LxDxH: tank: Ø219x1060mm brine: Ø480x660mm	
0S3336	Automatic water softeners LARGE SERIES PERFORMA TIME with Autotrol 268 Logix 740 valve Fiberglass tank: 50 lt 10"x44"; Resins per tank: 35 lt; Max flow rate: 4000 lt/h; Brine: 120 kg; Salt per regeneration cycle: 7.2 kg; Power supply: 230V 50/60 Hz; Water connections: Ø 1" G; Min/max pressure: 2-8 bar; Water supply temp.: 4-25°C; LxDxH: tank: Ø271x1300mm brine: Ø541x810mm	



Automatic Water Softeners

Code	Spare Part Description	Picture
0S3313	Automatic water softeners LARGE SERIES PERFORMA TIME with Autotrol 268 Logix 740 valve Fiberglass tank: 84 lt 13"x44"; Resins per tank: 59 lt; Max flow rate: 4000 lt/h; Brine: 120 kg; Salt per regeneration cycle: 12.2 kg; Power supply: 230V 50/60 Hz; Water connections: Ø 1" G; Min/max pressure: 2-8 bar; Water supply temp.: 4-25°C; LxDxH: tank: Ø360x1300mm brine: Ø541x810mm	

Manual Water Softeners

Code	Spare Part Description	Picture
0C1903	Manual water softeners AISI 304 cylinder: 8 lt; Resins per cylinder: 5.6 lt; Max flow rate: 1000 l/h; Salt for regeneration cycle: 1.0 kg; Water connections: Ø 3/4" G; Min/max pressure: 1-8 bar; Supply H2O temp.: 8-25°C; WxDxH: Ø190x400 mm	
0S0330	Manual water softeners AISI 304 cylinder: 12 lt; Resins per cylinder: 8.4 lt; Max flow rate: 1000 l/h; Salt for regeneration cycle: 1.5 kg; Water connections: Ø 3/4" G; Min/max pressure: 1-8 bar; Supply H2O temp.: 8-25°C; WxDxH: Ø190x515 mm	
0S3284	Manual water softeners. AISI 304 cylinder: 16 lt; Resins per cylinder: 12 lt; Max flow rate: 1000 lt/h; Salt per regeneration cycle: 2 kg; Water connections: Ø 3/4" G; Min/max pressure: 1-8 bar; Water supply temp.: 8-25°C; LxWxH: Ø190x600 mm	
0S0329	Manual water softeners AISI 304 cylinder: 20 lt; Resins per cylinder: 14 lt; Max flow rate: 1000 l/h; Salt for regeneration cycle: 2.5 kg; Water connections: Ø 3/4" G; Min/max pressure: 1-8 bar; Supply H2O temp.: 8-25°C; WxDxH: Ø190x900 mm	
0S1074	Manual "by pass" water softeners AISI 304 cylinder: 8 lt; Resins per cylinder: 5.6 lt; Max flow rate: 1000 l/h; Salt for regeneration cycle: 1.0 kg; Water connections: Ø 3/4" G; Min/max pressure: 1-8 bar; Supply H2O temp.: 8-25°C; WxDxH: Ø190x400 mm	



Manual Water Softeners

Code	Spare Part Description	Picture
0S1076	Manual "by pass" water softeners AISI 304 cylinder: 12 lt; Resins per cylinder: 8.4 l; Max flow rate: 1000 l/h; Salt for regeneration cycle: 1.5 kg; Water connections: Ø 3/4" G; Min/max pressure: 1-8 bar; Supply H2O temp.: 8-25°C; WxDxH: Ø190x500 mm	

Consumables For Manual and Automatic Water Softeners

Code	Spare Part Description	Picture
0L1140	NK111 mechanical filter with 50µm wire wound filter, recommended on every manual water softener. Reduces ferrous residues Ø 5", 3/8" connection	
0L1141	NK112 mechanical filter with 50µm wire wound filter, recommended on every manual water softener. Reduces ferrous residues Ø 5", 3/4" connection for filter system 0S1822, 0S1901 and 0S1912	
0S1027	Spare wound wire 5" 50µm Ø 61 H 127 mm for 0L1140 and 0L1141. Reduces ferrous residues	
0S2250	Replacement 5" activated carbon cartridge for 0L1140 and 0L1141. Reduces chlorine and ferrous residues	



Consumables For Manual and Automatic Water Softeners

Code	Spare Part Description	Picture
0S1423	NK223C mechanical filter with 5µm activated carbon cartridge; recommended on every automatic water softener, Mini, Maxi and Large series. Reduces chlorine and ferrous residues Ø 9", 1/2" G m/f connection	
0S1029	Spare wound wire 9" 50µm Ø 61 H 247 mm for 0S1423. Reduces ferrous residues	
005480	Replacement 9" activated carbon cartridge for 0S1423. Reduces chlorine and ferrous residues	
0S2165	Salt for water softeners 25 kg pack	
0S2191	Cationic resin suitable for all resin softeners of any size pack. 5 kg (6.14 litres)	
0S0333	Cationic resin suitable for all resin softeners of any size pack. 25 kg (30.71 litres)	
0S2245	Waterproof pH/EC/TDS/Temperature meter – low EC/TDS scale	
0S2850	Salt Detector for automatic water softeners	



Consumables For Manual and Automatic Water Softeners

Code	Spare Part Description	Picture
0S3049	Salt for water softeners 10 kg pack	

Reverse Osmosis Water Treatment

Code	Spare Part Description	Picture
0S1822	Reverse osmosis system without collection tank; supply voltage: 220...240 V/1N ph/50/60 Hz absorbed power 0.18kw; feed water pressure 1 - 4 bar for atmospheric boiler; feed water temperature 5-35 °C; water inlet pipe dimensions 3/4"	
0S1821	Small chloride filter cartridge	
0PRY39	Vessel container for filter membrane 3012 connection 1/4" - 3/8" (membrane not included)	
0PRAH2	Reverse osmosis filter wheels Kit 4 pieces	
0S1826	Headboard with wall bracket	



Reverse Osmosis Water Treatment

Code	Spare Part Description	Picture
OS1848	Filter membrane 3012 300 GPD	
OS0730	Descaler kit for cleaning osmosis membranes Complete with 2 carbon filters and 1 200g descaler agent Code Qt. Description OS0728 2 Carbon filter , OS0729 1 Descaling agent	
OS0728	Carbon filter for RO600C	
OS0735	Pump filter with membranes For RO400/600"	
OS0738	RO600 pump kit	
OS0737	RO600 23V engine	
OS2912	EF reverse osmosis system with high flow and high instantaneous flow rate	
OS1901	Reverse osmosis system with high flow and high instantaneous flow rate With 20 liter expansion vessel supply voltage: 230 V / 1N / 50-60 Hz absorbed power 0.25kw absorbed current 2.5 A supply water pressure 1.5 - 6 bars; feed water temperature 5-30 °C; in/out water inlet pipe dimensions 3/4"M dim. WxDxH: 271x499x451 mm	



Reverse Osmosis Water Treatment

Code	Spare Part Description	Picture
0S2422	Medium replacement chloride filter cartridge for osmosis code OS1901	
0S2913	TWB2A1 filter membrane	
0PRRA9	Vessel container for TWB2A1 filter membrane 1/8" connection (membrane not included)	
0S2830	Low pressure fitting Kit for osmosis code OS1822	
0S3057	Sani Clean Sanitizer Ideal for sanitizing filters, osmosis systems, refrigerators, automatic hot and cold drink dispensers. Recommended during routine maintenance every 3/6 months. 1 pack of 6 vials To be used with code OS2163	
0S3105	PG reverse osmosis system with high flow and high instantaneous flow rate Operating flow rate 140 l/h at 15°C Power supply 220 VAC / 50 Hz Feed water pressure 1 - 6 bar Feed water temperature 4-35 °C; Dim water inlet pipes in/out 3/4"G Dim. WxDxH: 145x410x430 mm Complete with pre-filter with head and installation kit	
0S3106	PROGUARD Gastronomy 200 pre-filter replacement cartridge Capacity 500,000 l	
0S3108	Membranes SET 2pcs PROGUARD Gastronomy 200	
0S3109	Installation kit for expansion tank	



Reverse Osmosis Water Treatment

Code	Spare Part Description	Picture
0S3110	8 l expansion tank	
0S3111	18 l expansion vessel	
0S2163	Disinfection small service cartridge for cleaning and disinfection of directly connected equipment. Ø 87 mm - H 269 mm maximum cartridge capacity 0.8 l operating pressure 2-6 bar temp. water inlet 4-30 °C The cartridge does not include the head To be used with code 0S3057	

Water Treatment

Code	Spare Part Description	Picture
0S1628	Purity C 150 Quell ST system Capacity 2408 on the 10th dH with 40% bypass (breakfasts) Capacity 1656 on the 10th dH with 10% bypass (ovens) temp. operating 4°C-30°C press. min/max 2-8.6 bar Head connections 3/8" dim. Ø117x417h complete with liter counter (0S2555), hardness test (0S1701) and head (0S1638)	
0S1629	Purity C 300 Quell ST system Capacity 4000 at the 10th dH with 40% bypass (breakfasts) Capacity 2750 at the 10th dH with 10% bypass (ovens) temp. operating 4°C-30°C press. min/max 2-8.6 bar Head connections 3/8" dim. Ø125x464h complete with liter counter (0S2555), hardness test (0S1701) and head (0S1638)	
0S1630	Purity C 500 Quell ST system Capacity 6800 at the 10th dH with 40% bypass (breakfasts) Nominal flow rate 100l/h Capacity 4675 at the 10th dH with 10% bypass (ovens) temp. operating 4°C-30°C press. min/max 2-8.6 bar Head connections 3/8" dim. Ø149x553h complete with liter counter (0S2555), hardness test (0S1701) and head (0S1638)	



Water Treatment

Code	Spare Part Description	Picture
OS3241	Purity C 1100 Quell ST system Capacity 11,500 at the 10th dH with 40% bypass (breakfasts) Nominal flow rate 100l/h Capacity 7906 at the 10th dH with 10% bypass (ovens) temp. operating 4°C-30°C press. min/max 2-8.6 bar Head connections 3/8" dim. Ø184x553h complete with liter counter (OS2555) and head (OS1638) Code Qt. Description OS1638 1 Head for water filters with bypass (0-70%); m 3/8", OS1708 1 Cartridge; purity c1100 quell st , OS2555 1 Digital flow-meter for water filters	
OS1638	Head with variable by pass 0%-70% and rinsing valves with 3/8" male fittings	
OS1892	Purity C service cartridge for cleaning, disinfection and descaling of directly connected equipment. Ø 125 mm - H 233 mm maximum cartridge capacity 0.5 l operating pressure 0.5-8.6 bar temp. water inlet 4-30 °C The cartridge does not include the OS1638 head	
OS1055	Purity C 300 Quell ST cartridge	
OS1056	Replacement cartridge for Purity C500 Quell	
OS1708	Replacement cartridge for Purity C1100 Quell	



Water Treatment

Code	Spare Part Description	Picture
0S2123	BRITA PURITY C reduction kit male thread 3/4" female Pack of 2 pieces.	
0S2555	Digital volumetric flow meter 10-100A flow rate 10-100 l/h temp. 4°C-30°C, max 8 bar indicates the residual liters that the filter system is able to treat. CR 2032 battery powered	
0S1054	Purity C 150 Quell ST cartridge	
0S2132	Purity C 1000 AC activated carbon filtration cartridge, ideal for cold and hot drink dispensers	
0S2226	Set of 20 Purity C 1000 AC cartridges	
0S2489	Head with 4-level bypass from 0%-30% Supplied with G3/8" fitting	
0S1223	Head for Purity CLEAN and CLEAN EXTRA with bypass	



Water Treatment

Code	Spare Part Description	Picture
0S0797	Purity AquaQuell 450 cartridge	
0S0798	Purity AquaQuell 600 cartridge	
0S0683	Purity AquaQuell 1200 cartridge	
0S2133	Purity C 50 Fresh cartridge; activated carbon filtration, ideal for coffee machines. Reduction of chlorine and all other substances with an unpleasant smell and taste	
0S2852	PURITY C1100 XtraSafe cartridge Ideal for corrosive and problematic waters. It offers targeted double protection against chlorides, sulphates and gypsum. It allows you to obtain totally demineralised water. Inlet water temperature 4-30°C Operating flow rate 300 l/h	
0S2119	MDU Display for Purity - Purity Steam	
0S2812	Black base with ejector for PURITY 1200	



Water Treatment

Code	Spare Part Description	Picture
0S1943	Head with MDU PURITY for Purity 1200 STEAM	
0S2621	Wall support for PURITY and PURITY C Compatible with PURITY 450, 600, 1200 or filter system C500, C1100 Dimensions: 212.2 x 271.5 x 453.5 mm	
0S1944	Head with PURITY MDU for Purity 450 and 600 STEAM	
0S3053	Remote indicator for Purity Quell ST and Purity Steam. Wall-mountable, it allows you to keep all the operating parameters of the PURITY system clearly visible. Dimensions 138x48x103mm Cable length 2m	
0S3281	iQ Meter Water Filter Unit. Check the remaining capacity of your filters remotely thanks to the integrated LTE SIM connection (included) and the BRITA iQ portal. Compatible with all Purity and Purity C filters. Compatible with current digital water filters. Battery-powered (up to 5 years of life, replaceable).	
0S3282	iQ Meter 10-100 l/h Water Meter. Check the remaining capacity of your filters remotely thanks to the integrated LTE SIM connection (included) and the BRITA iQ portal. Compatible with all Purity C filters. Battery powered (up to 5 years of life, replaceable). Temp. 4°C-40°C, max 8 bar. G 3/8 connections.	
0S3283	iQ Meter 100-700 l/h Water Meter. Check the remaining capacity of your filters remotely thanks to the integrated LTE SIM connection (included) and the BRITA iQ portal. Compatible with all Purity Clean filters. Battery powered (up to 5 years of life, replaceable). Temp. 4°C-40°C, max. 8 bar. G 3/4" connections.	



Water Treatment

Code	Spare Part Description	Picture
0S3292	WALL BRACKET FOR PURITY C Recommended for heads from C150 up to C500	
0S3319	PURITY C1100 CLEAN KIT with PARTIAL demineralization. Connections: G3/8" Min./max. inlet pressure 2-6 bar Flow rate 300 l/h Operating temperature 4°-60°C Capacity: 9,000 l at 10° KH Complete with cartridge (0S3315), head (0S2489), 3/4" reductions (0S2123) and flow meter (0S2556) Code Qt. Description 0S2123 1 Reducer; 3/4"-3/8"; set; purity c , 0S2489 1 Head for water filters with 4 levels of bypass, 0S2556 1 Digital flowmeter, 0S3315 1 Cartridge; purity c1100 clean	
0S3320	PURITY C1100 CLEAN EXTRA KIT with TOTAL demineralization Connections: G3/8" Min./max. inlet pressure: 2-6 bar Flow rate 300 l/h Operating temperature 4°-60°C Capacity: 3,200 l at 10° KH Complete with cartridge (0S3316), head (0S2489), 3/4" reductions (0S2123) and flow meter (0S2556) Code Qt. Description 0S2123 1 Reducer; 3/4"-3/8"; set; purity c , 0S2489 1 Head for water filters with 4 levels of bypass, 0S2556 1 Digital flowmeter, 0S3316 1 Cartridge; purity c1100 clean extra	
0S3315	PURITY C1100 CLEAN Cartridge	
0S3316	PURITY C1100 CLEAN EXTRA cartridge	



Excellence is central to everything we do.
By anticipating our customers' needs, we strive for
Excellence with our people, innovations, solutions and services.
To be the OnE making our customers' work-life easier,
more profitable – and truly sustainable every day.

Follow us on



www.electroluxprofessional.com

Excellence with the environment in mind

- ▶ The majority of Electrolux Professional Group factories are third-party certified according to ISO (International Organization for Standardization) standards ISO 9001 and ISO 14001, with some sites also certified ISO 5001 and ISO 45001.*
- ▶ We are focused on developing innovative and sustainable solutions designed for low water, energy and detergent consumptions and reduced emissions.
- ▶ Our products are tailored to human comfort based on ergonomic principles and according to the user's natural workflow, achieving maximum efficiency with minimum effort. We also perform third-party ergonomic certifications on certain products (ERGOCERT).
- ▶ The selection of materials and technologies for our products complies with REACH (Registration, Evaluation, Authorization and Restriction of Chemicals) and RoHS directives (Restriction of Hazardous Substances 2011/65/EU) for the protection of human health and the environment



*for more details, refer to annual Sustainability Report at: electroluxprofessionalgroup.com